

Encoded Archival Context - Corporate Bodies, Persons, and Families (EAC-CPF) Tag Library Version EAC-CPF 3.0.0

2025 Edition

**Prepared and maintained by the
Technical Subcommittee for Encoded Archival
Standards of the Society of American Archivists
and the Staatsbibliothek zu Berlin**



**Encoded Archival Context - Corporate Bodies, Persons, and
Families (EAC-CPF) Tag Library Version EAC-CPF 3.0.0, 2025
Edition**

Available from

17 North State Street, suite 1425
Chicago, IL 60602-3315
USA
312-606-0722
Fax: 312-606-0728
info@archivists.org
www.archivists.org

©Society of American Archivists in collaboration with Staatsbibliothek
zu Berlin, 2025.

Edition : 2025 Edition

Printed : Printed in the United States of America



This work is licensed under a Creative Commons Attribution 4.0 International License (CC BY 4.0). See <http://creativecommons.org/licenses/by/4.0/>. Some rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, mechanical or photocopying, recording, or otherwise without attribution.

PLACEHOLDER ISBN VALUE

Table of Contents

Related Standards.....	7
-------------------------------	----------

Release and Revision Notes.....	8
--	----------

Tag Library Conventions.....	9
-------------------------------------	----------

Elements.....	11
----------------------	-----------

abstract.....	12
address.....	14
addressLine.....	16
agencyCode.....	18
agencyName.....	21
agent.....	23
alternativeSet.....	26
biogHist.....	28
citedRange.....	31
componentEntry.....	33
contact.....	35
contactLine.....	37
control.....	39
conventionDeclaration.....	43
cpfDescription.....	46
date.....	48
dateRange.....	51
dateSet.....	54
demographicDescription.....	56
demographicDescriptions.....	58
description.....	60
descriptiveNote.....	63
eac.....	65
entityType.....	66
eventDateTime.....	68
eventDescription.....	70
existDates.....	72
formattingExtension.....	74
fromDate.....	76
functionPerformed.....	78
functionsPerformed.....	80
generalContext.....	82

geographicCoordinates.....	84
identity.....	86
identityId.....	88
label.....	90
language.....	92
languageDeclaration.....	94
languageUsed.....	96
languagesUsed.....	98
legalStatus.....	100
legalStatuses.....	102
localDescription.....	104
localDescriptions.....	106
localTypeDeclaration.....	108
maintenanceAgency.....	110
maintenanceEvent.....	112
maintenanceHistory.....	114
mandate.....	116
mandates.....	118
multipleIdentities.....	120
nameEntry.....	122
nameEntrySet.....	124
narrativeEvent.....	126
objectXMLWrap.....	128
narrativeEvent.....	130
occupation.....	132
occupations.....	134
otherAgencyCode.....	136
otherEntityType.....	138
otherEntityTypes.....	140
otherRecordId.....	142
p.....	144
part.....	147
place.....	149
placeName.....	153
places.....	156
recordId.....	158
reference.....	160
relation.....	162
relations.....	165
relationship.....	167
referringString.....	169
rightsDeclaration.....	171
role.....	173
setComponent.....	175
shortCode.....	177
source.....	179

sources.....	181
span.....	183
structureOrGenealogy.....	185
term.....	187
toDate.....	190
useDates.....	192
writingSystem.....	194
Attributes.....	196
addressLineType.....	198
addressLineTypeEncoding.....	199
agentType.....	200
agentTypeEncoding.....	202
audience.....	203
audienceEncoding.....	204
calendar.....	205
certainty.....	206
contactLineType.....	207
contactLineTypeEncoding.....	208
conventionDeclarationReference.....	209
coordinateSystem.....	210
countryCode.....	211
countryEncoding.....	212
dateEncoding.....	213
detailLevel.....	214
detailLevelEncoding.....	215
era.....	216
href.....	217
id.....	218
identityType.....	220
identityTypeEncoding.....	221
languageCode.....	222
languageEncoding.....	223
languageOfElement.....	224
linkRole.....	225
linkTitle.....	226
localType.....	227
localTypeDeclarationReference.....	228
maintenanceEventReference.....	229
maintenanceEventType.....	230
maintenanceEventTypeEncoding.....	231
maintenanceStatus.....	232
maintenanceStatusEncoding.....	233
normalizedForm.....	234
notAfter.....	235
notBefore.....	236
placeType.....	237

placeTypeEncoding.....	238
preferredForm.....	239
publicationStatus.....	240
publicationStatusEncoding.....	241
referredEntityRelationship.....	242
referredEntityType.....	243
referredEntityTypeEncoding.....	244
relationType.....	245
relationTypeEncoding.....	246
repositoryEncoding.....	247
scriptCode.....	248
scriptEncoding.....	249
scriptOfElement.....	250
sourceReference.....	251
standardDate.....	252
standardDateTime.....	253
status.....	254
statusEncoding.....	255
style.....	256
target.....	257
targetType.....	258
targetTypeEncoding.....	259
unit.....	260
value.....	261
valueURI.....	262
vocabularySource.....	264
vocabularySourceURI.....	265
.....	267

Related Standards

The standards maintained by the Society of American Archivists' [Technical Subcommittee on Encoded Archival Standards](#) (TS-EAS) are XML schemas based on established models developed by the [International Council on Archives](#) (ICA).

EAC-CPF is based on the [International Standard Archival Authority Record for Corporate Bodies, Persons and Families](#) (ISAAR-CPF). Revisions to the EAD and EAC-CPF standards are being undertaken by TS-EAS based on the requirements of the Society of American Archivists' standards maintenance schedule and policies, and are not tied to ongoing development of standards by the ICA, though keeping close connections to the ICA [Experts Group on Archival Description](#) as a related standards body.

For this reason, the EAC-CPF 2.0 continues to be based on ISAAR(CPF) rather than the draft versions of Records in Contexts. We anticipate that future versions of EAC-CPF and other standards maintained by TS-EAS will take the Records in Contexts - Conceptual Model into account once it is finalized and approved.

International Standard Archival Authority Record for Corporate Bodies, Persons and Families (ISAAR(CPF))

[ISAAR\(CPF\)](#) is a descriptive standard for descriptions of agent entities (corporate bodies, persons and families) associated with the creation and maintenance of archives. ISAAR(CPF) is maintained by the ICA.

Encoded Archival Description (EAD)

[EAD](#) is an XML standard for encoding archival finding aids, maintained by the TS-EAS of the Society of American Archivists, in partnership with the Library of Congress.

Encoded Archival Guide (EAG)

[EAG](#) is an XML standard for encoding data about archives and related organizations. EAG is maintained by the Archives Portal Europe Foundation and its Working Group on Standards (WGoS). The development of EAG is coordinated in close cooperation with the TS-EAS, which is responsible for EAD and EAC-CPF.

Encoding Standards

The international community of cultural heritage organizations is working on a broad set of diverse standards to meet the challenges of the digital age. Established standards concerning digitization and metadata are maintained by the [Library of Congress](#).

Records in Contexts - Conceptual Model (RiC-CM)

[RiC-CM](#) is a high-level conceptual model that focuses on intellectually identifying and describing records, the people that created and use(d) them, and the activities pursued by the people that the records both facilitate and document. RiC-CM is maintained by the ICA.

Release and Revision Notes

This is the release of the Tag Library for EAC-CPF 3.0. This major release includes changes and updates in the schema undertaken by the SAA [Technical Subcommittee on Encoded Archival Standards](#) (TS EAS) for the third major revision of the standard EAC-CPF. It supersedes the standard version EAC-CPF 2.0.1 (2024).

The release reflects the commitment to align all EAS where possible and practica.

The EAC-CPF Tag Library is a living document. As such, it will continue to be developed as users suggest areas in need of clarification or expansion. The TS-EAS still encourages implementers to provide any queries, comments, and suggestions regarding the tag library and its content. In addition, the contribution of examples is highly encouraged. Questions, comments or examples may be directed to the TS-EAS ([ts-eas\[at\]archivists.org](mailto:ts-eas[at]archivists.org)). The underlying encoding of the Tag Library is based on TEI P5 and is designed to facilitate incorporating documentation into the schema to provide guidance in XML editors. While the initial release of the Tag Library is in English, the underlying encoding is designed to facilitate providing the Tag Library in additional languages at later dates.

All elements and attributes in EAC-CPF 2.0.1 were evaluated with particular attention to elements and attributes shared across EAS.

Following ISAAR(CPF), the established structure of control area, identity area, description area, and relations is still available, as is the availability of encoding multiple identities in one EAC-CPF instance.

Working in parallel with the ICA Experts Group on Archival Description (ICA EGAD), EAC-CPF 3.0 reflects the Records on Contexts - Conceptual Model (RiC-CM) where feasible.

Tag Library Conventions

The EAC-CPF Elements section of the Tag Library contains descriptions of the elements, arranged alphabetically by element name.

Tag Name:

Short, mnemonic form of the element name that is used in the machine-readable encoded document. The tag name is the first word at the top of the page. Tag names appear between angle brackets, e.g., `<nameEntry>`, except in the listings under "May occur within" and "May contain," and are always in camel case (camelCase).

Element Name:

Expanded version of the tag name that more fully describes the element's meaning. The full name of the element is usually a word or phrase that identifies the element's purpose. In the Tag Library, the element name follows the tag name on the page defining that element and appears with initial capital letters, e.g., `<nameEntry>` Name Entry.

Summary:

A brief statement that provides a concise definition of the element, suitable for quick reference.

May Contain:

Identifies what child nodes (text or elements) may occur within the element being defined. Elements are listed in alphabetical order by tag name. Elements may be empty (e.g., an element which allows no child text or element nodes), or they may contain text (listed as [text]), other elements, or a mixture of text and other elements. Text content cannot include characters that would be interpreted by a parser as action codes. For example, a left angle bracket must be represented as the character entity reference `<`; so that it is not misinterpreted as the start of an element name. The technical availability of child elements is listed in brackets beside each element, e.g. place (0..1). The first character represents the minimum occurrences of the child element and the final character represents the maximum occurrences of the child element, with 'n' representing unlimited occurrences.

May Occur Within:

Identifies all the parent elements within which the described element may appear, listed in alphabetical order by tag name. This information conveys information about where and how often an element is available throughout the schema. The definitions for parent elements may provide additional information about an element's usage.

Attributes:

Identifies all attributes that can be associated with an element. Attributes are represented in camelCase letters in XML coding. The Tag Library uses the convention of preceding an attribute name with an @ symbol (e.g.,

[@localType](#)), following XPath syntax. See the EAC-CPF Attributes section of the tag library for definitions and additional information.

Description and Usage:

This section begins with one or more paragraphs that provide a more thorough description of the element than that found in the Summary, which may be followed by guidance on use. The terms "parent" and "child" are used to indicate hierarchical relationships between elements. Standard terminology is also used to suggest the kind of element being discussed. "Wrapper element" indicates an element that cannot contain text directly; a second, nested element must be opened first. When the schema enforces a specific sequence of child elements, that sequence is indicated. If useful, context-specific guidance for the usage of an element's attributes is given in an "Attribute usage" section. A "See also" section may be provided to indicate additional elements that are similar, easily confused, or otherwise related to the element being described.

Availability:

Indicates, within the context of its parent(s), whether the element is required or optional, and whether or not it is repeatable.

Examples:

Element and attribute descriptions link to an example to indicate how attributes and elements can be used together. Many of the examples are taken from real authority records; others have been specially constructed for the Tag Library. The examples illustrate any required sequences of elements, as in the case of children within `<control>`, or required attributes such as `@part` in `<nameEntry>`. In other cases, the examples simply show what is possible. Some examples have ellipses, either between or within elements, indicating that other elements or text have been omitted. Some elements have multiple examples: one may show very dense markup with numerous attributes while another may illustrate a minimalist approach to the markup. Either approach is valid in EAC-CPF, and it is up to the instance creator to determine the optimal level of markup based on their specific purposes, functional requirements, resources, or consortial guidelines.

Elements

< abstract >

Abstract

Summary

An optional element within narrative elements such as [<biogHist>](#) that contains a brief summary of the information contained within the narrative element as a whole.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[biogHist](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

The [<abstract>](#) is a brief synopsis of the information in the narrative element that it is used with. Its purpose is to help readers quickly identify the most important aspects in each context. The content within this element may also be harvested by other systems to provide explanatory context when appearing e.g. in a set of search results.

[<abstract>](#) may include one or more [<reference>](#) elements to point to external resources that provide additional descriptive data. It may furthermore include one or more [<referringString>](#) elements to emphasize entities' names as part of the descriptive texts and to point to external vocabularies for more information about these, where applicable.

Availability

Optional, not repeatable

Examples

[<biogHist>](#) [<abstract>](#) Hubert H. Humphrey was born in Wallace, South Dakota (1911). He was elected Mayor of Minneapolis in 1945 and served until 1948. In November of 1948, he was elected to the United States Senate and he also served as the Senate Democratic Whip from 1961 to 1964 and in 1968, Humphrey was the Democratic Party's candidate for President, but he was defeated by Richard M. Nixon. [</abstract>](#) [<p>](#) Hubert H. Humphrey was born in Wallace, South Dakota, on May 27, 1911. He left South Dakota to attend the University of Minnesota but returned to South Dakota to help manage his father's drug store early in the depression. He attended the Capitol College of Pharmacy in Denver, Colorado, and became a register pharmacist in 1933. On September 3, 1936, Humphrey married Muriel Fay Buck. He returned to the University of Minnesota and earned a B.A. degree in 1939. In 1940 he earned an M.A. in political science from Louisiana State University and returned to Minneapolis to teach and pursue further graduate study, he began working for the W.P.A. (Works Progress Administration). He moved on from there to a series of positions with wartime agencies. In 1943, he ran unsuccessfully for Mayor of Minneapolis and returned to teaching as a visiting professor at Macalester College in St. Paul. Between 1943 and 1945 Humphrey worked at a variety of jobs. In 1945, he was elected Mayor of Minneapolis and served until 1948. In 1948, at the Democratic National Convention, he gained national attention when he delivered a stirring speech in favor of a strong civil rights plank in the party's platform. In November of 1948, Humphrey was elected to the United States Senate. He served as the Senate Democratic Whip from 1961 to 1964. [</p>](#) [<p>](#) In 1964, at the Democratic National Convention, President Lyndon B. Johnson asked the convention to select Humphrey as the Vice Presidential nominee. The ticket was elected in November in a Democratic landslide. In 1968, Humphrey was the Democratic Party's candidate for President, but he was defeated narrowly by Richard M. Nixon. After the defeat, Humphrey returned to Minnesota to teach at the University of Minnesota and Macalester College. He returned to the U.S. Senate in 1971, and he won re-election in 1976. He died January 13, 1978 of cancer. [</p>](#) [</biogHist>](#)

[Table of Contents](#)

<address>

Address

Summary

An optional child element of [<place>](#) that binds together one or more [<addressLine>](#) elements to encode a postal or other address.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
addressLine	1..n

May occur within

[place](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[<address>](#) is an optional wrapper element within [<place>](#) used to encode a physical or analog address.

Ideally [<address>](#) should be bundled with a [<label>](#) element within [<place>](#) to provide both the name and address of a location.

[<address>](#) must include one or more [<addressLine>](#) element(s) that provide full or sufficient information identifying a postal or other physical address related to the entity being described.

Availability

Optional, repeatable

See also

Use [<contact>](#) to encode digital addresses and contact information.

Examples

```
<address audience="external" id="IDaddress1"> <addressLine
languageOfElement="se">Kungl. Hovstaterna</addressLine> <addressLine
languageOfElement="se">Kungl. Slottet</addressLine> <addressLine
addressLineType="postalCode">10770</addressLine> <addressLine
languageOfElement="se" addressLineType="municipality">Stockholm</
addressLine> <addressLine languageOfElement="se"
addressLineType="country">Sverige</addressLine> <addressLine
languageOfElement="en" addressLineType="country">Sweden</
addressLine> </address>
```

[Table of Contents](#)

<addressLine>

Address Line

Summary

A required child element of [<address>](#) used for recording one line of a postal or other address.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[address](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
addressLineType	Optional
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use the optional [@addressLineType](#) attribute to encode the part of the address that the [<addressLine>](#) refers to, for example "street".
Use the optional [@addressLineTypeEncoding](#) in [<control>](#) to specify the source or rules for values supplied in [@addressLineType](#).

Description and Usage

[<addressLine>](#) is used to encode parts or lines of a physical address within a parent [<address>](#) element.
[<addressLine>](#) may be repeated as many times as necessary to enter all parts of an address.

Availability

Required, repeatable

Examples

```
<address> <addressLine languageOfElement="se">Kungl. Hovstaterna</addressLine> <addressLine languageOfElement="se">Kungl. Slottet</addressLine> <addressLine addressLineType="postalCode">10770</addressLine> <addressLine languageOfElement="se" addressLineType="municipality">Stockholm</addressLine> <addressLine languageOfElement="se" addressLineType="country">Sverige</addressLine> <addressLine languageOfElement="en" addressLineType="country">Sweden</addressLine> </address>
```

[Table of Contents](#)

<agencyCode>

Agency Code

Summary

A optional child element of [<maintenanceAgency>](#) that provides a code for the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[maintenanceAgency](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
status	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@status](#) with values such as “authorised” or “alternative” to declare whether the [<agencyCode>](#) is using an authorised value, e.g. a registered ISIL code, or an alternative code. Use [@statusEncoding](#) in [<control>](#) to specify the source or rules for values supplied in [@status](#).

Description and Usage

Use [<agencyCode>](#) to record a code indicating the institution or service responsible for the creation, maintenance and/or dissemination of the EAS instance. Use of [<agencyCode>](#) is recommended, as the combination of

`<agencyCode>` and the required `<recordId>` can provide a globally unique identifier for the instance.

`<maintenanceAgency>` must include one or both of `<agencyCode>` and `<agencyName>`.

It is recommended that the code follows the format of the International Standard Identifier for Libraries and Related Organizations (ISIL: ISO 15511): a prefix, a dash, and an identifier. The code is alphanumeric (characters A-Z, 0-9, solidus, hyphen-minus, and colon) with a maximum of 16 characters. If appropriate to local or national convention, insert a valid ISIL for an institution, whether provided by a national authority (usually the national library) or a service (such as OCLC). If this is not the case then local institution codes may be given with the ISO 3166-1 alpha-2 country code as the prefix to ensure international uniqueness in `<agencyCode>`.

Availability

Optional, not repeatable

See also

Use `<agencyName>` to record the name of the agency. Use `<otherAgencyCode>` to record any alternative codes representing the agency. Use `<recordId>` in combination with `<agencyCode>` to form a globally unique identifier for the EAS instance.

Examples

```
<maintenanceAgency> <agencyCode status="authorized"
vocabularySource="ISIL" vocabularySourceURI="http://
id.loc.gov/vocabulary/identifiers/isil">US-ctybr</agencyCode>
<agencyName>Beinecke Rare Book and Manuscript Library</
agencyName> <otherAgencyCode status="authorized" valueURI="https://
id.loc.gov/vocabulary/organizations/ctybr" vocabularySource="MARC
Code List for Organizations" vocabularySourceURI="https://
www.loc.gov/marc/organizations/">CtY-BR</otherAgencyCode>
<otherAgencyCode status="alternative" valueURI="https://
www.wikidata.org/wiki/Q814779" vocabularySource="Wikidata"
vocabularySourceURI="https://www.wikidata.org/">Q814779</
otherAgencyCode> </maintenanceAgency> <maintenanceAgency>
<agencyCode status="alternative" vocabularySource="NAD"
vocabularySourceURI="https://sok.riksarkivet.se/">SE/G066</
agencyCode> <agencyName>Kommunalförbundet Sydarkivera</
agencyName> </maintenanceAgency> <maintenanceAgency
countryCode="DE"> <agencyCode status="authorized"
vocabularySource="ISIL" vocabularySourceURI="https://
sigel.staatsbibliothek-berlin.de/de/suche/" valueURI="https://ld.zdb-
services.de/resource/organisations/DE-611">DE-611</agencyCode>
```

<agencyName>Staatsbibliothek zu Berlin - Preußischer Kulturbesitz, Kalliope-
Verbund</agencyName> <agencyName languageOfElement="eng">Berlin
State Library - Prussian Cultural Heritage, Kalliope Union Catalog</
agencyName> </maintenanceAgency>

[Table of Contents](#)

<agencyName>

Agency Name

Summary

An optional child element of [<maintenanceAgency>](#) that provides the name of the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[maintenanceAgency](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

Use [<agencyName>](#) to record the name of the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance. Examples include the repository name or the name of an aggregation service.

[<maintenanceAgency>](#) must include one or both of [<agencyName>](#) and [<agencyCode>](#).

It is recommended to use the form of the agency name that is authorized by an appropriate national or international agency or service.

[<agencyName>](#) may be repeated in order to provide the name of the institution or service responsible for the EAS instance in multiple languages or

name settings. If `<agencyName>` is repeated it is recommended to indicate the language of each name using `@languageOfElement`.

Availability

Optional, repeatable

See also

Use `<agencyCode>` to record a code representing the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance.

Examples

```
< maintenanceAgency countryCode = "DE" > < agencyCode
status = "authorized" vocabularySource = "ISIL" vocabularySourceURI = "https://
sigel.staatsbibliothek-berlin.de/de/suche/" valueURI = "https://ld.zdb-
services.de/resource/organisations/DE-611" > DE-611 < /agencyCode >
< agencyName > Staatsbibliothek zu Berlin - Preußischer Kulturbesitz, Kalliope-
Verbund < /agencyName > < agencyName languageOfElement = "eng" > Berlin
State Library - Prussian Cultural Heritage, Kalliope Union Catalog < /
agencyName > < /maintenanceAgency > < maintenanceAgency >
< agencyCode status = "authorized" vocabularySource = "ISIL"
vocabularySourceURI = "http://id.loc.gov/vocabulary/identifiers/isil" > US-
nnmnh < /agencyCode > < agencyName > American Museum of Natural
History < /agencyName > < /maintenanceAgency >
```

[Table of Contents](#)

< agent >

Agent

Summary

A required child element of [< maintenanceEvent >](#) that provides the name of a person, institution, or system responsible for a specific event in the EAS instance's maintenance history, such as its creation, modification, or deletion. Also available in [< narrativeEvent >](#) to name a person, institution, or other type of agent of importance to the history of the CPF entity being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
label	1..n
placeName	0..n
relationship	0..n
role	0..n

May occur within

[maintenanceEvent](#), [narrativeEvent](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
agentType	Optional
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use the `@agentType` attribute to specify whether the agent is, for example, a "corporateBody", "mechanism", or "person". Use the optional `@agentTypeEncoding` in `<control>` to specify the source or rules for values supplied in `@agentType`.

Use the attributes `@valueURI`, `@vocabularySource`, and `@vocabularySourceURI` with `<agent>` when referencing an entry of an external vocabulary, thesaurus, ontology applicable to the agent overall. In case of referencing different vocabularies or different entries within the same vocabulary for the name or the role of the agent, use the three attributes with the sub-elements `<label>` or `<role>` directly.

Description and Usage

Use `<agent>` to indicate the person, institution, or system responsible for a maintenance event. Examples include the name of the author or encoder, the database responsible for creating the EAS instance, and the style sheet used to update an instance to a new version of the EAS. Each `<maintenanceEvent>` element must have a child `<agent>` element. Use `<agent>` as an optional sub-element in `<narrativeEvent>` to name a person, institution, or other type of agent of importance to a specific event in the history of the CPF entity being described.

The prescribed order of all child elements (both required and optional) is:

`<label>`

One of `<date>` , `<dateRange>` , or `<dateSet>`

`<placeName>`

`<role>`

`<relationship>`

`<descriptiveNote>`

Availability

Within `<maintenanceEvent>` : required, not repeatable

Within `<narrativeEvent>` : optional, repeatable

Examples

```
<maintenanceHistory> <maintenanceEvent
maintenanceEventType="derived"> <agent agentType="machine">
<label>export.xml/Saxon B9</label> </agent> <eventDateTime
standardDateTime="2024-08-30T09:37:17.029-04:00"/
> <eventDescription>Derived from local collection
```


management system </eventDescription </maintenanceEvent >
 < maintenanceEvent maintenanceEventType="revised"> < agent
 agentType="unknown"> < label/> </agent> < eventDateTime
 standardDateTime="2024-11-27"/> </maintenanceEvent >
 < maintenanceEvent maintenanceEventType="updated"> < agent
 agentType="person"> < label>K. Bredenberg</label> </
 agent> < eventDateTime>December 2024</eventDateTime>
 </maintenanceEvent > </maintenanceHistory> <biogHist>
 <narrativeEvent> <date standardDate="1964-10">October 1964</
 date> <agent agentType="group"> <label>Labour government</
 label> </agent> <eventDescription>Created the new office of
 Secretary of State for Economic Affairs (combined with First Secretary
 of State) and set up the Department of Economic Affairs under the
 Ministers of the Crown Act 1964 to carry primary responsibility for long
 term economic planning.</eventDescription> </narrativeEvent>
 <narrativeEvent> <date standardDate="1964-10-16">16 October
 1964</date> <agent agentType="person"> <label>George Brown</
 label> </agent> <eventDescription>Appointed as First Secretary of
 State and Secretary of State for Economic Affairs, and as chairman of the
 National Economic Development Council (NEDC).</eventDescription>
 </narrativeEvent> [...] </biogHist> <biogHist> <narrativeEvent>
 <date standardDate="1964-10">October 1964</date> <agent
 agentType="group"> <label>Labour government</label> </agent>
 <eventDescription>Created the new office of Secretary of State for Economic
 Affairs (combined with First Secretary of State) and set up the Department of
 Economic Affairs under the Ministers of the Crown Act 1964 to carry primary
 responsibility for long term economic planning.</eventDescription> </
 narrativeEvent> <narrativeEvent> <date standardDate="1964-10-16">16
 October 1964</date> <agent agentType="person"> <label>George
 Brown</label> </agent> <eventDescription>Appointed as First
 Secretary of State and Secretary of State for Economic Affairs, and as
 chairman of the National Economic Development Council (NEDC).</
 eventDescription> </narrativeEvent> [...] </biogHist> <archDesc>
 <identificationData> <unitTitle>National Association for the
 Advancement of Colored People records, 1842-2019</unitTitle>
 <unitDate> <dateRange> <fromDate standardDate="1842">1842</
 fromDate> <toDate standardDate="2019">2019</toDate>
 <dateRange> <unitDate> </identificationData> <agents> <agent
 agentType="corporateBody"> <label>National Association for the
 Advancement of Colored People</label> <role>Creator</role>
 </agent> <agent agentType="corporateBody"> <label>Library of
 Congress</label> <role>Holding institution</role> </agent> </
 agents> [...] </archDesc>

[Table of Contents](#)

< alternativeSet >

Alternative Set

Summary

A container for one or more authority records derived from one or more authority systems, expressed within a single EAC-CPF instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
setComponent	1..n

May occur within

[cpfDescription](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
languageOfElement	Optional
id	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

< [alternativeSet](#) > is a container element for one or more authority records derived from one or more alternative systems. Authority record aggregation may be used in cooperative or consortial contexts that gather together records describing the same CPF entity in different languages, from different rules, or from different contexts, when it is desirable to provide users with alternative descriptions of the same entity. For example in the context of the European Union, an international cooperative project may want to provide users the option of storing descriptions in English, French, German, Italian, Spanish, and in other European languages.

Alternative authority records are contained within the required < [setComponent](#) > child elements. This approach allows different descriptions of the same CPF entity to be contained within a single EAC-CPF instance.

Availability

Optional, not repeatable

See also

[<alternativeSet>](#) should not be confused with [<sources>](#) , wherein authority records are not intended to be displayed as alternative versions.

Examples

See [<alternativeSet>](#) encoding

[Table of Contents](#)

<biogHist>

Biography or History

Summary

A concise essay and/or chronology that provides biographical or historical information about the EAC-CPF entity.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
narrativeEvent	0..n
p	0..n

May occur within

[description](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[<biogHist>](#) includes significant details about the life of an individual or family, or the administrative history of a corporate body. Use the element [<abstract>](#) to provide a brief summary of the information encoded in [<biogHist>](#) that could be extracted for inclusion in a remote source, such as a MARC record. Use the repeatable [<p>](#) element to structure longer texts in several paragraphs. If required and suitable, use [<formattingExtension>](#) to make use of more detailed formatting options

such as lists, tables, or section headers in XHTML and to accommodate greater complexity in expressing or representing the biography or history of the CPF entity. Use `<narrativeEvent>` to provide a chronology of the biography or history of the entity.

The prescribed order of all child elements (both required and optional) is:

`<abstract>` (if used)

`<formattingExtension>` or `<p>`

`<narrativeEvent>`

Availability

Optional, repeatable

Examples

```
<biogHist> <abstract> Established in 1961, the United States Peace Corps
administered and coordinated Federal international volunteer and related
domestic volunteer programs in areas of agricultural assistance, community
development, education, environmental protection, and nation assistance. </
abstract> <p> The Peace Corps was established as an operating agency in the
Department of State Delegation of Authority 85-11, effective March 3, 1961,
pursuant to Executive Order (E.O.) 10924, March 1, 1961. It was recognized
legislatively by the Peace Corps Act (75 Stat. 612), approved September 22,
1961. The Peace Corps was reassigned to the newly established ACTION
by Reorganization Plan No. 1 of 1971, effective July 1, 1971. It was made
autonomous within ACTION by E.O. 12137, May 16, 1979, and was made an
independent agency by Title VI of the International Security and Development
Corporation Act of 1981 (95 Stat. 1540), February 21, 1982. The Peace Corps
administered and coordinated Federal international volunteer and related
domestic volunteer programs including the areas of agricultural assistance,
community development, education, environmental protection, and nation
assistance. </p> </biogHist> <biogHist> <p> Ilma Mary Brewer, nee
Pidgeon, was Lecturer in Botany/Biology, University of Sydney 1963-70 and
Senior Lecturer in Biological Sciences 1970-78. She developed new methods
of teaching based on the recognition that a student learnt more by working at
his/her own place and instruction him/her self. Her findings were published
as a book, "Learning More and Teaching Less." </p> <narrativeEvent>
<date standardDate="1936">1936</date> <eventDescription> Bachelor of
Science (BSc) completed at the University of Sydney</eventDescription> </
narrativeEvent> <narrativeEvent> <date standardDate="1937">1937</
date> <eventDescription> Master of Science (MSc) completed at
the University of Sydney</eventDescription> </narrativeEvent>
<narrativeEvent> <date standardDate="1937/1941">until 1941</date>
<eventDescription> Linnean Macleay Fellow</eventDescription> </
```

```

narrativeEvent> </biogHist> <biogHist> <!-- Note: the way how the
XHTML schema is integrated can differ depending on your local application
context. The following encoding validates e.g. in Oxygen XML Editor
20.1. --> <formattingExtension> <xhtml:div xmlns:xhtml="http://
www.w3.org/1999/xhtml" https://www.w3.org/2002/08/xhtml/xhtml1-
strict.xsd"> <xhtml:h4> Biography Johann Sebastian Bach</xhtml:h4>
<xhtml:p> [...]</xhtml:p> [...] <xhtml:h3> Family life</xhtml:h3>
<p> Bach was married twice and had 20 children, 10 of whom survived
into adulthood.</p> <xhtml:ul> <xhtml:h4> Children of Johann
Sebastian Bach and Maria Barbara Bach</xhtml:h4> <xhtml:li> Catharina
Dorothea Bach</xhtml:li> <xhtml:li> Wilhelm Friedemann Bach</
xhtml:li> <xhtml:ul> <xhtml:h5> Children of Wilhelm Friedemann
Bach</xhtml:h5> <xhtml:li> Friederica Sophia Bach</xhtml:li>
<xhtml:li> Two sons who did not live past infancy</xhtml:li> </
xhtml:ul> <xhtml:li> Carl Philipp Emanuel Bach</xhtml:li> <xhtml:ul>
<xhtml:h5> Children of Carl Philipp Emanuel Bach</xhtml:h5>
<xhtml:li> Johann Adam Bach</xhtml:li> <xhtml:li> Anna Carolina
Philippina Bach</xhtml:li> <xhtml:li> Johann Sebastian Bach ("the
Younger")</xhtml:li> <xhtml:li> Other children who did not live to
adulthood</xhtml:li> </xhtml:ul> <xhtml:li> Johann Gottfried Bernhard
Bach</xhtml:li> <xhtml:li> Three more children who did not live to their
first birthday</xhtml:li> </xhtml:ul> <xhtml:ul> <xhtml:h4> Children
of Johann Sebastian Bach and Anna Magdalena Wilcken</xhtml:h4>
<xhtml:li> Gottfried Heinrich Bach</xhtml:li> <xhtml:li> Johann
Christoph Friedrich Bach</xhtml:li> <xhtml:ul> <xhtml:h5> Children
of Johann Christoph Friedrich Bach</xhtml:h5> <xhtml:li> Anna
Philippiana Friederica Bach</xhtml:li> <xhtml:li> Wilhelm Friedrich
Ernst Bach</xhtml:li> <xhtml:ul> <xhtml:h6> Children of Wilhelm
Friedrich Ernst Bach</xhtml:h6> <xhtml:li> Carolina Auguste Wilhelmine
Bach</xhtml:li> <xhtml:li> Juliane Friederica Bach</xhtml:li> </
xhtml:ul> <xhtml:li> Christine Luise Bach</xhtml:li> </xhtml:ul>
<xhtml:li> Johann Christian Bach</xhtml:li> <xhtml:li> Elisabeth
Juliane Friederica Bach</xhtml:li> <xhtml:ul> <xhtml:h5> Children of
Elisabeth Juliane Friederica Bach</xhtml:h5> <xhtml:li> Johann Sebastian
Altnickol</xhtml:li> </xhtml:ul> <xhtml:li> Johanna Carolina Bach</
xhtml:li> <xhtml:li> Regina Susanna Bach</xhtml:li> <xhtml:li> Six
more children who did not live to adulthood</xhtml:li> </xhtml:ul> </
xhtml:div> </formattingExtension> </biogHist>

```

[Table of Contents](#)

< citedRange >

Cited Range

Summary

An optional child element of [< source >](#) that identifies precisely where supporting evidence was found within the source.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[source](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
unit	Optional

Attribute usage

Use the optional [@unit](#) attribute to specify the format that the [< citedRange >](#) refers to, for example page number or volume number.

Description and Usage

The [< citedRange >](#) element can be used to refer to a specific location within a source where supporting evidence can be found. It may refer to a specific location such as a single page, or a broader location such as a range of pages.

Availability

Optional, repeatable

Examples

```
<source id="source1" href="https://www.theguardian.com/
books/2018/aug/10/langston-hughes-born-a-year-before-
accepted-date-poet"> <reference>Flood, Alison <referringString
referredEntityType="title">"Langston Hughes 'born a year before accepted
date', researcher finds," </referringString> The Guardian. Published 10
August 2018. </reference> <citedRange unit="page">1 </citedRange>
<descriptiveNote> <p>Poet researching archives of local African American
newspaper finds story reporting on 'little Langston' before his recorded birth
date</p> </descriptiveNote> </source>
```

[Table of Contents](#)

< componentEntry >

Component Entry

Summary

A child element of [<setComponent>](#) that can be used to provide identification and access to a linked resource.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[setComponent](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[< componentEntry >](#) is used within [<setComponent>](#) to provide a textual note about the alternative authority record that is being bundled together with others describing the same entity. The bundled alternative records for a given EAC-CPF entity may be in different languages or come from different authority systems. The bundling allows them to be transmitted or stored together. The [< componentEntry >](#) element provides a place where a particular alternative record can be described or explained in relation to the other authority records.

Availability

Optional, repeatable

Examples

See [<alternativeSet>](#) encoding

[Table of Contents](#)

<contact>

Contact

Summary

An optional child element of [<place>](#) that binds together one or more [<contactLine>](#) elements to encode contact details or digital addresses.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
contactLine	1..n

May occur within

[place](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[<contact>](#) is an optional wrapper element within [<place>](#) used to encode digital addresses and contact information.

[<contact>](#) must include one or more [<contactLine>](#) element(s) that provide relevant contact details for the entity being described.

Availability

Optional, repeatable

See also

Use [<address>](#) to encode a physical or analog address.

Examples

```
<contact audience="external" id="IDcontact1"> <contactLine  
contactLineType="phoneNumber">08-402 60 00</contactLine>  
<contactLine languageOfElement="se" contactLineType="homepage"  
href="https://www.kungahuset.se/2.1c3432a100d8991c5b80001816.html"  
linkTitle="Besök vår hemsida"/> <contactLine languageOfElement="en"  
contactLineType="homepage" href="https://www.kungahuset.se/  
royalcourt.4.367010ad11497db6cba800054503.html" linkTitle="Visit our  
website"/> </contact>
```

[Table of Contents](#)

< contactLine >

Contact Line

Summary

A required child element of [< contact >](#) used for recording one line of contact details or digital addresses.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[contact](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
contactLineType	Optional
conventionDeclarationReference	Optional
href	Optional
id	Optional
languageOfElement	Optional
linkRole	Optional
linkTitle	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use the optional [@contactLineType](#) attribute to encode the type of contact detail that the [< contactLine >](#) refers to, for example "phoneNumber".

Use [@contactLineTypeEncoding](#) in [< control >](#) to specify the source or rules for values supplied in [@contactLineType](#).

Description and Usage

[< contactLine >](#) is used to encode separate details or lines of contact details or digital addresses within a parent [< contact >](#) element.

[< contactLine >](#) may be repeated as many times as necessary to enter all relevant contact details.

Availability

Required, repeatable

Examples

```
< contact audience = "external" id = "IDcontact1" > < contactLine  
contactLineType = "phoneNumber" > 08-402 60 00 < /contactLine >  
< contactLine languageOfElement = "se" contactLineType = "homepage"  
href = "https://www.kungahuset.se/2.1c3432a100d8991c5b80001816.html"  
linkTitle = "Besök vår hemsida" / > < contactLine languageOfElement = "en"  
contactLineType = "homepage" href = "https://www.kungahuset.se/  
royalcourt.4.367010ad11497db6cba800054503.html" linkTitle = "Visit our  
website" / < /contact >
```

[Table of Contents](#)

< control >

Control

Summary

A required child element of the root element that contains information about the creation, maintenance, status and the rules and authorities used in the composition of the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
conventionDeclaration	0..n
languageDeclaration	0..n
localTypeDeclaration	0..n
maintenanceAgency	1..1
maintenanceHistory	1..1
otherRecordId	0..n
recordId	1..1
rightsDeclaration	0..n
sources	0..1

May occur within

[eac](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
addressLineTypeEncoding	Optional (values limited to: EASList, otherAddressLineTypeEncoding)
agentTypeEncoding	Optional (values limited to: EASList, otherAgentTypeEncoding)
audience	Optional
audienceEncoding	Optional (values limited to: EASList, otherAudienceEncoding)
contactLineTypeEncoding	Optional (values limited to: EASList, otherContactLineTypeEncoding)
countryEncoding	Optional (values limited to: iso3166-1-alpha-2, iso3166-1-alpha-3, iso3166-1-numeric, iso3166-2, iso3166-3, other-CountryEncoding)

<i>Attribute name</i>	<i>Attribute values</i>
dateEncoding	Optional (values limited to: iso8601, otherDateEncoding)
detailLevel	Optional
detailLevelEncoding	Optional (values limited to: EASList, otherDetailLevelEncoding)
id	Optional
identityTypeEncoding	Optional (values limited to: EASList, otherIdentityTypeEncoding)
languageEncoding	Optional (values limited to: ietf-bcp-47, iso639-1, iso639-2, iso639-2b, iso639-2t, iso639-3, iso639-5, other-LanguageEncoding)
languageOfElement	Optional
maintenanceEventTypeEncoding	Optional (values limited to: EASList, otherMaintenanceEventTypeEncoding)
maintenanceStatus	Optional
maintenanceStatusEncoding	Optional (values limited to: EASList, otherMaintenanceStatusEncoding)
placeTypeEncoding	Optional (values limited to: EASList, otherPlaceTypeEncoding)
publicationStatus	Optional
publicationStatusEncoding	Optional (values limited to: EASList, otherPublicationStatusEncoding)
referredEntityTypeEncoding	Optional (values limited to: EASList, otherReferredEntityTypeEncoding)
relationTypeEncoding	Optional (values limited to: EASList, otherRelationTypeEncoding)
repositoryEncoding	Optional (values limited to: iso15511, otherRepositoryEncoding)
scriptEncoding	Optional (values limited to: iso15924, otherScriptEncoding)
scriptOfElement	Optional
statusEncoding	Optional (values limited to: EASList, otherStatusEncoding)
target	Optional
targetTypeEncoding	Optional (values limited to: EASList, otherTargetTypeEncoding)

Attribute usage

Use the optional [@maintenanceStatus](#), [@publicationStatus](#), and [@detailLevel](#) attributes to document the current version status of the EAS instance, its current editorial status and the current level of detail included in its descriptive sections.

Use the optional encoding attributes such as [@countryEncoding](#), [@maintenanceEventTypeEncoding](#) or [@relationTypeEncoding](#) to specify the

source or rules for values supplied in those attributes used throughout the EAS instance that rely either on code lists from ISO standards or make use of the value lists defined and maintained by the Technical Subcommittee on Encoded Archival Standards (TS-EAS). Should you decide to use other authorized value lists in these attributes instead, it is highly recommended to indicate this by using the "other..." value in the encoding attributes and to name and refer to these other value lists in [<conventionDeclaration>](#) to still enable semantic interoperability.

Description and Usage

This required wrapper element within the root element of an EAS instance contains the information necessary to manage the instance itself. This includes information about its creation, maintenance and status as well as the languages, rules and authorities used in the composition of the description. It must contain a unique identifier for the instance within the [<recordId>](#) element. Other associated identifiers may be given in [<otherRecordId>](#). There must be a description of the agency responsible for its creation and maintenance in [<maintenanceAgency>](#) as well as statements about the creation, maintenance, and disposition of the instance, as applicable, in [<maintenanceHistory>](#).

There are optional elements available to declare languages, rules, conventions and sources used in the EAS instance and licensing information about the EAS instance itself. Local types for certain elements used throughout the EAS instance are recommended to be defined in the [<localTypeDeclaration>](#) element.

The available child elements (both required and optional), in their prescribed order, are:

[<recordId>](#) - Required. Contains the unique identifier for the EAS instance.

[<maintenanceAgency>](#) - Required. Contains the name and coded information about the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance.

[<maintenanceHistory>](#) - Required. Contains information about the date, type and events within the life cycle of an EAS instance.

[<sources>](#) - Optional. Contains information about the sources consulted in creating the descriptive parts of the EAS instance.

The following elements may appear in any order after the above elements:

[<conventionDeclaration>](#) - Optional. Contains information on the rules or conventions used to construct the EAS instance.

[< languageDeclaration >](#) - Optional. Contains coded and natural language information about the language or languages of the EAS instance.

[< localTypeDeclaration >](#) - Optional. Contains information about local conventions used in the [@localType](#) attribute.

[< otherRecordId >](#) - Optional. An element that allows the recording of additional identifiers that may be associated with the EAS instance.

[< rightsDeclaration >](#) - Optional. Contains information about the usage rights of the EAS instance.

Availability

Required, not repeatable

Examples

See [< control >](#) encoding

[Table of Contents](#)

< conventionDeclaration >

Convention Declaration

Summary

An optional child element of [< control >](#) , used to declare the rules or conventions, including authorized controlled vocabularies and thesauri, applied in creating the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
reference	1..1
shortCode	0..1

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[< conventionDeclaration >](#) is used for declaring references to any rules and conventions, including authorized controlled vocabularies or thesauri, applied in the construction of the description. The element binds together the required [< reference >](#) element with optional [< shortCode >](#) and [< descriptiveNote >](#) elements that identify rules or conventions applied in compiling the EAS instance.

Each additional rule or set of rules, controlled vocabulary, or standard should be contained in a separate [< conventionDeclaration >](#) .

`<shortCode>` may be used to identify the standard or controlled vocabulary in a coded structure. Any notes relating to how these rules or conventions have been used may be given within `<descriptiveNote>` .

Use `<conventionDeclaration>` to name and refer to other authorized value lists, if you use these instead of the EAS lists or ISO standards available with the optional encoding attributes in `<control>` (e.g. `@countryEncoding`, `@maintenanceEventTypeEncoding` or `@relationTypeEncoding`). It is recommended that `<reference>` includes a link to these other value lists to still enable semantic interoperability.

The prescribed order of all child elements (both required and optional) is:

`<reference>`

`<shortCode>`

`<descriptiveNote>`

Availability

Optional, repeatable

See also

Use `<localTypeDeclaration>` to indicate any local or consortial value lists that you might use with `@localType` throughout the EAS instance.

Examples

```
<conventionDeclaration id="cd1"> <reference href="https://
www.legifrance.gouv.fr/loda/id/JORFTEXT000033553530/"> Décret
n° 2016-1689 du 8 décembre 2016 fixant le nom, la composition et le
chef-lieu des circonscriptions administratives régionales - Légifrance</
reference> </conventionDeclaration> <conventionDeclaration
id="cd2"> <reference href="https://deliberation.maregionsud.fr/docs/
ASSEMBLEEPLENIERE/2017/12/15/DELIBERATION/D0V0Q.pdf">
DELIBERATION N° 17-1166, 15 DECEMBRE 2017</reference> </
conventionDeclaration> <conventionDeclaration id="cd3"> <reference
href="cnig.gouv.fr/wp-content/uploads/2015/03/CNT-site-collectivit
%C3%A9s-fran%C3%A7aises.pdf"> Commission nationale de toponymie:
Collectivités territoriales françaises</reference> </conventionDeclaration>
<control dateEncoding="iso8601" languageEncoding="ietf-
bcp-47" repositoryEncoding="otherRepositoryEncoding"
maintenanceEventTypeEncoding="EASList"
agentTypeEncoding="otherAgentTypeEncoding"> [...] <maintenanceAgency
countryCode="EE"> <agencyCode status="authorized"> ErTrt-
ElvRK</agencyCode> <agencyName> Elva Linnaraamatukogu</
agencyName> </maintenanceAgency> <maintenanceHistory>
```

```

< maintenanceEvent maintenanceEventType = "created" > < agent
agentType = "prov:SoftwareAgent" > < label > teisendusskript A2B.xsl < /
label > < / agent > < eventDateTime standardDateTime = "2025-04-16" / > < /
maintenanceEvent > < / maintenanceHistory > [...] < conventionDeclaration
id = "repositoryCode" > < reference href = "https://www.rara.ee/wp-content/
uploads/koik_koodid_22.04.2025.csv" > Kataloogimiskohad < / reference >
< descriptiveNote > < p languageOfElement = "et-EE" > Kataloogimiskohad
(välja andnud Eesti Rahvusraamatukogu) < / p > < p languageOfElement = "en-
GB" > Cataloguing Source Codes (issued by the National Library of Estonia) < /
p > < / descriptiveNote > < / conventionDeclaration > < conventionDeclaration
id = "agentType" > < reference href = "https://www.w3.org/TR/2013/REC-
prov-dm-20130430/#term-agent" > PROV-DM agent types < / reference > < /
conventionDeclaration > < / control >

```

[Table of Contents](#)

< cpfDescription >

CPF Description

Summary

A wrapper element that binds together the descriptive information of one CPF identity.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
alternativeSet	0..1
description	0..1
identity	1..1
relations	0..1

May occur within

[eac](#), [multipleIdentities](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use the [@id](#) attribute to identify individual [< cpfDescription >](#) elements when using the [< multipleIdentities >](#) structure.

Description and Usage

[< cpfDescription >](#) contains the description of one identity. The [< cpfDescription >](#) includes a required [< identity >](#) element containing the entity type and authorized or alternative name entries. It also includes the optional [< description >](#) and [< relations >](#) elements that provide contextual

information about the CPF entity being described, including the relations to other corporate bodies, persons, families, resources, and functions.

An optional [<alternativeSet>](#) element allows the incorporation of one or more authority records derived from one or more authority systems.

The prescribed order of all child elements (both required and optional) is:

[<identity>](#)

[<description>](#)

[<relations>](#)

[<alternativeSet>](#)

Availability

Within [<eac>](#) : one of [<cpfDescription>](#) or [<multipleIdentities>](#) required, not repeatable

Within [<multipleIdentities>](#) : two or more [<cpfDescription>](#) required, repeatable

Examples

See [<eac>](#) encoding

[Table of Contents](#)

< date >

Date

Summary

An element for encoding a single date relating to the entity or materials being described, or in their relationship to other entities.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[agent](#), [dateSet](#), [demographicDescription](#), [existDates](#), [functionPerformed](#), [legalStatus](#), [localDescription](#), [mandate](#), [narrativeEvent](#), [occupation](#), [otherEntityType](#), [place](#), [relation](#), [useDates](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
calendar	Optional
certainty	Optional
conventionDeclarationReference	Optional
era	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
notAfter	Optional
notBefore	Optional
scriptOfElement	Optional
standardDate	Optional
status	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@certainty](#) to indicate the degree of precision in the dating, for example, "uncertain" or "approximate".

Use [@localType](#) to supply a more specific characterization of the date.

Use [@notAfter](#) and [@notBefore](#) to capture the latest and earliest possible dates in machine-processable form in cases when the date is uncertain.

Use [@standardDate](#) to provide a machine-processable form of the date.

Use [@status](#) e.g. with the value "unknown" to indicate where a date is unknown.

Description and Usage

An element for expressing the single date of an event in the history of the person, corporate body or family being described, or in their relationship to, e.g., a name entry, a place, an occupation, another CPF entity, a resource, or a function.

The content of the element is intended to be a human-readable natural language date with a machine-readable date provided as the value of the [@standardDate](#) attribute, formulated according to ISO 8601 or another rule for encoding dates as defined by [@dateEncoding](#) within [<control>](#). Uncertain or approximate dates can be encoded in [@standardDate](#) using Extended Date/Time Format (EDTF).

Availability

Within [<agent>](#), [<demographicDescription>](#), [<functionPerformed>](#), [<legalStatus>](#), [<localDescription>](#), [<mandate>](#), [<occupation>](#), [<otherEntityType>](#), [<place>](#), [<relation>](#): one of [<date>](#), [<dateRange>](#), or [<dateSet>](#) optional, not repeatable

Within [<existDates>](#) and [<useDates>](#): one of [<date>](#), [<dateRange>](#), or [<dateSet>](#) required, not repeatable

Within [<narrativeEvent>](#): required, repeatable

Within [<dateSet>](#): at least two of [<date>](#) and/or [<dateRange>](#) required, repeatable

See also

If the event or relationship has inclusive dates use the [<dateRange>](#) element, while more complex dates (combining singles dates and date ranges) can be expressed in [<dateSet>](#).

Dates of existence for the entity being described are encoded with the [<existDates>](#) element, while the dates of use of a particular name of an entity are encoded in [<useDates>](#).

The date and time of a maintenance event in the history of the EAS instance are given in the [<eventDateTime>](#) element.

Examples

<date standardDate="1765-09-18">September 18, 1765</date> <date
certainty="uncertain" standardDate="1968?">c.1968</date>

[Table of Contents](#)

< dateRange >

Date Range

Summary

A wrapper element for binding together [< fromDate >](#) and [< toDate >](#) in order to represent a range of dates. Either [< fromDate >](#) or [< toDate >](#) must be present within a [< dateRange >](#) , but it is recommended to use both child elements whenever possible.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
fromDate	0..1
toDate	0..1

May occur within

[agent](#), [dateSet](#), [demographicDescription](#), [existDates](#), [functionPerformed](#), [legalStatus](#), [localDescription](#), [mandate](#), [narrativeEvent](#), [occupation](#), [otherEntityType](#), [place](#), [relation](#), [useDates](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@localType](#) to supply a more specific characterization of the date range.

Description and Usage

An element that expresses inclusive dates of an event in the history of, or a relationship with, the person, family, or corporate body being described in the EAC-CPF instance.

`<dateRange>` contains `<fromDate>` and/or `<toDate>` , and therefore may express a range of dates as a starting point with no end point, a start and end point, or an end point with no starting point. Either `<fromDate>` or `<toDate>` must be present within a `<dateRange>` , but it is recommended to use both child elements whenever possible.

The content of the children of `<dateRange>` is intended to be a human-readable, natural language expression of the dates. If, however, indexing or other machine processing of dates is desired, `@standardDate` should be used on the children of `<dateRange>` to record the date in machine-processable form as well.

The prescribed order of all child elements (both required and optional) is:

`<fromDate>`

`<toDate>`

Availability

Within `<agent>` , `<demographicDescription>` , `<functionPerformed>` , `<legalStatus>` , `<localDescription>` , `<mandate>` , `<occupation>` , `<otherEntityType>` , `<place>` , `<relation>` : one of `<date>` , `<dateRange>` , or `<dateSet>` optional, not repeatable

Within `<existDates>` and `<useDates>` : one of `<date>` , `<dateRange>` , or `<dateSet>` required, not repeatable

Within `<dateSet>` : at least two of `<date>` and/or `<dateRange>` required, repeatable

See also

If the event or relationship has single dates use the `<date>` element, while more complex dates (combining singles dates and date ranges) can be expressed in `<dateSet>` .

Dates of existence for the entity being described are encoded with the `<existDates>` element, while the dates of use of a particular name of an entity are encoded in `<useDates>` .

The date and time of a maintenance event in the history of the EAS instance are given in the `<eventDateTime>` element.

Examples

```
<dateRange> <fromDate standardDate="1765-08-18">September
18, 1765</fromDate> <toDate standardDate="1846-06-01">June
1, 1846</toDate> </dateRange> <dateRange> <fromDate
standardDate="1912-01-01">1912</fromDate> <toDate status="ongoing"/
```

> </dateRange> <dateRange> <fromDate status="unknown"/> <toDate
standardDate="2010-12-31"> 2010</toDate> </dateRange>

[Table of Contents](#)

<dateSet>

Date Set

Summary

A wrapper element for encoding complex dates that cannot be adequately represented in one [<date>](#) or [<dateRange>](#) .

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange	2..n

May occur within

[agent](#), [demographicDescription](#), [existDates](#), [functionPerformed](#), [legalStatus](#), [localDescription](#), [mandate](#), [occupation](#), [otherEntityType](#), [place](#), [relation](#), [useDates](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[<dateSet>](#) binds together single dates and date ranges, multiple single dates, or multiple date ranges. [<dateSet>](#) is used in situations where complex date information needs to be conveyed and requires at least two child elements. These can be any combination of [<date>](#) and [<dateRange>](#) .

Availability

Within [<agent>](#) , [<demographicDescription>](#) , [<functionPerformed>](#)
 , [<legalStatus>](#) , [<localDescription>](#) , [<mandate>](#) , [<occupation>](#)
 , [<otherEntityType>](#) , [<place>](#) , [<relation>](#) : one of [<date>](#) ,
 [<dateRange>](#) , or [<dateSet>](#) optional, not repeatable
 Within [<existDates>](#) , [<useDates>](#) : one of [<date>](#) , [<dateRange>](#) , or
 [<dateSet>](#) required, not repeatable

Examples

```
<dateSet> <dateRange> <fromDate standardDate="1928-09">1928  
settembre</fromDate> <toDate standardDate="1930-08">1930  
autunno</toDate> </dateRange> <dateRange> <fromDate  
standardDate="1947">1947</fromDate> <toDate  
standardDate="1949">1949</toDate> </dateRange> <date>1950</  
date> <date standardDate="1951-10-27">27 ottobre 1951</date> </  
dateSet>
```

[Table of Contents](#)

< demographicDescription >

Demographic Description

Summary

A required child element of [< demographicDescriptions >](#) that can be used to provide demographic information about the CPF entity being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..n
placeName	0..n
term	1..n

May occur within

[demographicDescriptions](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[< demographicDescription >](#) is a wrapper element used to encode an index term, using the required child element [< term >](#) .

Terms are used within [< demographicDescription >](#) to encode demographic information about the CPF entity being described. This could include, but is not

limited to, nationality, gender, age group, or religion. They may be drawn from controlled vocabularies or may be natural language terms.

[<demographicDescription>](#) must include at least one [<term>](#) element.

[<term>](#) can be repeated within [<demographicDescription>](#) to include translations of the same term. Use the [@languageOfElement](#) attribute to identify the language used in each [<term>](#) .

Associated date(s) ([<date>](#) , [<dateRange>](#) , or [<dateSet>](#)) and place(s) ([<placeName>](#)) may be included to further constrain the term's meaning. A [<descriptiveNote>](#) may be included if a fuller textual explanation is needed.

The prescribed order of all child elements (both required and optional) is:

[<term>](#)

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<placeName>](#)

[<descriptiveNote>](#)

Availability

Required, repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

< demographicDescriptions >

Demographic Descriptions

Summary

An optional child element of < description > used to group together one or more < demographicDescription > elements.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
demographicDescription	1..n
descriptiveNote	0..1

May occur within

description

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use the optional < demographicDescriptions > element to group together one or more occurrences of < demographicDescription > . < demographicDescriptions > must include at least one < demographicDescription > element.

The prescribed order of all child elements (both required and optional) is:

< demographicDescription >

< descriptiveNote >

Availability

Optional, not repeatable

Examples

See [<description>](#) examples

[Table of Contents](#)

< description >

Description

Summary

An optional child element of [< cpfDescription >](#) , [< description >](#) is a wrapper element for all of the content elements comprising descriptive information about the CPF entity.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
biogHist	0..n
demographicDescriptions	0..1
existDates	0..n
functionsPerformed	0..1
generalContext	0..n
languagesUsed	0..1
legalStatuses	0..1
localDescriptions	0..1
mandates	0..1
occupations	0..1
places	0..1
structureOrGenealogy	0..n

May occur within

[cpfDescription](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

The child elements that constitute `<description>` together permit descriptive information to be encoded in either structured or unstructured fashions, or in a combined approach. `<description>` accommodates the encoding of all the data elements that comprise the Description Area of ISAAR (CPF) including historical, biographical, and genealogical information; legal status and mandates; functions, occupations, and activities, and the dates and places that further constrain those elements.

The prescribed order of all child elements (both required and optional) is:

`<demographicDescriptions>`

`<functionsPerformed>`

`<languagesUsed>`

`<legalStatuses>`

`<localDescriptions>`

`<mandates>`

`<occupations>`

`<places>`

Any of `<biogHist>` , `<existDates>` , `<generalContext>` , and `<structureOrGenealogy>`

Availability

Optional, not repeatable

Examples

```
<description> <places> <place> <label vocabularySource="local"
id="IDPlaceName1">East Side (Buffalo, N.Y.)</label>
<geographicCoordinates coordinateSystem="WGS84">N 42°53'48"
W 78°50'2"</geographicCoordinates> </place> </places>
<functionsPerformed> <functionPerformed valueURI="http://
vocab.getty.edu/page/aat/300055433" vocabularySource="aat"
vocabularySourceURI="https://www.getty.edu/research/tools/vocabularies/
aat/"> <term>community development</term> <placeName
target="IDPlaceName1">East Side (Buffalo, N.Y.)</placeName>
<descriptiveNote> <p>The organization's mission is to create programs to
improve the quality of residential housing and develop projects to improve the
East Side of Buffalo and Western New York.</p> </descriptiveNote> </
functionPerformed> </functionsPerformed> </description>
```

Table of Contents

< descriptiveNote >

Descriptive Note

Summary

An element used to provide general descriptive information related to its parent element, either as narrative text or encoded in a related standard.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
objectXMLWrap	0..1
p	1..n

May occur within

[agent](#), [conventionDeclaration](#), [demographicDescription](#), [demographicDescriptions](#), [existDates](#), [functionPerformed](#), [functionsPerformed](#), [identity](#), [languageDeclaration](#), [languageUsed](#), [languagesUsed](#), [legalStatus](#), [legalStatuses](#), [localDescription](#), [localDescriptions](#), [localTypeDeclaration](#), [maintenanceAgency](#), [mandate](#), [mandates](#), [occupation](#), [occupations](#), [otherEntityType](#), [otherEntityTypes](#), [place](#), [places](#), [relation](#), [relations](#), [rightsDeclaration](#), [setComponent](#), [source](#), [sources](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[< descriptiveNote >](#) provides additional descriptive information about the element in which it is contained. [< descriptiveNote >](#) must contain one or more [< p >](#) elements.

With the optional element [< objectXMLWrap >](#) , [< descriptiveNote >](#) also allows for the inclusion of information encoded in other formats and standards

that add further details to its parent element which could not be encoded in the EAS.

Availability

Optional, not repeatable

Examples

```
<functionPerformed valueURI="http://vocab.getty.edu/page/aat/300055433"
vocabularySource="aat" vocabularySourceURI="https://www.getty.edu/
research/tools/vocabularies/aat/" > <term>community development</
term> <placeName target="IDPlaceName1">East Side (Buffalo, N.Y.)</
placeName> <descriptiveNote> <p>The organization's mission is to
create programs to improve the quality of residential housing and develop
projects to improve the East Side of Buffalo and Western New York.</p>
</descriptiveNote> </functionPerformed> <languageOfMaterial>
<languageSet> <writingSystem scriptCode="Latn">Latin</
writingSystem> <language languageCode="eng">English</language>
<language languageCode="ang">Old English</language> <language
languageCode="lat">Latin</language> </languageSet> <languageSet>
<language languageCode="gre">Greek</language> <writingSystem
scriptCode="Grek">Greek</writingSystem> </languageSet>
<descriptiveNote> <p>The majority of the documents are written
in Modern English. Roberts copied multiple passages from original
manuscripts in Latin, Greek and Old English.</p> </descriptiveNote> </
languageOfMaterial>
```

[Table of Contents](#)

< eac >

Encoded Archival Context - Corporate Bodies, Persons, and Families

Summary

The required root element of an EAC-CPF instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
control	1..1
cpfDescription or multipleIdentities	1..1

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional

Description and Usage

[< eac >](#) wraps all other elements in a particular instance of an archival authority record encoded with the EAC-CPF XML Schema.

[< eac >](#) must contain [< control >](#) followed by either a [< cpfDescription >](#) or a [< multipleIdentities >](#) element.

In order to validate an EAC-CPF instance, it is highly recommended to include according information about the EAC-CPF namespace and the EAC-CPF schema location.

Availability

Required, not repeatable

Examples

See [< eac >](#) encoding

[Table of Contents](#)

< entityType >

< entityType >

Entity Type

Summary

A required child element of < identity > encoding the type of CPF entity being described.

May contain

Element/content type	Occurrences
[empty]	

May occur within

identity

Attributes

Attribute name	Attribute values
audience	Optional
id	Optional
target	Optional
value	Required (values limited to: corporate-Body, family, person)

Attribute usage

Use the required @value attribute with one of the values "corporateBody", "family", or "person" to identify the type of entity.

Description and Usage

Within < identity > the required < entityType > element specifies the type of CPF entity being described in the EAC-CPF instance as being a corporate body, family or person.

Availability

Required, not repeatable

See also

Use [<otherEntityType>](#) to encode additional or alternative entity types, such as a translation or a specification of the default entity types.

Examples

See [<identity>](#) encoding

[Table of Contents](#)

<eventDateTime>

Maintenance Event Date and Time

Summary

A required child element of [<maintenanceEvent>](#) that records the date and time of a specific maintenance action for an EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[maintenanceEvent](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
standardDateTime	Optional
target	Optional

Attribute usage

Use [@standardDateTime](#) to provide a machine-processable expression of the date or date and time, formulated according to the ISO 8601 standard.

Description and Usage

A required child element of [<maintenanceEvent>](#) , [<eventDateTime>](#) is for recording the date and time that a maintenance event occurred. Examples of maintenance events include the creation, update, revision, or other modification to an EAS instance, e.g. in the context of reparative description or as a result of applying Artificial Intelligence models for improving the description.

The date and time may be captured in natural language in the element. It is highly recommended to provide at least a human-readable date

in [<eventDateTime>](#) directly or a machine-processable date in [@standardDateTime](#), in case it is not possible to provide both.

Availability

Required, not repeatable

Examples

```
<maintenanceEvent maintenanceEventType="revised">
  <agent agentType="unknown"> <label/> <eventDateTime
standardDateTime="2021-11-27"/> </maintenanceEvent>
  <maintenanceEvent maintenanceEventType="updated"> <agent
agentType="human"> <label>K. Bredenberg</label> </
agent> <eventDateTime>December 2021</eventDateTime> </
maintenanceEvent>
```

[Table of Contents](#)

<eventDescription>

Event Description

Summary

An optional child element of [<maintenanceEvent>](#) and [<narrativeEvent>](#) that provides the description of a maintenance event in the life of the EAS instance respectively the description of an event in the life of the CPF entity described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[maintenanceEvent](#), [narrativeEvent](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

A child element of [<maintenanceEvent>](#) used for describing the maintenance event and of [<narrativeEvent>](#) used for describing a chronology of events in the life of the CPF entity described. The element allows a full description of the event to be given alongside information about the time and date of the event, the agent involved, and - in the context of [<maintenanceEvent>](#) - the type respectively - in the context of [<narrativeEvent>](#) - the place of the event.

Availability

Optional, repeatable

Examples

```
<maintenanceEvent maintenanceEventType="derived"> <agent
agentType="machine"> <label>export.xml/Saxon B9</label> </agent>
<eventDateTime standardDateTime="2024-08-30T09:37:17.029-04:00"/>
<eventDescription>Derived from local collection management system</
eventDescription> </maintenanceEvent> <biogHist> <narrativeEvent>
<date standardDate="1964-10">October 1964</date> <agent
agentType="group"> <label>Labour government</label> </agent>
<eventDescription>Created the new office of Secretary of State for Economic
Affairs (combined with First Secretary of State) and set up the Department of
Economic Affairs under the Ministers of the Crown Act 1964 to carry primary
responsibility for long term economic planning.</eventDescription> </
narrativeEvent> <narrativeEvent> <date standardDate="1964-10-16">16
October 1964</date> <agent agentType="person"> <label>George
Brown</label> </agent> <eventDescription>Appointed as First Secretary
of State and Secretary of State for Economic Affairs, and as chairman of the
National Economic Development Council (NEDC).</eventDescription>
</narrativeEvent> [...] </biogHist> <biogHist> <narrativeEvent>
<date standardDate="1964-10">October 1964</date> <agent
agentType="group"> <label>Labour government</label> </agent>
<eventDescription>Created the new office of Secretary of State for Economic
Affairs (combined with First Secretary of State) and set up the Department of
Economic Affairs under the Ministers of the Crown Act 1964 to carry primary
responsibility for long term economic planning.</eventDescription> </
narrativeEvent> <narrativeEvent> <date standardDate="1964-10-16">16
October 1964</date> <agent agentType="person"> <label>George
Brown</label> </agent> <eventDescription>Appointed as First Secretary
of State and Secretary of State for Economic Affairs, and as chairman of the
National Economic Development Council (NEDC).</eventDescription> </
narrativeEvent> [...] </biogHist>
```

[Table of Contents](#)

< existDates >

Dates of Existence

Summary

An optional element within [<description>](#) used for encoding the dates of existence of the CPF entity being described, such as dates of establishment and dissolution for corporate bodies and dates of birth and death or floruit for persons.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	1..1
descriptiveNote	0..1

May occur within

[description](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

The dates of existence of the CPF entity being described, such as dates of establishment and dissolution for corporate bodies and dates of birth and death or floruit for persons.

[< existDates >](#) must contain one of [< date >](#) , [< dateRange >](#) , or [< dateSet >](#) . These child elements may contain actual or approximate dates. A [< descriptiveNote >](#) may be included if a fuller explanation of the dates of existence is needed.

Use the [<date>](#) element to record the date of a single event, such as a date of birth or date of incorporation. Use [<dateRange>](#) to encode a pair of inclusive dates. Use [<dateSet>](#) to encode more complex date expressions that intermix [<date>](#) and [<dateRange>](#) elements.

The prescribed order of all child elements (both required and optional) is:

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<descriptiveNote>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<useDates>](#) , which is a child element of [<nameEntry>](#) or [<nameEntrySet>](#) and represents the dates of use for a particular name or set of names.

Examples

See [<description>](#) encoding

[Table of Contents](#)

<formattingExtension>

Formatting Extension

Summary

An optional, wrapping element that may be utilized to encode more complex formatting features that are not part of the EAS data model such as lists, tables, nested headers, etc. When using the EAS-provided NVDL Schema validation procedure, this element will require that all elements encoded within are from the XHTML namespace.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[Any element that is in a namespace other than the current namespace]	

May occur within

biogHist, generalContext, structureOrGenealogy

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
target	Optional

Description and Usage

<formattingExtension> provides the option to embed external namespaces directly within the source file, when complex formatting is required. It should preferably be used for embedding XHTML data. When using this element, it is recommended that the EAS file is associated with the EAS NVDL for validation purposes.

Availability

Optional, not repeatable
In these narrative contexts, the encoder must choose between using a <formattingExtension> element (to wrap XHTML content), or using one or more <p> elements that are defined within the current EAS schema.

Examples

See encoding examples in parent elements of [<formattingExtension>](#) , e.g. in [<biogHist>](#) .

[Table of Contents](#)

<fromDate>

From Date

Summary

A child element of [<dateRange>](#) that records the starting point in a range of dates.

May contain

Element/content type
[text]

Occurrences

May occur within

[dateRange](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
calendar	Optional
certainty	Optional
conventionDeclarationReference	Optional
era	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
notAfter	Optional
notBefore	Optional
scriptOfElement	Optional
standardDate	Optional
status	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@certainty](#) to indicate the degree of precision in the dating, for example, "uncertain" or "approximate".

Use [@localType](#) to supply a more specific characterization of the start date.

Use [@notAfter](#) and [@notBefore](#) to capture the latest and earliest possible dates in machine-processable form in cases when the date is uncertain.
Use [@standardDate](#) to provide a machine-processable form of the date.
Use [@status](#) with the value "unknown" to indicate where the start of a date range is unknown.

Description and Usage

Use [<fromDate>](#) to record the beginning date in a range of dates.
[<fromDate>](#) may contain actual, approximate or unknown dates. The content of the element is intended to be a human-readable, natural language expression of the date. If, however, indexing or other machine processing of dates is desired, the [@standardDate](#) should be used to record the date in machine-processable form as well. If the [<fromDate>](#) is not known, it may be omitted from [<dateRange>](#) , or the [@status](#) attribute used.

Availability

Optional, not repeatable

See also

Use [<toDate>](#) to record the ending point of a date range.

Examples

```
<dateRange> <fromDate standardDate="1868"> 1868 </  
fromDate> <toDate standardDate="1936"> 1936 </toDate> </  
dateRange> <dateRange> <fromDate status="unknown"/> <toDate  
certainty="uncertain" standardDate="2010?"> c.2010 </toDate> </  
dateRange>
```

[Table of Contents](#)

<functionPerformed>

Function Performed

Summary

A required child element of [<functionsPerformed>](#) that provides information about a function, activity, role, or purpose performed by the CPF entity being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	(0..1)
descriptiveNote	(0..1)
placeName	(0..n)
term	(1..n)

May occur within

[functionsPerformed](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

A [<functionPerformed>](#) element is a wrapper element used to encode an index term, using the required child element [<term>](#) . Terms are used to identify the functions, processes, activities, tasks, or transactions performed

by the CPF entity. They may be drawn from controlled vocabularies or may be natural language terms.

[<functionPerformed>](#) must include at least one [<term>](#) element.

[<term>](#) can be repeated within [<functionPerformed>](#) to include translations of the same function. Use the [@languageOfElement](#) attribute to identify the language used in each [<term>](#) .

Associated date(s) ([<date>](#) , [<dateRange>](#) , or [<dateSet>](#)) and place(s) ([<placeName>](#)) may be included to further constrain the term's meaning. A [<descriptiveNote>](#) may be included if a fuller textual explanation is needed. The prescribed order of all child elements (both required and optional) is:

[<term>](#)

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<placeName>](#)

[<descriptiveNote>](#)

Availability

Required, repeatable

See also

Use [<relation>](#) with [<targetEntity>](#) having the [@targetType](#) "function" when describing the relationship between the function and the CPF entity being described in more detail.

Examples

See [<description>](#) encoding

[Table of Contents](#)

< functionsPerformed >

Functions Performed

Summary

An optional child element of < description > used for grouping together one or more < functionPerformed > elements.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	(0..1)
functionPerformed	(1..n)

May occur within

description

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use the optional < functionsPerformed > element to group together one or more occurrences of < functionPerformed > . < functionsPerformed > must include at least one < functionPerformed > element.

The prescribed order of all child elements (both required and optional) is:

< functionPerformed >

< descriptiveNote >

Availability

Optional, not repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

< generalContext >

General Context

Summary

An optional child element of [< description >](#) that encodes information about the general social and cultural context of the CPF entity being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
formattingExtension	0..n
p	0..n

May occur within

[description](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[< generalContext >](#) encodes information about the social, cultural, economic, political, and/or historical context in which the CPF entity being described existed. The general context provides wide latitude to record contextual information not specifically accommodated by other elements contained in [< description >](#) .

The optional [< formattingExtension >](#) element may be used to accommodate greater complexity in expressing or representing the general context being described. A simpler discursive expression of the general context may be encoded as one or more [< p >](#) elements.

Availability

Optional, repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

< geographicCoordinates >

Geographic Coordinates

Summary

An optional child element of [< place >](#) that encodes a set of geographic coordinates.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[place](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
coordinateSystem	Required
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use the required [@coordinateSystem](#) attribute to provide a commonly used code for the system used to express the coordinates. Examples include WGS84, OSGB36, ED50.

Description and Usage

Use [< geographicCoordinates >](#) to express a set of geographic coordinates such as latitude, longitude, and altitude representing a point, line, or area on the surface of the earth.

It is recommended that the values included in [< geographicCoordinates >](#) are based on a commonly used system for expressing geographic coordinates.

Availability

Optional, repeatable

Examples

```
<places> <place> <label>Berlin, Germany</label>  
<geographicCoordinates coordinateSystem="mgrs">33UUU9029819737</  
geographicCoordinates> </place> <place placeType="populatedPlace">  
<label>Clear Spring</label> <address> <addressLine  
addressLineType="state">Maryland</addressLine> </address>  
<geographicCoordinates coordinateSystem="UTM">18S 248556mE  
4393694mN</geographicCoordinates> </place> <place  
placeType="populatedPlace"> <label>Hardeeville</label> <address>  
<addressLine addressLineType="state">South Carolina</addressLine> </  
address> <geographicCoordinates coordinateSystem="WGS84">-81.1, 32.2,  
-81.0, 32.3</geographicCoordinates> </place> </places>
```

[Table of Contents](#)

<identity>

Identity

Summary

A required child element of [<cpfDescription>](#) used to encode the name or names related to the identity being described within the EAC-CPF instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
entityType	1..1
identityId	0..n
nameEntry or nameEntrySet	1..n
otherEntityTypes	0..n

May occur within

[cpfDescription](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
identityType	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[<identity>](#) is a wrapper element used to group the elements necessary to encode the name or names related to the identity of the CPF entity within the [<cpfDescription>](#) element.

The required child element [<entityType>](#) specifies the type of entity (i.e., corporate body, family, or person). The optional [<otherEntityTypes>](#) element can be used to encode other entity types used in the local context. An

optional [<identityId>](#) is available for any identifiers associated with the CPF entity.

One or more [<nameEntry>](#) elements and/or one or more [<nameEntrySet>](#) elements must be included. All names by which the identity being described within one [<cpfDescription>](#) element is known are provided within [<identity>](#). Each of the names, whether authorized or alternatives, should be recorded in a separate [<nameEntry>](#) element.

[<identity>](#) may accommodate two or more parallel names in different languages or scripts. In countries where there is more than one official language, such as Canada or Switzerland, names of CPF entities are frequently provided in more than one language. Within [<identity>](#), a [<nameEntrySet>](#) element should be used to group two or more [<nameEntry>](#) elements that represent parallel forms of the name of the CPF entity being described.

Within [<identity>](#), a [<descriptiveNote>](#) element may be used to record other information in a textual form that assists in the identification of the CPF entity.

In case of multiple identities of the same entity in one EAC-CPF instance, such that multiple [<cpfDescription>](#) elements are used, a separate [<identity>](#) element is contained in each of the [<cpfDescription>](#) elements of the EAC-CPF instance.

The prescribed order of all child elements (both required and optional) is:

[<entityType>](#)

[<nameEntry>](#) and/or [<nameEntrySet>](#)

[<otherEntityTypes>](#)

[<identityId>](#)

[<descriptiveNote>](#)

Availability

Required, not repeatable

Examples

```
<identity> <entityType value="person"/> <nameEntry> <part
localType="familyname"> Hill </part> <part localType="givenname">
Dorothy </part> </nameEntry> </identity>
```

[Table of Contents](#)

<identityId>

<identityId>

Identity Identifier

Summary

An optional child element of [<identity>](#) used to record any identifier associated with the CPF entity being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[identity](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<identityId>](#) may be used to record any identifier associated with the CPF entity being described in the EAS instance. Identifiers such as legal identifiers, typically assigned by an authoritative agency, may be recorded in this element. If multiple identifiers are recorded, each should be in its own [<identityID>](#) .

Availability

Optional, repeatable

See also

Do not confuse with [<recordId>](#) within [<control>](#) , which refers to an identifier for the EAS instance rather than the entity it describes.

Examples

```
<control> [...] <localTypeDeclaration id="localTypeDeclaration1"
vocabularySource="SwedishRegistrationCodeVocabulary"> <reference
href="https://link.to.source"> The Swedish vocabulary for identification
codes</reference> </localTypeDeclaration> </control>
[...] <identity> [...] <identityId localType="RegistrationCode"
localTypeDeclarationReference="localTypeDeclaration1"> 222000-3103</
identityId> <identityId localType="VATRegistrationCode"
localTypeDeclarationReference="localTypeDeclaration1"> SE222000310301</
identityId> <identityId localType="EInvoiceID"
localTypeDeclarationReference="localTypeDeclaration1"> 2220003103</
identityId>
```

[Table of Contents](#)

<label>

<label>

Label

Summary

A required child element of [<agent>](#) , [<place>](#) , and [<relation>](#) that indicates the name of the related entity.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[agent](#), [place](#), [relation](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide the sequence of characters (e.g., URI) that uniquely identifies the entity in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) to identify the source where [@valueURI](#) comes from, and [@vocabularySourceURI](#) to point univocally to the organization system used.

Description and Usage

Use [<label>](#) to indicate the name of the related entity, either in the generic [<relation>](#) element or in one of the specific entity elements. Depending on the type of related entity, such a name can also take the form of a numeric denominator.

In [<agent>](#), this is the name of the agent responsible for the creation, modification, or deletion of an EAC-CPF instance, as captured in [<maintenanceEvent>](#). In [<place>](#), this might e.g. be the name of the place where a person was born or an organization was established.

It is recommended to use authorized vocabularies in cases where the element is valorized with a well-known corporation (i.e. "Library of Congress").

Availability

Required, repeatable

See also

Use this element in combination with type and role information which can also be encoded within the parent elements of [<label>](#). E.g.: [<label>](#) : "John Bianchi", [@agentType](#): "person", [<role>](#) : "author".

Examples

```
<maintenanceHistory> <maintenanceEvent id="me1"> <agent>
<label>Tanya Smith</label> <role>Archivist</role> <relationship
valueURI="https://www.ica.org/standards/RiC/ontology#AuthorshipRelation"
vocabularySourceURI="https://www.ica.org/standards/RiC/ontology"/>
</agent> <eventDateTime standardDateTime="2021-09">September
2021</eventDateTime> <eventDescription>Creation of the encoded
archival description</eventDescription> </maintenanceEvent>
<maintenanceEvent id="me2"> <agent> <label>Gregory Miller</label>
<role>Volunteer</role> <relationship valueURI="https://www.ica.org/
standards/RiC/ontology#CreationRelation" vocabularySourceURI="https://
www.ica.org/standards/RiC/ontology"/> </agent> <eventDateTime
standardDateTime="2023-05">May 2023</eventDateTime>
<eventDescription>Marking persons and organisations named in
narrative texts as part of a crowdsourcing project</eventDescription>
</maintenanceEvent> </maintenanceHistory> <relation
targetType="resource"> <label>Mémorial du colonel Gustafsson. - 1829</
label> <role>Publication</role> </relation>
```

[Table of Contents](#)

< language >

Language

Summary

An element that identifies the language or communication system used by the entity or in the materials described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

languageUsed

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageCode	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use @languageCode to provide a code for the language itself.
Use @languageOfElement to provide a code for the language in which the element is given.

Description and Usage

An optional element within < languageUsed > that gives the language or languages used by the entity being described.

Availability

Optional, repeatable

See also

Use [<writingSystem>](#) to specify, in a human-readable form, the script corresponding to the language.

Examples

```
<languageUsed> <language languageCode="eng">English</  
language> <writingSystem scriptCode="Latn">Latin</writingSystem>  
</languageUsed> <languageOfMaterial> <languageSet>  
<writingSystem scriptCode="Latn">Latin</writingSystem>  
<language languageCode="eng">English</language> <language  
languageCode="ang">Old English</language> <language  
languageCode="lat">Latin</language> </languageSet>  
<languageSet> <language languageCode="gre">Greek</  
language> <writingSystem scriptCode="Grek">Greek</  
writingSystem> </languageSet> <descriptiveNote> <p>The  
majority of the documents are written in Modern English. Roberts  
copied multiple passages from original manuscripts in Latin, Greek and  
Old English.</p> </descriptiveNote> </languageOfMaterial>  
<languageOfMaterial> <language languageCode="eng">English</  
language> <language languageCode="fre">French</language>  
</languageOfMaterial> <languageOfMaterial> <languageSet>  
<language languageCode="jpn">Japanese</language> <writingSystem  
scriptCode="Hira">hiragana</writingSystem> <writingSystem  
scriptCode="Kana">katakana</writingSystem> </languageSet>  
<descriptiveNote> <p>This file contains documents in Japanese, in  
both the hiragana and katakana scripts.</p> </descriptiveNote> </  
languageOfMaterial>
```

[Table of Contents](#)

<languageDeclaration>

Language Declaration

Summary

An optional child element of [<control>](#) that indicates the language and script in which an EAS instance is written.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageCode	Required
languageOfElement	Optional
scriptCode	Optional
scriptOfElement	Optional
target	Optional

Attribute usage

Use the required [@languageCode](#) to provide a code for the language used in the EAS instance.

Use [@languageOfElement](#) to provide a code for the language in which the [<languageDeclaration>](#) element is given.

Use [@scriptCode](#) to provide a code for the writing system used in the EAS instance.

Use [@scriptOfElement](#) to provide a code for the writing system in which the [<languageDeclaration>](#) element is given.

Description and Usage

An optional child element of [<control>](#) that declares the languages and scripts in which an EAS instance is written in the [@languageCode](#)

and [@scriptCode](#) attributes. Any comments about the languages and scripts in which the EAS instance is written may be included in the optional [<descriptiveNote>](#) element. While [<languageDeclaration>](#) states the language(s) and script(s) for the EAS instance in general, the [@languageOfElement](#) and [@scriptOfElement](#) attributes available with all elements may be used to encode language and script information specific to the content of one element in cases where this is different from the overall language(s) and script(s).

Availability

Optional, repeatable

Examples

```
<languageDeclaration languageCode="ger" scriptCode="Latn"/>
```

[Table of Contents](#)

<languageUsed>

Language Used

Summary

A required child element of [<languagesUsed>](#) describing the language and writing system used by the CPF entity being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
language	0..n
writingSystem	0..n

May occur within

[languagesUsed](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[<languageUsed>](#) is an element used to indicate the language and writing system, or script, in which the CPF entity being described was creative or productive. Use the [<language>](#) element to specify the language and a corresponding [<writingSystem>](#) element for the writing system.

The prescribed order of all child elements (both required and optional) is:

[<language>](#) and/or [<writingSystem>](#)

[<descriptiveNote>](#)

Availability

Required, repeatable

See also

Do not confuse with [<languageDeclaration>](#) which refers to the language and script of the EAC-CPF instance.

Examples

See [<description>](#) encoding

[Table of Contents](#)

<languagesUsed>

Languages Used

Summary

An optional child element of <description> used for grouping together one or more <languageUsed> elements.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
languageUsed	1..n

May occur within

description

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use the optional <languagesUsed> element to group together one or more occurrences of <languageUsed> . <languagesUsed> must include at least one <languageUsed> element.

The prescribed order of all child elements (both required and optional) is:

<languageUsed>

<descriptiveNote>

Availability

Optional, not repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

<legalStatus>

Legal Status

Summary

A required child element of [<legalStatuses>](#) used to encode information about the legal status of a corporate body.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
placeName	0..n
term	1..n

May occur within

[legalStatuses](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

The legal status is typically defined and granted by authorities or through authorized agencies. Enter terms in accordance with provisions of the controlling legislation. Terms may be drawn from controlled vocabularies or may be natural language terms.

`<legalStatus>` must include at least one `<term>` element, where the legal status is encoded. `<term>` can be repeated within `<legalStatus>` to include translations of the same term. Use the `@languageOfElement` attribute to identify the language used in each `<term>`.

Associated date(s) (`<date>` , `<dateRange>` , or `<dateSet>`) and place(s) (`<placeName>`) may be included to further constrain the term's meaning. A `<descriptiveNote>` element may be included if a fuller textual explanation is needed.

Multiple `<legalStatus>` elements may be grouped within a `<legalStatuses>` element.

The prescribed order of all child elements (both required and optional) is:

`<term>`

One of `<date>` , `<dateRange>` , or `<dateSet>`

`<placeName>`

`<descriptiveNote>`

Availability

Required, repeatable

Examples

```
<legalStatus> <term>Public Record(s)</term> </legalStatus>
<identificationData> <legalStatus> <term>Student records</term>
<descriptiveNote> <p>Student records are governed by the Family
Educational Rights and Privacy Act (FERPA), 20 U.S.C. § 1232g.</p>
</descriptiveNote> </legalStatus> <legalStatus> <term>Patient
records</term> <descriptiveNote> <p>Patient records are governed
by the Health Insurance Portability and Accountability Act, Pub.L. 104–
191 and 110 Stat. 1936. Article 8 ECHR may also apply.</p> </
descriptiveNote> </legalStatus> </identificationData> <legalStatus>
<term>Department of State</term> </legalStatus> <legalStatus>
<term>Organismo de la Administracion Central del Estado</term> <date
standardDate="1769">1769</date> </legalStatus>
```

[Table of Contents](#)

< legalStatuses >

Legal Statuses

Summary

An optional child element of < description > used to bundle together one or more < legalStatus > element.

May contain

Element/content type	Occurrences
descriptiveNote	0..1
legalStatus	1..n

May occur within

description

Attributes

Attribute name	Attribute values
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

< legalStatuses > groups together one or more occurrences of < legalStatus > . < legalStatuses > must include at least one < legalStatus > element.
The prescribed order of all child elements (both required and optional) is:

- < legalStatus >
- < descriptiveNote >

Availability

Optional, not repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

<localDescription>

Local Description

Summary

A required child element of [<localDescriptions>](#) used to extend the descriptive categories to others available in a local system.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
placeName	0..n
term	1..n

May occur within

[localDescriptions](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<localDescription>](#) provides a means to extend the list of description elements specified in the EAC-CPF schema. It should be used to record structured index terms rather than discursive text. The [<localDescription>](#) element should be used whenever a separate semantic process of the

descriptive information is required in a local system that cannot be accommodated by the existing categories available in EAC-CPF.

[<localDescription>](#) must contain at least one [<term>](#) child element. Terms may be drawn from controlled vocabularies or may be natural language terms. Associated date(s) ([<date>](#) , [<dateRange>](#) , or [<dateSet>](#)) and place(s) ([<placeName>](#)) may be included to further constrain the term's meaning. A [<descriptiveNote>](#) may be included if a fuller textual explanation is needed. The prescribed order of all child elements (both required and optional) is:

[<term>](#)

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<placeName>](#)

[<descriptiveNote>](#)

Availability

Required, repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

<localDescriptions>

Local Descriptions

Summary

An optional child element of [<description>](#) used for grouping together one or more [<localDescription>](#) elements.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
localDescription	1..n

May occur within

[description](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use the optional [<localDescriptions>](#) element to group together one or more occurrences of [<localDescription>](#) . [<localDescriptions>](#) must include at least one [<localDescription>](#) element.

The prescribed order of all child elements (both required and optional) is:

[<localDescription>](#)

[<descriptiveNote>](#)

Availability

Optional, not repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

<localTypeDeclaration>

Local Type Declaration

Summary

An optional child element of [<control>](#) used to declare any local conventions or controlled vocabularies used in [@localType](#) in the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
reference	1..1
shortCode	0..1

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<localTypeDeclaration>](#) specifies the local conventions and controlled vocabularies used in [@localType](#) attributes in the EAS instance. Each additional rule or set of rules, controlled vocabulary, or standard should be contained in a separate [<localTypeDeclaration>](#) . The child [<reference>](#) must be used to cite the resource that lists the local rules or controlled terms. Any notes relating to how these rules or conventions have been used may be given in [<descriptiveNote>](#) . The child [<shortCode>](#) may be used to identify any abbreviation or code representing the local convention or controlled vocabulary.

The prescribed order of all child elements (both required and optional) is:

[<reference>](#)

[<shortCode>](#)

[<descriptiveNote>](#)

Availability

Optional, repeatable

See also

Use [<conventionDeclaration>](#) to indicate any more broadly (i.e. nationally or internationally) used rules or conventions, including authorized controlled vocabularies and thesauri, applied in creating the EAS instance.

When using [@localType](#) throughout the EAS instance, use [@localTypeDeclarationReference](#) in parallel to refer back to the relevant [<localTypeDeclaration>](#) via its [@id](#) attribute.

Examples

```
<localTypeDeclaration id="identifiers"> <reference href="https://  
example.org/value-lists/identifiers.csv">List of identifier types</reference>  
</localTypeDeclaration> >
```

[Table of Contents](#)

< maintenanceAgency >

Maintenance Agency

Summary

A required child element of [< control >](#) that identifies the institution or service responsible for the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
agencyCode	0..1
agencyName	0..n
descriptiveNote	0..1
otherAgencyCode	0..n

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
countryCode	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional
vocabularySource	Optional
vocabularySourceURI	Optional
valueURI	Optional

Attribute usage

Use [@countryCode](#) to indicate a unique code for the country of the maintenance agency.

Description and Usage

[< maintenanceAgency >](#) encodes information about the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance.

`<maintenanceAgency>` must include one or both of `<agencyCode>` or `<agencyName>` to provide the identifier or the name of the institution or service. It may also include the optional child element `<otherAgencyCode>` to provide any additional identifiers. Any general information about the institution or service in relation to the EAS instance may be given in `<descriptiveNote>` .

The prescribed order of all child elements (both required and optional) is:

`<agencyCode>` (if used)

`<agencyName>`

`<otherAgencyCode>`

`<descriptiveNote>`

Availability

Required, not repeatable

Examples

```
<maintenanceAgency> <agencyCode status="authorized"
vocabularySource="ISIL" vocabularySourceURI="http://id.loc.gov/
vocabulary/identifiers/isil"> US-ctybr </agencyCode> <agencyName>
Beinecke Rare Book and Manuscript Library </agencyName>
<otherAgencyCode status="authorized" valueURI="https://
id.loc.gov/vocabulary/organizations/ctybr" vocabularySource="MARC
Code List for Organizations" vocabularySourceURI="https://
www.loc.gov/marc/organizations/"> CtY-BR </otherAgencyCode>
<otherAgencyCode status="alternative" valueURI="https://
www.wikidata.org/wiki/Q814779" vocabularySource="Wikidata"
vocabularySourceURI="https://www.wikidata.org/"> Q814779 </
otherAgencyCode> </maintenanceAgency> <maintenanceAgency>
<agencyCode status="alternative" vocabularySource="NAD"
vocabularySourceURI="https://sok.riksarkivet.se/"> SE/G066 </
agencyCode> <agencyName> Kommunalförbundet Sydarkivera </
agencyName> </maintenanceAgency>
```

[Table of Contents](#)

< maintenanceEvent >

Maintenance Event

Summary

A required child element of [< maintenanceHistory >](#) used to record information about maintenance activities in the history of the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
agent	1..1
eventDateTime	1..1
eventDescription	0..n

May occur within

[maintenanceHistory](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
maintenanceEventType	Optional
scriptOfElement	Optional
target	Optional

Attribute usage

Use [@maintenanceEventType](#) to document the type of maintenance activity that the [< maintenanceEvent >](#) is recording. Use [@maintenanceEventTypeEncoding](#) in [< control >](#) to specify the source or rules for values supplied in [@maintenanceEventType](#).

Description and Usage

A required child element of [< maintenanceHistory >](#) , [< maintenanceEvent >](#) is used to record an activity in the creation and ongoing maintenance of an EAS instance, including revisions, updates, and deletions, e.g. as a result of reparative description or the application of Artificial Intelligence models. There

will always be at least one maintenance event for each instance, which will typically be its creation.

[< maintenanceEvent >](#) must include [< agent >](#) and [< eventDateTime >](#) child elements to record the agent that carried out the maintenance event, and the date and time the maintenance event occurred.

The prescribed order of all child elements (both required and optional) is:

[< agent >](#)

[< eventDateTime >](#)

[< eventDescription >](#)

Availability

Required, repeatable

Examples

```
< maintenanceHistory > < maintenanceEvent
maintenanceEventType = "derived" > < agent agentType = "machine" >
< label > export.xml/Saxon B9 </label > </agent > < eventDateTime
standardDateTime = "2024-08-30T09:37:17.029-04:00"/
> < eventDescription > Derived from local collection
management system </eventDescription </maintenanceEvent >
< maintenanceEvent maintenanceEventType = "revised" > < agent
agentType = "unknown" > < label / > </agent > < eventDateTime
standardDateTime = "2024-11-27"/ > </maintenanceEvent >
< maintenanceEvent maintenanceEventType = "updated" > < agent
agentType = "person" > < label > K. Bredenberg </label > </
agent > < eventDateTime > December 2024 </eventDateTime > </
maintenanceEvent > </maintenanceHistory >
```

[Table of Contents](#)

< maintenanceHistory >

Maintenance History

Summary

A required child element of [< control >](#) that captures the history of the creation and maintenance of the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
maintenanceEvent	1..n

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional

Description and Usage

A required child element of [< control >](#) , [< maintenanceHistory >](#) is for recording the history of the creation, revisions, updates, and other modifications to the EAS instance.

There must be at least one child [< maintenanceEvent >](#) in [< maintenanceHistory >](#) , which usually will be a record of the creation of the instance. There may be many other [< maintenanceEvent >](#) elements documenting the milestone changes or activities in the maintenance of the instance.

Availability

Required, not repeatable

See also

Use [@maintenanceStatus](#) within [<control>](#) to reflect the current drafting status of the EAS instance as recorded in [<maintenanceHistory>](#) .

Examples

```
<maintenanceHistory> <maintenanceEvent
maintenanceEventType="derived"> <agent agentType="machine">
<label>export.xml/Saxon B9</label> </agent> <eventDateTime
standardDateTime="2024-08-30T09:37:17.029-04:00"/
> <eventDescription>Derived from local collection
management system</eventDescription </maintenanceEvent>
<maintenanceEvent maintenanceEventType="revised"> <agent
agentType="unknown"> <label/> </agent> <eventDateTime
standardDateTime="2024-11-27"/> </maintenanceEvent>
<maintenanceEvent maintenanceEventType="updated"> <agent
agentType="person"> <label>K. Bredenberg</label> </
agent> <eventDateTime>December 2024</eventDateTime> </
maintenanceEvent> </maintenanceHistory>
```

[Table of Contents](#)

<mandate>

Mandate

Summary

A required child element of [<mandates>](#) used for identifying the source of authority or mandate for the corporate body in terms of its powers, functions, responsibilities or activities, such as a law, directive, or charter.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
placeName	0..n
term	1..n

May occur within

[mandates](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<mandate>](#) is used to identify the source of authority or mandate for the entity being described in terms of its powers, functions, responsibilities or sphere of activities, such as a law, directive, or charter.

[<mandate>](#) must include at least one [<term>](#) element. Terms may be drawn from controlled vocabularies or may be natural language terms. [<term>](#) can be repeated within [<mandate>](#) to include translations of the same mandate. Use the [@languageOfElement](#) attribute to identify the language used in each [<term>](#) .

Associated date(s) ([<date>](#) , [<dateRange>](#) , or [<dateSet>](#)) and place(s) ([<placeName>](#)) may be included to further constrain the term's meaning. A [<descriptiveNote>](#) may be included if a fuller textual explanation is needed. Multiple [<mandate>](#) elements may be grouped within a [<mandates>](#) element.

The prescribed order of all child elements (both required and optional) is:

[<term>](#)

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<placeName>](#)

[<descriptiveNote>](#)

Availability

Required, repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

< mandates >

Mandates

Summary

An optional child element of < description > used for grouping together one or more < mandate > elements.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
mandate	1..n

May occur within

[description](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

< mandates > groups together one or more occurrences of < mandate > .

< mandates > must include at least one < mandate > element.

The prescribed order of all child elements (both required and optional) is:

< mandate >

< descriptiveNote >

Availability

Optional, not repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

<multipleIdentities>

Multiple Identities

Summary

A child element of [<eac>](#) used to group together more than one [<cpfDescription>](#) within a single EAC-CPF instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
cpfDescription	2..n

May occur within

[eac](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
target	Optional

Description and Usage

A grouping element used to encode more than one [<cpfDescription>](#) in a single EAC-CPF instance.

The [<multipleIdentities>](#) element can be used to resolve two identity circumstances. Firstly, it can be used to represent more than one identity (including official identities) of the same CPF entity, each with a separate [<cpfDescription>](#). Secondly, it can be used to represent a collaborative identity that includes multiple individuals operating under a shared identity (such as a shared pseudonym).

[<multipleIdentities>](#) must include two or more [<cpfDescription>](#) elements.

Availability

Within [<eac>](#) : one of [<cpfDescription>](#) or [<multipleIdentities>](#) required, not repeatable

Examples

See [<eac>](#) examples

[Table of Contents](#)

<nameEntry>

Name Entry

Summary

An element containing a name entry for a corporate body, person, or family.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
part	1..n
useDates	0..n

May occur within

[identity](#), [nameEntrySet](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
preferredForm	Optional (values limited to: false, true)
scriptOfElement	Optional
sourceReference	Optional
status	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

The [@status](#) attribute may be used to indicate whether the [<nameEntry>](#) is an authorized or alternative form of the name.

The [@scriptOfElement](#) and [@languageOfElement](#) attributes can be used to specify the script and language of each name recorded in [<nameEntry>](#) .

Description and Usage

Within `<identity>`, the element `<nameEntry>` is used to record a name by which the corporate body, person, or family described in the EAC-CPF instance is known.

When `<nameEntry>` occurs within `<nameEntrySet>` it is used to record two or more forms of a name, for example official and non-official forms of the name in different languages and/or scripts.

When `<nameEntry>` occurs within `<nameEntrySet>` it is used to record two or more forms of a name, for example official and non-official forms of the name in different languages and/or scripts.

Each form of the name is recorded in a separate `<nameEntry>` element.

Each `<nameEntry>` must contain at least one `<part>` element. Within `<nameEntry>` each of the component parts of a name may be recorded in a separate `<part>` element.

The `<nameEntry>` element may also contain a `<useDates>` element to indicate the dates the name was used.

The prescribed order of all child elements (both required and optional) is:

`<part>`

`<useDates>`

Availability

Within `<identity>`: one of `<nameEntry>` or `<nameEntrySet>` required, repeatable

Within `<nameEntrySet>`: two or more `<nameEntry>` required, repeatable

Examples

```
<nameEntrySet languageOfElement="fre"> <nameEntry  
conventionDeclarationReference="cd1" preferredForm="true"> <part>  
Provence-Alpes-Côte d'Azur </part> </nameEntry> <nameEntry  
conventionDeclarationReference="cd2"> <part> Région Sud  
Provence-Alpes-Côte d'Azur </part> </nameEntry> <nameEntry  
conventionDeclarationReference="cd3"> <part> Provence-Alpes-Côte-d'Azur  
</part> </nameEntry> </nameEntrySet>
```

[Table of Contents](#)

<nameEntrySet>

Name Entry Set

Summary

An optional child element of [<identity>](#) used as a wrapper element for two or more [<nameEntry>](#) elements representing different forms of the same name (e.g., official and non-official forms of the name in different languages and/or scripts).

May contain

<i>Element/content type</i>	<i>Occurrences</i>
nameEntry	2..n
useDates	0..n

May occur within

[identity](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

A wrapper element used to group two or more [<nameEntry>](#) elements representing parallel or other forms of the name for the same CPF entity which are used at the same time (e.g., official and non-official forms of the name in different languages and/or scripts).

The [<nameEntrySet>](#) element may contain a [<useDates>](#) element to indicate the dates the set of name forms was used.

The prescribed order of all child elements (both required and optional) is:

[< nameEntry >](#)

[< useDates >](#)

Availability

Within [< identity >](#) : one of [< nameEntry >](#) or [< nameEntrySet >](#) required, repeatable

Examples

```
< nameEntrySet localType = "parallel" > < nameEntry
languageOfElement = "de" preferredForm = "true" status = "authorized"
localType = "native" > < part localType = "surname" > Arendt </part> < part
localType = "firstname" > Hannah </part> </nameEntry> < nameEntry
languageOfElement = "ja" scriptOfElement = "Jpan" preferredForm = "false"
status = "authorized" localType = "translation" > < part localType = "surname" >
アーレント </part> < part localType = "firstname" > ハナ </part> </
nameEntry> < nameEntry languageOfElement = "en" preferredForm = "false"
status = "authorized" > < part localType = "surname" > Arendt </part>
< part localType = "firstname" > Hannah </part> </nameEntry> </
nameEntrySet >
```

[Table of Contents](#)

< narrativeEvent >

Narrative Event

Summary

An optional child element of [< biogHist >](#) used to record chronological events in the history or biography of the CPF entity.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
agent	0..n
date	1..n
eventDescription	0..n
placeName	0..n

May occur within

[biogHist](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use [< narrativeEvent >](#) to record a chronology of life events of the CPF entity. This may include any event between the birth and the death of a person or between the foundation and the closure of an organization.

The type of each event may be defined with the attribute [@localType](#). Use [@localTypeDeclarationReference](#) to refer to a [< localTypeDeclaration >](#) within [< control >](#) where you have defined those types. Use the required child element [< date >](#) to record when the event took place. Using the

optional child element [<agent>](#) to provide information about who or what carried out, or was responsible for the activity is highly recommended. The child element [<placeName>](#) may be used to provide information about where the event happened. Information about the event may be described in [<eventDescription>](#) .

The prescribed order of all child elements (both required and optional) is:

[<date>](#)

[<agent>](#)

[<placeName>](#)

[<eventDescription>](#)

Availability

Optional, repeatable

Examples

```
<biogHist> <p>Ilma Mary Brewer, nee Pidgeon, was Lecturer in Botany/  
Biology, University of Sydney 1963-70 and Senior Lecturer in Biological  
Sciences 1970-78. She developed new methods of teaching based on the  
recognition that a student learnt more by working at his/her own place  
and instruction him/her self. Her findings were published as a book,  
"Learning More and Teaching Less."</p> <narrativeEvent> <date  
standardDate="1936">1936</date> <placeName>Sydney</placeName>  
<eventDescription> Bachelor of Science (BSc) completed at the University  
of Sydney</eventDescription> </narrativeEvent> <narrativeEvent>  
<date standardDate="1937">1937</date> <placeName>Sydney</  
placeName> <eventDescription> Master of Science (MSc) completed  
at the University of Sydney</eventDescription> </narrativeEvent>  
<narrativeEvent> <date standardDate="1937/1941">until 1941</date>  
<eventDescription> Linnean Macleay Fellow</eventDescription> </  
narrativeEvent> </biogHist>
```

[Table of Contents](#)

< objectXMLWrap >

Object XML Wrap

Summary

An optional child element of [< descriptiveNote >](#) , [< relation >](#) , [< setComponent >](#) , and [< source >](#) that allows for the inclusion of XML encoding from any other XML namespace.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[any element from any namespace]	

May occur within

[descriptiveNote](#), [relation](#), [setComponent](#), [source](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
target	Optional

Description and Usage

A wrapper element that provides a place to express data in any XML encoding language.

To facilitate interoperability the XML should conform to an open, standard XML schema and a namespace attribute should be present on the root element referencing the namespace of the standard.

If interoperability is not a main objective in a specific application context of the EAS, it is also possible to encode data in XML without a namespace within the [< objectXMLWrap >](#) element.

[< objectXMLWrap >](#) may be used to store related XML data locally rather than linking to external resources in order to facilitate processing or in cases where the related data may not be reliably accessible.

Availability

Optional, not repeatable

Examples

```
<objectXMLWrap> <mods:mods xmlns:mods="http://www.loc.gov/mods/v3" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://www.loc.gov/mods/v3 http://www.loc.gov/mods/v3/mods-3-3.xsd"> <mods:titleInfo> <mods:title> Artisti trentini
tra le due guerre</mods:title> </mods:titleInfo> <mods:name>
<mods:namePart type="given"> Nicoletta</mods:namePart>
<mods:namePart type="family"> Boschiero</mods:namePart> </
mods:name> </mods:mods> </objectXMLWrap> <objectXMLWrap>
<tei:bibl xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:tei="http://www.tei-c.org/ns/1.0" xsi:schemaLocation="https://
www.tei-c.org/release/xml/tei/custom/schema/xsd/tei_all.xsd"
default="false"> <tei:title> <tei:emph rend="italic"> Paris
d'hier et d'aujourd'hui</tei:emph> </tei:title> <tei:respStmt>
<tei:resp> photographes</tei:resp> <tei:name> Roger Henrard</
tei:name> <tei:name> Yann Arthus-Bertrand</tei:name> </tei:respStmt>
</tei:bibl> </objectXMLWrap> <objectXMLWrap> <note>
<to> Tove</to> <from> Jani</from> <heading> Reminder</
heading> <body> Don't forget me this weekend!</body> </note> </
objectXMLWrap>
```

[Table of Contents](#)

< narrativeEvent >

Narrative Event

Summary

An optional child element of < biogHist > used to record chronological events in the history or biography of the CPF entity.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
agent	0..n
date	1..n
eventDescription	0..n
placeName	0..n

May occur within

[biogHist](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use < [narrativeEvent](#) > to record a chronology of life events of the CPF entity. This may include any event between the birth and the death of a person or between the foundation and the closure of an organization.

The type of each event may be defined with the attribute [@localType](#). Use [@localTypeDeclarationReference](#) to refer to a < [localTypeDeclaration](#) > within < [control](#) > where you have defined those types. Use the required child element < [date](#) > to record when the event took place. Using the

optional child element [<agent>](#) to provide information about who or what carried out, or was responsible for the activity is highly recommended. The child element [<placeName>](#) may be used to provide information about where the event happened. Information about the event may be described in [<eventDescription>](#) .

The prescribed order of all child elements (both required and optional) is:

[<date>](#)

[<agent>](#)

[<placeName>](#)

[<eventDescription>](#)

Availability

Optional, repeatable

Examples

```
<biogHist> <p>Ilma Mary Brewer, nee Pidgeon, was Lecturer in Botany/  
Biology, University of Sydney 1963-70 and Senior Lecturer in Biological  
Sciences 1970-78. She developed new methods of teaching based on the  
recognition that a student learnt more by working at his/her own place  
and instruction him/her self. Her findings were published as a book,  
"Learning More and Teaching Less."</p> <narrativeEvent> <date  
standardDate="1936">1936</date> <placeName>Sydney</placeName>  
<eventDescription> Bachelor of Science (BSc) completed at the University  
of Sydney</eventDescription> </narrativeEvent> <narrativeEvent>  
<date standardDate="1937">1937</date> <placeName>Sydney</  
placeName> <eventDescription> Master of Science (MSc) completed  
at the University of Sydney</eventDescription> </narrativeEvent>  
<narrativeEvent> <date standardDate="1937/1941">until 1941</date>  
<eventDescription> Linnean Macleay Fellow</eventDescription> </  
narrativeEvent> </biogHist>
```

[Table of Contents](#)

< occupation >

Occupation

Summary

A required child element of [< occupations >](#) that provides information about an occupation of the CPF entity being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
placeName	0..n
term	1..n

May occur within

[occupations](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[< occupation >](#) is a wrapper element that uses the child element [< term >](#) to identify an occupation held by the CPF entity. Terms may be drawn from controlled vocabularies or may be natural language terms.

[< occupation >](#) must include at least one [< term >](#) element. [< term >](#) can be repeated within [< occupation >](#) to include translations of the same function. Use the [@languageOfElement](#) attribute to identify the language used in each [< term >](#) .

Associated date(s) ([< date >](#) , [< dateRange >](#) , or [< dateSet >](#)) and place(s) ([< placeName >](#)) may be included to further constrain the term's meaning. A [< descriptiveNote >](#) element may be included if a textual explanation needed. The prescribed order of all child elements (both required and optional) is:

[< term >](#)

One of [< date >](#) , [< dateRange >](#) , or [< dateSet >](#)

[< placeName >](#)

[< descriptiveNote >](#)

Availability

Required, repeatable

Examples

See [< description >](#) encoding

[Table of Contents](#)

< occupations >

Occupations

Summary

An optional child element of < description > used for grouping together one or more < occupation > elements.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
occupation	1..n

May occur within

[description](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use the optional < occupations > element to group together one or more occurrences of < occupation > . < occupations > must include at least one < occupation > element.

The prescribed order of all child elements (both required and optional) is:

< occupation >

< descriptiveNote >

Availability

Optional, not repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

< otherAgencyCode >

Other Agency Code

Summary

An optional child element of < maintenanceAgency > that provides an alternative code for the institution or service responsible for the EAS instance.

May contain

Element/content type	Occurrences
[text]	

May occur within

[maintenanceAgency](#)

Attributes

Attribute name	Attribute values
audience	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
scriptOfElement	Optional
status	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide the sequence of characters (e.g., URI) that uniquely identifies the code in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system.

Use [@vocabularySource](#) to identify the source where [@valueURI](#) comes from, and [@vocabularySourceURI](#) to point univocally to the organization system used.

Use [@localType](#) to specify the type of code being provided.

Use [@status](#) to encode whether the < otherAgencyCode > is an authorized or alternative code.

Description and Usage

Use [<otherAgencyCode>](#) to provide an alternative and/or local code that represents the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance. Any code other than that given in [<agencyCode>](#) may be provided in [<otherAgencyCode>](#). The addition of an ISO 3166-1 alpha-2 country code as the prefix to a local code is recommended to ensure international uniqueness.

Availability

Optional, repeatable

Examples

```
<maintenanceAgency> <agencyCode status="authorized"
vocabularySource="ISIL" vocabularySourceURI="http://id.loc.gov/
vocabulary/identifiers/isil"> US-nbuuar </agencyCode> <agencyName>
State University of New York at Buffalo, Archives </agencyName>
<otherAgencyCode status="authorized" valueURI="http://id.loc.gov/
vocabulary/organizations/nbuuar" vocabularySource="MARC Code
List for Organizations" vocabularySourceURI="http://id.loc.gov/
vocabulary/organizations"> NBuU-AR </otherAgencyCode> </
maintenanceAgency> <maintenanceAgency> <agencyCode
status="authorized" vocabularySource="ISIL" vocabularySourceURI="http://
id.loc.gov/vocabulary/identifiers/isil"> US-ctybr </agencyCode>
<agencyName> Beinecke Rare Book and Manuscript Library </
agencyName> <otherAgencyCode status="authorized" valueURI="https://
id.loc.gov/vocabulary/organizations/ctybr" vocabularySource="MARC Code
List for Organizations" vocabularySourceURI="http://id.loc.gov/vocabulary/
organizations"> CtY-BR </otherAgencyCode> <otherAgencyCode
status="alternative" valueURI="http://www.wikidata.org/entity/
Q814779" vocabularySource="Wikidata" vocabularySourceURI="https://
www.wikidata.org/"> Q814779 </otherAgencyCode> </
maintenanceAgency>
```

[Table of Contents](#)

<otherEntityType>

Other Entity Type

Summary

A required and repeatable child element of [<otherEntityTypes>](#) used to encode additional or alternative entity types.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
placeName	0..n
term	1..n

May occur within

[otherEntityTypes](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<otherEntityType>](#) is a required child element of [<otherEntityTypes>](#) used to encode any additional or alternative entity types used for the CPF instance in addition to the required [<entityType>](#) element with values of corporateBody, person, or family. For example, in a local context

"organization" might be used as an entity type instead of "corporateBody".
[<otherEntityType>](#) allows "organization" to be encoded.
[<otherEntityType>](#) must include one [<term>](#) element containing the term for the other entity type.
Each CPF instance may include more than one [<otherEntityType>](#) element within the [<otherEntityTypes>](#) wrapper element.
The prescribed order of all child elements (both required and optional) is:
[<term>](#)

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<placeName>](#)

[<descriptiveNote>](#)

Availability

Required, repeatable

Examples

See [<identity>](#) encoding

[Table of Contents](#)

< otherEntityType >

Other Entity Types

Summary

An optional child element of < identity > used for grouping one or more < otherEntityType > elements.

May contain

Element/content type	Occurrences
descriptiveNote	0..1
otherEntityType	1..n

May occur within

identity

Attributes

Attribute name	Attribute values
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

A wrapper element used to group one or more < otherEntityType > elements. These elements are used to encode any additional or alternative entity types used for the CPF instance in addition to the required < entityType > element with values of corporateBody, person or family. < otherEntityTypes > must include at least one < otherEntityType > element. < descriptiveNote > can be used to add any additional descriptive information to the < otherEntityTypes > .

The prescribed order of all child elements (both required and optional) is:

< otherEntityType >

< descriptiveNote >

Availability

Optional, not repeatable

Examples

See [<identity>](#) encoding

[Table of Contents](#)

< otherRecordId >

Other Record Identifier

Summary

An optional child element of [< control >](#) that encodes any local identifier for the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide the sequence of characters (e.g., URI) that uniquely identifies the alternative identifier in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system.

Use [@vocabularySource](#) to identify the source where [@valueURI](#) comes from, e.g, the institution or service providing the associated record identifier, and [@vocabularySourceURI](#) to point univocally to the organization system used, if available.

Description and Usage

[<otherRecordId>](#) can be used to record an identifier that is an alternative to the mandatory identifier provided in [<recordId>](#) . These might include the identifiers of merged EAS instances representing the same entity or those of records that are no longer current but had some part in the history and maintenance of the EAS instance.

Availability

Optional, repeatable

Examples

```
<otherRecordId valueURI="https://pares.mcu.es/ParesBusquedas20/
catalogo/autoridad/140149" vocabularySource="PARES">140149</
otherRecordId> <otherRecordId localType="original"
localTypeDeclarationReference="identifierTypes">AUBT-ISAAR-C-002</
otherRecordId>
```

[Table of Contents](#)

<p>

< p >

Paragraph

Summary

A general purpose element used to encode blocks of text.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[biogHist](#), [descriptiveNote](#), [generalContext](#), [structureOrGenealogy](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use [<p>](#) for blocks of text. A paragraph may be a subdivision of a larger composition or it may exist alone. It is usually typographically distinguished: a line space is often left blank before it; the text begins on a new line; and the first letter of the first word may be indented, enlarged, or both.

Availability

Within [<descriptiveNote>](#) : required, repeatable.
Within all other parents: optional, repeatable.

In all parents except `<descriptiveNote>`, the encoder must choose between using one or more `<p>` elements that are defined within the current EAS schema, or using a `<formattingExtention>` element (to wrap XHTML content) for more complex formatting.

Examples

`<biogHist>` `<p>` Robert Carlton Brown (1886-1959) was a writer, editor, publisher, and traveler. From 1908 to 1917, he wrote poetry and prose for numerous magazines and newspapers in New York City, publishing two pulp novels, `<span style="font-style:italic">`What Happened to Mary`</span>` and `<span style="font-style:italic">`The Remarkable Adventures of Christopher Poe`</span>` (1913), and one volume of poetry, `<span style="font-style:italic">`My Marjonyary`</span>` (1916). `</p>` `<p>` During 1918, he traveled extensively in Mexico and Central America, writing for the U.S. Committee of Public Information in Santiago de Chile. In 1919, he moved with his wife, Rose Brown, to Rio de Janeiro, where they founded `<span style="font-style:italic">`Brazilian American`</span>`, a weekly magazine that ran until 1929. With Brown's mother, Cora, the Browns also established magazines in Mexico City and London: `<span style="font-style:italic">`Mexican American`</span>` (1924-1929) and `<span style="font-style:italic">`British American`</span>` (1926-1929). `</p>` `</biogHist>` `<biogHist>` `<p>` Robert Carlton Brown (1886-1959) was a writer, editor, publisher, and traveler. From 1908 to 1917, he wrote poetry and prose for numerous magazines and newspapers in New York City, publishing two pulp novels, `<span style="font-style:italic">`What Happened to Mary`</span>` and `<span style="font-style:italic">`The Remarkable Adventures of Christopher Poe`</span>` (1913), and one volume of poetry, `<span style="font-style:italic">`My Marjonyary`</span>` (1916). `</p>` `<p>` During 1918, he traveled extensively in Mexico and Central America, writing for the U.S. Committee of Public Information in Santiago de Chile. In 1919, he moved with his wife, Rose Brown, to Rio de Janeiro, where they founded `<span style="font-style:italic">`Brazilian American`</span>`, a weekly magazine that ran until 1929. With Brown's mother, Cora, the Browns also established magazines in Mexico City and London: `<span style="font-style:italic">`Mexican American`</span>` (1924-1929) and `<span style="font-style:italic">`British American`</span>` (1926-1929). `</p>` `</biogHist>` `<functionHistory>` `<p>` In 1968 Yale stated they will admit 500 women into Yale College in the following Fall. The Planning Committee on Coeducation (1968-1969) oversaw every aspect of planning. In 1969, the University Committee on Coeducation was formed. The Committee continued to oversee the transition and facilitate integration of the female students. The Coeducation Office was also established to facilitate programs initiated by the Committee and to serve as a resource for the undergraduates, as well as graduate students, other women on campus, and administrators. Wasserman left Yale in 1972. Mary Arnstein became Acting Special Assistant to the President and chair of the University Committee on Coeducation.

The Committee voted to terminate the position of Special Assistant and the Coeducation Office and transfer responsibilities to existing offices and a reorganized University Committee on the Education of Women in 1973. Some functions of the Coeducation Office were assumed by the new Office on the Education of Women. The University Committee on the Education of Women served as an advisory group to the president on issues related to women at Yale until 1977. </p> </functionHistory>

[Table of Contents](#)

< part >

Part

Summary

A required and repeatable child of [< nameEntry >](#) used to distinguish components of a name.

May contain

Element/content type
[text]

Occurrences

May occur within

[nameEntry](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

The designation of the information contained in the [< part >](#) element can be specified by the attribute [@localType](#).

Description and Usage

Within [< nameEntry >](#) each of the components of a name, such as forename, surname or honorific title, may be recorded in a separate [< part >](#) element. [< part >](#) may also contain the full name of the entity when it is not possible to distinguish the different components of the name.

`<part>` cannot be empty and requires at least one non-whitespace character, such as a hyphen, if no actual name can be given.

Availability

Required, repeatable

Examples

```
<nameEntry languageOfElement="de" preferredForm="true"
status="authorized" localType="native"> <part
localType="surname">Arendt</part> <part
localType="firstname">Hannah</part> </nameEntry> <nameEntry
conventionDeclarationReference="cd1" preferredForm="true">
<part>Provence-Alpes-Côte d'Azur</part> </nameEntry>
<!-- The following example has been adapted from the EADiva Tag
Libray by Ruth Kitchin Tillman, https://eadiva.com/filedesc/ -->
<ead> <control> [...] </control> <findAidDesc href="https://
archives.piecemaking.edu/finding-aids/quilting-technologies-department/
quilting-technologies-department.xml" linkTitle="Download the encoded
finding aid" linkRole="text/xml"> <title localType="mainTitle"
localTypeDeclarationReference="titles"> <part>Guide to Quilting
Technologies Department Records, 1978-2020</part> <part
localType="edition" localTypeDeclarationReference="titles">2nd
edition</part> </title> <title localType="subtitle"
localTypeDeclarationReference="titles"> <part>A guide to the records of
the Quilting Technologies Department at Piecemaking University</part> </
title> <title localType="seriesTitle" localTypeDeclarationReference="titles">
<part>Piecemaking University Departmental Records<part> <part
localType="issueNumber" localTypeDeclarationReference="titles">13</
part> </title> [...] </findAidDesc>
```

[Table of Contents](#)

<place>

Place

Summary

An element that provides information about a place or jurisdiction, including places where the CPF entity was based, lived, or with which it had some other significant connection.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
address	0..n
contact	0..n
date or dateRange or dateSet	0..1
descriptiveNote	0..1
geographicCoordinates	0..n
label	1..n
role	0..n
relationship	0..n

May occur within

[places](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
placeType	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

A `<place>` element is a wrapper element used to encode information about a place or jurisdiction. This includes identifying the places or jurisdictions where the CPF entity was based, lived, or with which it had some other significant connection. It can also be used to encode address and contact information, the role that the place has with regard to the entity described, the relationship between both as well as a temporal dimension of that relationship.

`<place>` must include at least one `<label>` to name the geographic feature or location that is related to the entity being described. The `<role>` element is available to specify the nature of the place in relation with the entity being described, e.g. "birthplace" for CPF entities or "placeOfStorage" for record resources, and its use is strongly recommended. The `@placeType` attribute may be used to classify the type of place for clarification, e.g., indicating whether the place is a city or town or a first or second-order administrative division. Use `<relationship>` to describe the nature of connection between the place and the entity being described more generally. Terms in these elements may be drawn from controlled vocabularies or may be natural language terms. These controlled vocabularies can be identified with the `@vocabularySource` and/or `@vocabularySourceURI` attributes.

The `<address>` element is available for specifying a postal or other address, while a digital address or other contact information can be encoded using the `<contact>` element. Specific coordinates for the geographic feature or location may be provided using the element `<geographicCoordinates>`. Associated date or date range (`<date>` , `<dateRange>` , or `<dateSet>`) information may be included to further constrain the place's meaning. A `<descriptiveNote>` may be included if a fuller explanation of the significance of the place to the CPF entity described is needed.

The prescribed order of all child elements (both required and optional) is:

`<label>`

One of `<date>` , `<dateRange>` , or `<dateSet>`

`<role>`

`<relationship>`

One or more of `<address>` , `<contact>` and
`<geographicCoordinates>`

`<descriptiveNote>`

Availability

Within `<places>` : required, repeatable.

Examples

<places> <place placeType="firstOrderAdministrativeDivision"> <label
 valueURI="https://www.geonames.org/2152274/state-of-queensland.html"
 vocabularySource="GeoNames"> Queensland</label> </place> <place
 placeType="reef"> <label valueURI="https://www.geonames.org/2164628/
 great-barrier-reef.html" vocabularySource="GeoNames"> Great
 Barrier Reef</label> </place> </places> <place> <label
 vocabularySource="local"> East Side (Buffalo, N.Y.)</label>
 <geographicCoordinates coordinateSystem="WGS84"> N 42°53'48"
 W 78°50'2"</geographicCoordinates </place> <c level="file">
 <identificationData> <unitTitle> Lettera di Iacopo II Barozzi a
 Pietro Gradenigo 49 o
 doge della Repubblica di Venezia</unitTitle> <unitDate> <date
 notBefore="1301" notAfter="1303"> all'inizio dell'anno 1302 (?)</
 date> </unitDate> </identificationData> <agents> <agent
 agentType="person"> <label> Iacopo II Barozzi</label> <role
 valueURI="https://www.ica.org/standards/RiC/ontology#isAccumulatorOf"
 vocabularySource="RiC-O"> creatore</role> </agent> <agent
 agentType="person"> <label> Pietro Gradenigo</label> <role
 valueURI="https://www.ica.org/standards/RiC/ontology#isReceiverOf"
 vocabularySource="RiC-O"> destinatario</role> </agent> <agent
 agentType="corporateBody"> <label> Archivio di Stato di Treviso</
 label> <placeName target="place1"> Treviso</placeName> <role
 valueURI="https://www.ica.org/standards/RiC/ontology#isOrWasHolderOf"
 vocabularySource="RiC-O"> istituzione detentrica</role> </agent>
 <agent agentType="person"> <label> Marco Polo</label> <role
 valueURI="https://www.ica.org/standards/RiC/ontology#isOrWasSubjectOf"
 vocabularySource="RiC-O"> soggetto</role> </agent> </agents>
 <places> <place placeType="populatedPlace" id="place1">
 <label> Treviso</label> <role valueURI="https://schema.org/
 serviceLocation" vocabularySource="schema.org"> sala lettura</
 role> <address> <addressLine addressLineType="street"> Via
 Pietro di Dante, 11</addressLine> <addressLine
 addressLineType="postalCode"> 31100</addressLine> <addressLine
 addressLineType="country"> Italia</addressLine> </address>
 <contact> <contactLine contactLineType="homepage" href="https://
 www.archiviodistatotreviso.beniculturali.it/"> Visita nostro sito web
 ufficiale</contactLine> </contact> </place> <place> <label> Stanza
 A, fila 7, scaffale 2</label> <role valueURI="https://schema.org/
 itemLocation" vocabularySource="schema.org"> deposito</role>
 </place> </place> <place placeType="administrativeDivision">
 <label valueURI="https://www.geonames.org/6697802/crete.html"
 vocabularySource="GeoNames"> Regno de Cândia</label> <role
 valueURI="https://www.ica.org/standards/RiC/ontology#isOrWasSubjectOf"
 vocabularySource="RiC-O"> soggetto</role> </place> </places> </c>
 <place placeType="county"> <label valueURI="http://vocab.getty.edu/
 page/tgn/7008153" vocabularySource="tgn" vocabularySourceURI="https://

www.getty.edu/research/tools/vocabularies/tgn/index.html" > Kent < /label >
< role > Residence < /role > < /place >

[Table of Contents](#)

< placeName >

Place Name

Summary

An optional element used to encode the name of a place or geographic feature that is of importance in the relation between the CPF entity and related named entities or in the history of the CPF entity being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[agent](#), [demographicDescription](#), [functionPerformed](#), [legalStatus](#), [localDescription](#), [mandate](#), [narrativeEvent](#), [occupation](#), [otherEntityType](#), [relation](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
countryCode	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use the attributes [@valueURI](#), [@vocabularySource](#), and [@vocabularySourceURI](#) with [< placeName >](#) when referencing an entry of an external vocabulary, thesaurus, ontology.

Description and Usage

[<placeName>](#) should be identified by the proper noun that commonly designates the place, natural feature, or political jurisdiction. It is recommended that place names be taken from authorized vocabularies. Use [<placeName>](#) within [<agent>](#) , [<demographicDescription>](#) , [<functionPerformed>](#) , [<legalStatus>](#) , [<localDescription>](#) , [<mandate>](#) , [<occupation>](#) , [<otherEntityType>](#) and [<relation>](#) to encode the name of a place or geographic feature that is of importance in the term's or the entity's relation with the CPF entity being described. Use [<placeName>](#) within [<narrativeEvent>](#) to encode the geographic dimension of the event.

Availability

Optional, repeatable

See also

Within [<place>](#) , the required element [<label>](#) is used to capture the name of the geographic feature or location. This is to align with the element [<relation>](#) which also uses [<label>](#) to name the related entity. Use [@target](#) within [<placeName>](#) to link to the [@id](#) attribute of a [<place>](#) , which might include more detailed information about the same place.

Examples

```
<relation relationType="https://www.ica.org/standards/RiC/ontology#FamilyRelation" targetType="person"> <label> Marie Skłodowska-Curie </label> <dateRange> <fromDate> 1895 </fromDate> <toDate> 1906 </toDate> </dateRange> <placeName valueURI="https://www.geonames.org/2988507/paris.html" vocabularySource="GeoNames"> Paris </placeName> <role valueURI="https://www.ica.org/standards/RiC/ontology#hasOrHadSpouse" vocabularySourceURI="https://www.ica.org/standards/RiC/ontology"> Esposa </role> </relation> <relation relationType="https://www.ica.org/standards/RiC/ontology#OccupationType" targetType="person"> <label> Marie Skłodowska-Curie </label> <dateRange> <fromDate> 1908 </fromDate> <toDate> 1934 </toDate> </dateRange> <placeName valueURI="https://www.geonames.org/2988507/paris.html" vocabularySource="GeoNames"> Paris </placeName> <role valueURI="https://www.ica.org/standards/RiC/ontology#hasOrHadOccupationOfType" vocabularySourceURI="https://www.ica.org/standards/RiC/ontology"> Cátedra de Física </role> </relation> <relation relationType="https://www.ica.org/standards/RiC/ontology#CreationRelation" targetType="person">
```

<label> Marie Skłodowska-Curie </label> <date> 1903 </date>
<placeName valueURI = "https://www.geonames.org/2988507/
paris.html" vocabularySource = "GeoNames"> Paris </placeName> <role
valueURI = "https://www.ica.org/standards/RiC/ontology#isAuthorOf"
vocabularySourceURI = "https://www.ica.org/standards/RiC/
ontology"> Estudiante de doctorado </role> </relation>

[Table of Contents](#)

< places >

Places

Summary

An optional child element of < description > used for grouping together one or more < place > elements.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
place	1..n

May occur within

[description](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use the optional < places > element to group together one or more occurrences of < place > . < places > must include at least one < place > element. A < descriptiveNote > element may be included if a fuller textual explanation is needed.

The prescribed order of all child elements (both required and optional) is:

< place >

< descriptiveNote >

Availability

Optional, not repeatable

Examples

```
<places> <place placeType="populatedPlace"> <label
valueURI="https://d-nb.info/gnd/4057648-6" vocabularySource="GND"
vocabularySourceURI="https://d-nb.info/gnd/"> Stockholm </label> <role
valueURI="https://d-nb.info/standards/elementset/gnd#placeOfBirth"
vocabularySource="GNDO" vocabularySourceURI="https://
d-nb.info/standards/elementset/gnd#"> Geburtsort </role>
</place> <place placeType="populatedPlace"> <label
valueURI="https://d-nb.info/gnd/4051594-1" vocabularySource="GND"
vocabularySourceURI="https://d-nb.info/gnd/"> Sankt Gallen </label>
<role valueURI="https://d-nb.info/standards/elementset/gnd#placeOfDeath"
vocabularySource="GNDO" vocabularySourceURI="https://d-
nb.info/standards/elementset/gnd#"> Sterbeort </role> </place>
</places> <places> <place placeType="populatedPlace">
<label> Treviso </label> <role valueURI="https://schema.org/
serviceLocation" vocabularySource="schema.org"> sala lettura </
role> <address> <addressLine addressLineType="street"> Via
Pietro di Dante, 11 </addressLine> <addressLine
addressLineType="postalCode"> 31100 </addressLine> <addressLine
addressLineType="country"> Italia </addressLine> </address>
<contact> <contactLine contactLineType="homepage" href="https://
www.archiviodistatotreviso.beniculturali.it/"> Visita nostro sito
web ufficiale </contactLine> </contact> </place> <place>
<label> Stanza A, fila 7, scaffale 2 </label> <role valueURI="https://
schema.org/itemLocation" vocabularySource="schema.org"> deposito </
role> </place> <place placeType="administrativeDivision">
<label valueURI="https://www.geonames.org/6697802/crete.html"
vocabularySource="GeoNames"> Regno de Cândia </label> <role
valueURI="https://www.ica.org/standards/RiC/ontology#isOrWasSubjectOf"
vocabularySource="RiC-O"> soggetto </role> </place> </places>
```

[Table of Contents](#)

<recordId>

<recordId>

Record Identifier

Summary

A required child element of [<control>](#) that designates a unique identifier for the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional

Description and Usage

[<recordId>](#) is used for recording a unique identifier for the EAS instance. The institution assigning the identifier ensures uniqueness of the [<recordId>](#) value within the archival descriptions under its control. A globally unique identifier may be constructed within [<recordId>](#) according to various external protocols (e.g. HTTP URI, DOI, PURL, or UUID), or in combination with [<agencyCode>](#) , which is an optional element within [<maintenanceAgency>](#) .
[<recordId>](#) cannot be empty.

Availability

Required, not repeatable

See also

Use [<agencyCode>](#) in combination with [<recordId>](#) to provide a globally unique identifier for the EAS instance.
Any alternative or additional record identifiers may be recorded in [<otherRecordId>](#) .

Examples

`<recordId>F10219</recordId> <recordId>ES-28079-PARES-AUT-140149</recordId> <recordId>DE-1981_C002</recordId>`

[Table of Contents](#)

<reference>

Reference

Summary

An element that cites an external resource.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
referringString	0..n
span	0..n

May occur within

[abstract](#), [conventionDeclaration](#), [eventDescription](#), [localTypeDeclaration](#), [p](#), [rightsDeclaration](#), [source](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
href	Optional
id	Optional
languageOfElement	Optional
linkRole	Optional
linkTitle	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@href](#) to link to the cited resource, in case this is available online.

Description and Usage

An element used for referencing external resources that have been used to compile the EAS instance, that provide additional context to the EAS instance, or that identify rules or conventions that have been applied.

[<reference>](#) is a required child element of [<conventionDeclaration>](#) , [<localTypeDeclaration>](#) , and [<rightsDeclaration>](#) for identifying any rules and conventions applied in the compilation of the description. It is also a required child element of [<source>](#) , used to identify any sources used in compiling the description. [<source>](#) may include multiple child [<reference>](#) elements.

In [<abstract>](#) , [<eventDescription>](#) and [<p>](#) , [<reference>](#) may be used to reference any external resources that provide additional context to the content of these elements, which may include multiple [<reference>](#) elements.

Availability

Within [<conventionDeclaration>](#) , [<localTypeDeclaration>](#) , [<rightsDeclaration>](#) : required, not repeatable

Within [<source>](#) : required, repeatable

Within [<abstract>](#) , [<eventDescription>](#) , [<p>](#) : optional, repeatable

See also

[<reference>](#) is used for external linking only. If any internal linking is required, use the [@target](#) attribute to point to the [@id](#) of the referenced element.

Examples

```
<source> <reference href="https://de.wikipedia.org/wiki/
Gustav_IV._Adolf_(Schweden)">Wikipedia</reference> </source>
<conventionDeclaration> <reference href="https://www.loc.gov/aba/
rda/">Resource Description and Access</reference> <shortCode>RDA</
shortCode> </conventionDeclaration> <maintenanceEvent
maintenanceEventType="revised"> <agent> <label>T. Baker</label>
</agent> <eventDateTime standardDateTime="2022-10">October
2022</eventDateTime> <eventDescription>The archival description
encoded in this document has been reviewed and, where necessary,
updated following the <reference href="https://guides.library.yale.edu/
reparativearchivaldescription">Reparative Archival Description Working
Group: Guiding Principles</reference>.</eventDescription> </
maintenanceEvent>
```

[Table of Contents](#)

<relation>

Relation

Summary

A required child element of [<relations>](#) for describing a relationship between the entity or records described and a related entity.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
label	1..n
objectXMLWrap	0..1
placeName	0..n
role	0..n

May occur within

[relations](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
relationType	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
targetType	Optional

Description and Usage

[<relation>](#) records descriptive information about a relationship between the CPF entity being described and other agents as well as all other types of entities like functions and records.

Use the required child element [<label>](#) to provide a textual identification of the related entity, such as a name or a title. Use the optional attribute

[@targetType](#) to classify the type of the related entity, the optional attribute [@relationType](#) to specify the type of relation in its most generic form, and the optional child element [<role>](#) to specify the role of the related entity towards the entity or the materials being described more concretely. It is recommended that the terms used in [<label>](#) and [<role>](#) be taken from an authorized vocabulary. When not using the EAS value lists for [@relationType](#) and [@targetType](#), any alternative value lists should ideally also be taken from authorized vocabularies.

Use [<objectXMLWrap>](#) to embed XML documenting the related entity from any other namespace. Use [<date>](#), [<dateRange>](#), or [<dateSet>](#) for specifying the time period of the relationship and [<placeName>](#) for relevant location information. [<descriptiveNote>](#) may be included for more detailed specifications or explanations of the relationship.

The prescribed order of all child elements (both required and optional) is:

[<label>](#)

One of [<date>](#), [<dateRange>](#), or [<dateSet>](#)

[<placeName>](#)

[<role>](#)

[<descriptiveNote>](#)

[<objectXMLWrap>](#)

Availability

Required, repeatable

Examples

```
<relation relationType="https://www.ica.org/standards/RiC/ontology#FamilyRelation" targetType="person"> <label>Marie Skłodowska-Curie</label> <dateRange> <fromDate>1895</fromDate> <toDate>1906</toDate> </dateRange> <placeName valueURI="https://www.geonames.org/2988507/paris.html" vocabularySource="GeoNames">Paris</placeName> <role valueURI="https://www.ica.org/standards/RiC/ontology#hasOrHadSpouse" vocabularySourceURI="https://www.ica.org/standards/RiC/ontology">Esposa</role> </relation> <!-- This is not consistent, as OccupationType is not a relation in RiC-O. The relation element should directly point to the rico:hasOrHadOccupationOfType that the role element refers to <relation relationType="https://www.ica.org/standards/RiC/ontology#OccupationType" targetType="person"> --> <relation relationType="https://www.ica.org/standards/RiC/
```

```

ontology#hasOrHadOccupationOfType" targetType = "person">
<label> Marie Skłodowska-Curie </label> <dateRange>
<fromDate> 1908 </fromDate> <toDate> 1934 </toDate> </
dateRange> <placeName valueURI = "https://www.geonames.org/2988507/
paris.html" vocabularySource = "GeoNames"> Paris </placeName>
<!-- <role valueURI = "https://www.ica.org/standards/RiC/
ontology#hasOrHadOccupationOfType" vocabularySourceURI = "https://
www.ica.org/standards/RiC/ontology"> Cátedra de Física </role>
</relation> --> <relation relationType = "https://www.ica.org/
standards/RiC/ontology#CreationRelation" targetType = "person">
<label> Marie Skłodowska-Curie </label> <date> 1903 </date>
<placeName valueURI = "https://www.geonames.org/2988507/
paris.html" vocabularySource = "GeoNames"> Paris </placeName> <role
valueURI = "https://www.ica.org/standards/RiC/ontology#isAuthorOf"
vocabularySourceURI = "https://www.ica.org/standards/RiC/
ontology"> Estudiante de doctorado </role> </relation>

```

[Table of Contents](#)

<relations>

Relations

Summary

An optional element that groups one or more [<relation>](#) elements, which identify external entities and characterize the nature of their relationships to the entity or records being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
relation	1..n

May occur within

[cpfDescription](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

A wrapper element that groups together one or more [<relation>](#) elements, each of which encodes a specific relationship.

The prescribed order of all child elements (both required and optional) is:

[<relation>](#)

[<descriptiveNote>](#)

Availability

Optional, not repeatable

Examples

```
<relations> <relation relationType="family" targetType="person"> <label
valueURI="https://d-nb.info/gnd/119067159X" vocabularySource="GND"
vocabularySourceURI="https://d-nb.info/gnd/">Arendt, Max
(1843-1913)</label> <role>grandfather</role> </relation>
<relation relationType="family" targetType="person"> <label
valueURI="https://d-nb.info/gnd/1190672170" vocabularySource="GND"
vocabularySourceURI="https://d-nb.info/gnd/">Arendt-Beerwald,
Martha (1874-1948)</label> <role>mother</role> </relation>
<relation relationType="family" targetType="person"> <label
valueURI="https://d-nb.info/gnd/1190671301" vocabularySource="GND"
vocabularySourceURI="https://d-nb.info/gnd/">Arendt, Paul
(1873-1913)</label> <role>father</role> </relation> </relations>
<relatedMaterial> <abstract>Several genealogies and biographies of
the Smith family have been published and are held in the Rare Books
Department.</abstract> <relations> <relation targetType="resource">
<label valueURI="4569982" vocabularySource="Rare Books
Department">Kavanaugh, Carol. The Smith Family in Johnson County
(New York: Penguin)</label> </relation> <relation> <label
valueURI="336712" vocabularySource="Rare Books Department">Llewellyn,
Gareth. Smythe, Smith: What's the Difference? (London: Jonathan Cape)</
label> </relation> </relations> </relatedMaterial>
```

[Table of Contents](#)

< relationship >

Relationship

Summary

A child element of [<agent>](#) and [<place>](#) used to specify the type of relationship that these entities have with the EAS instance respectively with the entity being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[agent](#), [place](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide a number, code, or string (e.g., URI) that uniquely identifies the relationship in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) and/or [@vocabularySourceURI](#) to name and/or point to the organization system used.

Description and Usage

Use `<relationship>` within `<agent>` and `<place>` to specify the type of relation that these entities have with the entity being described within the EAS instance, e.g. "maintenance" for the agent named in `<maintenanceEvent>`, "residence" for places. To more specifically indicate the role of the related entity towards the entity being described in the EAS instance (e.g. "archivist" or "volunteer" for the agent in `<maintenanceEvent>`, "birthplace" or "currentResidence" for places), the element `<role>` should be used instead of or in combination with `<relationship>`.

The `<relationship>` element contains a textual description of the relation. It is recommended that values used in `<relationship>` be taken from an authorized vocabulary.

Availability

Optional, Repeatable

See also

Use `<role>` to more specifically indicate the role of the related entity towards the entity being described in the EAS instance respectively towards the EAS instance itself.

Examples

```
<maintenanceHistory> <maintenanceEvent id="me1"> <agent>
<label>Tanya Smith</label> <role>Archivist</role> <relationship
valueURI="https://www.ica.org/standards/RiC/ontology#AuthorshipRelation"
vocabularySourceURI="https://www.ica.org/standards/RiC/ontology"/>
</agent> <eventDateTime standardDateTime="2021-09">September
2021</eventDateTime> <eventDescription>Creation of the encoded
archival description</eventDescription> </maintenanceEvent>
<maintenanceEvent id="me2"> <agent> <label>Gregory Miller</label>
<role>Volunteer</role> <relationship valueURI="https://www.ica.org/
standards/RiC/ontology#CreationRelation" vocabularySourceURI="https://
www.ica.org/standards/RiC/ontology"/> </agent> <eventDateTime
standardDateTime="2023-05">May 2023</eventDateTime>
<eventDescription>Marking persons and organisations named in
narrative texts as part of a crowdsourcing project</eventDescription> </
maintenanceEvent> </maintenanceHistory>
```

[Table of Contents](#)

<referringString>

Referring String

Summary

An element for marking words or phrases in a longer text as named entities.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[abstract](#), [eventDescription](#), [p](#), [reference](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
normalizedForm	Optional
referredEntityRelationship	Optional
referredEntityType	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@referredEntityType](#) to indicate the type of entity that is named in the narrative text and [@referredEntityRelationship](#) to specify the relation between that named entity and the entity being described in the EAS instance. Use [@normalizedForm](#) to provide a standardised form of the name following e.g. an external vocabulary.

Use [@valueURI](#) to provide a number, code, or string (e.g., URI) that uniquely identifies the entity in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) and/or [@vocabularySourceURI](#) to name and/or point to the organization system used.

Description and Usage

Use [<referringString>](#) in longer texts to indicate that certain words or phrases within these texts represent named entities such as persons, organisations, places, functions, resources, etc.

Use [<referringString>](#) e.g. when the identification of such named entities within existing archival descriptions is the result of some natural language processing or when capturing the results of named entity recognition having been conducted as part of Optical Character Recognition or Handwritten Text Recognition tasks.

Availability

Optional, repeatable

See also

Only fall back on using [<referringString>](#) in the contexts mentioned above.

Examples

```
<p> See the following publication for background
information: <referringString referredEntityType="person"
normalizedForm="Bernier, Pierre-François (1779-1803)"> P.-F.
BERNIER </referringString>, <referringString referredEntityType="work"
referredEntityRelationship="https://www.ica.org/standards/RiC/
ontology#RecordResourceGeneticRelation"> Études particulières </
referringString> </p>
```

[Table of Contents](#)

<rightsDeclaration>

Rights Declaration

Summary

An optional child element of [<control>](#) that indicates a standard rights statement associated with the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
reference	1..1
shortCode	0..1

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

Use [<rightsDeclaration>](#) to provide structured information about the usage rights of the EAS instance. [<rightsDeclaration>](#) should only be used to reference shared published licenses, such as Creative Commons, RightsStatements.org, or published locally-defined licenses. In cases where different licenses apply depending on the type of descriptive metadata, e.g. the Public Domain Mark for any factual metadata, but CC BY for any more narrative metadata that requires an additional research effort in its creation such as scope and content notes or biographies of records creators, these can be encoded in two separate [<rightsDeclaration>](#) elements. Include an [@id](#)

for each `<rightsDeclaration>` element and use `@target` with descriptive elements to point to the license that applies.

`<reference>` must be used to provide a machine-readable reference to a license statement (for example, a URI). It may also be used to encode the name of the license statement.

`<shortCode>` may be used to provide the abbreviated name for the rights statement. The value of `<shortCode>` should align with the rights statement referenced by `<reference>` and `<descriptiveNote>` .

`<descriptiveNote>` may be used to provide a human-readable description of the license statement.

The prescribed order of all child elements (both required and optional) is:

`<reference>`

`<shortCode>`

`<descriptiveNote>`

Availability

Optional, repeatable

Examples

```
<rightsDeclaration> <reference href="https://creativecommons.org/publicdomain/zero/1.0/deed.de"> Creative Commons CC0 1.0 Universal (CC0 1.0) Public Domain Dedication </reference> <shortCode> CC0 1.0 </shortCode> </rightsDeclaration>
```

[Table of Contents](#)

<role>

Role

Summary

An optional child element of [<agent>](#) , [<place>](#) , and [<relation>](#) that indicates the role of the related entity towards the entity being described in the EAS instance or the EAS instance itself.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[agent](#), [place](#), [relation](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

Use [<role>](#) to indicate the role of the related entity towards the entity being described in the EAS instance or the EAS instance itself. It is recommended that the terms in [<role>](#) be taken from authorized vocabularies.

[<role>](#) might be used in combination with the specific type attribute available with each of the elements where [<role>](#) is available. While these attributes provide a generic typology of each entity class, e.g. "corporateBody", "person", and "family" for [@agentType](#), [<role>](#) looks more specifically at the related entity itself in a certain context.

Furthermore, `<role>` may be used in combination with `<relationship>` which is available in `<agent>` and `<place>`. While `<relationship>` is used to encode a more general denominator for the relation between the related entity and the entity being described in the EAS instance, e.g. "creation" or "authorship" for agents, `<role>` allows to be more specific to the individual related entity, e.g. by assigning the role of "archivist" to one `<agent>` and the role of "volunteer" to another.

Availability

Optional, repeatable

See also

Use the element `<label>` to encode the related entity's name.

Examples

```
<maintenanceHistory> <maintenanceEvent id="me1"> <agent>
<label>Tanya Smith</label> <role>Archivist</role> <relationship
valueURI="https://www.ica.org/standards/RiC/ontology#AuthorshipRelation"
vocabularySourceURI="https://www.ica.org/standards/RiC/ontology"/>
</agent> <eventDateTime standardDateTime="2021-09">September
2021</eventDateTime> <eventDescription>Creation of the encoded
archival description</eventDescription> </maintenanceEvent>
<maintenanceEvent id="me2"> <agent> <label>Gregory Miller</label>
<role>Volunteer</role> <relationship valueURI="https://www.ica.org/
standards/RiC/ontology#CreationRelation" vocabularySourceURI="https://
www.ica.org/standards/RiC/ontology"/> </agent> <eventDateTime
standardDateTime="2023-05">May 2023</eventDateTime>
<eventDescription>Marking persons and organisations named in
narrative texts as part of a crowdsourcing project</eventDescription> </
maintenanceEvent> </maintenanceHistory>
```

[Table of Contents](#)

< setComponent >

Set Component

Summary

A required child element of [< alternativeSet >](#) that allows an alternative authority record of the EAC-CPF instance being described to be referenced and described, as well as allowing the inclusion of the entire encoding of such alternative authority record in any XML format.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
componentEntry	0..n
descriptiveNote	0..1
objectXMLWrap	0..1

May occur within

[alternativeSet](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
href	Optional
id	Optional
languageOfElement	Optional
linkRole	Optional
linkTitle	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@href](#) to provide a general reference to alternative sets.

Description and Usage

[<setComponent>](#) provides a wrapper to link to, describe, or contain one or more alternative authority record, so that multiple records for the same entity from separate authority systems, or in different languages, may be combined together within a single EAC-CPF instance.

The [<componentEntry>](#) child element allows for the provision of a name or title for the alternative authority record and the inclusion of a link to the record in an external system, if using a vocabulary or similar.

Use the optional [<descriptiveNote>](#) for a textual note providing further information about the record referenced in [<setComponent>](#).

Use the optional [<objectXMLWrap>](#) child element when including the entire authority record within the EAC-CPF instance.

Availability

Required, repeatable

Examples

See [<alternativeSet>](#) encoding

[Table of Contents](#)

< shortCode >

Short Code

Summary

An optional element for encoding the shortened form of the rule, code list, vocabulary, rights statement etc applied in creating and maintaining the EAS instance and captured in [< conventionDeclaration >](#) , [< localTypeDeclaration >](#) and [< rightsDeclaration >](#) .

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[conventionDeclaration](#), [localTypeDeclaration](#), [rightsDeclaration](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional

Description and Usage

Use [< shortCode >](#) within [< conventionDeclaration >](#) or [< localTypeDeclaration >](#) to identify the shortened form, acronym, or code for a thesaurus, controlled vocabulary, or another standard used in creating the EAS description. Use within [< rightsDeclaration >](#) to provide an abbreviated name for the rights statement.

To improve interoperability, it is recommended that the value be selected from an authorized list of codes such as the MARC Field Index to Source Code Usage (<http://www.loc.gov/marc/sourcelist/>).

Availability

Optional, not repeatable

Examples

```
< conventionDeclaration id = "conventiondeclaration1" > <reference> Anglo-  
American Cataloging Rules, Revised </reference> <shortCode> AACR2 </  
shortCode> </conventionDeclaration> <rightsDeclaration> <reference  
href = "https://creativecommons.org/licenses/by/4.0/" > Creative Commons  
Attribution 4.0 International Public License </reference> <shortCode> CC  
BY </shortCode> </rightsDeclaration>
```

[Table of Contents](#)

< source >

Source

Summary

A required and repeatable child element of [<sources>](#) used to identify a particular source of evidence used for the establishment of the descriptive parts in an EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
citedRange	0..n
descriptiveNote	0..1
objectXMLWrap	0..1
reference	1..n

May occur within

[sources](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
href	Optional
languageOfElement	Optional
linkRole	Optional
linkTitle	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

In the case of online sources, use [@href](#) to provide a URL. In case an online source is identified via a persistent identifier (PID) such as a DOI or and ARK, use [@valueURI](#) instead and indicate the PID scheme in [@vocabularySource](#) and/or [@vocabularySourceURI](#).

Description and Usage

Use `<source>` to cite a published resource used in creating the descriptive parts of the EAS instance. Use the required child element `<reference>` to include a textual identification of the source. Use the optional child element `<citedRange>` to point to a specific location within a source.

Use the optional `<descriptiveNote>` for any additional notes about the source. Use the optional `<objectXMLWrap>` to embed XML documenting the source from any other namespace.

The prescribed order of all child elements (both required and optional) is:

`<reference>`

`<citedRange>`

`<descriptiveNote>`

`<objectXMLWrap>`

Availability

Required, repeatable

Examples

```
<sources> <source href="https://de.wikipedia.org/wiki/Gustav_IV._Adolf_(Schweden)"> <reference> Wikipedia-Seite zu Gustav IV. Adolf</reference> </source> <source href="https://sok.riksarkivet.se/sbl/Presentation.aspx?id=13318"> <reference> Svenskt biografiskt lexikon</reference> <descriptiveNote> <p>Stand: 03.12.2020</p> </descriptiveNote> </source> </sources>
```

[Table of Contents](#)

< sources >

Sources

Summary

An optional child element of [< control >](#) that groups one or more [< source >](#) s of evidence used in the descriptive parts in the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
source	1..n

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional

Description and Usage

Use [< sources >](#) to bind together one or more [< source >](#) elements.

[< sources >](#) must include at least one [< source >](#) element.

The prescribed order of all child elements (both required and optional) is:

[< source >](#)

[< descriptiveNote >](#)

Availability

Optional, not repeatable

Examples

< sources> < source> < reference> Provenienzmerkmal </reference> </source> < source href="http://staatsbibliothek-berlin.de/die-staatsbibliothek/geschichte/"> < reference> Geschichte der Staatsbibliothek zu Berlin </reference> < descriptiveNote> < p> Stand: 31.07.2018 </p> </descriptiveNote> </source> </sources>

[Table of Contents](#)

< span >

span

Summary

Specifies the beginning and the end of a span of text.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[abstract](#), [eventDescription](#), [reference](#), [p](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
style	Optional
target	Optional

Attribute usage

Use the optional [@style](#) attribute to specify an arbitrary stylistic difference.

Description and Usage

[< span >](#) is an optional formatting element for distinguishing words or phrases that are intentionally stressed or emphasized for linguistic effect or identifying some qualities of the words or phrases.

Availability

Optional, repeatable

Examples

<p> Robert Carlton Brown (1886-1959) was a writer, editor, publisher, and traveler. From 1908 to 1917, he wrote poetry and prose for numerous magazines and newspapers in New York City, publishing two pulp novels, What Happened to Mary and The Remarkable Adventures of Christopher Poe (1913), and one volume of poetry, My Marjonary (1916). </p>

[Table of Contents](#)

<structureOrGenealogy>

Structure or Genealogy

Summary

An optional child element of [<description>](#) used to describe internal administrative structure(s) of a corporate body or the genealogy of a family.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
p or formattingExtension	0..n

May occur within

[description](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[<structureOrGenealogy>](#) encodes information expressing the internal administrative structure(s) of a corporate body and the dates of any changes to that structure that are significant to understanding the way that corporate body conducted affairs (such as dated organization charts), or the genealogy of a family (such as a family tree) in a way that demonstrates the interrelationships of its members with relevant dates.

The optional [<formattingExtension>](#) element may be used to accommodate greater complexity in expressing or representing the structure(s) or genealogy being described. A simpler discursive expression of the structure(s) or genealogy may be encoded as one or more [<p>](#) elements.

Availability

Optional, repeatable

Examples

See [<description>](#) encoding

[Table of Contents](#)

< term >

Term

Summary

An element used to encode a descriptive term in accordance with authorized vocabularies or local rules.

May contain

Element/content type
[text]

Occurrences

May occur within

[demographicDescription](#), [functionPerformed](#), [legalStatus](#), [localDescription](#), [mandate](#), [occupation](#), [otherEntityType](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

< term > is a required child element of < [demographicDescription](#) >, < [functionPerformed](#) >, < [legalStatus](#) >, < [localDescription](#) >, < [mandate](#) >, < [occupation](#) >, and < [otherEntityType](#) >, used to specify a descriptive term in accordance with authorized vocabularies or local rules. < term > can be repeated within its parent element to include translations of the same term. Use the @[languageOfElement](#) attribute to identify the language used in each < term > grouped within a single parent element.

Availability

Required, repeatable

Examples

```
<functionPerformed> <term>Estate ownership</term>
<descriptiveNote> <p>Social, political, and cultural role typical of
landed aristocracy in England. The first Viscount Campden amassed a large
fortune in trade in London and purchased extensive estates, including Exton
(Rutland), and Chipping Campden (Gloucestershire). The Barham Court
(Kent) estate was the acquisition of the first Baron Barham, a successful
admiral and naval administrator (First Lord of the Admiralty 1805).</
p> </descriptiveNote> </functionPerformed> <legalStatus> <term
scriptOfElement="Latn">Organismo de la Administracion Central del
Estado</term> <date standardDate="1769">1769</date> </
legalStatus> <mandate> <term>Minnesota. Executive Session Laws 1919
c49</term> <dateRange> <fromDate standardDate="1919">1919</
fromDate> <toDate standardDate="1925">1925</toDate> </
dateRange> <descriptiveNote> <p>Board created in 1919 to receive
and examine applications for bonuses from Minnesota soldiers</p> </
descriptiveNote> </mandate> <occupation> <term>Teacher</
term> </occupation> <subjectHeadings> <p>Use the following
index to find photographs within the collection related to specific
subjects.</p> <subject valueURI="https://id.loc.gov/authorities/
subjects/sh85016829" vocabularySource="LCSH" target="photo-1234-001
photo-1234-010 photo-1234-015"> <term>Bridges</term> </subject>
<subject valueURI="http://id.loc.gov/authorities/subjects/sh85025854"
vocabularySource="LCSH" target="photo-1234-002 photo-1234-003
photo-1234-004 photo-1234-019 photo-1234-020"> <term>Churches</
term> </subject> <subject valueURI="http://id.loc.gov/authorities/
subjects/sh85046823" vocabularySource="LCSH" target="photo-1234-030
photo-1234-031 photo-1234-032 photo-1234-040"> <term>Factories</
term> </subject> <subject valueURI="https://id.loc.gov/authorities/
subjects/sh85051067" vocabularySource="LCSH" target="photo-1234-012
photo-1234-016 photo-1234-021"> <term>Fountains</term> </
subject> <subject valueURI="https://id.loc.gov/authorities/subjects/
sh85053101" vocabularySource="LCSH" target="photo-1234-027
photo-1234-039"> <term>Gardens</term> </subject> <subject
valueURI="http://id.loc.gov/authorities/subjects/sh85062487"
vocabularySource="LCSH" target="photo-1234-005 photo-1234-011
photo-1234-029"> <term>Hotels</term> </subject> <subject
valueURI="http://id.loc.gov/authorities/subjects/sh85088723"
vocabularySource="LCSH" target="photo-1234-006 photo-1234-014
photo-1234-017 photo-1234-018 photo-1234-026 photo-1234-033">
<term>Museums</term> </subject> <subject valueURI="http://
id.loc.gov/authorities/subjects/sh85118451" vocabularySource="LCSH"
target="photo-1234-024 photo-1234-025"> <term>Schools</term>
</subject> <subject valueURI="http://id.loc.gov/authorities/subjects/
sh85134578" vocabularySource="LCSH" target="photo-1234-013
photo-1234-035 photo-1234-038"> <term>Theaters</term> </
```

subject> <subject valueURI="http://id.loc.gov/authorities/subjects/sh85141086" vocabularySource="LCSH" target="photo-1234-007 photo-1234-008 photo-1234-022 photo-1234-028 photo-1234-032 photo-1234-034"> <term>Universities and colleges</term> </subject>
 </subjectHeadings> <legalStatus> <term>Student records</term>
 <descriptiveNote> <p>Student records are governed by the Family Educational Rights and Privacy Act (FERPA), 20 U.S.C. § 1232g.</p> </descriptiveNote> </legalStatus> <legalStatus> <term>Patient records</term>
 <descriptiveNote> <p>Patient records are governed by the Health Insurance Portability and Accountability Act, Pub.L. 104–191 and 110 Stat. 1936. Article 8 ECHR may also apply.</p> </descriptiveNote> </legalStatus>

[Table of Contents](#)

< toDate >

To Date

Summary

A child element of [< dateRange >](#) that records the end point in a range of dates.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[dateRange](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
calendar	Optional
certainty	Optional
conventionDeclarationReference	Optional
era	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
notAfter	Optional
notBefore	Optional
scriptOfElement	Optional
standardDate	Optional
status	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@certainty](#) to indicate the degree of precision in the dating, for example, "uncertain" or "approximate".

Use [@localType](#) to supply a more specific characterization of the end date.

Use [@notAfter](#) and [@notBefore](#) to capture the latest and earliest possible dates in machine-processable form in cases when the date is uncertain.
Use [@standardDate](#) to provide a machine-processable form of the date.
Use [@status](#) with the values "unknown" or "ongoing" to indicate where part of a date range is unknown, or the date range is ongoing.

Description and Usage

Use [<toDate>](#) to record the end date in a range of dates, whether they be known, approximate or unknown. The content of the element is intended to be a human-readable, natural language expression of the date. If, however, indexing or other machine processing of dates is desired, the [@standardDate](#) should be used to record the date in machine-processable form as well.
[<toDate>](#) may be omitted from [<dateRange>](#) , or the [@status](#) attribute used, if the date span is ongoing or the [<toDate>](#) is unknown.

Availability

Optional, not repeatable

See also

Use [<fromDate>](#) to record the starting point of a date range.

Examples

```
<dateRange> <fromDate standardDate="1868"> 1868 </fromDate> <toDate standardDate="1936"> 1936 </toDate> </dateRange> <dateRange> <fromDate status="unknown"/> <toDate certainty="uncertain" standardDate="2010?"> c.2010 </toDate> </dateRange> <dateRange> <fromDate standardDate="2016-09"> September 2016 </fromDate> <toDate status="ongoing"/> </dateRange>
```

[Table of Contents](#)

< useDates >

Dates of Use

Summary

An optional child element of < nameEntry > and < nameEntrySet > that provides the dates when the name or names were used for or by the entity being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	1..1

May occur within

nameEntry, nameEntrySet

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Within < nameEntry > , < useDates > provides the dates during which the name was used for or by the entity being described. For parallel names (e.g., official forms of the name in different languages and/or scripts), < useDates > may occur in < nameEntrySet > rather than in the individual < nameEntry > elements contained in < nameEntrySet > .
< useDates > must include one of < date > , < dateRange > , or < dateSet > .

Availability

Optional, repeatable

Examples

```
<nameEntry status="authorized"> <part> Technical Subcommittee  
for Encoded Archival Standards</part> <useDates> <dateRange>  
<fromDate> 2015</fromDate> <toDate status="ongoing"/> </  
dateRange> </useDates> </nameEntry>
```

[Table of Contents](#)

< writingSystem >

Writing System

Summary

An optional child element of [< languageUsed >](#) that identifies the writing script for a language used by the described entity.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[languageUsed](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptCode	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@scriptCode](#) to provide a code for the writing system itself.
Use [@scriptOfElement](#) to provide a code for the writing system in which the element is given.

Description and Usage

An optional element within [< languageUsed >](#) that gives the main script used by the entity being described.

Availability

Optional, repeatable

Examples

```
<languageUsed> <language languageCode="eng"> English </  
language> <writingSystem scriptCode="Latn"> Latin </writingSystem>  
</languageUsed> <languageOfMaterial> <languageSet>  
<writingSystem scriptCode="Latn"> Latin </writingSystem>  
<language languageCode="eng"> English </language> <language  
languageCode="ang"> Old English </language> <language  
languageCode="lat"> Latin </language> </languageSet> <languageSet>  
<language languageCode="gre"> Greek </language> <writingSystem  
scriptCode="Grek"> Greek </writingSystem> </languageSet>  
<descriptiveNote> <p>The majority of the documents are written  
in Modern English. Roberts copied multiple passages from original  
manuscripts in Latin, Greek and Old English. </p> </descriptiveNote>  
</languageOfMaterial> <languageOfMaterial> <languageSet>  
<language languageCode="jpn"> Japanese </language> <writingSystem  
scriptCode="Hira"> hiragana </writingSystem> <writingSystem  
scriptCode="Kana"> katakana </writingSystem> </languageSet>  
<descriptiveNote> <p>This file contains documents in Japanese, in  
both the hiragana and katakana scripts. </p> </descriptiveNote> </  
languageOfMaterial>
```

[Table of Contents](#)

Attributes

Introduction

Attributes are associated with most of the elements contained in EAC-CPF. Attributes reflect named properties of an element and may take on different values, depending on the context in which they occur. In order to set one or more attributes, an encoder should include the name of the attribute(s) within the same angle brackets as the start tag, together with the value(s) to which the attribute(s) is/are to be set. That is, `<[tag] [attribute] = "[value]">` or `<[tag] [attribute1] = "[value1]" [attribute2] = "[value2]">` For example: `<fromDate standardDate = "1939"> 1939</fromDate>` or `<fromDate certainty = "approximate" standardDate = "1939"> 1939</fromDate>` Most attributes are optional, though some are required. The attribute description indicates whether an attribute is required. This information is also available in the Attributes section of each element description. The value of attributes may be constrained by the schema using specific attribute type values. For example, the `@id` attribute is of type ID, which constrains its value to a string beginning with an alphabetic character. An id value must be unique within the EAC-CPF instance within which it occurs, that is, no other tag in the entire document can have the same id value. EAC-CPF attributes have the following data types (capitalization of data types follows the documentation found in the W3C Recommendation XML Schema Part 2: Datatypes Second Edition (<http://www.w3.org/TR/xmlschema-2/>):

anyURI:

A Uniform Resource Identifier. This may be a Uniform Resource Locator (URL) or a Uniform Resource Name (URN). Both relative and absolute URIs are allowed.

ID:

Unique identifier. For example, most elements have an id, so that a unique code can be established for and used to refer to that specific element. The content of the id is of the type called "ID". Parsers verify that the value of attributes of type "ID" are unique. The values of id must begin with an alpha, not numeric, character, either upper or lowercase, and may contain a . (period), : (colon), - (hyphen), or _ (underscore), but not a blank space. See also attributes of type "IDREF."

IDREFS:

List of ID reference values; values must match an existing ID of another element in the document.

NMTOKEN:

A name token, which can consist of any alpha or numeric character, as well as a . (period), : (colon), - (hyphen), or _ (underscore), but not a blank space. A

number of attributes in EAC-CPF where a character string from a code list is to be used are of the type "NMTOKEN".

normalizedString:

The most general data type, a string can contain any sequence of characters allowed in XML. Certain characters may have to be represented with an entity reference, for example < for <, and & for &.

token:

A type of string that may not contain carriage return, line feed or tab characters, leading or trailing spaces, and any internal sequence of two or more spaces.

When the EAC-CPF schema limits attribute values to a few choices, those values are declared in the schema in what is known as a "closed list." For example, the values of [@audience](#) are limited to either "external" or "internal." Other attributes are associated with semi-closed lists. Such lists include those values believed to be the most useful in many contexts, but other values are allowed. For example, [<language>](#) defines several values for [@languageEncoding](#), including "otherLanguageEncoding" which may be used to specify values that are not in the semi-closed list for [@languageEncoding](#). The definitions for some values in the closed and semi-closed lists appear below. The following is a complete list of all the attributes that occur in EAC-CPF, and some discussion of how they may be used. Further, context-specific information about the use of certain attributes may be found in the "Attribute usage" section of the element descriptions.

@addressLineType

Address Line Type

Summary

Used to specify the type of address line encoded in [<addressLine>](#) .

Description and Usage

Use [@addressLineType](#) with [<addressLine>](#) to specify the type of address line, e.g. "street", "country" or "postalCode". Use the attribute [@addressLineTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@addressLineType](#).

Data Type

token

Examples

```
<address> <addressLine languageOfElement="se"> Kungl. Hovstaterna  
</addressLine> <addressLine languageOfElement="se"> Kungl.  
Slottet </addressLine> <addressLine addressLineType="postalCode">  
10770 </addressLine> <addressLine languageOfElement="se"  
addressLineType="municipality"> Stockholm </addressLine>  
<addressLine languageOfElement="se" addressLineType="country">  
Sverige </addressLine> <addressLine languageOfElement="en"  
addressLineType="country"> Sweden </addressLine> </address>
```

[Table of Contents](#)

@addressLineTypeEncoding

Address Line Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of address line given as part of a physical address.

Description and Usage

[@addressLineTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@addressLineType](#) within [<addressLine>](#) . If the value "EASList" is selected, [@addressLineType](#) will be expected with the values "county", "country", "district", "municipality", "postBox", "postalCode", "region", or "street". If the value "otherAddressLineTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherAddressLineTypeEncoding

Examples

```
<control addressLineTypeEncoding = "EASList"/>
```

[Table of Contents](#)

@agentType

Agent Type

Summary

An optional attribute of `<agent>` that indicates the type of agent relevant in a specific context.

Description and Usage

Use `@agentType` in `<agent>` to specify the type of agent responsible for the creation, modification, or deletion of an EAS instance, when used within `<maintenanceEvent>`, or the type of agent relevant in the context of a `<narrativeEvent>`. Use the attribute `@agentTypeEncoding` in `<control>` to identify the list of authoritative terms that can be used as values of `@agentType`.

Data Type

token

Examples

```
<maintenanceEvent maintenanceEventType="updated"> <agent
agentType="human"> <label>A. Smith</label> </agent>
<eventDateTime standardDateTime="2021-12">December 2021</
eventDateTime> </maintenanceEvent> <biogHist> <narrativeEvent>
<date standardDate="1964-10">October 1964</date> <agent
agentType="group"> <label>Labour government</label> </agent>
<eventDescription>Created the new office of Secretary of State for Economic
Affairs (combined with First Secretary of State) and set up the Department of
Economic Affairs under the Ministers of the Crown Act 1964 to carry primary
responsibility for long term economic planning.</eventDescription> </
narrativeEvent> <narrativeEvent> <date standardDate="1964-10-16">16
October 1964</date> <agent agentType="person"> <label>George
Brown</label> </agent> <eventDescription>Appointed as First Secretary
of State and Secretary of State for Economic Affairs, and as chairman of the
National Economic Development Council (NEDC).</eventDescription>
</narrativeEvent> [...] </biogHist> <biogHist> <narrativeEvent>
<date standardDate="1964-10">October 1964</date> <agent
agentType="group"> <label>Labour government</label> </agent>
<eventDescription>Created the new office of Secretary of State for Economic
Affairs (combined with First Secretary of State) and set up the Department of
```


Economic Affairs under the Ministers of the Crown Act 1964 to carry primary responsibility for long term economic planning. </eventDescription> </narrativeEvent> <narrativeEvent> <date standardDate="1964-10-16">16 October 1964</date> <agent agentType="person"> <label>George Brown</label> </agent> <eventDescription> Appointed as First Secretary of State and Secretary of State for Economic Affairs, and as chairman of the National Economic Development Council (NEDC). </eventDescription> </narrativeEvent> [...] </biogHist> <archDesc> <identificationData> <unitTitle> National Association for the Advancement of Colored People records, 1842-2019</unitTitle> <unitDate> <dateRange> <fromDate standardDate="1842">1842</fromDate> <toDate standardDate="2019">2019</toDate> <dateRange> <unitDate> </identificationData> <agents> <agent agentType="corporateBody"> <label> National Association for the Advancement of Colored People</label> <role> Creator</role> </agent> <agent agentType="corporateBody"> <label> Library of Congress</label> <role> Holding institution</role> </agent> </agents> [...] </archDesc>

[Table of Contents](#)

@agentTypeEncoding

Agent Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of agent.

Description and Usage

[@agentTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@agentType](#) within `<agent>`. If the value "EASList" is selected, [@agentType](#) will be expected with the values "corporateBody", "family", "group", "human", "mechanism", "person", "position", or "unknown". If the value "otherAgentTypeEncoding" is selected, an alternate code list should be specified in `<conventionDeclaration>`. This optional attribute is available only in `<control>`.

Values

EASList, otherAgentTypeEncoding

Examples

```
<control agentTypeEncoding = "EASList"/>
```

[Table of Contents](#)

@audience

Audience

Summary

An optional attribute that helps control whether the information contained in the element should be available to all viewers or only to repository staff.

Description and Usage

Available as global attribute for all elements. The attribute can be set to "external" in e.g. `<cpfDescription>` in EAC-CPF, `<archDesc>` in EAD, or `<functionsDescription>` in EAF to allow access to all the information about the entity, materials, or functions being described, but specific elements within these sections can also be set to "internal" to reserve that information for repository access only. This feature is intended to assist application software in restricting access to particular information by explicitly identifying data that is potentially sensitive or may otherwise have a limited audience. Special software capability may be needed, however, to prevent the display or export of an element marked "internal" when a whole EAS instance is displayed in a networked environment. Use the attribute `@audienceEncoding` in `<control>` to identify the list of terms to be used as values of `@audience`.

Data Type

token

Examples

```
<eac audience="external"> [...] </eac> <ead audience="external"> [...]
</ead> <eaf audience="external"> [...] </eaf>
```

[Table of Contents](#)

@audienceEncoding

Audience Encoding

Summary

Specifies the authoritative source or rules for values used to indicate whether information encoded in a specific element is available for all or only for a restricted audience.

Description and Usage

[@audienceEncoding](#) specifies the authoritative source or rules for values supplied in [@audience](#) available in all elements. If the value "EASList" is selected, [@audience](#) will be expected with the values "external" or "internal". If the value "otherAudienceEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherAudienceEncoding

Examples

```
<control audienceEncoding="EASList"/>
```

[Table of Contents](#)

@calendar

Calendar

Summary

System of reckoning time, such as Gregorian calendar or Julian calendar.

Description and Usage

Suggested values include, but are not limited to, "gregorian" and "julian". Available in [<date>](#) , [<fromDate>](#) , [<toDate>](#) .

Data Type

token

Examples

```
<dateRange> <fromDate calendar="gregorian" certainty="approximate"
era="ce" standardDate="1950"> 1950 </fromDate> <toDate
calendar="gregorian" certainty="approximate" era="ce"
standardDate="2000"> 2000 </toDate> </dateRange>
```

[Table of Contents](#)

@certainty

Certainty

Summary

The level of confidence for a date.

Description and Usage

The optional attribute [@certainty](#) provides level of confidence for the information given in [<date>](#) , [<fromDate>](#) , or [<toDate>](#) , e.g., approximate or circa.

Data Type

token

Examples

`<date certainty="uncertain" standardDate="1968?"> c.1968 </date>`
[Table of Contents](#)

@contactLineType

Contact Line Type

Summary

Used to specify the type of contact line encoded in [<contactLine>](#) .

Description and Usage

An attribute used to specify the type of contact line encoded in [<contactLine>](#) , e.g. "email", "phoneNumber" or "homepage".

Data Type

token

Examples

```
<contact> <contactLine contactLineType="phoneNumber">
08-402 60 00 </contactLine> <contactLine
languageOfElement="se" contactLineType="homepage"> https://
www.kungahuset.se/2.1c3432a100d8991c5b80001816.html
</contactLine> <contactLine languageOfElement="en"
contactLineType="homepage"> https://www.kungahuset.se/
royalcourt.4.367010ad11497db6cba800054503.html </contactLine> </
contact>
```

[Table of Contents](#)

@contactLineTypeEncoding

Contact Line Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of contact line given as part of a digital address.

Description and Usage

[@contactLineTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@contactLineType](#) within [<contactLine>](#) . If the value "EASList" is selected, [@contactLineType](#) will be expected with the values "directions", "email", "fax", "homepage", "mobileNumber", or "phoneNumber". If the value "otherContactLineTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherContactLineTypeEncoding

Examples

```
<control contactLineTypeEncoding="EASList"/>
```

[Table of Contents](#)

@conventionDeclarationReference

Convention Declaration Reference

Summary

Use [@conventionDeclarationReference](#) to provide a direct link to a [<conventionDeclaration>](#) element within [<control>](#) .

Description and Usage

The attribute can be used to link to a convention or rule that prescribes a method for converting one script into another script (transliteration). It also can be used to link to a national, international, or other rule that governs the construction of a name. This optional attribute is available in elements that can contain text.

Data Type

IDREFS

Examples

```
<agent conventionDeclarationReference="cd2" agentType="person">  
<label>Karin Bredenberg</label> </agent>
```

[Table of Contents](#)

@coordinateSystem

Coordinate System

Summary

A code for a system used to express geographic coordinates.

Description and Usage

A code for a system used to express geographic coordinates, for example WGS84, (World Geodetic System), OSGB36 (Ordnance Survey Great Britain), or ED50 (European Datum). Required in [<geographicCoordinates>](#) .

Data Type

token

Examples

```
<geographicCoordinates coordinateSystem="mgrs">  
33UUU9029819737 </geographicCoordinates> <geographicCoordinates  
coordinateSystem="WGS84"> -81.1, 32.2, -81.0, 32.3 </  
geographicCoordinates>
```

[Table of Contents](#)

@countryCode

Country Code

Summary

A unique code representing a country.

Description and Usage

Content of the optional attribute should be a code taken from the part of ISO 3166 Country Codes or another controlled list specified in the [@countryEncoding](#) attribute in `<control>`. Available in `<maintenanceAgency>` and `<placeName>`.

Data Type

token

Examples

```
<maintenanceAgency countryCode="IE"> <agencyCode> IE-NAI </agencyCode> <agencyName> National Archives of Ireland </agencyName> </maintenanceAgency> <relation relationType="resourceRelation"> <label> Charles Darwin, On the Origin of Species by Means of Natural Selection, or the Preservation of Favoured Races in the Struggle for Life (London, John Murray, 1859) </label> <role valueURI="https://www.ica.org/standards/RiC/RiC-O_1-1.html#hasOrHadSubject" vocabularySource="RiC-O" vocabularySourceURI="https://www.ica.org/standards/RiC/ontology"> hasOrHadSubject </role> <placeName countryCode="GB"> London </placeName> </relation> <unitId countryCode="US" repositoryCode="cu-i"> MS-R72 </unitId>
```

[Table of Contents](#)

@countryEncoding

Country Encoding

Summary

Specifies the authoritative source or rules for codes used to identify a country as part of the maintenance agency's location or of describing a geographic feature.

Description and Usage

[@countryEncoding](#) specifies the authoritative source or rules for values supplied in [@countryCode](#) within [<maintenanceAgency>](#) and [<placeName>](#) . This can either be a specific part of the ISO standard 3166 or an alternative code list. If the value "otherCountryEncoding" is selected, such an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

iso3166-1-alpha-2, iso3166-1-alpha-3, iso3166-1-numeric, iso3166-2, iso3166-3, otherCountryEncoding

Examples

```
<control countryEncoding="iso3166-1-alpha-2" dateEncoding="iso8601"
languageEncoding="otherLanguageEncoding" repositoryEncoding="iso15511"
scriptEncoding="iso15924"> [...] </control>
```

[Table of Contents](#)

@dateEncoding

Date Encoding

Summary

Specifies the authoritative source or rules used to normalize date information.

Description and Usage

[@dateEncoding](#) specifies the authoritative source or rules for normalized values supplied in [@standardDate](#) within [<date>](#) , [<fromDate>](#) and [<toDate>](#) as well as in [@standardDateTime](#) within [<eventDateTime>](#) . This can either be the ISO standard 8601 or an alternative code list. If the value "otherDateEncoding" is selected, such an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

iso8601, otherDateEncoding

Examples

```
<control countryEncoding="iso3166-1-alpha-2" dateEncoding="iso8601"
languageEncoding="otherLanguageEncoding" repositoryEncoding="iso15511"
scriptEncoding="iso15924"> [...] </control>
```

[Table of Contents](#)

@detailLevel

Level of Detail

Summary

Provides information about the level of detail of the description encoded within the EAS instance.

Description and Usage

An optional attribute within `<control>`, used to provide information about the level of detail in accordance with relevant description guidelines and/or rules. Use the attribute `@detailLevelEncoding` in `<control>` to identify the list of authoritative terms that can be used as values of `@detailLevel`.

Data Type

token

Examples

```
<control countryEncoding="iso3166-1-alpha-2" dateEncoding="iso8601"
detailLevel="basic" languageEncoding="iso639-2b"
repositoryEncoding="iso15511" scriptEncoding="iso15924"> [...] </
control>
```

[Table of Contents](#)

@detailLevelEncoding

Detail Level Encoding

Summary

Specifies the authoritative source or rules for values used to indicate whether the EAS instance encodes minimal, basic, or extended information.

Description and Usage

[@detailLevelEncoding](#) specifies the authoritative source or rules for values supplied in [@detailLevel](#) within `<control>`. If the value "EASList" is selected, [@detailLevel](#) will be expected with the values "basic", "extended" or "minimal". If the value "otherDetailLevelEncoding" is selected, an alternate code list should be specified in `<conventionDeclaration>`. This optional attribute is available only in `<control>`.

Values

EASList, otherDetailLevelEncoding

Examples

```
<control detailLevelEncoding="EASList"/>
```

[Table of Contents](#)

@era

Era

Summary

Period during which years are numbered and dates reckoned.

Description and Usage

Period during which years are numbered and dates reckoned, such as CE (Common Era) or BCE (Before Common Era). Suggested values include, but are not limited to, "ce" and "bce". This optional attribute is available in [<date>](#) , [<fromDate>](#) , and [<toDate>](#) .

Data Type

token

Examples

```
<dateRange> <fromDate calendar="gregorian" certainty="approximate"
era="ce" standardDate="1950~"> 1950 </fromDate> <toDate
calendar="gregorian" certainty="approximate" era="ce"
standardDate="2000~"> 2000 </toDate> </dateRange>
```

[Table of Contents](#)

@href

Hypertext Reference

Summary

The address for a remote resource.

Description and Usage

The optional [@href](#) attribute takes the form of a Uniform Resource Identifier (URI). Available in [<contactLine>](#) , [<reference>](#) , [<setComponent>](#) and [<source>](#) . Being of type "anyURI", [@href](#) is meant to point to any dereferencable resource. The term resource is used in a general sense and includes, but is not limited to, electronic documents, images, services (e.g. an HTTP-to-SMS gateway), collections of other resources, etc. A resource is not necessarily accessible via the Internet, i.e. not every URI is a URL, and abstract concepts can be resources too, such as the operators and operands of a mathematical equation or numeric values (e.g., zero, one, and infinity). While the use of complete URIs is recommended, it is also possible to use relative references in [@href](#), e.g. only consisting of a string of numbers.

Data Type

anyURI

Examples

```
< conventionDeclaration id = "cd1" > <reference href = "https://
www.legifrance.gouv.fr/loda/id/JORFTEXT000033553530/" > Décret n°
2016-1689 du 8 décembre 2016 fixant le nom, la composition et le chef-lieu
des circonscriptions administratives régionales - Légifrance </reference> </
conventionDeclaration >
Table of Contents
```

@id

ID

Summary

A unique identifier to name a specific element within an EAS instance.

Description and Usage

An identifier that must be unique within the current EAS instance and is used to name the element so that it can be referred to from somewhere else in the EAS instance. This facilitates building links between the element and other elements within the same XML file, though it can also be used to point to a specific element from outside of the EAS instance. Use [@target](#), [@conventionDeclarationReference](#), [@localTypeDeclarationReference](#), [@maintenanceEventReference](#), or [@sourceReference](#) to link to an [@id](#) attribute within the EAS instance.

Data Type

ID

Examples

```
<occupations> <occupation> <term> Assistant examiner - level
III</term> <placeName target="#place1"> Bern</placeName>
</occupation> </occupations> <places> <place id="place1">
<label> Bern</label> <role> Place of work</role> <address>
<addressLine addressLineType="street"> Stauffacherstrasse 65/59g</
addressLine> <addressLine addressLineType="postalCode"> 3003</
addressLine> <addressLine addressLineType="municipality"> Bern</
addressLine> </address> </place> </places> <agents>
<agent> <label> Schweizerisches Bundesarchiv</label>
<role> holdingInstitution</role> <placeName target="#place1"> Bern</
placeName> </agent> </agents> <places> <place id="place1">
<label> Bern</label> <role> Place of storage</role> <address>
<addressLine addressLineType="street"> Archivstrasse 24</addressLine>
<addressLine addressLineType="postalCode"> 3005</addressLine>
<addressLine addressLineType="municipality"> Bern</addressLine>
</address> </place> </places> <description> <functionHistory>
<p target="#lex1"> Since 1862, liquidation also meant bringing criminal
proceedings against directors and others who were alleged to have
committed offences in relation to the company.</p> </functionHistory>
```

<legislations> <legislation id="lex1">Joint Stock Companies Act, 1856;
Companies Act, 1862; Companies Act, 1900; Companies Act, 1907; Companies
(Consolidation) Act, 1908; Companies Act, 1928; Companies Act, 1929;
Companies Act, 1947</legislation> </legislations> </description> </
functionsDescription>

[Table of Contents](#)

@identityType

Identity Type

Summary

Indicates whether the identity is given or acquired. May be useful for processing when multiple identities are described in the same instance.

Description and Usage

The [@identityType](#) may occur on [<identity>](#) . Though optional, it is recommended that it be used when multiple identities are described in the same EAS instance using [<multipleIdentities>](#) , for example when describing pseudonyms. It will enable processors to distinguish between the description of a person and one or more personae. Use the attribute [@identityTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@identityType](#).

Examples

```
<identity identityType="acquired"> [...] </identity>
```

[Table of Contents](#)

@identityTypeEncoding

Identity Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of identity being used.

Description and Usage

[@identityTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@identityType](#) within [<identity>](#) . If the value "EASList" is selected, [@identityType](#) will be expected with the values "acquired" or "given". If the value "otherIdentityTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is on available in [<control>](#) .

Values

EASList, otherIdentityTypeEncoding

Examples

```
<control identityTypeEncoding = "EASList"/>
```

[Table of Contents](#)

@languageCode

Language Code

Summary

The code for the language used in the EAS instance or by the records or entity being described.

Description and Usage

Content of the attribute should be a code taken from ISO 639-1, ISO 639-2, ISO 639-2b, ISO 639-2t, ISO 639-3, ISO 639-5, IETF BCP 47 or another controlled list, as specified in the [@languageEncoding](#) attribute in [<control>](#) . Required in [<languageDeclaration>](#) and optionally available in [<language>](#) .

Data Type

token

Examples

```
<languageDeclaration languageCode="gre" scriptCode="Grek"/>]]</egXML> <egXML xml:lang="eng" type="eac"><![CDATA[<languagesUsed> <languageUsed> <language languageCode="eng">English</language> <writingSystem scriptCode="Latn">Latin</writingSystem> </languageUsed> <languageUsed> <language languageCode="spa">Spanish</language> <writingSystem scriptCode="Latn">Latin</writingSystem> </languageUsed> <descriptiveNote> <p>Published works in English and Spanish.</p> </descriptiveNote> </languagesUsed> <languageOfMaterial> <languageSet> <writingSystem scriptCode="Latn">Latin</writingSystem> <language languageCode="dut">Dutch</language> <language languageCode="fre">French</language> </languageSet> <descriptiveNote> <p>The materials are in Dutch and French.</p> </descriptiveNote> </languageOfMaterial>
```

[Table of Contents](#)

@languageEncoding

Language Encoding

Summary

Specifies the authoritative source or rules for codes used to identify the language of the EAS instance as a whole, of a specific element, or represented in the creative work of the CPF entity being described.

Description and Usage

[@languageEncoding](#) specifies the authoritative source or rules for values supplied in [@languageCode](#) within [<languageDeclaration>](#) and [<language>](#) and in [@languageOfElement](#) available in all non-empty elements. This can either be one of the ISO standards 639-1, 639-2, 639-2b, 639-2t, 639-3, and 639-5, the IETF BCP 47 language tag or an alternative code list. If the value "otherLanguageEncoding" is selected, such an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

iso639-1, iso639-2, iso639-2b, iso639-2t, iso639-3, iso639-5, ietf-bcp-47, otherLanguageEncoding

Examples

```
<control countryEncoding="iso3166-1-alpha-2" dateEncoding="iso8601"
languageEncoding="otherLanguageEncoding" repositoryEncoding="iso15511"
scriptEncoding="iso15924"> [...] </control>
```

[Table of Contents](#)

@languageOfElement

Language of Element

Summary

Indicates the language of the content of an element.

Description and Usage

Content of the attribute should be a code taken from ISO 639-1, ISO 639-2, ISO 639-2b, ISO 639-2t, ISO 639-3, ISO 639-5, IETF BCP 47 or another controlled list, as specified in the [@languageEncoding](#) attribute in `<control>`. May be used consistently in a multi-lingual EAS instance to specify which elements are written in which language. Optionally available on all non-empty elements.

Data Type

token

Examples

```
<agencyName languageOfElement="eng">Berlin State Library - Prussian  
Cultural Heritage, Kalliope Union Catalog</agencyName> <agencyName  
languageOfElement="ger">Staatsbibliothek zu Berlin - Preußischer  
Kulturbesitz, Kalliope Verbundkatalog</agencyName>
```

[Table of Contents](#)

@linkRole

Link Role

Summary

A URI that characterizes the nature of the remote resource to which a linking element refers.

Description and Usage

A URI that characterizes the nature of the remote resource to which a linking element refers. Optionally available in `<contactLine>` , `<reference>` , `<setComponent>` , and `<source>` . Being of type "anyURI", `@linkRole` is meant to point to any dereferencable resource. The term resource is used in a general sense and includes, but is not limited to, electronic documents, images, services (e.g. an HTTP-to-SMS gateway), collections of other resources, etc. A resource is not necessarily accessible via the Internet, i.e. not every URI is a URL, and abstract concepts can be resources too, such as the operators and operands of a mathematical equation or numeric values (e.g., zero, one, and infinity). While the use of complete URIs is recommended, it is also possible to use relative references in `@linkRole`, e.g. only consisting of a string of numbers.

Data Type

anyURI

Examples

```
<reference href="https://deliberation.maregionsud.fr/docs/
ASSEMBLEEPLENIERE/2017/12/15/DELIBERATION/D0V0Q.pdf"
linkRole="document/pdf"> DELIBERATION N° 17-1166, 15 DECEMBRE 2017
</reference>
```

[Table of Contents](#)

@linkTitle

Link Title

Summary

Viewable caption of a link text.

Description and Usage

Information that serves as a viewable caption which explains to users the part that a remote resource plays in a link. May be used alongside any [@href](#) attribute in order to support accessibility guidelines, such as those defined within the W3C's Web Content Accessibility Guidelines (WCAG). Optionally available in [<contactLine>](#) , [<reference>](#) , [<setComponent>](#) , and [<source>](#) .

Data Type

token

Examples

```
<setComponent href="http://nla.gov.au/anbd.aut-an35995526"
linkTitle="Hill, Dorothy, 1907-1997 - Full record view - Libraries
Australia Search"> <componentEntry> Libraries Australia record. </
componentEntry> </setComponent> <p> More information is available
on our <reference linkTitle="Archives at Yale, Help Page" href="https://
archives.yale.edu/help"> Help page</reference> . </p>
Table of Contents
```

@localType

Local Type

Summary

This optional attribute provides a means to narrow the semantics of an element, or provide semantics for elements that are primarily structural or semantically weak.

Description and Usage

The value of [@localType](#) may be from a local or generally used external vocabulary. While the value of [@localType](#) may be any string, to facilitate exchange of data, it is recommended that the value be either the URI or the preferred label for a term defined in a formal vocabulary (e.g., SKOS), which is identified by an absolute URI, and is resolvable to a web resource that describes the semantic scope and use of the value. Local conventions or controlled vocabularies used in [@localType](#) may be declared in [<localTypeDeclaration>](#) within [<control>](#) . [@localTypeDeclarationReference](#) should always be used alongside [@localType](#) to provide a direct link to the [<localTypeDeclaration>](#) .

Data Type

token

Examples

```
<nameEntry status="authorized"> <part localType="https://
d-nb.info/standards/elementset/gnd#personalName"
localTypeDeclarationReference="GNDO">Arendt,
Hannah</part> <part localType="https://d-nb.info/
standards/elementset/gnd#dateOfBirthAndDeath"
localTypeDeclarationReference="GNDO">1906-1975</part>
</nameEntry> <relation relationType="agentRelation"
targetType="person"> <label valueURI="https://d-nb.info/gnd/117145971"
vocabularySource="GND" vocabularySourceURI="https://d-nb.info/gnd/"
localType="https://d-nb.info/standards/elementset/gnd#NameOfThePerson"
localTypeDeclarationReference="GNDO">Wasa, Gustav</label> [...] </
relation>
```

[Table of Contents](#)

@localTypeDeclarationReference

Local Type Declaration Reference

Summary

Use [@localTypeDeclarationReference](#) to provide a direct link to a [<localTypeDeclaration>](#) element within [<control>](#) from another element within the EAS instance using [@localType](#).

Description and Usage

[@localTypeDeclarationReference](#) should always be used when [@localType](#) is used, in order to link to the local type declaration.

Data Type

IDREFS

Examples

```
< nameEntry status="authorized"> < part localType="https://  
d-nb.info/standards/elementset/gnd#personalName"  
localTypeDeclarationReference="GNDO"> Arendt, Hannah </  
part> < part localType="https://d-nb.info/standards/elementset/  
gnd#dateOfBirthAndDeath" localTypeDeclarationReference="GNDO">  
1906-1975 </part> </nameEntry> < relation relationType="agentRelation"  
targetType="person"> < label valueURI="https://d-nb.info/gnd/117145971"  
vocabularySource="GND" vocabularySourceURI="https://d-nb.info/gnd/"  
localType="https://d-nb.info/standards/elementset/gnd#NameOfThePerson"  
localTypeDeclarationReference="GNDO"> Wasa, Gustav </label> [...] </  
relation>
```

[Table of Contents](#)

@maintenanceEventReference

Maintenance Event Reference

Summary

Use [@maintenanceEventReference](#) to provide a direct link to a [<maintenanceEvent>](#) element within [<maintenanceHistory>](#) .

Description and Usage

The attribute can be used to link to a maintenance event in order to verify any assertion added to the entity's description. The attribute is optionally available in all elements that can contain text and are available outside of [<control>](#) .

Data Type

IDREFS

Examples

```
<maintenanceHistory> <maintenanceEvent
maintenanceEventType="updated" id="me2"> <agent
agentType="person"> <label>K. Bredenberg</label> </
agent> <eventDateTime>May 2024</eventDateTime>
<eventDescription>Relation added</eventDescription> </
maintenanceEvent> </maintenanceHistory> [...] <relation
sourceReference="source1" maintenanceEventReference="me2"
targetType="corporateBody" relationType="https://www.wikidata.org/wiki/
Q166118"> <label valueURI="https://snaccooperative.org/ark:/99166/
w63z1x39" vocabularySourceURI="https://snaccooperative.org">Princeton
University</label> </relation>
```

[Table of Contents](#)

@maintenanceEventType

Maintenance Event Type

Summary

An optional attribute of [< maintenanceEvent >](#) that identifies the type of maintenance activity.

Description and Usage

Identifies the type of maintenance event with values such as "created", "derived" or "updated". Use the attribute [@maintenanceEventTypeEncoding](#) in [< control >](#) to identify the list of authoritative terms that can be used as values of [@maintenanceEventType](#).

Data Type

token

Examples

```
< maintenanceHistory > < maintenanceEvent
maintenanceEventType = "derived" > < agent agentType = "machine" >
< label > export.xml/Saxon B9 </label > </agent > < eventDateTime
standardDateTime = "2024-08-30T09:37:17.029-04:00"/
> < eventDescription > Derived from local collection
management system </eventDescription </maintenanceEvent >
< maintenanceEvent maintenanceEventType = "revised" > < agent
agentType = "unknown" > < label / > </agent > < eventDateTime
standardDateTime = "2024-11-27"/ > </maintenanceEvent >
< maintenanceEvent maintenanceEventType = "updated" > < agent
agentType = "person" > < label > K. Bredenberg </label > </
agent > < eventDateTime > December 2024 </eventDateTime > </
maintenanceEvent > </maintenanceHistory >
```

[Table of Contents](#)

@maintenanceEventTypeEncoding

Maintenance Event Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of maintenance activity.

Description and Usage

[@maintenanceEventTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@maintenanceEventType](#) within `<maintenanceEvent>`. If the value "EASList" is selected, [@maintenanceEventType](#) will be expected with the values "cancelled", "created", "deleted", "derived", "revised", "unknown", or "updated". If the value "otherMaintenanceEventTypeEncoding" is selected, an alternate code list should be specified in `<conventionDeclaration>`. This optional attribute is available only in `<control>`.

Values

EASList, otherMaintenanceEventTypeEncoding

Examples

```
<control maintenanceEventTypeEncoding="EASList"/>
```

[Table of Contents](#)

@maintenanceStatus

Maintenance Status

Summary

The current drafting status of the EAS instance.

Description and Usage

The maintenance status may occur on [<control>](#) . As an EAS instance is modified or other events happen to it (as recorded in the [<maintenanceHistory>](#) element), the maintenance status should also be updated to reflect the current drafting status. On first creation the status would e.g. be "new", which on revision could be changed to "revised". Use the attribute [@maintenanceStatusEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@maintenanceStatus](#).

Data Type

token

[Table of Contents](#)

@maintenanceStatusEncoding

Maintenance Status Encoding

Summary

Specifies the authoritative source or rules for values used to indicate the current version status of the EAS instance.

Description and Usage

[@maintenanceStatusEncoding](#) specifies the authoritative source or rules for values supplied in [@maintenanceStatus](#) within `<control>`. If the value "EASList" is selected, [@maintenanceStatus](#) will be expected with the values "cancelled", "deleted", "deletedMerged", "deletedReplaced", "deletedSplit", "derived", "new", or "revised". If the value "otherMaintenanceStatusEncoding" is selected, an alternate code list should be specified in `<conventionDeclaration>`. This optional attribute is available only in `<control>`.

Values

EASList, otherMaintenanceStatusEncoding

Examples

```
<control maintenanceStatusEncoding="EASList"/>
```

[Table of Contents](#)

@normalizedForm

Normalized Form

Summary

A standardized form of the content of [<referringString>](#) that is in uncontrolled or natural language.

Description and Usage

Use [@normalizedForm](#) to provide a standardized form, usually from a controlled vocabulary list, of the content of [<referringString>](#) e.g. to facilitate retrieval.

Data Type

token

Examples

```
<p> See the following publication for background information:  
<referringString referredEntityType="person" normalizedForm="Bernier,  
Pierre-François (1779-1803)"> P.-F. BERNIER </referringString> ,  
<referringString referredEntityType="work"> Études particulières </  
referringString> </p>
```

[Table of Contents](#)

@notAfter

Not After

Summary

A standard numerical form of an approximate date for which a latest possible date is known.

Description and Usage

Optionally available in `<date>` , `<fromDate>` , and `<toDate>` . It is recommended that `@notAfter` values follow ISO 8601 or another standard date format as specified in `@dateEncoding`.

Data Type

token

Examples

```
<dateRange> <fromDate notBefore="1971" notAfter="1975"> around  
1973</fromDate> <toDate standardDate="1992"> 1992</toDate> </  
dateRange>
```

[Table of Contents](#)

@notBefore

Not Before

Summary

A standard numerical form of an approximate date for which an earliest possible date is known.

Description and Usage

Optionally available in [<date>](#) , [<fromDate>](#) , and [<toDate>](#) . It is recommended that [@notBefore](#) values follow ISO 8601 or another standard date format as specified in [@dateEncoding](#).

Data Type

token

Examples

```
<dateRange> <fromDate notBefore="1971" notAfter="1975"> around  
1973</fromDate> <toDate standardDate="1992"> 1992</toDate> </  
dateRange>
```

[Table of Contents](#)

@placeType

Place Type

Summary

An optional attribute of [<place>](#) that specifies the type of the geographic feature or location being described.

Description and Usage

Use [@placeType](#) with [<place>](#) to specify the type of geographic feature or location being described. Use the attribute [@placeTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@placeType](#).

Data Type

token

Examples

```
<places> <place placeType="firstOrderAdministrativeDivision"> <label
valueURI="https://www.geonames.org/2152274/state-of-queensland.html"
vocabularySource="GeoNames">Queensland</label> </place> <place
placeType="reef"> <label valueURI="https://www.geonames.org/2164628/
great-barrier-reef.html" vocabularySource="GeoNames">Great Barrier Reef</
label> </place> </places>
```

[Table of Contents](#)

@placeTypeEncoding

Place Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of geographic feature or location.

Description and Usage

[@placeTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@placeType](#) within [<place>](#) . If the value "EASList" is selected, [@placeType](#) will be expected with the values "...". If the value "otherPlaceTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherPlaceTypeEncoding

Examples

```
< control placeTypeEncoding = "EASList" />
```

[Table of Contents](#)

@preferredForm

Preferred Form

Summary

Attribute that specifies whether or not a name provides the preferred form of the entity's name for display purposes.

Description and Usage

Attribute that specifies whether or not a [<nameEntry>](#) provides the preferred form of the name of the EAS entity for display or other purposes in a given context. Use the value "true" if the name entry is preferred for any display or other purposes. This optional attribute is only available in [<nameEntry>](#) .

Values

false, true

Examples

```
<nameEntrySet languageOfElement="fre"> <nameEntry
conventionDeclarationReference="cd1" preferredForm="true">
<part> Provence-Alpes-Côte d'Azur</part> </nameEntry>
<nameEntry conventionDeclarationReference="cd2"> <part> Région
Sud Provence-Alpes-Côte d'Azur</part> </nameEntry> <nameEntry
conventionDeclarationReference="cd3"> <part> Provence-Alpes-Côte-
d'Azur</part> </nameEntry> </nameEntrySet>
```

[Table of Contents](#)

@publicationStatus

Publication Status

Summary

The current publication status of the EAS instance.

Description and Usage

The publication status may occur on [<control>](#) to indicate the current publication status of the EAS instance, for example "inProcess", "approved" or "published". As an EAS instance is modified or other events happen to it (as recorded in the [<maintenanceHistory>](#) element), the publication status should also be updated. Use the attribute [@publicationStatusEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@publicationStatus](#).

Data Type

token

Examples

```
<control countryEncoding="iso3166-1-alpha-2" dateEncoding="iso8601"
languageEncoding="iso639-3" maintenanceStatusEncoding="EASList"
maintenanceStatus="new" publicationStatusEncoding="EASList"
publicationStatus="published" repositoryEncoding="iso15511"
scriptEncoding="iso15924"> [...] </control>
```

[Table of Contents](#)

@publicationStatusEncoding

Publication Status Encoding

Summary

Specifies the authoritative source or rules for values used to indicate the current publishing status of the EAS instance.

Description and Usage

[@publicationStatusEncoding](#) specifies the authoritative source or rules for values supplied in [@publicationStatus](#) within `<control>`. If the value "EASList" is selected, [@publicationStatus](#) will be expected with the values "approved", "inProcess", or "published". If the value "otherPublicationStatusEncoding" is selected, an alternate code list should be specified in `<conventionDeclaration>`. This optional attribute is available only in `<control>`.

Values

EASList, otherPublicationStatusEncoding

Examples

```
<control publicationStatusEncoding="EASList"/>
```

[Table of Contents](#)

@referredEntityRelationship

Referred Entity Relationship

Summary

An optional attribute of [<referringString>](#) that specifies the relationship between the entity named in a narrative text and the entity being described in the EAS instance.

Description and Usage

Use [@referredEntityRelationship](#) with [<referringString>](#) to specify the relationship between the entity named in a narrative text and the entity being described in the EAS instance. While [@referredEntityRelationship](#) does not come with a set of predefined values, it is highly recommended to use terms from controlled vocabularies whenever possible.

Data Type

token

Examples

```
<p> See the following publication for background  
information: <referringString referredEntityType="person"  
normalizedForm="Bernier, Pierre-François (1779-1803)">P.-F.  
BERNIER</referringString>, <referringString referredEntityType="work"  
referredEntityRelationship="https://www.ica.org/standards/RiC/  
ontology#RecordResourceGeneticRelation"> Études particulières </  
referringString> </p>
```

[Table of Contents](#)

@referredEntityType

Referrered Entity Type

Summary

An optional attribute of [<referringString>](#) that specifies the type of entity named in a narrative text.

Description and Usage

Use [@referredEntityType](#) with [<referringString>](#) to specify the type of entity named in a narrative text. Use the attribute [@referredEntityTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@referredEntityType](#).

Data Type

token

Examples

```
<p> See the following publication for background information:
<referringString referredEntityType="person" normalizedForm="Bernier,
Pierre-François (1779-1803)">P.-F. BERNIER</referringString>,
<referringString referredEntityType="work">Études particulières</
referringString></p>
```

[Table of Contents](#)

@referredEntityTypeEncoding

Referred Entity Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of entity that is being referred to in a narrative text.

Description and Usage

[@referredEntityTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@referredEntityType](#) within `<referringString>` . If the value "EASList" is selected, [@referredEntityType](#) will be expected with the values "corpName", "famName", "function", "genreForm", "geogName", "name", "occupation", "persName", "subject" or "title". If the value "otherReferredEntityTypeEncoding" is selected, an alternate code list should be specified in `<conventionDeclaration>` . This optional attribute is available only in `<control>` .

Values

EASList, otherReferredEntityTypeEncoding

Examples

```
<control referredEntityTypeEncoding="EASList"/>
```

[Table of Contents](#)

@relationType

Relation Type

Summary

An optional attribute of [<relation>](#) that specifies the type of relation between the related entity and the entity being described in the EAS instance.

Description and Usage

Use [@relationType](#) with [<relation>](#) to specify the type of relation between the related entity and the entity being described in the EAS instance. Use the attribute [@relationTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@relationType](#).

Data Type

token

Examples

```
<relation relationType="https://www.ica.org/standards/RiC/ontology#AgentTemporalRelation" targetType="person">
<label valueURI="https://viaf.org/en/viaf/43170438"
vocabularySource="VIAF">Vigdís Finnbogadóttir</
label> <role>Successor</role> </relation> <relation
relationType="https://www.ica.org/standards/RiC/ontology#RecordResourceToRecordResourceRelation"
targetType="recordResource"> <label>Papers of Jean Batten</label>
</relation> <relation relationType="https://www.ica.org/standards/RiC/ontology#performsOrPerformed" targetType="group"> <label>Obama Cabinet</label> </relation>
```

[Table of Contents](#)

@relationTypeEncoding

Relation Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of relation between the related entity and the entity being described in the EAS instance.

Description and Usage

[@relationTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@relationType](#) within [<relation>](#) . If the value "EASList" is selected, [@relationType](#) will be expected with the values "...". If the value "otherRelationTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherRelationTypeEncoding

Examples

```
<control relationTypeEncoding = "EASList"/>
```

[Table of Contents](#)

@repositoryEncoding

Repository Encoding

Summary

Specifies the authoritative source or rules for codes used to identify the maintenance agency of an EAS instance.

Description and Usage

[@repositoryEncoding](#) specifies the authoritative source or rules for values used within [<agencyCode>](#) . This can either be the ISO standard 15511 or an alternative code list. If the value "otherRepositoryEncoding" is selected, such an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

iso15511, otherRepositoryEncoding

Examples

```
<control countryEncoding="iso3166-1-alpha-2" dateEncoding="iso8601"  
languageEncoding="iso639-2b" repositoryEncoding="iso15511"  
scriptEncoding="iso15924"> [...] </control>
```

[Table of Contents](#)

@scriptCode

Script Code

Summary

The code for the writing system, or script, used in the EAS instance or by the described entity or records.

Description and Usage

Content of the attribute should be a code taken from ISO 15924, or another controlled list, as specified in the [@scriptEncoding](#) attribute in [<control>](#) . Optionally available in [<languageDeclaration>](#) and [<writingSystem>](#) .

Data Type

token

Examples

```
<languageDeclaration languageCode="gre" scriptCode="Grek"/>]]</egXML> <egXML xml:lang="eng" type="eac"><![CDATA[<languagesUsed> <languageUsed> <language languageCode="eng">English</language> <writingSystem scriptCode="Latn">Latin</writingSystem> </languageUsed> <languageUsed> <language languageCode="spa">Spanish</language> <writingSystem scriptCode="Latn">Latin</writingSystem> </languageUsed> <descriptiveNote> <p>Published works in English and Spanish.</p> </descriptiveNote> </languagesUsed> <languageOfMaterial> <languageSet> <writingSystem scriptCode="Latn">Latin</writingSystem> <language languageCode="dut">Dutch</language> <language languageCode="fre">French</language> </languageSet> <descriptiveNote> <p>The materials are in Dutch and French.</p> </descriptiveNote> </languageOfMaterial>
```

[Table of Contents](#)

@scriptEncoding

Script Encoding

Summary

Specifies the authoritative source or rules for codes used to identify the writing system of the EAS instance as a whole or, of a specific element, or represented in the creative work of the CPF entity being described.

Description and Usage

[@scriptEncoding](#) specifies the authoritative source or rules for values supplied in [@scriptCode](#) within [<languageDeclaration>](#) and [<writingSystem>](#) and in [@scriptOfElement](#) available in all non-empty elements. This can either be the ISO standard 15924 or an alternative code list. If the value "otherScriptEncoding" is selected, such an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

iso15924, otherScriptEncoding

Examples

```
<control countryEncoding="iso3166-1-alpha-2" dateEncoding="iso8601"
languageEncoding="iso639-2b" repositoryEncoding="iso15511"
scriptEncoding="iso15924"> [...] </control>
```

[Table of Contents](#)

@scriptOfElement

Script of Element

Summary

Indicates the writing script of the content of an element (e.g., Cyrillic, Katakana).

Description and Usage

Content should be taken from ISO 15924, or another controlled list, as specified in the [@scriptEncoding](#) attribute in `<control>`. May be used consistently in a multi-lingual EAS instance to specify which elements are written in which script. Optionally available on all non-empty elements.

Data Type

token

Examples

```
<nameEntry status="alternative"> <part localType="https://  
d-nb.info/standards/elementset/gnd#personalName"  
localTypeDeclarationReference="GNDO" scriptOfElement="Hans"> 阿伦  
特, 汉娜 </part> </nameEntry> <unitTitle languageOfElement="ukr"  
scriptOfElement="Cyr" > Лист Миколи Хвильового до Михайла  
(Ялового) </unitTitle> <unitTitle languageOfElement="eng"  
scriptOfElement="Latn"> Letter from Mykoly Khvylovoho  
to Mykhayla (Yalovoho) </unitTitle> <nameEntrySet>  
<nameEntry> <part valueURI="http://vocab.getty.edu/page/  
aat/300191862" vocabularySource="AAT" languageOfElement="eng"  
scriptOfElement="Latn"> educating </part> </nameEntry>  
<nameEntry> <part valueURI="http://vocab.getty.edu/page/  
aat/300191862" vocabularySource="AAT" languageOfElement="spa"  
scriptOfElement="Latn"> educar </part> </nameEntry>  
<nameEntry> <part valueURI="http://vocab.getty.edu/page/  
aat/300191862" vocabularySource="AAT" languageOfElement="zho"  
scriptOfElement="Hant"> 教導 </part> </nameEntry> </nameEntrySet>
```

[Table of Contents](#)

@sourceReference

Source Reference

Summary

Use [@sourceReference](#) to provide a direct link to a [<source>](#) element within [<sources>](#) in [<control>](#) from an element within the EAS instance that uses the source.

Description and Usage

The attribute can be used to link any detailed information about the described entity to a source. The attribute is optionally available in elements which can contain text.

Data Type

IDREFS

Examples

```
< sources> < source id="source1"> < reference> R. Greene, S.Cushman
(ed.): The Princeton Handbook of World Poetries</reference> </
source> </sources> [...] <relation sourceReference="source1"
maintenanceEventReference="me2" targetType="corporateBody"
relationType="https://www.wikidata.org/wiki/Q166118"> <label
valueURI="https://snaccooperative.org/ark:/99166/w63z1x39"
vocabularySourceURI="https://snaccooperative.org"> Princeton University</
label> </relation>
```

[Table of Contents](#)

@standardDate

Standard Date

Summary

The standardized form of date.

Description and Usage

The standardized form of date expressed in [<date>](#) , [<fromDate>](#) , and [<toDate>](#) . It is recommended that [@standardDate](#) values follow ISO 8601, for example, 2011-07-22, 1963, or 1912-11, or another standard date format as specified in [@dateEncoding](#).

Data Type

token

Examples

```
<dateRange> <fromDate standardDate="1609-07-04"> 4 juillet 1609 </fromDate> <toDate standardDate="1640-07-07"> 7 juillet 1640 </toDate> </dateRange>
```

[Table of Contents](#)

@standardDateTime

Standard Date and Time

Summary

Standardized form of a date, or date and time in [<eventDateTime>](#) .

Description and Usage

An ISO 8601 compliant form of the date, or date and time, of a specific maintenance event expressed in [<eventDateTime>](#) . For example, 2021-12-31, 2021, 2021-12, 2021-12-31T23:59:59. Optionally available only in [<eventDateTime>](#) . It is recommended to either have the date and time stated as a literal in [<eventDateTime>](#) or to provide a standardised date with [@standardDateTime](#), if not using both options in parallel. Note that the requirement of ISO 8601 compliance for [@standardDateTime](#) is different from the usage of the attribute [@standardDate](#), which can also follow other date encoding rules as specified in [@dateEncoding](#) within [<control>](#) .

Data Type

Constrained to the following patterns: YYYY-MM-DD, YYYY-MM, YYYY, or YYYY-MM-DDThh:mm:ss [with optional timezone offset from UTC in the form of [+|-][hh:mm], or "Z" to indicate the dateTime is UTC. No timezone implies the dateTime is UTC.]

Examples

```
<maintenanceEvent maintenanceEventType="revised"> <agent
agentType="machine"> <label>export.xml</label> </agent>
<eventDateTime standardDateTime="2024-11-27"/> </maintenanceEvent>
```

[Table of Contents](#)

@status

Status

Summary

Attribute that follows controlled terminology detailing the status of elements.

Description and Usage

[@status](#) provides controlled terminology detailing the status of specific elements. The terms available for [@status](#) are defined in closed lists that can vary by element. Use [@statusEncoding](#) in `<control>` to identify lists of terms from EAS lists that can be used as values of [@status](#). It is also possible to define one's own list by using the value "otherStatusEncoding". Optionally available in `<agencyCode>` , `<otherAgencyCode>` , `<nameEntry>` , `<date>` , `<fromDate>` , and `<toDate>` .

Data Type

token

Examples

```
<nameEntry languageOfElement="de" preferredForm="true"
status="authorized" localType="native"> <part
localType="surname">Arendt</part> <part
localType="firstname">Hannah</part> </nameEntry> <dateRange>
<fromDate standardDate="2016-09">September 2016</fromDate>
<toDate status="ongoing"/> </dateRange> <date status="unknown"/>
```

[Table of Contents](#)

@statusEncoding

Status Encoding

Summary

The authoritative source or rules for values supplied in [@status](#).

Summary

Specifies the authoritative source or rules for values used to indicate the status and certainty of the information provided in various elements.

Description and Usage

[@statusEncoding](#) specifies the authoritative source or rules for values supplied in [@status](#) within [<agencyCode>](#) , [<otherAgencyCode>](#) , [<date>](#) , [<fromDate>](#) , [<toDate>](#) , and [<nameEntry>](#) . If the value "EASList" is selected, [@status](#) will be expected with the values "authorized" and "alternative" (for agency codes and [<nameEntry>](#)), "unknown" or "ongoing" (for dates). If the value "otherStatusEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherStatusEncoding

Examples

```
<control statusEncoding = "EASList"/>
```

[Table of Contents](#)

@style

Style

Summary

Used to specify a rendering style for a string. It is recommended that the value conforms to W3C CSS.

Description and Usage

The [@style](#) attribute may occur on `<span>` to indicate rendering instructions. It is highly recommended that the value of [@style](#) be expressed as a W3C CSS style to facilitate interoperability.

Data Type

normalizedString

Examples

`<p>` During 1918, Robert Carlton Brown (1886-1959) traveled extensively in Mexico and Central America, writing for the U.S. Committee of Public Information in Santiago de Chile. In 1919, he moved with his wife, Rose Brown, to Rio de Janeiro, where they founded `<span style="font-style:italic">` Brazilian American`</span>`, a weekly magazine that ran until 1929. With Brown's mother, Cora, the Browns also established magazines in Mexico City and London: `<span style="font-style:italic">` Mexican American`</span>` (1924-1929) and `<span style="font-style:italic">` British American`</span>` (1926-1929).`</p>`

[Table of Contents](#)

@target

Target

Summary

A pointer to the ID of another element.

Description and Usage

Used to create internal links within an XML instance. Optionally available in all elements except the root element.

Data Type

IDREFS

Examples

```
<occupations> <occupation> <term> Assistant examiner - level
III</term> <placeName target="place1"> Bern</placeName>
</occupation> </occupations> <places> <place id="place1">
<label> Bern</label> <role> Place of work</role> <address>
<addressLine addressLineType="street"> Stauffacherstrasse 65/59g</
addressLine> <addressLine addressLineType="postalCode"> 3003</
addressLine> <addressLine addressLineType="municipality"> Bern</
addressLine> </address> </place> </places> <agents>
<agent> <label> Schweizerisches Bundesarchiv</label>
<role> holdingInstitution</role> <placeName target="place1"> Bern</
placeName> </agent> </agents> <places> <place id="place1">
<label> Bern</label> <role> Place of storage</role> <address>
<addressLine addressLineType="street"> Archivstrasse 24</addressLine>
<addressLine addressLineType="postalCode"> 3005</addressLine>
<addressLine addressLineType="municipality"> Bern</addressLine>
</address> </place> </places> <description> <functionHistory>
<p target="lex1"> Since 1862, liquidation also meant bringing criminal
proceedings against directors and others who were alleged to have
committed offences in relation to the company.</p> </functionHistory>
<legislations> <legislation id="lex1"> Joint Stock Companies Act, 1856;
Companies Act, 1862; Companies Act, 1900; Companies Act, 1907; Companies
(Consolidation) Act, 1908; Companies Act, 1928; Companies Act, 1929;
Companies Act, 1947</legislation> </legislations> </description> </
functionsDescription>
```

[Table of Contents](#)

@targetType

Target Type

Summary

Identifies the type of entity related to the entity or records being described.

Description and Usage

An optional attribute of [<relation>](#) that specifies the type of entity that is related to the entity or records being described. Use the attribute [@targetTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@targetType](#).

Data Type

token

Examples

```
<relation targetType="resource"> <label>Mémorial du colonel  
Gustafsson. - 1829</label> </relation> <relation targetType="person"  
valueURI="https://d-nb.info/gnd/120636123" vocabularySource="GND"  
vocabularySourceURI="https://d-nb.info/gnd/"> <label>Sophie, Baden,  
Großherzogin, 1801-1865</label> </relation>
```

[Table of Contents](#)

@targetTypeEncoding

Target Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of related entity.

Description and Usage

[@targetTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@targetType](#) within [<relation>](#) . If the value "EASList" is selected, [@targetType](#) will be expected with the values "corporateBody", "family", "function", "group", "instantiation", "mechanism", "person", "place", "position", "record", "recordSet", "recordPart", or "resource". If the value "otherTargetTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherTargetTypeEncoding

Examples

```
<control targetTypeEncoding="EASList"/>
```

[Table of Contents](#)

@unit

Unit

Summary

Defines the format or unit specified in [< citedRange >](#) .

Description and Usage

Use [@unit](#) to document the format or unit that is specified in [< citedRange >](#) , for example page number ("pageNumber") or volume number ("volumeNumber").

Data Type

token

Examples

```
< citedRange unit = "page" > 1 < /citedRange >
```

[Table of Contents](#)

@value

Value

Summary

Defines the type of entity described in the EAC-CPF instance.

Description and Usage

Required attribute within the [<entityType>](#) element that defines the type of entity described in the EAC-CPF instance.

Values

corporateBody, family, person

Examples

See [<identity>](#) encoding
[Table of Contents](#)

@valueURI

Value URI

Summary

An attribute for including a URI identifying the resource to be used as the element's value.

Description and Usage

Use the optional [@valueURI](#) attribute to provide the URI identifying the authority resource to be used as the element's content. Available in all elements that can contain any type of entity. Being of type "anyURI", [@valueURI](#) is meant to point to any dereferencable resource. The term resource is used in a general sense and includes, but is not limited to, electronic documents, images, services (e.g. an HTTP-to-SMS gateway), collections of other resources, etc. A resource is not necessarily accessible via the Internet, i.e. not every URI is a URL, and abstract concepts can be resources too, such as the operators and operands of a mathematical equation or numeric values (e.g., zero, one, and infinity). While the use of complete URIs is recommended, it is also possible to use relative references in [@valueURI](#), e.g. only consisting of a string of numbers.

Data Type

anyURI

Examples

```
<place valueURI="https://d-nb.info/gnd/4076982-3"
vocabularySource="GND" vocabularySourceURI="https://d-nb.info/
gnd/"> <label>Salzburg</label> <role valueURI="https://
d-nb.info/standards/elementset/gnd#characteristicPlace"
vocabularySource="GNDO" vocabularySourceURI="https://d-nb.info/
standards/elementset/gnd#"> Charakteristischer Ort </role> </
place> <place valueURI="https://d-nb.info/gnd/4076982-3"
vocabularySource="GND" vocabularySourceURI="https://d-nb.info/
gnd/"> <label>Salzburg</label> <role valueURI="https://d-nb.info/
standards/elementset/gnd#characteristicPlace" vocabularySource="GNDO"
vocabularySourceURI="https://d-nb.info/standards/elementset/
gnd#"> Charakteristischer Ort </role> </place> <nameEntry>
<part valueURI="http://vocab.getty.edu/page/aat/300191862"
vocabularySource="AAT"> educating </part> </nameEntry>
```

Table of Contents

@vocabularySource

Vocabulary Source

Summary

An attribute for identifying a vocabulary that is the source of the element's value.

Description and Usage

Use the optional [@vocabularySource](#) attribute to provide a name or title of the authority or vocabulary source of the element's content. Available in all elements that can contain any type of entity.

Data Type

token

Examples

```
< occupation valueURI = "https://d-nb.info/gnd/4053311-6"
vocabularySource = "GND" vocabularySourceURI = "https://d-nb.info/
gnd/" > < term > Schriftstellerin < /term > < /occupation > < place
valueURI = "https://d-nb.info/gnd/4076982-3" vocabularySource = "GND"
vocabularySourceURI = "https://d-nb.info/gnd/" > < label > Salzburg < /
label > < role valueURI = "https://d-nb.info/standards/
elementset/gnd#characteristicPlace" vocabularySource = "GNDO"
vocabularySourceURI = "https://d-nb.info/standards/elementset/
gnd#" > Charakteristischer Ort < /role > < /place > < nameEntry >
< part valueURI = "http://vocab.getty.edu/page/aat/300191862"
vocabularySource = "AAT" vocabularySourceURI = "https://www.getty.edu/
research/tools/vocabularies/aat/index.html" > educating < /part > < /
nameEntry >
```

[Table of Contents](#)

@vocabularySourceURI

Vocabulary Source URI

Summary

An optional attribute for including a URI identifying the vocabulary source for the element's value.

Description and Usage

Use the optional attribute to provide the URI of the authority or vocabulary source given in [@vocabularySource](#). Available in all elements that can contain any type of entity. Being of type "anyURI", [@vocabularySourceURI](#) is meant to point to any dereferencable resource. The term resource is used in a general sense and includes, but is not limited to, electronic documents, images, services (e.g. an HTTP-to-SMS gateway), collections of other resources, etc. A resource is not necessarily accessible via the Internet, i.e. not every URI is a URL, and abstract concepts can be resources too, such as the operators and operands of a mathematical equation or numeric values (e.g., zero, one, and infinity). While the use of complete URIs is recommended, it is also possible to use relative references in [@vocabularySourceURI](#), e.g. only consisting of a string of numbers.

Data Type

anyURI

Examples

```
<place valueURI="https://d-nb.info/gnd/4076982-3"
vocabularySource="GND" vocabularySourceURI="https://d-nb.info/
gnd/" > <label>Salzburg</label> <role valueURI="https://
d-nb.info/standards/elementset/gnd#characteristicPlace"
vocabularySource="GNDO" vocabularySourceURI="https://d-nb.info/
standards/elementset/gnd#" > Charakteristischer Ort </role> </
place> <place valueURI="https://d-nb.info/gnd/4076982-3"
vocabularySource="GND" vocabularySourceURI="https://d-nb.info/
gnd/" > <label>Salzburg</label> <role valueURI="https://d-nb.info/
standards/elementset/gnd#characteristicPlace" vocabularySource="GNDO"
vocabularySourceURI="https://d-nb.info/standards/elementset/
gnd#" > Charakteristischer Ort </role> </place> <nameEntry>
<part valueURI="http://vocab.getty.edu/page/aat/300191862"
vocabularySource="AAT" vocabularySourceURI="https://www.getty.edu/
```

research/tools/vocabularies/aat/index.html">educating</part> </
nameEntry>
[Table of Contents](#)

Appendix :

eac

<

control

```
<control addressLineTypeEncoding="EASList"
agentTypeEncoding="EASList" audienceEncoding="EASList"
contactLineTypeEncoding="EASList" countryEncoding="iso3166-1-
alpha-2" dateEncoding="iso8601" identityTypeEncoding="EASList"
languageEncoding="iso639-2b" maintenanceStatus="revised"
maintenanceEventTypeEncoding="EASList"
maintenanceStatusEncoding="EASList" placeTypeEncoding="EASList"
publicationStatus="published" publicationStatusEncoding="EASList"
referredEntityTypeEncoding="EASList" relationTypeEncoding="EASList"
repositoryEncoding="iso15511" scriptEncoding="iso15924"
scriptOfElement="Latn" targetTypeEncoding="EASList"
statusEncoding="EASList">
  <recordId>
    21159483
  </recordId>
  <maintenanceAgency>
    <agencyCode>
      NBuU-AR
    </agencyCode>
    <agencyName>
      University Archives
    </agencyName>
  </maintenanceAgency>
  <maintenanceHistory>
    <maintenanceEvent maintenanceEventType="revised">
      <agent agentType="machine">
        <label>
          CPF merge program
        </label>
      </agent>
      <eventDateTime standardDateTime="2015-09-18">
        2015-09-18
      </eventDateTime>
      <eventDescription>
        Merge v2.0
      </eventDescription>
    </maintenanceEvent>
    <maintenanceEvent maintenanceEventType="revised">
      <agent agentType="machine">
        <label>
          SNAC EAC-CPF Parser
        </label>
      </agent>
    </maintenanceEvent>
  </maintenanceHistory>
</control>
```

```

        </agent>
        <eventDateTime standardDateTime="2016-08-11T10:39:38">
            2016-08-11T10:39:38
        </eventDateTime>
        <eventDescription>
            Bulk ingest into SNAC Database
        </eventDescription>
    </maintenanceEvent>
    <maintenanceEvent maintenanceEventType="revised">
        <agent agentType="human">
            <label>
                R. Elia
            </label>
        </agent>
        <eventDateTime standardDateTime="2025-10-15"/>
    </maintenanceEvent>
</maintenanceHistory>
<sources>
    <source id="source1" href="http://search.worldcat.org/
title/1181498130">
        <reference>
            Handley-Taylor, Geoffrey, <span style="font-
style:italic">The International Who's Who in Poetry</span>, vol. 2,
            London, The Cranbrook Tower Press, 1958.
        </reference>
    </source>
    <source id="source2">
        <reference>
            "What Poetry Means to Me," manuscript in Sjanna
            Solum papers, dated 1952 May 16
        </reference>
    </source>
    <source id="source3" href="https://search.worldcat.org/
title/25575262">
        <reference>
            "Who's Who Poet, Sjanna Solum Living At Kelsey Hill,
            Deep River," <span style="font-style:italic">The New Era</span>,
            Deep River, CT, 1959 April 30.
        </reference>
        <citedRange unit="page">
            11
        </citedRange>
    </source>
</sources>
<conventionDeclaration id="cd1">
    <reference href="https://viaf.org/">
        Virtual International Authority File
    </reference>
    <shortCode>
        VIAF
    </shortCode>
</conventionDeclaration>
<conventionDeclaration id="cd2">
    <reference href="https://www.ica.org/standards/RiC/RiC-
0_1-1.html">
        Records in Contexts Ontology (ICA RiC-0) version 1.1
    </reference>

```

```

    <shortCode>
      RICO
    </shortCode>
  </conventionDeclaration>
  <conventionDeclaration id="cd3">
    <reference href="http://vocab.getty.edu/page/aat">
      Getty Art and Architecture Thesaurus
    </reference>
    <shortCode>
      AAT
    </shortCode>
  </conventionDeclaration>
  <conventionDeclaration id="cd4">
    <reference href="https://id.loc.gov/authorities/names.html">
      Library of Congress Name Authority Files
    </reference>
    <shortCode>
      lcnaf
    </shortCode>
  </conventionDeclaration>
  <otherRecordId localType="ARK">
    http://n2t.net/ark:/99166/w6dz099z
  </otherRecordId>
  <otherRecordId vocabularySource="VIAF"
    vocabularySourceURI="#cd1" valueURI="http://viaf.org/
    viaf/3162902797577782447">
    3162902797577782447
  </otherRecordId>
</control>

```

identity

```

<identity>
  <entityType value="person"/>
  <nameEntry audience="external" languageOfElement="eng"
    scriptOfElement="latn"
    status="alternative">
    <part localType="surname">Solum</part>
    <part localType="forename">Sjanna</part>
  </nameEntry>
</identity>

```

```

<identity>
  <entityType value="corporateBody"/>
  <nameEntry scriptOfElement="Latn"
    languageOfElement="eng" status="authorized">
    <part localType="primary_name">State University of
    New York at Buffalo</part>
    <part localType="subordinate_name_1">University
    Council</part>
  </nameEntry>
</identity>

```

description

```

<description>
  <occupations>
    <occupation valueURI="http://vocab.getty.edu/page/
aat/300025513"
      vocabularySourceURI="#cd3">
      <term>poets</term>
    </occupation>
  </occupations>
  <places>
    <place placeType="populatedPlace">
      <label valueURI="http://id.loc.gov/authorities/
names/n82024107" conventionDeclarationReference="cd4">Rye (N.Y.)</
label>
      <role>Residence</role>
      <geographicCoordinates
coordinateSystem="WGS84">N 40°58'814" W 73°41'004"</
geographicCoordinates>
    </place>
  </places>
  <existDates>
    <dateRange localType="existence">
      <fromDate standardDate="1906-08-19"/>
      <toDate certainty="uncertain" notBefore="1963"/>
    </dateRange>
  </existDates>
  <biogHist>
    <p>Sjanna Solum (1906-1963?) was an American poet
and author of short stories. Solum
      was born August 19, 1906, and in 1930 married
Harold Irving Beadle, who died
      when their three children were still young.
Solum lived in Rye, New York and
      Greenwich, Connecticut and published as Sjanna
Solum throughout her life.</p>
    <p>Solum's only known book is <span style="font-
style:italic">Lodestone</span>
      (Dierkes Press, 1950), published as a result of
winning the 1949 Dierkes Press
      Book Publication Contest; however, during her
lifetime she published hundreds of
      poems in newspapers and periodicals, including
<span style="font-style:italic"
      >American Mercury</span> (first appearance),
<span style="font-style:italic"
      >The American-Scandinavian Review</span>,
<span style="font-style:italic"
      >The Christian Science Monitor</span>, <span
style="font-style:italic">Good
      Housekeeping</span>, <span style="font-
style:italic">The Folio</span>, <span

```

, Friends Journal, Kaleidograph, The Ladies Home Journal, The Lantern, The Lyric, New York Herald Tribune, The New York Times, Palmetto Voices, The Poetry Chap-book, The Saturday Evening Post, The Saturday Review of Literature, and Yankee. Solum's poem <referringString target="relation1">"Foggy Night"</referringString> was set to music by the composer Florence Price.</p>
 <p>In addition to publication, Solum's professional poetic activity included readings, lectures and radio broadcast. She was a member of the <referringString target="relation2">Poetry Society of America</referringString>, the <referringString target="relation3">Pen and Brush Club of Manhattan</referringString> and was included in the International Who's Who in Poetry (The Cranbrook Tower Press, 1958), which lists her recreations as Siamese cats and books.</p>
 </biogHist>
 </description>

```

<description>
  <functionsPerformed>
    <functionPerformed valueURI="http://vocab.getty.edu/page/
aat/300133011" conventionDeclarationReference="cd3">
      <term>
        administration
      </term>
      <placeName valueURI="http://id.loc.gov/authorities/
names/n79075597" conventionDeclarationReference="cd1">
        Buffalo (N.Y.)
      </placeName>
      <descriptiveNote>
        <p></p>
      </descriptiveNote>
    </functionPerformed>
  </functionsPerformed>
</description>

```

```

    </functionsPerformed>
    <legalStatuses>
      <legalStatus>
        <term>New York State Department of Education</term>
      </legalStatus>
    </legalStatuses>
    <mandates>
      <mandate id="mandate1">
        <term>New York State Education Law, Article 8, Section
356</term>
        <date standardDate="2014">2014</date>
        <placeName valueURI="http://vocab.getty.edu/page/
tgn/7007568"
vocabularySource="tgn"
vocabularySourceURI="https://www.getty.edu/research/tools/
vocabularies/tgn/">New York (state)</placeName>
      </mandate>
    </mandates>
    <biogHist>
      <p>The UB Council serves as the primary oversight and
advisory body to the
        University at Buffalo and its president and senior
officers. Established in
        accordance with New York State Education Law, the
council consists of ten
        members, nine who are appointed to seven-year terms by
the governor of the State
        of New York, and one student member who is elected to an
annual term by the
        university's students.</p>
      <p>Among the regular duties of the council are reviewing all
major plans and
        activities of the university in the areas of academics,
student life, finances,
        buildings and grounds, as well as making recommendations
and regulations for the
        benefit of the university in matters of community and
alumni relations. One of
        the council's foremost, albeit infrequent,
responsibilities is to recommend
        candidates to the state university trustees to serve as
campus president.</p>
      <p>The University Council of the University of Buffalo was
established in 1922; its
        name changed when the university joined the SUNY system
in 1962. See <reference
href="https://findingaids.lib.buffalo.edu/agents/
corporate_entities/1566">UB
Council</reference> for records associated with this body before
1962.</p>
      <p>See the <reference href="https://www.buffalo.edu/
ubcouncil.html">UB Council
website</reference> for more information.</p>
    </biogHist>
  </description>

```


relations

```

<relations>
  <relation id="relation1" relationType="https://www.ica.org/
standards/RiC/ontology#AuthorshipRelation" targetType="resource"
  conventionDeclarationReference="cd2">
    <label valueURI="https://find.library.upenn.edu/
catalog/9923566873503681">
      Foggy night They lie, they lie, by David Morton and
      Florence B. Price, Ms. Coll. 199: Marian Anderson Collection of
      Music Manuscripts, folder 1404
    </label>
    <dateRange>
      <fromDate standardDate="1949-02-05">
        February 5, 1949
      </fromDate>
      <toDate standardDate="1989">
        1989
      </toDate>
    </dateRange>
    <role>
      Lyricist
    </role>
  </relation>
  <relation id="relation2" relationType="https://
www.ica.org/standards/RiC/ontology#MembershipRelation"
  targetType="corporateBody" conventionDeclarationReference="cd2">
    <label valueURI="http://id.loc.gov/authorities/names/
n50065387" conventionDeclarationReference="cd4">
      Poetry Society of America
    </label>
  </relation>
  <relation id="relation3" relationType="https://
www.ica.org/standards/RiC/ontology#MembershipRelation"
  targetType="corporateBody" conventionDeclarationReference="cd2">
    <label valueURI="http://id.loc.gov/authorities/names/
no2003010198" conventionDeclarationReference="cd4">
      Pen and Brush, Inc.
    </label>
  </relation>
</relations>

```

```

<relations>
  <relation targetType="function">
    <label valueURI="Example Function Description.xml">
      Function name (placeholder)
    </label>
  </relation>
  <relation targetType="corporateBody" relationType="https://
www.ica.org/standards/RiC/ontology#AgentControlRelation">
    <label valueURI="https://lccn.loc.gov/n83167936"
    vocabularySource="LCNAF" vocabularySourceURI="https://lccn.loc.gov"
    conventionDeclarationReference="cd1">
      New York (State). Governor

```

```

        </label>
        <descriptiveNote>
            <p>
                Established in accordance with <referringString
                referredEntityType="name" target="mandate1">New York State
                Education Law</referringString>, the council consists of ten
                members, nine who are appointed to seven-year terms by the governor
                of the State of New York, and one student member who is elected to
                an annual term by the university's students.
            </p>
        </descriptiveNote>
    </relation>
</relations>

```

alternativeSet

```

<alternativeSet>
  <setComponent href="http://www.womenaustralia.info/biogs/
  AWE0064b.htm" linkTitle="Hill, Dorothy - Woman - The Australian
  Women's Register">
    <componentEntry>
      The Australian Women's Register record.
    </componentEntry>
  </setComponent>
  <setComponent href="http://nla.gov.au/anbd.aut-an35995526"
  linkTitle="Hill, Dorothy, 1907-1997 - Full record view - Libraries
  Australia Search">
    <componentEntry>
      Libraries Australia record.
    </componentEntry>
  </setComponent>
  <setComponent href="https://www.eoas.info/biogs/P000494b.htm"
  linkTitle="Hill, Dorothy - Biographical entry - Encyclopedia of
  Australian Science">
    <componentEntry>
      Encyclopedia of Australian Science record.
    </componentEntry>
  </setComponent>
</alternativeSet>

```