


# C Programming

Inventor:-

Dennis Ritchie



case sensitive programming  
file extension '.c'

#include <stdio.h> → Preprocessor Directive

- ④ ✓ Preprocessor Directive :- It is used to call the header file before processing.
- ④ ✓ include :- It is a key word which is used to include the header file within the programme before the processing has been started.  
< > → header file sign
- ④ ✓ <stdio.h> :- Standard Input Output Header file.  
It is a header file which is used to impart to system defined function in our programme.
  - (1) printf()
  - (2) scanf()
- ✓ printf() :- It is a system defined function which is present within <stdio.h>. It is used to print or display anything on the screen.
- ✓ scanf() :- It is also a system defined function which is present within <stdio.h>, is also used to take input from users.  
#include <conio.h>
- ✓ <conio.h> :- console input output. It is a header file which consists of getch() which is used to stay the output on the screen, until any key is pressed output will not closed.

\* console means black screen.

## Datatype

Integer

key word  $\rightarrow$  int  
(It only stores numbers)  
eg: a = '65'  
denoted by:  
%.d  
size = 2-4 byte

Flcoat

Keyword  $\rightarrow$  float  
(It stores fractions numbers)  
Capacity: 6 decimal place.  
eg:  $a = '65.707389'$   
denoted by: %f  
Size: 8 byte

### Double Character

Key word  $\rightarrow$  ~~double~~ char  
(It also stores single letters)  
eg: 's'  
denoted by: %c  
size = 1 byte

Double

key word  $\rightarrow$  double  
(It also stores fractions numbers)  
Capacity : 14 decimal place  
eg: '5.77689432145781'  
denoted by: %.ld  
Size : 16 byte

String

string  $\rightarrow$  char(array)  
keyword  $\rightarrow$  string  
(It contains multiple words)  
denoted by: %s  
\* It also stores special characters and space  
size: NA

```
void main ()
```

BODY OF MAIN

Statement

↓

void main:- It is a system defined function, within the body section of main(). We have to write the programme to get the desired output because operating system can only identify main().

[':=' = Terminating operators, It is a operator which is used to give instruction to the computer that the statement has been terminated or end.]

```
printf ("Subhasree");
```

scanf ("%d", &a); &: ampersand / address operator

- ✓ printf(): It is used to display anything on the screen, we have to write the word or sentence within the double quotation mark.
- ✓ &:- It is an address operator which is used to store the variable's value within the RAM memory.
- ✓ Datatype:- "%d" or any datatype is wanted.
  - ✓ \n: It is an escape sequence which is used to put the cursor into the next line.

### Theory - If Else

- ✓ / → (Divide)