

# Maintaining a Sequence

Please write a program that maintains a sequence, supporting the following 6 operations:

Operation	Input Format	Description
1. Insert	INSERT $posi$ $tot$ $c_1$ $c_2$ ... $c_{tot}$	After the $posi$ -th number in the current sequence, insert a total of $tot$ numbers: $c_1, c_2, \dots, c_{tot}$ . Insertion to the beginning of the sequence will have $posi$ equal to 0.
2. Delete	DELETE $posi$ $tot$	Starting at the $posi$ -th number in the current sequence, delete a total of $tot$ consecutive numbers.
3. Modify	MAKE-SAME $posi$ $tot$ $c$	Starting at the $posi$ -th number in the current sequence, change all the values of $tot$ consecutive numbers to $c$ .
4. Reverse	REVERSE $posi$ $tot$	Starting at the $posi$ -th number in the current sequence, reverse the order of $tot$ consecutive numbers.
5. Get Sum	GET-SUM $posi$ $tot$	Starting at the $posi$ -th number in the current sequence, output the sum of $tot$ consecutive numbers.
6. Max Sum	MAX-SUM	Output the largest sum of any (non-empty) consecutive subsequence of the current sequence.

## Input Specification

The first line of input contains two integers  $N$  and  $M$ , where  $N$  is the initial length of the sequence and  $M$  is the number of operations.

The second line of input contains  $N$  integers, describing the initial sequence.

For the next  $M$  lines, each line will contain a command in one of the formats described above.

## Output Specification

For each `GET-SUM` or `MAX-SUM` operation in the input, output the result of the query on a separate line.

## Sample Input

```
9 8
2 -6 3 5 1 -5 -3 6 3
GET-SUM 5 4
MAX-SUM
INSERT 8 3 -5 7 2
DELETE 12 1
MAKE-SAME 3 3 2
REVERSE 3 6
GET-SUM 5 4
MAX-SUM
```

## Sample Output

---

```
-1
10
1
10
```

## Constraints

---

You may assume that at any given time, the sequence will contain at least 1 number. The data in the input is guaranteed to be valid, and will always refer to existing positions in the sequence.

In test data worth 50% of the points, the sequence may contain up to 30 000 numbers at any given moment.

In test data worth 100% of the points, the sequence may contain up to 500 000 numbers at any given moment.

In test data worth 100% of the points, the value of any number in the sequence will be in the range  $[-1\,000, 1\,000]$ .

In test data worth 100% of the points,  $M \leq 20\,000$ , the sum of all inserted values will not exceed 4 000 000, and the input will not exceed 20MB.