

# IOI '15 P3 - Teams

There is a class of  $N$  students, numbered  $0$  through  $N - 1$ . Every day the teacher of the class has some projects for the students. Each project has to be completed by a team of students within the same day. The projects may have various difficulty. For each project, the teacher knows the exact size of a team that should work on it.

Different students may prefer different team sizes. More precisely, student  $i$  can only be assigned to a team of size between  $A[i]$  and  $B[i]$  inclusive. On each day, a student may be assigned to at most one team. Some students might not be assigned to any teams. Each team will work on a single project.

The teacher has already chosen the projects for each of the next  $Q$  days. For each of these days, determine whether it is possible to assign students to teams so that there is one team working on each project.

## Example

Suppose there are  $N = 4$  students and  $Q = 2$  days. The students' constraints on team sizes are given in the table below:

Student	0	1	2	3
A	1	2	2	2
B	2	3	3	4

On the first day there are  $M = 2$  projects. The required team sizes are  $K[0] = 1$  and  $K[1] = 3$ . These two teams can be formed by assigning student 0 to a team of size 1 and the remaining three students to a team of size 3.

On the second day there are projects  $M = 2$  again, but this time the required team sizes are  $K[0] = 1$  and  $K[1] = 1$ . In this case it is not possible to form the teams, as there is only one student who can be in a team of size 1.

## Task

You are given the description of all students:  $N$ ,  $A$ , and  $B$ , as well as a sequence of  $Q$  questions — one about each day. Each question consists of the number  $M$  of projects on that day and a sequence  $K$  of length  $M$  containing the required team sizes. For each question, your program must return whether it is possible to form all the teams.

You need to implement functions:

```
void init(int N, int A[], int B[]);
```

- The grader will call this function first and exactly once.

- `N`: the number of students.
- `A`: an array of length  $N$ : `A[i]` is the minimum team size for student  $i$ .
- `B`: an array of length  $N$ : `B[i]` is the maximum team size for student  $i$ .
- You may assume that  $1 \leq A[i] \leq B[i] \leq N$  for each  $i = 0, \dots, N - 1$ .

```
int can(int M, int K[]);
```

- After calling `init` once, the grader will call this function  $Q$  times in a row, once for each day.
- `M`: the number of projects for this day.
- `K`: an array of length  $M$  containing the required team size for each of these projects.
- The function should return `1` if it is possible to form all the required teams and `0` otherwise.
- You may assume that  $1 \leq M \leq N$ , and that for each  $i = 0, \dots, M - 1$  we have  $1 \leq K[i] \leq N$ . Note that the sum of all  $K[i]$  may exceed  $N$ .

Subtasks

Let us denote by  $S$  the sum of values of  $M$  in all calls to `can(M, K)`.

subtask	points	$N$	$Q$	Additional Constraints
1	21	$1 \leq N \leq 100$	$1 \leq Q \leq 100$	none
2	13	$1 \leq N \leq 100\,000$	$Q = 1$	none
3	43	$1 \leq N \leq 100\,000$	$1 \leq Q \leq 100\,000$	$S \leq 100\,000$
4	23	$1 \leq N \leq 500\,000$	$1 \leq Q \leq 200\,000$	$S \leq 200\,000$