JARVIS

Double-clap desktop automation | Windows setup guide

A beginner-friendly walkthrough for installing, configuring and running the JARVIS project. Written for the repository maintained by Aima I. Feroz.

WHAT YOU WILL BUILD

Two quick claps trigger a desktop startup sequence: a Spotify link, Chrome pages, an optional ElevenLabs spoken greeting, and Cursor IDE. This is a clap-activated automation workflow, not a voice-command chatbot.

```
Microphone → RMS / adaptive threshold → double clap → workspace actions
```

Before starting: Use Windows, a working microphone, an internet connection for online services, and permission to install Python. Chrome and Cursor are needed for their respective actions.

Part 1 | Install and open the project

01 Install Python

Visit python.org/downloads and install Python 3 for Windows. If the installer offers Add python.exe to PATH, enable it. Open Command Prompt or PowerShell and verify:

```
python --version
```

02 Install Visual Studio Code

Download VS Code from code.visualstudio.com. Install and open it.

03 Get JARVIS from GitHub

Visit github.com/aimaferoz/jarvis-desktop-assistant (once the repository is public), choose Code → Download ZIP, and extract the folder. Alternatively clone it with Git. The folder should contain jarvis.py, requirements.txt, README.md and .env.example.

04 Open the folder

In VS Code choose File → Open Folder, select the extracted project folder, then choose Terminal → New Terminal. The terminal should be in that folder.

05 Install dependencies

Run the following command. It installs NumPy, SoundDevice, ElevenLabs, python-dotenv and other required packages:

```
python -m pip install -r requirements.txt
```

Part 2 | Set up ElevenLabs safely

The voice greeting is optional. JARVIS can still perform its other actions without ElevenLabs credentials. Each user must obtain their own API key; a placeholder is not a functioning key.

06 Create your own ElevenLabs API key

Sign in at elevenlabs.io. Find the Developers / API Keys area (the exact menu labels can change), create a key with suitable text-to-speech access, and copy it privately. Service limits or charges may apply depending on your plan.

07 Choose a voice

In ElevenLabs, visit Voices / My Voices, choose a voice and copy its Voice ID from the voice options. This is different from the API key.

08 Create a private .env file

In the project folder, duplicate .env.example and rename the copy .env. Replace the placeholders with your own credentials. Do not edit the example file to contain real secrets.

```
ELEVENLABS_API_KEY=your_own_key_here
ELEVENLABS_VOICE_ID=your_chosen_voice_id_here
```

Security: Never upload, commit, screenshot or share your real .env. The repository includes a .gitignore rule to exclude it. If you expose a key, revoke it in ElevenLabs and create a replacement.

Part 3 | Run and test

09 Start JARVIS

In the VS Code terminal run:

```
python jarvis.py
```

Allow microphone access if Windows prompts you. The terminal should show the listener starting and information about the selected audio device.

10 Test the double clap

Clap twice quickly, with a short gap between claps (the default accepted interval is roughly 0.05 to 0.35 seconds). If the configured programs are installed and accessible, the script attempts to open Spotify, Claude and Binance in Chrome, play the ElevenLabs welcome, and focus or launch Cursor.

Important: The startup actions run only once per process. To test again, press Ctrl+C in the terminal, restart python jarvis.py, and clap twice again.

Part 4 | Customize your workspace

Open jarvis.py and review the constants near the top. The project ships with its creator’s example links, welcome phrase, and monitor positions. Change these to match your computer before running.

Setting	What it controls
SONG_URI	Spotify or YouTube link opened after the clap
JARVIS_WELCOME_PHRASE	Spoken greeting text
SPIKE_RATIO	Clap sensitivity (higher = stricter)
MIN_DOUBLE_GAP_S / MAX_DOUBLE_GAP_S	Accepted gap between claps
OPEN_CLAUDE_CODE_IN_CHROME	Enable or disable Claude browser window
OPEN_BINANCE_BTC_IN_CHROME	Enable or disable Binance browser window
CLAUDE_CHROME_MONITOR / BINANCE_CHROME_MONITOR	1-based target monitor numbers
FOCUS_EXISTING_CURSOR_ON_DOUBLE_CLAP	Focus or start Cursor
JARVIS_WELCOME_CACHE_ENABLED	Reuse generated WAV audio

Some browser destinations and microphone choices can also be overridden privately in .env:

```
CLAUDE_CODE_URL=https://claude.ai/new
BINANCE_BTC_URL=https://www.binance.com/en/trade/BTC_USDT
# JARVIS_INPUT_DEVICE=your_microphone_name
```

On a single-monitor computer, the script may fall back to an available monitor if a higher monitor index is requested. Chrome window placement and fullscreen are Windows-specific.

Part 5 | Troubleshooting

No clap detected: Clap closer to the microphone; reduce SPIKE_RATIO slightly; check Windows microphone permissions and input level.

Wrong microphone: Run the command below to list input devices, then set JARVIS_INPUT_DEVICE in .env to an index or matching name.

No ElevenLabs voice: Check your private key and Voice ID; verify your account can access text-to-speech; inspect terminal warnings.

Audio / PortAudio error: Check microphone drivers; try SAMPLE_RATE = 48000 in jarvis.py.

Chrome or Cursor does not open: Install the app, check the executable path, and review the terminal logs.

Clap works only once: Expected: stop the script with Ctrl+C and run it again.

```
python -c "import sounddevice as sd; print(sd.query_devices())"
```

If you change the code, keep a backup of the original working version and test on Windows before publishing updates.

Project links and attribution

JARVIS repository: github.com/aimaferoz/jarvis-desktop-assistant
Project packaging and this guide: Aima I. Feroz
Learning reference: Hector Garcia, Jarvis Setup Guide (August 11, 2026), supplied as a reference for the installation workflow. This document is newly written for the JARVIS repository and is not a reproduction of the original guide.