

LorDong's Blog

最永恒的幸福是平凡，最长久的拥有是珍惜

[« Nexus设备手动刷机步骤](#)
[在树莓派中部署MySQL »](#)

在树莓派中部署Nginx+PHP的方法

参考来源: [点这里](#)

1. 安装

```
1  sudo apt-get update
2  sudo apt-get install nginx
3  sudo service nginx start
4  sudo apt-get install php5-fpm php-apc
5  sudo service php5-fpm restart
```

2. 部署

默认安装的nginx在/etc/nginx目录下，部署的目录是sites-available和sites-enabled，其中前者是存放所有配置文件，通过软链接把需要的配置链进后者。默认安装nginx已经建好/var/www目录，只需要创建default的一副本并在上面修改即可，把php部分的注释去掉就可以了，这里php里选择php5-fpm项，完整的mysite文件如下：

```
1  server {
2  listen 80;
3  root /var/www;
4  index index.php index.html index.htm;
5  location ~ \.php$ {
6  include snippets/fastcgi-php.conf;
7  fastcgi_pass unix:/var/run/php5-fpm.sock;
8  }
9  }
```

文件关联及重启服务的相关命令：

```
1 sudo unlink /etc/nginx/sites-enabled/default
2 cd /etc/nginx/sites-enabled
3 sudo ln -s ../sites-available/mysite
4 sudo service nginx restart
5 sudo service php5-fpm restart
```

增加对图像函数imagecreate等的支持使用以下命令：

```
1 sudo apt-get install php5-gd
2 sudo service php5-fpm restart
```

相关日志

- [树莓派Raspbmc上开启cron](#) (0)
- [在树莓派中部署MySQL](#) (0)
- [VM虚拟机安装CentOS](#) (0)
- [树莓派上安装XBMC并部署PT下载](#) (0)
- [XBMC插件汇总](#) (0)

Tags: [Linux](#), [树莓派](#)

This entry was posted on 星期四, 一月 14th, 2016 at 10:32 and is filed under [东东博客](#). You can follow any responses to this entry through the [RSS 2.0](#) feed. You can [leave a response](#), or [trackback](#) from your own site.

Leave a Reply

Name (required)

Mail (will not be published) (required)

Website