A Artifact Appendix

A.1 Abstract

The artifact discovers the vulnerability gap between manual models and automl models against various kinds of attacks (adversarial, poison, backdoor, extraction and membership) in image classification domain. It implements all datasets, models, and attacks used in our paper.

We expect the artifact could support the paper's claim that automl models are more vulnerable than manual models against various kinds of attacks, which could be explained by their small gradient variance.

A.2 Artifact check-list (meta-information)

- · Binary: on pypi with any platform.
- Model: Our pretrained models are available on Google Drive (link). Follow the model path style {model_dir}/image/{dataset}/{model}.pth to place them in correct location.
- Data set: CIFAR10, CIFAR100 and ImageNet32. Use

 --download flag to download them automatically at first running. ImageNet32 requires manual set-up at their website due to legality.

· Run-time environment:

At any platform (Windows and Ubuntu tested).

'Pytorch' and 'torchvision' required. (CUDA 11.3 recommended)

'adversarial-robustness-toolbox' required for extraction attack and membership attack.

- · Hardware: GPU with CUDA support is recommended.
- Execution: Model training and backdoor attack would be timeconsuming. It would cost more than half day on a Nvidia Quodro RTX6000.
- Metrics: Model accuracy, attack success rate, clean accuracy drop and cross entropy.
- · Output: console output and saved model files (.pth).
- Experiments: OS scripts. Recommend to run scripts 3-5 times to reduce the randomness of experiments.
- How much disk space required (approximately)?: less than 5GB.
- How much time is needed to prepare workflow (approximately)?: within 1 hour.
- How much time is needed to complete experiments (approximately)?: 3-4 days.
- · Publicly available?: on GitHub.
- Code licenses (if publicly available)?: GPL-3.
- Archived (provide DOI)?: GitHub commit eb20d02a9cf785e48843b10ff8084374491d238e.

A.3 Description

A.3.1 How to access

• GitHub: pip install -e .

• PYPI: pip install autovul

• Docker Hub: docker pull local0state/autovul

• GitHub Packages: docker pull ghcr.io/ain-soph/autovul

A.3.2 Hardware dependencies

Recommend to use GPU with CUDA 11.3 and CUDNN 8.0. Less than 5GB disk space is needed.

A.3.3 Software dependencies

You need to install python==3.9, pytorch==1.10.x, torchvision==0.11.x manually.

ART (IBM) is required for extraction attack and membership attack. pip install adversarial-robustness-toolbox

A.3.4 Data sets

We use CIFAR10, CIFAR100 and ImageNet32 datasets. Use --download flag to download them automatically at first running. ImageNet32 requires manual set-up at their website due to legality.

A.3.5 Models

Our pretrained models are available on Google Drive (link). Follow the model path style {model_dir}/image/{dataset}/{model}.pth to place them in correct location.

A.4 Installation

· GitHub: pip install -e .

• PYPI: pip install autovul

• Docker Hub: docker pull local0state/autovul

• GitHub Packages: docker pull ghcr.io/ain-soph/autovul

(optional) Config Path

You can set the config files to customize data storage location and many other default settings. View /configs_example as an example config setting.

We support 3 configs (priority ascend):

- · package (DO NOT MODIFY)
 - autovul/base/configs/*.yml
 - autovul/vision/configs/*.yml
- user
 - /.autovul/configs/base/*.yml
 - /.autovul/configs/vision/*.yml
- workspace
 - ./configs/base/*.yml
 - ./configs/vision/*.yml

A.5 Experiment workflow

Bash Files

Check the bash files under /bash to reproduce our paper results.

Train Models

You need to first run /bash/train.sh to get pretrained models.

If you run it for the first time, please run with --download flag to download the dataset:

bash ./bash/train.sh "--download"

It takes a relatively long time to train all models, here we provide our pretrained models on Google Drive (link). Follow the model path style {model_dir}/image/{dataset}/{model}.pth to place them in correct location.

Run Attacks

/bash/adv_attack.sh

/bash/poison.sh

/bash/backdoor.sh

/bash/extraction.sh

/bash/membership.sh

Run Other Exps

/bash/grad_var.sh

/bash/mitigation_backdoor.sh

/bash/mitigation_extraction.sh

For mitigation experiments, the architecture names in our paper map to:

darts-i: diy_deep

darts-ii: diy_noskip

darts-iii: diy_deep_noskip

These are the 3 options for --model_arch {arch} (with --model darts)

A.6 Evaluation and expected results

Our paper claims that automl models are more vulnerable than manual models against various kinds of attacks, which could be explained by low gradient variance.

Training

(Table 1) Most models around 96%-97% accuracy on CIFAR10.

Attack

For automl models on CIFAR10,

- adversarial: (Figure 2) higher success rate around 10% (±4%).
- poison: (Figure 6) lower accuracy drop around 5% (±2%).

- backdoor: (Figure 7) higher success rate around 2% (±1%) and lower accuracy drop around 1% (±1%).
- extraction: (Figure 9) lower inference cross entropy around 0.3 (±0.1).
- membership: (Figure 10) higher auc around 0.04 (±0.01).

Others

- gradient variance: (Figure 12) automl with lower gradient variance around 2.2 (±0.5).
- mitigation architecture: (Table 4, Figure 16, 17) deep architectures (darts-i, darts-iii) have larger cross entropy for extraction attack around 0.5, and higher accuracy drop for poisoning attack around 7% (±3%) with setting of 40% poisoning fraction.

A.7 Experiment customization

Use _-h or _--help flag for example python files to check available arguments.

A.8 Notes

A.9 Methodology

Submission, reviewing and badging methodology:

- https://www.acm.org/publications/policies/ artifact-review-badging
- http://cTuning.org/ae/submission-20201122.html
- http://cTuning.org/ae/reviewing-20201122.html