

Calcu3 M3

Calcu3 M3

Here!

<http://web.ctflearn.com/web7/>

I forgot how we were doing those calculations, but something tells me it was pretty insecure.

Flag: CTFlearn{watch_Out_f0r_th3_m0ng00s3}

Writeup:

captured request with Burp, and found 3 functions, with 1 passing values to the vulnerable `eval` function. using 'HTTP Request Maker' toolbar I added the `expression` function and gave it a value of `1=1` (encoded as `1%2B1`) and server replied with '2'

using same tool I gave the expression function a value of `;ls`, and was given flag as returned data: `calc.jsctf{watch_Out_f0r_th3_m0ng00s3}index.phpmain.cssmain.css`

calc.js

```
function c(val)
{
  document.getElementById("d").value=val;
}
function v(val)
{
  document.getElementById("d").value+=val;
}
function e()
{
  try
  {
    c(eval(document.getElementById("d").value))
  }
  catch(e)
  {
    c('Error')
  }
}
```

web7.html

```
<html>
<head>
<meta http-equiv="content-type" content="text/html; charset=windows-1252">
<link rel="stylesheet" href="web7_files/main.css">
<script type="text/javascript" src="web7_files/calc.js">
</script>
</head>
<body>
<div class="box">
<div class="display">
<form action="." method="post">
<input type="text" name="expression" readonly="readonly" size="18" id="d">
</form>
```

```

</div>
<div class="keys">
  <p>
    <input type="button" class="button gray" value="mrc" onclick='c("Created.....")'>

    <input type="button" class="button gray" value="m-" onclick='c(" .....by.....")'>

    <input type="button" class="button gray" value="m+" onclick='c(" .....Anoop")'>

    <input type="button" class="button pink" value="/" onclick='v("/ ")'>
  </p>
  <p>
    <input type="button" class="button black" value="7 " onclick='v("7 ")'>
    <input type="button" class="button black" value="8 " onclick='v("8 ")'>

    <input type="button" class="button black" value="9 " onclick='v("9 ")'>
    <input type="button" class="button pink" value="*" onclick='v("* ")'>
  </p>
  <p>
    <input type="button" class="button black" value="4" onclick='v("4 ")'>
    <input type="button" class="button black" value="5" onclick='v("5 ")'>

    <input type="button" class="button black" value="6 " onclick='v("6 ")'>
    <input type="button" class="button pink" value="- " onclick='v("- ")'>
  </p>
  <p>
    <input type="button" class="button black" value="1 " onclick='v("1 ")'>
    <input type="button" class="button black" value=" 2" onclick='v("2 ")'>

    <input type="button" class="button black" value=" 3" onclick='v("3 ")'>
    <input type="button" class="button pink" value=" +" onclick='v(" + ")'>
  </p>
  <p>
    <input type="button" class="button black" value=" 0" onclick='v("0 ")'>
    <input type="button" class="button black" value="." onclick='v(" .")'>

    <input type="button" class="button black" value="C" onclick='c("")'>
    <input type="submit" class="button orange" value="=">
  </p>
</div>
</div>

</body>
</html>

```