# LAB211 Assignment

Type: Code: LOC: Slot(s): Short Assignment J1.S. P0001

40 1

Title

Bubble sort algorithm

# **Background Context**

Bubble sort is a simple and well-known sorting algorithm. It is used in practice once in a blue moon and its main application is to make an introduction to the sorting algorithms. Bubble sort belongs to Q(n²) sorting algorithms, which makes it quite inefficient for sorting large data volumes. Bubble sort is **stable** and **adaptive**. **Program Specifications** 

Design a program that allows users to input the number of array. Generate random integer in number range input. Dspl ay unsorted array and sorted array using bubble sort.

#### Functi on det ails:

- 1. Display a screen to prompt users to input a positive integer number.
  - O Users run the program, display a screen to ask users to enter a positive integer number.
  - Us ersinput a positive integer number. Then, perfor mFunction 2
- 2. Display & sort array.
  - o Generate rando minteger in number range for each array element.
  - Display array before and after sorting.

## Expectation of User interface:

```
Enter number of array:

10

Unsorted array: [2, 6, 3, 6, 8, 6, 1, 2, 9, 8]

Sorted array: [1, 2, 2, 3, 6, 6, 6, 8, 8, 9] BUILD SUCCESSFUL (total time: 1 second)
```

#### Gui del i nes

## Algorithm

- 1. Compare each pair of adjacent elements from the beginning of an array and, if they are in reversed order, swap them
- 2. If at least one swap has been done, repeat step 1.

You can imagine that on every step big bubbles float to the surface and stay there. At the step, when no bubble moves, sorting stops. Let us see an example of sorting an array to make the idea of bubble sort dearer.

Example. Sort {5, 1, 12, -5, 16} using bubble sort.

12 -5 unsorted -5 5 > 1, swap 5 < 12, ok -5 12 > -5, swap -5 12 < 16, ok -5 1 < 5, ok -5 5 > -5, swap 5 < 12, ok -5 1 > -5, swap 1 < 5, ok -5 -5 < 1, ok

sorted