

TempMal.com — Complete AI Builder Prompt

Build a **fully functional, production-quality temporary email website** called **TempMal.com**.

This must be a **real working temporary email application**, not a UI mockup, prototype, or fake demo.

1. BRAND

Website: TempMal.com

Main tagline:

Temporary Email That Shields Your Real Mailbox

Supporting text:

Create a free disposable email address instantly. Receive emails online without exposing your personal inbox.

Use **TempMal.com** consistently throughout the website.

Production URL:

`https://tempmal.com/`

2. REAL MAIL.TM API

Use the official **Mail.tm API** as the real temporary-email provider.

API base:

`https://api.mail.tm`

Mail.tm currently documents a REST API with no API key required, an 8 QPS general limit, and SSE support for real-time messages.

DO NOT use fake emails, fake inbox messages, mock API responses, or simulated functionality.

The actual Mail.tm API response must power the application.

3. MAIL.TM ACCOUNT FLOW

Implement this exact flow:

Step 1 — Get Domains

GET `https://api.mail.tm/domains`

Use the returned `hydra:member` array.

Select an active domain where:

`isActive === true`

Do not hardcode a Mail.tm domain. The domains endpoint is paginated, so handle pagination when necessary.

Step 2 — Create Account

Generate a random valid username and secure random password.

POST `https://api.mail.tm/accounts`

```
{
  "address": "generated_username@available_domain",
  "password": "secure_random_password"
}
```

Store the returned account ID and address.

Step 3 — Authenticate

POST `https://api.mail.tm/token`

```
{
  "address": "generated_username@available_domain",
  "password": "secure_random_password"
}
```

Store the returned token for the current session.

Use:

`Authorization: Bearer TOKEN`

for authenticated requests. Mail.tm requires a Bearer token for authenticated endpoints.

Step 4 — Verify Account

Use:

```
GET https://api.mail.tm/me
```

Verify that the current temporary mailbox is valid.

Step 5 — Get Inbox

Use:

```
GET https://api.mail.tm/messages
```

with the Bearer token.

Display the actual returned:

- Sender name
- Sender email
- Subject
- Intro/preview
- Date
- Read/unread state
- Attachment indicator

Mail.tm returns paginated messages, with up to 30 messages per page. Use `hydra:totalItems` and pagination correctly.

Step 6 — Open Message

When the user clicks a message:

```
GET https://api.mail.tm/messages/{id}
```

Display the actual:

- Sender
- Recipient
- Subject
- Text
- HTML
- Date
- Attachments

provided by Mail.tm.

Step 7 — Mark Read

When the user opens an unread message:

```
PATCH https://api.mail.tm/messages/{id}
```

Update the UI only after the API confirms the operation.

Step 8 — Real-Time Inbox

Prefer Mail.tm's documented **SSE/Mercure real-time events** for detecting new messages.

If SSE cannot be reliably implemented in the selected builder environment, use conservative polling.

Never exceed the Mail.tm rate limit.

Step 9 — Delete Account

When the user explicitly chooses to permanently delete the mailbox:

```
DELETE https://api.mail.tm/accounts/{id}
```

Require confirmation first.

The Mail.tm account deletion is permanent.

4. HOMEPAGE

Create this structure:

1. Header
2. Hero
3. Temporary Email Card
4. Live Inbox
5. How It Works
6. Features
7. Privacy Section
8. FAQ
9. Footer

The temporary email generator and inbox are the main focus.

5. HEADER

Create a modern responsive header.

Left:

TempMal.com

Use an original envelope/shield logo.

Navigation:

- Home
- How It Works
- FAQ
- Privacy

Right:

- Dark Mode
- New Email

Mobile:

- Logo
 - Hamburger menu
-

6. HERO

Headline:

Temporary Email That Shields Your Real Mailbox

Description:

Create a free disposable email address instantly. Receive emails online without exposing your personal inbox. No registration required.

Primary button:

Generate New Email

Secondary button:

How It Works

Use a clean privacy/email illustration.

7. TEMPORARY EMAIL CARD

Create a prominent card.

Title:

Your Temporary Email

Display the actual Mail.tm address.

Example format:

```
random123@domain.com
```

Do not hardcode the example.

Buttons:

Copy

Refresh

New Email

Copy

Copy the real email address to the clipboard.

Show:

Copied!

Then restore the button.

Refresh

Refresh the current inbox.

Do NOT create a new mailbox.

New Email

Create a completely new Mail.tm account.

8. MAILBOX STATUS

Display the real current status:

- Connecting...
- Active
- Offline
- Error

Do not invent expiration times.

Only display an expiration time if the underlying API actually provides reliable information for it.

9. LIVE INBOX

Title:

Inbox

Display actual message count.

Example:

Inbox · 3 messages

Controls:

- Refresh
- New Email

Show the actual last-refresh time.

10. EMPTY INBOX

If there are no messages:

Your inbox is empty

Emails sent to your temporary address will appear here automatically.

Button:

Refresh Inbox

Never display fake messages.

11. MESSAGE LIST

For every real Mail.tm message display:

- Sender
- Sender email
- Subject
- Preview
- Date/time
- Unread/read status
- Attachment indicator

Unread messages must be visually emphasized.

Clicking a message opens the message reader.

12. MESSAGE READER

Create a dedicated email-reading interface.

Display:

- Back to Inbox
- Sender
- Sender email
- Recipient
- Subject
- Date/time
- Email content
- Attachments where supported

Button:

← Back to Inbox

13. EMAIL HTML SECURITY

Received email content is untrusted.

Never blindly execute or inject untrusted email HTML.

Sanitize HTML before displaying it.

Prevent:

- JavaScript execution
- Event-handler injection
- Dangerous HTML
- Malicious iframes
- Script injection

If safe HTML sanitization is unavailable, display the `text` version instead.

14. ATTACHMENTS

If Mail.tm provides attachments:

Display:

- Filename
- File type
- File size
- Download/open action where safely supported

Do not execute downloaded files automatically.

Follow the actual Mail.tm attachment data/encoding requirements.

15. NEW EMAIL

When **New Email** is clicked, show:

Create a New Temporary Email?

Text:

Your current temporary mailbox will be replaced with a new mailbox.

Buttons:

Cancel

Create New Email

After confirmation:

1. Stop old SSE/polling
2. Clear old UI state
3. Delete the old Mail.tm account if the user explicitly confirmed deletion
4. Clear old session
5. Fetch available domain
6. Generate username/password
7. Create account
8. Authenticate
9. Save session
10. Display new address
11. Load inbox
12. Start real-time listener

Do not delete the old mailbox merely because the user presses Refresh.

16. SESSION RESTORATION

On page load:

1. Check for a saved temporary session.
2. Verify it with Mail.tm.
3. If valid, restore the mailbox.
4. Load inbox.
5. Start real-time updates.
6. If invalid, create a new mailbox.

Store only the minimum required session information.

17. COPY FUNCTION

Use the Clipboard API.

If clipboard access fails:

Show:

Please copy the email address manually.

Do not let clipboard errors break the app.

18. AUTO REFRESH / REAL-TIME

Prefer SSE.

If polling is required:

- Use a conservative interval.
- Never create multiple polling loops.
- Stop polling when the tab is hidden where appropriate.
- Resume when the user returns.
- Prevent duplicate requests.
- Respect the **8 QPS per IP** Mail.tm limit.

Handle HTTP 429 by backing off instead of immediately retrying.

19. ERROR HANDLING

Handle Mail.tm HTTP errors correctly.

Examples:

400

Invalid request. Please try again.

401

Your temporary mailbox session is no longer valid.

Attempt session recovery where appropriate.

404

The requested mailbox or email could not be found.

422

This email address could not be created. Please try again.

429

Too many requests. Please wait a moment and try again.

Mail.tm documents these response categories, including 429 for exceeding the 8 QPS limit.

For other errors:

Temporary email service is currently unavailable. Please try again later.

Never expose raw API errors to normal users.

20. TOAST NOTIFICATIONS

Create reusable toast notifications.

Success:

Email copied!

Inbox refreshed

New email created

New email received

Error:

Unable to load inbox

Unable to create email

Make notifications mobile-friendly.

21. DARK MODE

Implement:

- Light mode
- Dark mode
- System preference if practical

Save the user's preference locally.

Apply the theme consistently to the entire website.

22. DESIGN

Create an original premium SaaS-style design.

Style:

- Modern
- Clean
- Minimal
- Professional
- Privacy-focused

Suggested colors:

- Deep navy
- Indigo
- Purple
- White
- Light gray
- Slate

Use:

- Rounded cards
- Soft shadows
- Subtle borders
- Clean typography
- Professional icons
- Smooth 150–250ms transitions

Do not overuse animations.

23. MOBILE-FIRST

Optimize for:

- 320px+
- 375px+
- 414px+
- 768px+
- 1024px+
- 1280px+
- 1440px+

No horizontal scrolling.

Buttons must be touch-friendly.

The temporary email address must remain readable on small screens.

24. HOW IT WORKS

Three steps:

01 — Generate

Create a temporary email instantly.

02 — Receive

Receive emails directly in your temporary inbox.

03 — Protect

Keep your personal email address private.

25. FEATURES

Create six cards:

Instant Email

Generate a temporary address in seconds.

No Registration

Start without traditional registration.

Live Inbox

Receive new emails automatically.

One-Click Copy

Copy your temporary address instantly.

Privacy Focused

Avoid unnecessarily exposing your personal email.

Mobile Friendly

Works across phones, tablets, and desktops.

Only advertise functionality that actually works.

26. PRIVACY SECTION

Headline:

Keep Your Real Email Private

Explain that disposable email can help users avoid exposing their primary email address.

Do not claim:

- 100% anonymity
- Complete privacy
- Impossible tracking
- Guaranteed security

Be transparent about the limitations of temporary email.

27. FAQ

Create an accordion.

What is TempMal.com?

TempMal.com provides temporary disposable email addresses for receiving emails without exposing your primary address.

Do I need to register?

No traditional registration is required.

How does TempMal.com create emails?

TempMal.com uses the Mail.tm API to create and manage temporary mailboxes.

Can I receive verification emails?

Yes, provided the sender accepts the temporary email domain and the Mail.tm service is available.

Can I send emails?

Only show this feature if it is genuinely implemented.

Can I create a new temporary email?

Yes. Click **New Email**.

How long does a mailbox last?

Do not invent a fixed lifetime. Explain the actual behavior of the underlying Mail.tm service.

Is TempMal.com completely anonymous?

Do not promise complete anonymity.

28. FOOTER

Display:

TempMal.com

Temporary Email That Shields Your Real Mailbox

Links:

- [Home](#)
- [How It Works](#)
- [Privacy](#)
- [FAQ](#)
- [Terms](#)

Required Mail.tm attribution:

Temporary email powered by Mail.tm

Link it to:

`https://mail.tm/`

Mail.tm's current documentation requires visible attribution/link-back when using its API.

Copyright:

© 2026 TempMal.com. All rights reserved.

29. MAIL.TM TERMS

Build the application in compliance with the current Mail.tm API terms.

The current Mail.tm documentation states:

- No API key is required.
- General limit is 8 QPS per IP.
- Illegal activity is prohibited.
- Reselling the API as a paid wrapper is prohibited.
- Mirroring/proxying the API under another domain is prohibited.
- Attribution/link-back is required.

Therefore:

Do not create a generic Mail.tm API proxy under `tempmal.com`.

Use Mail.tm's API as documented for the application's temporary-email functionality.

Before commercial launch, re-check the current Mail.tm terms.

30. SECURITY

Never display:

- Temporary account password
- Bearer token
- Internal credentials

Never log passwords or tokens.

Validate API responses.

Sanitize received email HTML.

Escape dynamic text.

Do not trust sender content.

Do not allow received emails to execute application JavaScript.

31. API CODE ARCHITECTURE

Separate API logic from UI.

Create reusable functions such as:

```
getDomains()  
createAccount()  
getToken()  
getCurrentAccount()  
getMessages()  
getMessage()  
markMessageAsRead()  
deleteMessage()  
createNewMailbox()  
saveSession()  
loadSession()  
clearSession()  
startRealtimeListener()  
stopRealtimeListener()
```

Do not scatter Mail.tm requests throughout UI event handlers.

32. APPLICATION STATE

Maintain a clear state containing:

- Current email
- Account ID
- Token
- Inbox
- Selected message
- Unread count
- Loading state
- Error state
- Connection status
- Theme

- Real-time listener status

Prevent stale API responses from overwriting newer state.

33. PERFORMANCE

Optimize for:

- Fast loading
- Mobile performance
- Minimal dependencies
- Efficient API requests
- No duplicate listeners
- No memory leaks
- Proper cleanup

Avoid unnecessary libraries.

If using a library for HTML sanitization, use a reputable maintained library.

34. SEO

Page title:

TempMal.com — Free Temporary Email | Disposable Email

Meta description:

Create a free temporary email address instantly with TempMal.com. Receive emails online without exposing your personal mailbox.

Use natural keywords:

- temporary email
- temp mail
- disposable email
- temporary email address
- temporary inbox
- free temporary email

Add:

- Canonical URL
- Open Graph metadata
- Semantic HTML
- One H1
- Proper H2/H3 hierarchy

- Descriptive button labels

Do not keyword-stuff.

35. ACCESSIBILITY

Implement:

- Semantic HTML
- Keyboard navigation
- Visible focus states
- Accessible buttons
- ARIA labels where necessary
- Accessible dialogs
- Escape-to-close modals
- Screen-reader-friendly notifications
- Good color contrast
- Touch-friendly controls

Do not rely only on color for status.

36. LOADING STATES

Show proper states:

Creating your temporary email...

Connecting to Mail.tm...

Loading inbox...

Refreshing inbox...

Opening email...

Creating new mailbox...

Disable buttons during operations where necessary.

37. NO FAKE FUNCTIONALITY

This is mandatory.

Never create:

- Fake emails
- Fake senders
- Fake inbox messages
- Fake unread counts
- Fake API responses
- Fake expiration timers
- Fake success states
- Fake account creation

If Mail.tm fails, show a real error state.

38. NO PLACEHOLDERS

Remove:

- Lorem ipsum
- Demo emails
- Dummy messages
- Placeholder buttons
- Fake testimonials
- Fake statistics
- Broken links
- Coming-soon functionality

Everything visible must be functional or clearly informational.

39. FILE STRUCTURE

Prefer a clean project structure.

If the builder supports a single-file application:

```
index.html
```

Otherwise:

```
index.html  
style.css  
script.js
```

If the platform genuinely requires backend/serverless files, create only the necessary backend components.

Also create:

README.md

with setup and deployment instructions.

40. FINAL TESTING

Before delivery, verify:

- ☐ TempMal.com branding is correct
 - ☐ Website loads without errors
 - ☐ Mail.tm domains load
 - ☐ Real account is created
 - ☐ Real token is obtained
 - ☐ `/me` works
 - ☐ Real inbox loads
 - ☐ Real emails appear
 - ☐ Message count is accurate
 - ☐ Message opens correctly
 - ☐ Message is marked read
 - ☐ HTML email is safely rendered
 - ☐ Attachments are handled safely
 - ☐ Copy works
 - ☐ Refresh works
 - ☐ New Email works
 - ☐ Old listener stops
 - ☐ New listener starts
 - ☐ Session restoration works
 - ☐ Invalid token is handled
 - ☐ 429 rate-limit response is handled
 - ☐ Network errors are handled
 - ☐ Empty inbox works
 - ☐ Loading states work
 - ☐ Toast notifications work
 - ☐ Dark mode works
 - ☐ Mobile layout works
 - ☐ Desktop layout works
 - ☐ FAQ works
 - ☐ Navigation works
 - ☐ SEO metadata exists
 - ☐ Accessibility basics work
 - ☐ Mail.tm attribution is visible
 - ☐ No fake data remains
 - ☐ No passwords/tokens are exposed
 - ☐ No JavaScript errors remain
-

41. FINAL BUILDER INSTRUCTION

Build TempMal.com completely now.

Do not return only an explanation.

Do not return pseudo-code.

Do not create a static mockup.

Do not use fake inbox data.

Implement the actual Mail.tm integration and the complete responsive website.

The final result must be:

TempMal.com

Temporary Email That Shields Your Real Mailbox

Prioritize:

Real functionality → Mail.tm integration → Security → Mobile UX → Reliability → Clean design → Performance → SEO

Use the current official Mail.tm API documentation as the source of truth for endpoint behavior and response formats.