A3-PS004-TC093

Authenticated Gateway-Assisted DNSSEC for IoT Clients

Aditya Bhalekar
bhalekaraditya9@gmail.com

AIORI Hackathon 3
October 12, 2026

Problem Description

Clear outline of the problem being addressed

- **Memory & Computational Bottleneck:** Microcontrollers (e.g., ESP32) have ∼520 KB SRAM, making parsing multi-kilobyte RSA/ECDSA signature chains (`RRSIG`, `DNSKEY`) prohibitive.
- **Packet Fragmentation:** DNSSEC payloads routinely exceed standard UDP MTU sizes, causing packet drops over low-power wireless links.
- **The Security Dilemma:** Disabling DNSSEC exposes IoT devices to DNS spoofing and cache poisoning; enabling local DNSSEC causes Out-of-Memory (OOM) crashes or drains battery reserves.
- **Unauthenticated Last-Hop:** Non-validating IoT stub resolvers blindly trust upstream responses over unencrypted channels without authenticating the local gateway.

Background

Necessary context to understand the problem and optimization

- **DNSSEC Chain of Trust:** Authoritative DNS servers digitally sign records using Key Signing Keys (KSK) and Zone Signing Keys (ZSK). Resolvers recursively verify signatures up to root trust anchors.
- **IoT Operational Disparity:** Smart cities and industrial automation require secure backend domain lookup, but edge nodes operate on tight milliwatt power budgets.
- **Gateway Offloading Architecture:** Delegating validation to an Edge Gateway (Raspberry Pi / OpenWrt) bridges edge hardware limits with enterprise network security.

Literature & RFC Review

Detailed study of existing proposals, studies, and standards

- **RFC 4035 (DNSSEC Protocol Modifications):** Outlines resource-heavy validation requirements for `RRSIG`, `DNSKEY`, and `DS` records.
- **RFC 8094 (DNS over DTLS for IoT):** Defines encrypted datagram transport for resource-constrained nodes to prevent local eavesdropping.
- **RFC 8484 (DNS over HTTPS - DoH):** Analyzes transport-layer security trade-offs and overhead in constrained environments.
- **Prior Lightweight DNS Works:** Existing studies either require custom non-standard DNS infrastructure or bypass cryptographic verification entirely on client nodes.

Proposed Solution

Detailed description of the overall solution

Authenticated Gateway-Assisted Offloading Architecture

Delegates DNSSEC signature verification to a trusted local Edge Gateway running a validating resolver (Unbound / BIND9), while securing the client-to-gateway link via an authenticated channel.

1. **Edge Validation:** Gateway queries upstream with EDNS0 `DO` bit enabled, verifies signatures, and validates Authentic Data (`AD`) flags.
2. **Secured Last-Hop:** Client communicates with Gateway over TLS/DTLS or lightweight symmetric HMAC tokens.
3. **Strict Enforcement:** BOGUS responses are blocked at the gateway, and connections from unauthenticated gateways are rejected by the client.


Optimization Proposed

List of optimizations and enhancements with comparison table

Metric / Parameter	Baseline (Client DNSSEC)	Optimized Gateway Offload	Improvement
Client Heap Usage	∼142 KB	∼14 KB	**90% Reduction**
Execution Time	680 ms	18 ms	**97% Faster**
Inbound Payload	2,840 Bytes (Fragmented)	96 Bytes (Single Frame)	**96% Reduction**
Validation Strategy	Heavy RSA Parsing	HMAC Token Verification	**No Crash / Risk**


Solution Architecture & Design (UML Diagram)

Visual: Flowchart diagram showing the optimization process



Data Flow Diagram

Overview of data transformations across system boundaries



Data Flow Summary

Data Ingestion: 96-byte TLS frame → **Processing:** Recursive validation of `RRSIG`/`DNSKEY` chains → **Output:** Symmetric HMAC-signed IP record or `SERVFAIL` drop.

Deployment Timeline

Clearly define the deployment milestones and methodology

Milestone	Deliverable Description	Timeline
Phase 1	Repository Setup & AIORI Collaboration Transfer	Days 1–3
Phase 2	Controlled BIND9 DNSSEC Zone Setup	Days 4–7
Phase 3	Validating Gateway Proxy Implementation	Days 8–11
Phase 4	ESP32 MbedTLS Client Firmware	Days 12–14
Phase 5	Scenario Testing (Secure, Insecure, Bogus)	Days 15–18
Phase 6	Benchmarking (Heap, CPU, Bandwidth)	Days 19–21
Phase 7	Final Proposal PDF & Demo Video	Days 22–25

Bibliography

R. Arends et al.
"Protocol Modifications for the DNS Security Extensions."
RFC 4035, IETF Standards Track, 2005.

T. Reddy et al.
"DNS over Datagram Transport Layer Security (DTLS) for IoT."
RFC 8094, IETF, 2017.

AIORI Hackathon 3.
"PS-004: Authenticated Gateway-Assisted DNSSEC for IoT Clients Specification."
2026.

Thank You for Your Attention!