

# Direct Preference Optimization: Your Language Model is Secretly a Reward Model

Rafael Rafailov<sup>\*†</sup>Archit Sharma<sup>\*†</sup>Eric Mitchell<sup>\*†</sup>Stefano Ermon<sup>†‡</sup>Christopher D. Manning<sup>†</sup>Chelsea Finn<sup>†</sup>

<sup>†</sup>Stanford University <sup>‡</sup>CZ Biohub  
 {rafaillow,architsh,eric.mitchell}@cs.stanford.edu

## Abstract

While large-scale unsupervised language models (LMs) learn broad world knowledge and some reasoning skills, achieving precise control of their behavior is difficult due to the completely unsupervised nature of their training. Existing methods for gaining such **steerability** collect human labels of the relative quality of model generations and fine-tune the unsupervised LM to align with these preferences, often with reinforcement learning from human feedback (RLHF). However, RLHF is a complex and often unstable procedure, first fitting a reward model that reflects the human preferences, and then fine-tuning the large unsupervised LM using reinforcement learning to maximize this estimated reward without drifting too far from the original model. In this paper we introduce a new parameterization of the reward model in RLHF that enables extraction of the corresponding optimal policy in closed form, allowing us to solve the standard RLHF problem with only a simple classification loss. The resulting algorithm, which we call *Direct Preference Optimization* (DPO), is stable, **performant**, and computationally lightweight, eliminating the need for sampling from the LM during fine-tuning or performing significant hyperparameter tuning. Our experiments show that DPO can fine-tune LMs to align with human preferences as well as or better than existing methods. Notably, fine-tuning with DPO exceeds PPO-based RLHF in ability to control sentiment of generations, and matches or improves response quality in summarization and single-turn dialogue while being substantially simpler to implement and train.

**조종가능성**  
 LLM은 Unsupervised Learning이기 때문에 행동의 정확한 컨트롤을 하기 어려움  
 RLHF는  
 1) Human Preference에 맞게 Reward 모델을 학습시키고  
 2) LLM을 강화학습을 통해 최대 Reward를 받으면서 기존 모델과 동떨어지지 않게함  
 DPO는 Closed Form에서 좀더 가볍게 최적의 Policy를 찾는 기법임  
 \*Closed Form : RL처럼 반복적인 과정을 거치지 않고 하나의 수식으로 명확하게 계산할 수 있는 형태  
 RLHF는 정답셋 없이 모델이 어떤 Generation의 방향으로 가야하느냐? 이기 때문에 강화학습을 사용하는 것  
 성능 기준에 맞는  
 DPO는 감정분석, 요약, 싱글턴 대화에서 효과가 좋음

## 1 Introduction

Large unsupervised language models (LMs) trained on very large datasets acquire surprising capabilities [11, 7, 42, 8]. However, these models are trained on data generated by humans with a wide variety of goals, priorities, and skillsets. Some of these goals and skillsets may not be desirable to imitate; for example, while we may want our AI coding assistant to *understand* common programming mistakes in order to correct them, nevertheless, when generating code, we would like to bias our model toward the (potentially rare) high-quality coding ability present in its training data. Similarly, we might want our language model to be *aware* of a common misconception believed by 50% of people, but we certainly do not want the model to claim this misconception to be true in 50% of queries about it! In other words, selecting the model's *desired responses and behavior* from its very wide *knowledge and abilities* is crucial to building AI systems that are safe, performant, and controllable [28]. While existing methods typically steer LMs to match human preferences using reinforcement learning (RL),

LLM을 통해 Coding Agent를 구성한다고 했을 때, 여러 Generation중 좀더 고품질로 Generation 하고싶음  
 => RLHF를 통해 Human Preference에 가까운 확률을 좀더 높임

DPO를 통해 강화학습의 Objective Function을 단순한 Binary Cross Entropy로 바꿔서 학습시킬 수 있음

<sup>\*</sup>Equal contribution; more junior authors listed earlier.




Figure 1: **DPO optimizes for human preferences while avoiding reinforcement learning.** Existing methods for fine-tuning language models with human feedback first fit a reward model to a dataset of prompts and human preferences over pairs of responses, and then use RL to find a policy that maximizes the learned reward. In contrast, DPO directly optimizes for the policy best satisfying the preferences with a simple classification objective, fitting an *implicit* reward model whose corresponding optimal policy can be extracted in closed form.

we will show that the RL-based objective used by existing methods can be optimized exactly with a simple binary cross-entropy objective, greatly simplifying the preference learning pipeline.

DPO는 Human Preference를 강화학습을 피해서 학습시킴  
DPO는 간단한 분류 학습을 통해 Human Preference를 만족시키는 Policy를 직접 최적화함  
이러한 Policy는 Closed Form형태로 추출하며, 암묵적인 Reward Model을 학습시킴

기존 방법중 가장 좋은 방법은 사람이 만든 데이터로 SFT를 수행하는 것임

그러나 SFT 데이터셋을 생성하는 것 자체가 시간도 비용도 많이 듦

따라서 RLHF 또는 RLAIIF를 통해 Alignment을 수행시킴

DPO는 직접적으로 Reward Model과 강화학습을 사용하지는 않음.

그러나 기존 모델이 사용하는 목표 (Reward는 최대화 하면서 KLD를 통제함)를 암묵적으로 최적화함

DPO Update는 Preference Response의 Log Probability를 올리지만, 동적으로 example마다 중요도 가중치를 통합하기 때문에 기존 모델의 probability와 이격되지 않음

DPO는 Policy 함수의 Preference Loss를 직접 정의하기 위해 변수들의 변화를 사용함

Policy는 BCE를 통해 최적화되며 Preference 데이터에 맞춰지는 Reward Function을 암묵적으로 도출하게 됨

Instruction Tuning은 좋은 효과를 보이지만, 전문가의 데이터셋을 모으기는 힘들  
=> 인간의 답변에 더 Alignment되는 데이터를 모으는게 더 쉬움  
이에 따라 RLHF가 유행

서서히 주입시키다

RLHF는,

1) 먼저 Reward 모델을 Human Preference에 맞춤

2) 그리고 RL을 사용해서 모델의 Response가 적절한 Response를 생성시 Reward를 많이 받도록 Policy를 최적화시킴

그러나 이러한 RLHF는 여러 LM을 학습시켜야하고 학습 Loop에서 샘플링 과정을 거침

\* 여러 모델을 학습 : 기존 모델, Reward 모델, Policy를 학습한 모델 등 여러 모델을 학습시켜야함  
\* 샘플링 과정 : 다양한 Response를 생성하여 Reward를 평가받아야함

통합하다

따라서 파이프라인이 SFT에 비해 상당히 복잡함

악화

In this paper, we show how to directly optimize a language model to adhere to human preferences, without explicit reward modeling or reinforcement learning. We propose *Direct Preference Optimization (DPO)*, an algorithm that implicitly optimizes the same objective as existing RLHF algorithms (reward maximization with a KL-divergence constraint) but is simple to implement and straightforward to train. Intuitively, the DPO update increases the relative log probability of preferred to dispreferred responses, but it *incorporates* a dynamic, per-example importance weight that prevents the *model degeneration* that we find occurs with a naive probability ratio objective. Like existing algorithms, DPO relies on a theoretical preference model (such as the Bradley-Terry model; [5]) that measures how well a given reward function aligns with empirical preference data. However, while existing methods use the preference model to define a preference loss to train a reward model and then train a policy that optimizes the learned reward model, DPO uses a change of variables to define the preference loss as a function of the policy directly. Given a dataset of human preferences over model responses, DPO can therefore optimize a policy using a simple binary cross entropy objective, producing the optimal policy to an implicit reward function fit to the preference data.

Our main contribution is Direct Preference Optimization (DPO), a simple RL-free algorithm for training language models from preferences. Our experiments show that DPO is at least as effective as existing methods, including PPO-based RLHF, for learning from preferences in tasks such as *sentiment modulation*, summarization, and dialogue, using language models with up to 6B parameters.

조절

6B 모델에서 실험했을 때 감정 분석, 요약, 심금턴 대화에서 효과적이었음

## 2 Related Work

Self-supervised language models of increasing scale learn to complete some tasks zero-shot [33] or with few-shot prompts [6, 27, 11]. However, their performance on downstream tasks and alignment with user intent can be significantly improved by fine-tuning on datasets of instructions and human-written completions [25, 38, 13, 41]. This ‘instruction-tuning’ procedure enables LLMs to generalize to instructions outside of the instruction-tuning set and generally increase their usability [13]. Despite the success of instruction tuning, *relative* human judgments of response quality are often easier to collect than expert demonstrations, and thus subsequent works have fine-tuned LLMs with datasets of human preferences, improving proficiency in translation [20], summarization [40, 51], story-telling [51], and instruction-following [28, 34]. These methods first optimize a neural network reward function for compatibility with the dataset of preferences under a preference model such as the

Bradley-Terry model [5], then fine-tune a language model to maximize the given reward using reinforcement learning algorithms, commonly REINFORCE [47], proximal policy optimization (PPO; [39]), or variants [34]. A closely-related line of work leverages LLMs fine-tuned for instruction following with human feedback to generate additional synthetic preference data for targeted attributes such as safety or harmlessness [2], using only weak supervision from humans in the form of a text rubric for the LLM's annotations. These methods represent a convergence of two bodies of work: one body of work on training language models with reinforcement learning for a variety of objectives [35, 29, 48] and another body of work on general methods for learning from human preferences [12, 21]. Despite the appeal of using relative human preferences, fine-tuning large language models with reinforcement learning remains a major practical challenge; this work provides a theoretically-justified approach to optimizing relative preferences without RL.

RLHF로 학습된 모델에게 Safety, Harmlessness를 타겟으로 하는 Synthetic Preference data를 생성하게 함 이때 사람의 Weak Supervision은 모델의 주석에 대한 텍스트 평가 기준이 됨

강화학습은 2가지 방향으로 사용됨  
- 다양한 목표를 학습(safety,...)  
- Human Preference를 학습

bandit : MAB같은 강화학습 방법중 하나

Outside of the context of language, learning policies from preferences has been studied in both bandit and reinforcement learning settings, and several approaches have been proposed. Contextual bandit learning using preferences or rankings of actions, rather than rewards, is known as a contextual dueling bandit (CDB; [50, 14]). In the absence of absolute rewards, theoretical analysis of CDBs substitutes the notion of an optimal policy with a *von Neumann winner*, a policy whose expected win rate against *any* other policy is at least 50% [14]. However, in the CDB setting, preference labels are given online, while in learning from human preferences, we typically learn from a fixed batch of offline preference-annotated action pairs [49]. Similarly, *preference-based RL* (PbRL) learns from binary preferences generated by an *unknown* "scoring" function rather than rewards [9, 37]. Various algorithms for PbRL exist, including methods that can reuse off-policy preference data, but generally involve first explicitly estimating the latent scoring function (i.e. the reward model) and subsequently optimizing it [16, 9, 12, 36, 21]. We instead present a single stage policy learning approach that directly optimizes a policy to satisfy preferences. DPO는 단일 단계로 Policy를 배우고 직접 Preference를 최적화함

CDB는 강화학습과 달리 Reward를 사용하지 않고, 승률이 최소한 50% 이상으로 예상되는 Policy인 폰노이만 winner Policy로 최적화함

유사하게 PbRL의 경우, Policy를 scoring 함수를 사용 Binary Preference를 사용함 Reward 모델이 명시되고 Policy를 최적화하는 구조임

CDB는 Preference 레이블이 온라인으로 제공되어야함 그러나 우리 모델들은 대부분 Offline으로 제공됨

### 3 Preliminaries

We review the RLHF pipeline in [Ziegler et al. (and later [40, 1, 28]). It usually includes three phases: 1) supervised fine-tuning (SFT); 2) preference sampling and reward learning and 3) RL optimization.

**SFT:** RLHF typically begins by fine-tuning a pre-trained LM with supervised learning on high-quality data for the downstream task(s) of interest (dialogue, summarization, etc.), to obtain a model  $\pi^{\text{SFT}}$ .

**Reward Modelling Phase:** In the second phase the SFT model is prompted with prompts  $x$  to produce pairs of answers  $(y_1, y_2) \sim \pi^{\text{SFT}}(y | x)$ . These are then presented to human labelers who express preferences for one answer, denoted as  $y_w \succ y_l | x$  where  $y_w$  and  $y_l$  denotes the preferred and dispreferred completion amongst  $(y_1, y_2)$  respectively. The preferences are assumed to be generated by some latent reward model  $r^*(y, x)$ , which we do not have access to. There are a number of approaches used to model preferences, the Bradley-Terry (BT) [5] model being a popular choice (although more general Plackett-Luce ranking models [32, 23] are also compatible with the framework if we have access to several ranked answers). The BT model stipulates that the human preference distribution  $p^*$  can be written as:

$$p^*(y_1 \succ y_2 | x) = \frac{\exp(r^*(x, y_1))}{\exp(r^*(x, y_1)) + \exp(r^*(x, y_2))} \quad (1)$$

Assuming access to a static dataset of comparisons  $\mathcal{D} = \{x^{(i)}, y_w^{(i)}, y_l^{(i)}\}_{i=1}^N$  sampled from  $p^*$ , we can parametrize a reward model  $r_\phi(x, y)$  and estimate the parameters via maximum likelihood. Framing the problem as a binary classification we have the negative log-likelihood loss:

$$\mathcal{L}_R(r_\phi, \mathcal{D}) = -\mathbb{E}_{(x, y_w, y_l) \sim \mathcal{D}} [\log \sigma(r_\phi(x, y_w) - r_\phi(x, y_l))] \quad (2)$$

where  $\sigma$  is the logistic function. In the context of LMs, the network  $r_\phi(x, y)$  is often initialized from the SFT model  $\pi^{\text{SFT}}(y | x)$  with the addition of a linear layer on top of the final transformer layer that produces a single scalar prediction for the reward value [51]. To ensure a reward function with lower variance, prior works normalize the rewards, such that  $\mathbb{E}_{x, y \sim \mathcal{D}} [r_\phi(x, y)] = 0$  for all  $x$ .

**RL Fine-Tuning Phase:** During the RL phase, the learned reward function is used to provide feedback to the language model. Following prior works [17, 18], the optimization is formulated as

$$\max_{\pi_\theta} \mathbb{E}_{x \sim \mathcal{D}, y \sim \pi_\theta(y | x)} [r_\phi(x, y)] - \beta \mathbb{D}_{\text{KL}}[\pi_\theta(y | x) || \pi_{\text{ref}}(y | x)] \quad (3)$$

기댓값을 최대화 시키는 Optimal Policy를 찾는다  
Dataset의 x \* "~"는 샘플링 됨을 의미  
x가 주어졌을 때, policy theta에 따른 결과값  
reward 함수  
Policy가 Reference의 Policy(기준 모델)의 KLD를 벗어나지 않는 선에서 \* || "는 두 분포의 차이(다양성)을 의미함 Beta가 클 수록 분포의 차이가 큰 것을 용인함

RLHF는 크게 3Step임  
1) SFT  
2) Preference 샘플링, Reward 모델 학습  
3) RL 최적화

Reward Modelling:  
SFT는 프롬프트 x로부터 2개의 결과를 생성 (y1, y2)  
Human Labeler는 이 y1, y2에서 선호되는 yw와 비선호 yl을 구분

win의 Reward와 loss의 Reward의 차이 값을 Sigmoid로 최우고 로그를 때림 => 이 값의 -기댓값이 목적함수: win을 높이고 loss를 낮추는 Policy를 찾는 것

RL Phase에서는 학습된 Reward Function으로 Model에 피드백을 줌

SFT: 모델은 고품질데이터에서 요약, 대화 등의 Downstream Task를 학습하여 SFT Policy를 얻음

Reward 모델은 SFT학습의 Policy로 초기화됨: 마지막 transformer Layer 위에 Single Scalar를 예측하는 Reward value

DPO는 Reward 모델을 명시적으로 따로 학습시키지 않기 때문에, SFT에서 사용한 데이터가 bias를 가지면 안됨. 따라서 Normalize 해주어야 함



beta는 기존 모델에서 너무 벗어나는 것을 막아줌 또한,  
1) Generation이 다양하게 유지해주며,  
2) 1개의 높은 Reward를 받는 answer 때문에 모델이 망가지는걸 막아줌

Beta는 Base Policy에서의 이탈을 조절하는 파라미터임  
Base Policy는 SFT모델의 Policy임

다시말해

Reference Policy는 SFT의 Policy로 초기화됨 근데, 실질적으로 Policy Theta도 SFT의 Policy로 똑같이 초기화됨 => 결국 SFT보다 더 나은 Policy를 찾는것임

where  $\beta$  is a parameter controlling the deviation from the base reference policy  $\pi_{\text{ref}}$ , namely the initial SFT model  $\pi^{\text{SFT}}$ . In practice, the language model policy  $\pi_{\theta}$  is also initialized to  $\pi^{\text{SFT}}$ . The added constraint is important, as it prevents the model from deviating too far from the distribution on which the reward model is accurate, as well as maintaining the generation diversity and preventing mode-collapse to single high-reward answers. Due to the discrete nature of language generation, this objective is not differentiable and is typically optimized with reinforcement learning. The standard approach [51, 40, 1, 28] has been to construct the reward function  $r(x, y) = r_{\phi}(x, y) - \beta(\log \pi_{\theta}(y | x) - \log \pi_{\text{ref}}(y | x))$ , and maximize using PPO [39].

미산적인

강화학습을 사용하는 이유  
Generation에서 샘플링 과정은 선택이기 때문에 미분이 불가능하므로 Optimum을 찾는게 불가능

강화학습은 선택(=Policy)를 찾는 학습법이므로, 샘플링을 학습시키는 방법이 되는 것

미분할 수 없는

## 4 Direct Preference Optimization

Motivated by the challenges of applying reinforcement learning algorithms on large-scale problems such as fine-tuning language models, our goal is to derive a simple approach for policy optimization using preferences directly. Unlike prior RLHF methods, which learn a reward and then optimize it via RL, our approach leverages a particular choice of reward model parameterization that enables extraction of its optimal policy in closed form, without an RL training loop. As we will describe next in detail, our key insight is to leverage an analytical mapping from reward functions to optimal policies, which enables us to transform a loss function over reward functions into a loss function over policies. This change-of-variables approach avoids fitting an explicit, standalone reward model, while still optimizing under existing models of human preferences, such as the Bradley-Terry model. In essence, the policy network represents both the language model and the (implicit) reward.

특정 reward 모델의 매개변수화를 활용하여 closed form으로 policy를 최적화할 수 있음

reward 함수의 Loss 함수를 Policy 함수의 Loss 함수로 변환함 이를 통해, 명시적인 reward 모델을 사용하지 않고 Policy를 최적화할 수 있음  
Policy 네트워크는 모델과 reward를 모두 표현하게 됨

**Deriving the DPO objective.** We start with the same RL objective as prior work, Eq. 3 under a general reward function  $r$ . Following prior work [31, 30, 19, 15], it is straightforward to show that the optimal solution to the KL-constrained reward maximization objective in Eq. 3 takes the form:

$$\pi_r(y | x) = \frac{1}{Z(x)} \pi_{\text{ref}}(y | x) \exp \left( \frac{1}{\beta} r(x, y) \right), \quad (4)$$

기존 연구에서 RL의 Optimal Policy는 4번 식과 같이 정의됨

where  $Z(x) = \sum_y \pi_{\text{ref}}(y | x) \exp \left( \frac{1}{\beta} r(x, y) \right)$  is the partition function. See Appendix A.1 for a complete derivation. Even if we use the MLE estimate  $r_{\phi}$  of the ground-truth reward function  $r^*$ , it is still expensive to estimate the partition function  $Z(x)$  [19, 15], which makes this representation hard to utilize in practice. However, we can rearrange Eq. 4 to express the reward function in terms of its corresponding optimal policy  $\pi_r$ , the reference policy  $\pi_{\text{ref}}$ , and the unknown partition function  $Z(\cdot)$ . Specifically, we first take the logarithm of both sides of Eq. 4 and then with some algebra we obtain:

ground-truth reward 함수를 얻었다고 가정해도,  $Z(x)$ 를 계산하는건 비용이 많이 들

따라서 5번식처럼 변형해서 사용해보자

$$r(x, y) = \beta \log \frac{\pi_r(y | x)}{\pi_{\text{ref}}(y | x)} + \beta \log Z(x). \quad (5)$$

We can apply this reparameterization to the ground-truth reward  $r^*$  and corresponding optimal model  $\pi^*$ . Fortunately, the Bradley-Terry model depends only on the difference of rewards between two completions, i.e.,  $p^*(y_1 \succ y_2 | x) = \sigma(r^*(x, y_1) - r^*(x, y_2))$ . Substituting the reparameterization in Eq. 5 for  $r^*(x, y)$  into the preference model Eq. 1 the partition function cancels, and we can express the human preference probability in terms of only the optimal policy  $\pi^*$  and reference policy  $\pi_{\text{ref}}$ . Thus, the optimal RLHF policy  $\pi^*$  under the Bradley-Terry model satisfies the preference model:

$$p^*(y_1 \succ y_2 | x) = \frac{1}{1 + \exp \left( \beta \log \frac{\pi^*(y_2 | x)}{\pi_{\text{ref}}(y_2 | x)} - \beta \log \frac{\pi^*(y_1 | x)}{\pi_{\text{ref}}(y_1 | x)} \right)} \quad (6)$$

5번식을 1번식에 대입

The derivation is in Appendix A.2. While Eq. 6 uses the Bradley-Terry model, we can similarly derive expressions under the more general Plackett-Luce models [32, 23], shown in Appendix A.3.

Now that we have the probability of human preference data in terms of the optimal policy rather than the reward model, we can formulate a maximum likelihood objective for a parametrized policy  $\pi_{\theta}$ . Analogous to the reward modeling approach (i.e. Eq. 2), our policy objective becomes:

유사한

$$\mathcal{L}_{\text{DPO}}(\pi_{\theta}; \pi_{\text{ref}}) = -\mathbb{E}_{(x, y_w, y_l) \sim \mathcal{D}} \left[ \log \sigma \left( \beta \log \frac{\pi_{\theta}(y_w | x)}{\pi_{\text{ref}}(y_w | x)} - \beta \log \frac{\pi_{\theta}(y_l | x)}{\pi_{\text{ref}}(y_l | x)} \right) \right]. \quad (7)$$

This way, we fit an implicit reward using an alternative parameterization, whose optimal policy is simply  $\pi_{\theta}$ . Moreover, since our procedure is equivalent to fitting a reparametrized Bradley-Terry

model, it enjoys certain theoretical properties, such as consistencies under suitable assumption of the preference data distribution [4]. In Section 5 we further discuss theoretical properties of DPO in relation to other works.

**What does the DPO update do?** For a mechanistic understanding of DPO, it is useful to analyze the gradient of the loss function  $\mathcal{L}_{\text{DPO}}$ . The gradient with respect to the parameters  $\theta$  can be written as:

$$\nabla_{\theta} \mathcal{L}_{\text{DPO}}(\pi_{\theta}; \pi_{\text{ref}}) = -\beta \mathbb{E}_{(x, y_w, y_l) \sim \mathcal{D}} \left[ \underbrace{\sigma(\hat{r}_{\theta}(x, y_l) - \hat{r}_{\theta}(x, y_w))}_{\text{higher weight when reward estimate is wrong}} \left[ \underbrace{\nabla_{\theta} \log \pi(y_w | x)}_{\text{increase likelihood of } y_w} - \underbrace{\nabla_{\theta} \log \pi(y_l | x)}_{\text{decrease likelihood of } y_l} \right] \right],$$

이 수식은, 암시적으로 언어모델의 Policy Theta와 Reference Policy로 정의된 Reward를 의미함

where  $\hat{r}_{\theta}(x, y) = \beta \log \frac{\pi_{\theta}(y|x)}{\pi_{\text{ref}}(y|x)}$  is the reward implicitly defined by the language model  $\pi_{\theta}$  and reference model  $\pi_{\text{ref}}$  (more in Section 5). Intuitively, the gradient of the loss function  $\mathcal{L}_{\text{DPO}}$  increases the likelihood of the preferred completions  $y_w$  and decreases the likelihood of dispreferred completions  $y_l$ . Importantly, the examples are weighed by how much higher the implicit reward model  $\hat{r}_{\theta}$  rates the dispreferred completions, scaled by  $\beta$ , i.e. how incorrectly the implicit reward model orders the completions, accounting for the strength of the KL constraint. Our experiments suggest the importance of this weighting, as a naïve version of this method without the weighting coefficient can cause the language model to degenerate (Appendix Table 3).

좀더 직관적으로 말하면, DPO의 Gradient는 y win의 확률을 높이고 y loss의 확률을 낮추는 것

Beta는 KLD 제한 내에서 어떻게 Reward 모델이 Generation할 것인지를 결정하는 것과 같음

**DPO outline.** The general DPO pipeline is as follows: 1) Sample completions  $y_1, y_2 \sim \pi_{\text{ref}}(\cdot | x)$  for every prompt  $x$ , label with human preferences to construct the offline dataset of preferences  $\mathcal{D} = \{x^{(i)}, y_w^{(i)}, y_l^{(i)}\}_{i=1}^N$  and 2) optimize the language model  $\pi_{\theta}$  to minimize  $\mathcal{L}_{\text{DPO}}$  for the given  $\pi_{\text{ref}}$  and  $\mathcal{D}$  and desired  $\beta$ . In practice, one would like to reuse preference datasets publicly available, rather than generating samples and gathering human preferences. Since the preference datasets are sampled using  $\pi^{\text{SFT}}$ , we initialize  $\pi_{\text{ref}} = \pi^{\text{SFT}}$  whenever available. However, when  $\pi^{\text{SFT}}$  is not available, we initialize  $\pi_{\text{ref}}$  by maximizing likelihood of preferred completions  $(x, y_w)$ , that is,  $\pi_{\text{ref}} = \arg \max_{\pi} \mathbb{E}_{x, y_w \sim \mathcal{D}} [\log \pi(y_w | x)]$ . This procedure helps mitigate the distribution shift between the true reference distribution which is unavailable, and  $\pi_{\text{ref}}$  used by DPO. Further details related to the implementation and hyperparameters can be found in Appendix B.

1) Reference Policy로부터 y1, y2를 샘플하고 Human Preference를 라벨링한다

2) 모델의 Policy theta를 Reference Policy로부터하여 DPO Loss 최소화해 구한다

학습은 공개된 Preference 데이터를 재사용하는게 효율적임

만약 SFT의 Policy를 못구한다면 => Unavailable한 true Reference 분포와 DPO에 사용되는 Reference Policy의 분포 미동을 완화시켜줌 즉, 학습으로 인한 분포 미동을 적게한단 얘기

## 5 Theoretical Analysis of DPO

In this section, we give further interpretation of the DPO method, provide theoretical backing, and relate advantages of DPO to issues with actor critic algorithms used for RLHF (such as PPO [39]).

### 5.1 Your Language Model Is Secretly a Reward Model

DPO는 명시적인 Reward 학습과 RL을 피해서 단일 MLE 목표를 통해 Policy를 최적화할 수 있는 방법임

DPO is able to bypass both fitting an explicit reward and performing RL to learn the policy using a single maximum likelihood objective. Note the optimization objective Eq. 5 is equivalent to a Bradley-Terry model with a reward parameterization  $r^*(x, y) = \beta \log \frac{\pi_{\theta}^*(y|x)}{\pi_{\text{ref}}(y|x)}$  and we optimize our parametric model  $\pi_{\theta}$ , equivalently to the reward model optimization in Eq. 2 under the change of variables. In this section we will build the theory behind this reparameterization, show that it does not constrain the class of learned reward models, and allows for the exact recovery of the optimal policy. We begin with by defining an equivalence relation between reward functions.

Eq.5는 Bradley-Terry 모델과 같이 Reward를 파라미터화함

그리고 DPO에서는 파라미터화된 모델의 Policy Theta를 최적화함 (Eq. 2와 같이 변수를 변환한 상태로)

이 섹션에서는 이러한 Reparameterization의 이론적 기반을 설명함

**Definition 1.** We say that two reward functions  $r(x, y)$  and  $r'(x, y)$  are equivalent iff  $r(x, y) - r'(x, y) = f(x)$  for some function  $f$ .

It is easy to see that this is indeed an equivalence relation, which partitions the set of reward functions into classes. We can state the following two lemmas:

**Lemma 1.** Under the Plackett-Luce, and in particular the Bradley-Terry, preference framework, two reward functions from the same class induce the same preference distribution.

**Lemma 2.** Two reward functions from the same equivalence class induce the same optimal policy under the constrained RL problem.

연기하다

The proofs are straightforward and we defer them to Appendix A.5. The first lemma is a well-known under-specification issue with the Plackett-Luce family of models [32]. Due to this under-specification,

we usually have to <sup>도입하다</sup>impose additional <sup>식별성</sup>identifiability constraints to achieve any guarantees on the MLE estimates from Eq. 2.4. The second lemma states that all reward functions from the same class yield the same optimal policy, hence for our final objective, we are only interested in recovering an arbitrary reward function from the optimal class. We prove the following Theorem in Appendix A.6

**Theorem 1.** *Under mild assumptions, all reward classes consistent with the Plackett-Luce (and Bradley-Terry in particular) models can be represented with the reparameterization  $r(x, y) = \beta \log \frac{\pi(y|x)}{\pi_{\text{ref}}(y|x)}$  for some model  $\pi(y | x)$  and a given reference model  $\pi_{\text{ref}}(y | x)$ .*

*Proof Sketch.* Consider any reward function  $r(x, y)$ , which induces a corresponding optimal model  $\pi_r(y | x)$ , specified by Eq. 4. We will show that a reward function from the equivalence class of  $r$  can be represented using the reparameterization given above. We define the projection  $f$  as

$$f(r; \pi_{\text{ref}}, \beta)(x, y) = r(x, y) - \beta \log \sum_y \pi_{\text{ref}}(y | x) \exp \left( \frac{1}{\beta} r(x, y) \right) \quad (8)$$

The operator  $f$  simply normalizes the reward function with the logarithm of the partition function of  $\pi_r$ . Since the added normalization term is only a function of the prefix  $x$ ,  $f(r; \pi_{\text{ref}}, \beta)(x, y)$  is a reward function in the equivalence class of  $r(x, y)$ . Finally, replacing  $r$  with the RHS of Eq. 5 (which holds for any reward function), we have  $f(r; \pi_{\text{ref}}, \beta)(x, y) = \beta \log \frac{\pi_r(y|x)}{\pi_{\text{ref}}(y|x)}$ . That is, the projection  $f$  produces a member of the equivalence class of  $r$  with the desired form, and we do not lose any generality in our reward model from the proposed reparameterization.  $\square$

We can alternatively view Theorem 1 as specifying exactly which reward function within each equivalence class the DPO reparameterization selects, that is, the reward function satisfying:

$$\sum_y \underbrace{\pi_{\text{ref}}(y | x) \exp \left( \frac{1}{\beta} r(x, y) \right)}_{=\pi(y|x), \text{ using Thm. 1 reparam.}} = 1, \quad (9)$$

i.e.,  $\pi(y | x)$  is a valid distribution (probabilities are positive and sum to 1). <sup>유도하다</sup>However, following Eq. 4, we can see that Eq. 9 is the partition function of the optimal policy <sup>유도하다</sup>induced by the reward function  $r(x, y)$ . The key insight of the DPO algorithm is that we can impose certain constraints on the under-constrained Plackett-Luce (and Bradley-Terry in particular) family of preference models, such that we preserve the class of representable reward models, but explicitly make the optimal policy in Eq. 4 analytically tractable for all prompts  $x$ .

## 5.2 <sup>불안정</sup>Instability of Actor-Critic Algorithms

We can also use our framework to diagnose instabilities with standard actor-critic algorithms used for the RLHF, such as PPO. We follow the RLHF pipeline and focus on the RL fine-tuning step outlined in Section 3. We can draw connections to the control as inference framework [22] for the constrained RL problem outlined in [3]. We assume a parameterized model  $\pi_\theta(y | x)$  and minimize  $\mathbb{D}_{\text{KL}}[\pi_\theta(y|x) || \pi^*(y | x)]$  where  $\pi^*$  is the optimal policy from Eq. 7 induced by the reward function  $r_\phi(y, x)$ . With some algebra this leads to the optimization objective:

$$\max_{\pi_\theta} \mathbb{E}_{\pi_\theta(y|x)} \left[ \underbrace{r_\phi(x, y) - \beta \log \sum_y \pi_{\text{ref}}(y | x) \exp \left( \frac{1}{\beta} r_\phi(x, y) \right)}_{f(r_\phi, \pi_{\text{ref}}, \beta)} - \underbrace{\beta \log \frac{\pi_\theta(y | x)}{\pi_{\text{ref}}(y | x)}}_{\text{KL}} \right] \quad (10)$$

This is the same objective optimized in prior works [51, 40, 1, 28] using the DPO-equivalent reward for the reward class of  $r_\phi$ . In this setting, we can interpret the normalization term in  $f(r_\phi, \pi_{\text{ref}}, \beta)$  as the soft value function of the reference policy  $\pi_{\text{ref}}$ . While this term does not affect the optimal solution, without it, the policy gradient of the objective could have high variance, making learning unstable. We can accommodate for the normalization term using a learned value function, but that can also be difficult to optimize. Alternatively, prior works have normalized rewards using a human completion baseline, essentially a single sample Monte-Carlo estimate of the normalizing term. In contrast the DPO reparameterization yields a reward function that does not require any baselines.




Figure 2: **Left.** The frontier of expected reward vs KL to the reference policy. DPO provides the highest expected reward for all KL values, demonstrating the quality of the optimization. **Right.** TL;DR summarization win rates vs. human-written summaries, using GPT-4 as evaluator. DPO exceeds PPO’s best-case performance on summarization, while being more robust to changes in the sampling temperature.

## 6 Experiments

In this section, we empirically evaluate DPO’s ability to train policies directly from preferences. First, in a well-controlled text-generation setting, we ask: how efficiently does DPO trade off maximizing reward and minimizing KL-divergence with the reference policy, compared to common preference learning algorithms such as PPO? Next, we evaluate DPO’s performance on larger models and more difficult RLHF tasks, including summarization and dialogue. We find that with almost no tuning of hyperparameters, DPO tends to perform as well or better than strong baselines like RLHF with PPO as well as returning the best of  $N$  sampled trajectories under a learned reward function. Before presenting these results, we describe the experimental set-up; additional details are in Appendix C.

**Tasks.** Our experiments explore three different open-ended text generation tasks. For all experiments, algorithms learn a policy from a dataset of preferences  $\mathcal{D} = \{x^{(i)}, y_w^{(i)}, y_l^{(i)}\}_{i=1}^N$ . In **controlled sentiment generation**,  $x$  is a prefix of a movie review from the IMDb dataset [24], and the policy must generate  $y$  with positive sentiment. In order to perform a controlled evaluation, for this experiment we generate preference pairs over generations using a pre-trained sentiment classifier, where  $p(\text{positive} \mid x, y_w) > p(\text{positive} \mid x, y_l)$ . For SFT, we fine-tune GPT-2-large until convergence on reviews from the train split of the IMDB dataset (further details in App C.1). In **summarization**,  $x$  is a forum post from Reddit; the policy must generate a summary  $y$  of the main points in the post. Following prior work, we use the Reddit TL;DR summarization dataset [43] along with human preferences gathered by Stiennon et al. We use an SFT model fine-tuned on human-written forum post summaries<sup>2</sup> with the TRLX [44] framework for RLHF. The human preference dataset was gathered by Stiennon et al. on samples from a different, but similarly-trained, SFT model. Finally, in **single-turn dialogue**,  $x$  is a human query, which may be anything from a question about astrophysics to a request for relationship advice. A policy must produce an engaging and helpful response  $y$  to a user’s query; we use the Anthropic Helpful and Harmless dialogue dataset [1], containing 170k dialogues between a human and an automated assistant. Each transcript ends with a pair of responses generated by a large (although unknown) language model along with a preference label denoting the human-preferred response. In this setting, no pre-trained SFT model is available; we therefore fine-tune an off-the-shelf language model on only the preferred completions to form the SFT model.

**Evaluation.** Our experiments use two different approaches to evaluation. In order to analyze the effectiveness of each algorithm in optimizing the constrained reward maximization objective, in the controlled sentiment generation setting we evaluate each algorithm by its frontier of achieved reward and KL-divergence from the reference policy; this frontier is computable because we have access to the ground-truth reward function (a sentiment classifier). However, in the real world, the ground truth reward function is not known; therefore, we evaluate algorithms with their win rate against a baseline policy, using GPT-4 as a proxy for human evaluation of summary quality and response helpfulness in the summarization and single-turn dialogue settings, respectively. For summarization, we use reference summaries in the test set as the baseline; for dialogue, we use the preferred response in the

**Sentiment Generation**  
IMDb 데이터셋에서 sentiment generation ভাল মিরি 학습된 Sentiment Classifier를 사용하여  $y_w$ 와  $y_l$ 를 분류하여 학습

**Summarization**  
Reddit의 데이터셋을 사용, 레딧의 TL;DR 요약 데이터 셋을 사용

**Single-turn dialogue**  
anthropic의 Helpful and Harmless dialogue 데이터셋을 사용함 이 경우, SFT 모델이 없어서 기본 언어모델을 Finetuning 하여 사용함

**Evaluation**  
2가지 방법이 사용됨  
1) ground-truth가 있는 경우 (Frontier Evaluation)  
reference 정책으로부터 KLD와 reward의 경계선을 통해 evaluate를 함 ground-truth가 있기 때문에 경계선을 계산할 수 있음  
2) ground-truth가 없는 경우 (Win rate)  
GPT-4로 부터 평가

<sup>2</sup>[https://huggingface.co/CarperAI/openai\\_summarize\\_tldr\\_sft](https://huggingface.co/CarperAI/openai_summarize_tldr_sft)






Figure 3: **Left.** Win rates computed by GPT-4 for Anthropic-HH one-step dialogue; DPO is the only method that improves over chosen summaries in the Anthropic-HH test set. **Right.** Win rates for different sampling temperatures over the course of training. DPO’s improvement over the dataset labels is fairly stable over the course of training for different sampling temperatures.

test dataset as the baseline. While existing studies suggest LMs can be better automated evaluators than existing metrics [10], we conduct a human study to justify our usage of GPT-4 for evaluation in Sec. 6.4. We find GPT-4 judgments **correlate** strongly with humans, with human agreement with GPT-4 typically similar or higher than inter-human annotator agreement.

**Methods.** In addition to DPO, we evaluate several existing approaches to training language models to adhere to human preferences. Most simply, we explore zero-shot prompting with **GPT-J** [45] in the summarization task and 2-shot prompting with **Pythia-2.8B** [3] in the dialogue task. In addition, we evaluate the **SFT** model as well as **Preferred-FT**, which is a model fine-tuned with supervised learning on the chosen completion  $y_w$  from either the SFT model (in controlled sentiment and summarization) or a generic LM (in single-turn dialogue). Another pseudo-supervised method is **Unlikelihood** [46], which simply optimizes the policy to maximize the probability assigned to  $y_w$  and minimize the probability assigned to  $y_l$ ; we use an optional coefficient  $\alpha \in [0, 1]$  on the ‘unlikelihood’ term. We also consider **PPO** [39] using a reward function learned from the preference data and **PPO-GT**, which is an oracle that learns from the ground truth reward function available in the controlled sentiment setting. In our sentiment experiments, we use two implementations of PPO-GT, one of-the-shelf version [44] as well as a modified version that normalizes rewards and further tunes hyperparameters to improve performance (we also use these modifications when running ‘normal’ PPO with learned rewards). Finally, we consider the **Best of  $N$**  baseline, sampling  $N$  responses from the SFT model (or Preferred-FT in dialogue) and returning the highest-scoring response according to a reward function learned from the preference dataset. This high-performing method decouples the quality of the reward model from the PPO optimization, but is computationally impractical even for moderate  $N$  as it requires sampling  $N$  completions for every query at test time.

다양한 기존 방법과 비교  
Zero-shot  
Few-shot  
SFT  
Preferred-FT  
(선호 응답으로 튜닝)  
Unlikelihood  
( $y_w$ 를 최대화,  $y_l$ 를 최소화  
unlikelihood 항목에 가중치 사용)  
PPO  
PPO-GT  
(ground-truth 보상함수로  
학습된 PPO)

## 6.1 How well can DPO optimize the RLHF objective?

The KL-constrained reward maximization objective used in typical RLHF algorithms balances exploitation of reward while restricting the policy from deviating far from the reference policy. Therefore, when comparing algorithms, we must **take into** account both reward achieved as well as the KL discrepancy; achieving slightly higher reward but with much higher KL is not necessarily desirable. Figure 2 shows the reward-KL frontier for various algorithms in the sentiment setting. We execute multiple training runs for each algorithm, using a different hyperparameter for policy conservativeness in each run (target  $KL \in \{3, 6, 9, 12\}$  for PPO,  $\beta \in \{0.05, 0.1, 1, 5\}$ ,  $\alpha \in \{0.05, 0.1, 0.5, 1\}$  for unlikelihood, random seeds for preferred-FT). This sweep includes 22 runs in total. After each 100 training steps until convergence, we evaluate each policy on a set of test prompts, computing the average reward under the true reward function as well as the average sequence-level KL<sup>3</sup> with the reference policy  $KL(\pi \parallel \pi_{ref})$ . We find that DPO produces by far the most efficient frontier, achieving the highest reward while still achieving low KL. This result is particularly notable for multiple reasons. First, DPO and PPO optimize the same objective, but DPO is notably more efficient;

DPO를 RLHF 목적에 맞게  
평가하려면, Reward도 높아야  
하고, KLD 도 높으면 안됨

<sup>3</sup>That is, the sum of the per-timestep KL-divergences.



DPO’s reward/KL tradeoff strictly dominates PPO. Second, DPO achieves a better frontier than PPO, even when PPO can access ground truth rewards (PPO-GT).

## 6.2 Can DPO scale to real preference datasets?

대충 DPO 성능이 좋다는 얘기

ROUGE같은 자동화 메트릭은 Human Preference가 낮게나올 수 있음

Next, we evaluate fine-tuning performance of DPO on summarization and single-turn dialogue. For summarization, automatic evaluation metrics such as ROUGE can be poorly correlated with human preferences [40], and prior work has found that fine-tuning LMs using PPO on human preferences to provide more effective summaries. We evaluate different methods by sampling completions on the test split of TL;DR summarization dataset, and computing the average win rate against reference completions in the test set. The completions for all methods are sampled at temperatures varying from 0.0 to 1.0, and the win rates are shown in Figure 2 (right). DPO, PPO and Preferred-FT all fine-tune the same GPT-J SFT model [4]. We find that DPO has a win rate of approximately 61% at a temperature of 0.0, exceeding the performance of PPO at 57% at its optimal sampling temperature of 0.0. DPO also achieves a higher maximum win rate compared to the best of  $N$  baseline. We note that we did not meaningfully tune DPO’s  $\beta$  hyperparameter, so these results may underestimate DPO’s potential. Moreover, we find DPO to be much more robust to the sampling temperature than PPO, the performance of which can degrade to that of the base GPT-J model at high temperatures. Preferred-FT does not improve significantly over the SFT model. We also compare DPO and PPO head-to-head in human evaluations in Section 6.4 where DPO samples at temperature 0.25 were preferred 58% times over PPO samples at temperature 0.

On single-turn dialogue, we evaluate the different methods on the subset of the test split of the Anthropic HH dataset [1] with one step of human-assistant interaction. GPT-4 evaluations use the preferred completions on the test as the reference to compute the win rate for different methods. As there is no standard SFT model for this task, we start with a pre-trained Pythia-2.8B, use Preferred-FT to train a reference model on the chosen completions such that completions are within distribution of the model, and then train using DPO. We also compare against the best of 128 Preferred-FT completions (we found the Best of  $N$  baseline plateaus at 128 completions for this task; see Appendix Figure 4) and a 2-shot prompted version of the Pythia-2.8B base model, finding DPO performs as well or better for the best-performing temperatures for each method. We also evaluate an RLHF model trained with PPO on the Anthropic HH dataset [5] from a well-known source [6] but are unable to find a prompt or sampling temperature that gives performance better than the base Pythia-2.8B model. Based on our results from TL;DR and the fact that both methods optimize the same reward function, we consider Best of 128 a rough proxy for PPO-level performance. Overall, DPO is the only computationally efficient method that improves over the preferred completions in the Anthropic HH dataset, and provides similar or better performance to the computationally demanding Best of 128 baseline. Finally, Figure 3 shows that DPO converges to its best performance relatively quickly.

## 6.3 Generalization to a new input distribution

대충 다른 새로운 데이터를 넣어도 DPO 성능이 좋다는 얘기

To further compare the performance of PPO and DPO under distribution shifts, we evaluate the PPO and DPO policies from our Reddit TL;DR summarization experiment on a different distribution, news articles in the test split of the CNN/DailyMail dataset [26], using the best sampling temperatures from TL;DR (0 and 0.25). The results are presented in Table 1. We computed the GPT-4 win rate against the ground-truth summaries in the datasets, using the same GPT-4 (C) prompt we used for Reddit TL;DR, but replacing the words “forum post” with “news article”. For this new distribution, DPO continues to outperform the PPO policy by a significant margin. This experiment provides initial evidence that DPO policies can generalize similarly well to PPO policies, even though DPO does not use the additional unlabeled Reddit TL;DR prompts that PPO uses.

Alg.	Win rate vs. ground truth	
	Temp 0	Temp 0.25
DPO	0.36	0.31
PPO	0.26	0.23

Table 1: GPT-4 win rates vs. ground truth summaries for out-of-distribution CNN/DailyMail input articles.

[https://huggingface.co/CarperAI/openai\\_summarize\\_tldr\\_sft](https://huggingface.co/CarperAI/openai_summarize_tldr_sft)

[https://huggingface.co/CarperAI/ppo\\_hh\\_pythia-6B](https://huggingface.co/CarperAI/ppo_hh_pythia-6B)

<https://github.com/CarperAI/trlx/tree/main/examples/hh>

#### 6.4 Validating GPT-4 judgments with human judgments GPT-4를 Preference의 judgement로 사용해도 충분히 의미 있음

We conduct a human study to verify the reliability of GPT-4’s judgments, using the results of the TL;DR summarization experiment and two different GPT-4 prompts. The **GPT-4 (S)** (simple) prompt simply asks for which summary better-summarizes the important information in the post. The **GPT-4 (C)** (concise) prompt also asks for which summary is more concise; we evaluate this prompt because we find that GPT-4 prefers longer, more repetitive summaries than humans do with the **GPT-4 (S)** prompt. See Appendix [C.2](#) for the complete prompts. We perform three comparisons, using the highest (DPO, temp. 0.25), the lowest (PPO, temp. 1.0), and a middle-performing (SFT, temp. 0.25) method with the aim of covering a diversity of sample qualities; all three methods are compared against greedily-sampled PPO (its best-performing temperature). We find that with both prompts, GPT-4 tends to agree with humans about as often as humans agree with each other, suggesting that GPT-4 is a reasonable proxy for human evaluations (due to limited human raters, we only collect multiple human judgments for the DPO and PPO-1 comparisons). Overall, the **GPT-4 (C)** prompt generally provides win rates more representative of humans; we therefore use this prompt for the main results in Section [6.2](#). For additional details about the human study, including the web interface presented to raters and the list of human volunteers, see Appendix [D.3](#).

	DPO	SFT	PPO-1
N respondents	272	122	199
GPT-4 (S) win %	47	27	13
GPT-4 (C) win %	54	32	12
Human win %	58	43	17
GPT-4 (S)-H agree	70	77	86
GPT-4 (C)-H agree	67	79	85
H-H agree	65	-	87

Table 2: Comparing human and GPT-4 win rates and per-judgment agreement on TL;DR summarization samples. **Humans agree with GPT-4 about as much as they agree with each other.** Each experiment compares a summary from the stated method with a summary from PPO with temperature 0.

## 7 Discussion

Learning from preferences is a powerful, scalable framework for training capable, aligned language models. We have introduced DPO, a simple training paradigm for training language models from preferences without reinforcement learning. Rather than **coercing** the preference learning problem into a standard RL setting in order to use off-the-shelf RL algorithms, DPO identifies a **mapping between language model policies and reward functions** that enables training a language model to satisfy human preferences *directly*, with a simple cross-entropy loss, without reinforcement learning or loss of generality. With virtually no tuning of hyperparameters, DPO performs similarly or better than existing RLHF algorithms, including those based on PPO; DPO thus meaningfully reduces the barrier to training more language models from human preferences.

강제하다

요약  
DPO는 LM의 Policy와  
Reward Function을 맵핑함

이는 Cross Entropy Loss로  
LM이 Human Preference를  
직접 학습할 수 있게함

**Limitations & Future Work.** Our results raise several important questions for future work. How does the DPO policy generalize out of distribution, compared with learning from an explicit reward function? Our initial results suggest that DPO policies can generalize similarly to PPO-based models, but more comprehensive study is needed. For example, can training with self-labeling from the DPO policy similarly make effective use of unlabeled prompts? On another front, how does reward over-optimization manifest in the direct preference optimization setting, and is the slight decrease in performance in Figure [3](#) right an instance of it? Additionally, while we evaluate models up to 6B parameters, exploration of scaling DPO to state-of-the-art models orders of magnitude larger is an exciting direction for future work. Regarding evaluations, we find that the win rates computed by GPT-4 are impacted by the prompt; future work may study the best way to elicit high-quality judgments from automated systems. Finally, many possible applications of DPO exist beyond training language models from human preferences, including training generative models in other modalities.

## Acknowledgements

EM gratefully acknowledges funding from a Knight-Hennessy Graduate Fellowship. CF and CM are CIFAR Fellows. This work was supported in part by the Stanford Accelerator for Learning (SAL) and Stanford Institute for Human-Centered Artificial Intelligence (HAI) *Generative AI for the Future of Learning* seed grant program. The Stanford Center for Research on Foundation Models (CRFM) provided part of the compute resources used for the experiments in this work. This work was supported in part by ONR grant N00014-20-1-2675.

## References

- [1] Y. Bai, A. Jones, K. Ndousse, A. Askell, A. Chen, N. DasSarma, D. Drain, S. Fort, D. Ganguli, T. Henighan, N. Joseph, S. Kadavath, J. Kernion, T. Conerly, S. El-Showk, N. Elhage, Z. Hatfield-Dodds, D. Hernandez, T. Hume, S. Johnston, S. Kravec, L. Lovitt, N. Nanda, C. Olsson, D. Amodei, T. Brown, J. Clark, S. McCandlish, C. Olah, B. Mann, and J. Kaplan. Training a helpful and harmless assistant with reinforcement learning from human feedback, 2022.
- [2] Y. Bai, S. Kadavath, S. Kundu, A. Askell, J. Kernion, A. Jones, A. Chen, A. Goldie, A. Mirhoseini, C. McKinnon, C. Chen, C. Olsson, C. Olah, D. Hernandez, D. Drain, D. Ganguli, D. Li, E. Tran-Johnson, E. Perez, J. Kerr, J. Mueller, J. Ladish, J. Landau, K. Ndousse, K. Lukosuite, L. Lovitt, M. Sellitto, N. Elhage, N. Schiefer, N. Mercado, N. DasSarma, R. Lasenby, R. Larson, S. Ringer, S. Johnston, S. Kravec, S. E. Showk, S. Fort, T. Lanham, T. Telleen-Lawton, T. Conerly, T. Henighan, T. Hume, S. R. Bowman, Z. Hatfield-Dodds, B. Mann, D. Amodei, N. Joseph, S. McCandlish, T. Brown, and J. Kaplan. Constitutional ai: Harmlessness from ai feedback, 2022.
- [3] S. Biderman, H. Schoelkopf, Q. Anthony, H. Bradley, K. O’Brien, E. Hallahan, M. A. Khan, S. Purohit, U. S. Prashanth, E. Raff, A. Skowron, L. Sutawika, and O. van der Wal. Pythia: A suite for analyzing large language models across training and scaling, 2023.
- [4] H. Bong and A. Rinaldo. Generalized results for the existence and consistency of the MLE in the Bradley-Terry-Luce model. *International Conference on Machine Learning*, 2022. arXiv:2110.11487.
- [5] R. A. Bradley and M. E. Terry. Rank analysis of incomplete block designs: I. the method of paired comparisons. *Biometrika*, 39(3/4):324–345, 1952. doi: <https://doi.org/10.2307/2334029>.
- [6] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, S. Agarwal, A. Herbert-Voss, G. Krueger, T. Henighan, R. Child, A. Ramesh, D. Ziegler, J. Wu, C. Winter, C. Hesse, M. Chen, E. Sigler, M. Litwin, S. Gray, B. Chess, J. Clark, C. Berner, S. McCandlish, A. Radford, I. Sutskever, and D. Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc., 2020. URL [https://proceedings.neurips.cc/paper\\_files/paper/2020/file/1457c0d6bfc4967418bfb8ac142f64a-Paper.pdf](https://proceedings.neurips.cc/paper_files/paper/2020/file/1457c0d6bfc4967418bfb8ac142f64a-Paper.pdf).
- [7] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.
- [8] S. Bubeck, V. Chandrasekaran, R. Eldan, J. Gehrke, E. Horvitz, E. Kamar, P. Lee, Y. T. Lee, Y. Li, S. Lundberg, H. Nori, H. Palangi, M. T. Ribeiro, and Y. Zhang. Sparks of artificial general intelligence: Early experiments with GPT-4, 2023. arXiv preprint arXiv:2303.12712.
- [9] R. Busa-Fekete, B. Szörényi, P. Weng, W. Cheng, and E. Hüllermeier. Preference-based reinforcement learning: evolutionary direct policy search using a preference-based racing algorithm. *Machine Learning*, 97(3):327–351, July 2014. doi: 10.1007/s10994-014-5458-8. URL <https://doi.org/10.1007/s10994-014-5458-8>.
- [10] Y. Chen, R. Wang, H. Jiang, S. Shi, and R.-L. Xu. Exploring the use of large language models for reference-free text quality evaluation: A preliminary empirical study. *ArXiv*, abs/2304.00723, 2023.
- [11] A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H. W. Chung, C. Sutton, S. Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.
- [12] P. F. Christiano, J. Leike, T. Brown, M. Martic, S. Legg, and D. Amodei. Deep reinforcement learning from human preferences. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL [https://proceedings.neurips.cc/paper\\_files/paper/2017/file/d5e2c0adad503c91f91df240d0cd4e49-Paper.pdf](https://proceedings.neurips.cc/paper_files/paper/2017/file/d5e2c0adad503c91f91df240d0cd4e49-Paper.pdf).

- [13] H. W. Chung, L. Hou, S. Longpre, B. Zoph, Y. Tay, W. Fedus, Y. Li, X. Wang, M. Dehghani, S. Brahma, A. Webson, S. S. Gu, Z. Dai, M. Suzgun, X. Chen, A. Chowdhery, A. Castro-Ros, M. Pellat, K. Robinson, D. Valter, S. Narang, G. Mishra, A. Yu, V. Zhao, Y. Huang, A. Dai, H. Yu, S. Petrov, E. H. Chi, J. Dean, J. Devlin, A. Roberts, D. Zhou, Q. V. Le, and J. Wei. Scaling instruction-finetuned language models, 2022.
- [14] M. Dudík, K. Hofmann, R. E. Schapire, A. Slivkins, and M. Zoghi. Contextual dueling bandits. In P. Grünwald, E. Hazan, and S. Kale, editors, *Proceedings of The 28th Conference on Learning Theory*, volume 40 of *Proceedings of Machine Learning Research*, pages 563–587, Paris, France, 03–06 Jul 2015. PMLR. URL <https://proceedings.mlr.press/v40/Dudik15.html>
- [15] D. Go, T. Korbak, G. Kruszewski, J. Rozen, N. Ryu, and M. Dymetman. Aligning language models with preferences through f-divergence minimization. In *Proceedings of the 40th International Conference on Machine Learning, ICML’23*. JMLR.org, 2023.
- [16] A. Jain, B. Wojcik, T. Joachims, and A. Saxena. Learning trajectory preferences for manipulators via iterative improvement. In C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 26. Curran Associates, Inc., 2013. URL [https://proceedings.neurips.cc/paper\\_files/paper/2013/file/c058f544c737782deacefa532d9add4c-Paper.pdf](https://proceedings.neurips.cc/paper_files/paper/2013/file/c058f544c737782deacefa532d9add4c-Paper.pdf)
- [17] N. Jaques, S. Gu, D. Bahdanau, J. M. Hernández-Lobato, R. E. Turner, and D. Eck. Sequence tutor: Conservative fine-tuning of sequence generation models with kl-control. In *International Conference on Machine Learning*, pages 1645–1654. PMLR, 2017.
- [18] N. Jaques, J. H. Shen, A. Ghandeharioun, C. Ferguson, A. Lapedriza, N. Jones, S. S. Gu, and R. Picard. Human-centric dialog training via offline reinforcement learning. *arXiv preprint arXiv:2010.05848*, 2020.
- [19] T. Korbak, H. Elsahar, G. Kruszewski, and M. Dymetman. On reinforcement learning and distribution matching for fine-tuning language models with no catastrophic forgetting. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh, editors, *Advances in Neural Information Processing Systems*, volume 35, pages 16203–16220. Curran Associates, Inc., 2022. URL [https://proceedings.neurips.cc/paper\\_files/paper/2022/file/67496dfa96afddab795530cc7c69b57a-Paper-Conference.pdf](https://proceedings.neurips.cc/paper_files/paper/2022/file/67496dfa96afddab795530cc7c69b57a-Paper-Conference.pdf)
- [20] J. Kreutzer, J. Uyheng, and S. Riezler. Reliability and learnability of human bandit feedback for sequence-to-sequence reinforcement learning. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1777–1788, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1165. URL <https://aclanthology.org/P18-1165>
- [21] A. Kupcsik, D. Hsu, and W. S. Lee. *Learning Dynamic Robot-to-Human Object Handover from Human Feedback*, pages 161–176. Springer International Publishing, 01 2018. ISBN 978-3-319-51531-1. doi: 10.1007/978-3-319-51532-8\_10.
- [22] S. Levine. Reinforcement learning and control as probabilistic inference: Tutorial and review, 2018.
- [23] R. D. Luce. Individual choice behavior: A theoretical analysis. *Courier Corporation*, 2012.
- [24] A. L. Maas, R. E. Daly, P. T. Pham, D. Huang, A. Y. Ng, and C. Potts. Learning word vectors for sentiment analysis. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pages 142–150, Portland, Oregon, USA, June 2011. Association for Computational Linguistics. URL <http://www.aclweb.org/anthology/P11-1015>
- [25] S. Mishra, D. Khashabi, C. Baral, and H. Hajishirzi. Cross-task generalization via natural language crowdsourcing instructions. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3470–3487, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-long.244. URL <https://aclanthology.org/2022.acl-long.244>



- [26] R. Nallapati, B. Zhou, C. dos Santos, Ç. Gulçehre, and B. Xiang. Abstractive text summarization using sequence-to-sequence RNNs and beyond. In *Proceedings of the 20th SIGNLL Conference on Computational Natural Language Learning*, pages 280–290, Berlin, Germany, Aug. 2016. Association for Computational Linguistics. doi: 10.18653/v1/K16-1028. URL <https://aclanthology.org/K16-1028>.
- [27] D. Narayanan, M. Shoeybi, J. Casper, P. LeGresley, M. Patwary, V. Korthikanti, D. Vainbrand, P. Kashinkunti, J. Bernauer, B. Catanzaro, A. Phanishayee, and M. Zaharia. Efficient large-scale language model training on gpu clusters using megatron-lm. In *Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis, SC '21*, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450384421. doi: 10.1145/3458817.3476209. URL <https://doi.org/10.1145/3458817.3476209>.
- [28] L. Ouyang, J. Wu, X. Jiang, D. Almeida, C. Wainwright, P. Mishkin, C. Zhang, S. Agarwal, K. Slama, A. Ray, J. Schulman, J. Hilton, F. Kelton, L. Miller, M. Simens, A. Askell, P. Welinder, P. F. Christiano, J. Leike, and R. Lowe. Training language models to follow instructions with human feedback. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh, editors, *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744. Curran Associates, Inc., 2022. URL [https://proceedings.neurips.cc/paper\\_files/paper/2022/file/b1efde53be364a73914f58805a001731-Paper-Conference.pdf](https://proceedings.neurips.cc/paper_files/paper/2022/file/b1efde53be364a73914f58805a001731-Paper-Conference.pdf).
- [29] R. Paulus, C. Xiong, and R. Socher. A deep reinforced model for abstractive summarization. In *International Conference on Learning Representations*, 2018. URL <https://openreview.net/forum?id=HkAClQgA->.
- [30] X. B. Peng, A. Kumar, G. Zhang, and S. Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *arXiv preprint arXiv:1910.00177*, 2019.
- [31] J. Peters and S. Schaal. Reinforcement learning by reward-weighted regression for operational space control. In *Proceedings of the 24th international conference on Machine learning*, pages 745–750, 2007.
- [32] R. L. Plackett. The analysis of permutations. *Journal of the Royal Statistical Society. Series C (Applied Statistics)*, 24(2):193–202, 1975. doi: <https://doi.org/10.2307/2346567>.
- [33] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, and I. Sutskever. Language models are unsupervised multitask learners, 2019. Ms., OpenAI.
- [34] R. Ramamurthy, P. Ammanabrolu, K. Brantley, J. Hessel, R. Sifa, C. Bauckhage, H. Hajishirzi, and Y. Choi. Is reinforcement learning (not) for natural language processing: Benchmarks, baselines, and building blocks for natural language policy optimization. In *The Eleventh International Conference on Learning Representations*, 2023. URL <https://openreview.net/forum?id=8aHzds2uUyB>.
- [35] M. Ranzato, S. Chopra, M. Auli, and W. Zaremba. Sequence level training with recurrent neural networks. *CoRR*, abs/1511.06732, 2015.
- [36] D. Sadigh, A. D. Dragan, S. Sastry, and S. A. Seshia. Active preference-based learning of reward functions. In *Robotics: Science and Systems (RSS)*, 2017.
- [37] A. Saha, A. Pacchiano, and J. Lee. Dueling rl: Reinforcement learning with trajectory preferences. In F. Ruiz, J. Dy, and J.-W. van de Meent, editors, *Proceedings of The 26th International Conference on Artificial Intelligence and Statistics*, volume 206 of *Proceedings of Machine Learning Research*, pages 6263–6289. PMLR, 25–27 Apr 2023. URL <https://proceedings.mlr.press/v206/saha23a.html>.
- [38] V. Sanh, A. Webson, C. Raffel, S. Bach, L. Sutawika, Z. Alyafeai, A. Chaffin, A. Stiegler, A. Raja, M. Dey, M. S. Bari, C. Xu, U. Thakker, S. S. Sharma, E. Szczechla, T. Kim, G. Chhablani, N. Nayak, D. Datta, J. Chang, M. T.-J. Jiang, H. Wang, M. Manica, S. Shen, Z. X. Yong, H. Pandey, R. Bawden, T. Wang, T. Neeraj, J. Rozen, A. Sharma, A. Santilli, T. Fevry, J. A. Fries, R. Teehan, T. L. Scao, S. Biderman, L. Gao, T. Wolf, and A. M. Rush. Multi-task prompted training enables zero-shot task generalization. In *International Conference on Learning Representations*, 2022. URL <https://openreview.net/forum?id=9Vrb9DOWI4>.

- [39] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms, 2017.
- [40] N. Stiennon, L. Ouyang, J. Wu, D. M. Ziegler, R. Lowe, C. Voss, A. Radford, D. Amodei, and P. Christiano. Learning to summarize from human feedback, 2022.
- [41] R. Thoppilan, D. D. Freitas, J. Hall, N. Shazeer, A. Kulshreshtha, H.-T. Cheng, A. Jin, T. Bos, L. Baker, Y. Du, Y. Li, H. Lee, H. S. Zheng, A. Ghafouri, M. Menegali, Y. Huang, M. Krikun, D. Lepikhin, J. Qin, D. Chen, Y. Xu, Z. Chen, A. Roberts, M. Bosma, V. Zhao, Y. Zhou, C.-C. Chang, I. Krivokon, W. Rusch, M. Pickett, P. Srinivasan, L. Man, K. Meier-Hellstern, M. R. Morris, T. Doshi, R. D. Santos, T. Duke, J. Soraker, B. Zevenbergen, V. Prabhakaran, M. Diaz, B. Hutchinson, K. Olson, A. Molina, E. Hoffman-John, J. Lee, L. Aroyo, R. Rajakumar, A. Butryna, M. Lamm, V. Kuzmina, J. Fenton, A. Cohen, R. Bernstein, R. Kurzweil, B. Aguera-Arcas, C. Cui, M. Croak, E. Chi, and Q. Le. Lamda: Language models for dialog applications, 2022.
- [42] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.
- [43] M. Völske, M. Potthast, S. Syed, and B. Stein. TL;DR: Mining Reddit to learn automatic summarization. In *Proceedings of the Workshop on New Frontiers in Summarization*, pages 59–63, Copenhagen, Denmark, Sept. 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-4508. URL <https://aclanthology.org/W17-4508>
- [44] L. von Werra, J. Tow, reciprocated, S. Matiana, A. Havrilla, cat state, L. Castricato, Alan, D. V. Phung, A. Thakur, A. Bukhtiyarov, aaronmm, F. Milo, Daniel, D. King, D. Shin, E. Kim, J. Wei, M. Romero, N. Pochinkov, O. Sanseviero, R. Adithyan, S. Siu, T. Simonini, V. Blagojevic, X. Song, Z. Witten, alexandremuzio, and crumb. CarperAI/trlx: v0.6.0: LLaMa (Alpaca), Benchmark Util, T5 ILQL, Tests, Mar. 2023. URL <https://doi.org/10.5281/zenodo.7790115>.
- [45] B. Wang and A. Komatsuzaki. GPT-J-6B: A 6 Billion Parameter Autoregressive Language Model. <https://github.com/kingoflolz/mesh-transformer-jax>, May 2021.
- [46] S. Welleck, I. Kulikov, S. Roller, E. Dinan, K. Cho, and J. Weston. Neural text generation with unlikelihood training. *arXiv preprint arXiv:1908.04319*, 2019.
- [47] R. J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Mach. Learn.*, 8(3–4):229–256, may 1992. ISSN 0885-6125. doi: 10.1007/BF00992696. URL <https://doi.org/10.1007/BF00992696>
- [48] Y. Wu and B. Hu. Learning to extract coherent summary via deep reinforcement learning. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence and Thirtieth Innovative Applications of Artificial Intelligence Conference and Eighth AAAI Symposium on Educational Advances in Artificial Intelligence*, AAAI’18/IAAI’18/EAAI’18. AAAI Press, 2018. ISBN 978-1-57735-800-8.
- [49] X. Yan, C. Luo, C. L. A. Clarke, N. Craswell, E. M. Voorhees, and P. Castells. Human preferences as dueling bandits. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR ’22, page 567–577, New York, NY, USA, 2022. Association for Computing Machinery. ISBN 9781450387323. doi: 10.1145/3477495.3531991. URL <https://doi.org/10.1145/3477495.3531991>
- [50] Y. Yue, J. Broder, R. Kleinberg, and T. Joachims. The k-armed dueling bandits problem. *Journal of Computer and System Sciences*, 78(5):1538–1556, 2012. ISSN 0022-0000. doi: <https://doi.org/10.1016/j.jcss.2011.12.028>. URL <https://www.sciencedirect.com/science/article/pii/S0022000012000281> JCSS Special Issue: Cloud Computing 2011.
- [51] D. M. Ziegler, N. Stiennon, J. Wu, T. B. Brown, A. Radford, D. Amodei, P. Christiano, and G. Irving. Fine-tuning language models from human preferences, 2020.

## Author Contributions

**All authors** provided valuable contributions to designing, analyzing, and iterating on experiments, writing and editing the paper, and generally managing the project’s progress.

**RR** proposed using autoregressive reward models in discussions with **EM**; derived the DPO objective; proved the theoretical properties of the algorithm and wrote the relevant sections and appendices. He also suggested and helped with organizing experiments and contributed some of the PPO and reward learning baselines.

**AS** initiated the discussion on using weighted regression methods as an alternative to PPO; initiated project-related organization, wrote initial analysis connecting DPO with weighted regression and unlikelihood; design and iterations of DPO + baseline implementations, initial exploratory experiments for DPO; substantial experiment organization and design (datasets, baselines, evaluation); led model training and evaluation for controlled sentiment generation and summarization; design iterations for GPT-4 evaluation (particularly summarization); substantial writing contributions to abstract, prelims/method and experiments; editing contributions to other sections.

**EM** provided input on early discussions on learning autoregressive reward functions; wrote the first implementation of DPO and ran the first DPO experiments; trained the large-scale (summarization and dialogue) DPO models used in paper experiments; conducted initial GPT-4 win rate evaluations and set up related infrastructure; recruited participants for, conducted, and analyzed results from the human study; wrote the abstract, introduction, related work, discussion, and most of experiments; and assisted with editing the rest of the paper.

**CF, CM, & SE** supervised the research, suggested ideas and experiments, and assisted in writing the paper.

## A Mathematical Derivations

### A.1 Deriving the Optimum of the KL-Constrained Reward Maximization Objective

In this appendix, we will derive Eq. 4. Analogously to Eq. 3, we optimize the following objective:

$$\max_{\pi} \mathbb{E}_{x \sim \mathcal{D}, y \sim \pi} [r(x, y)] - \beta \mathbb{D}_{\text{KL}} [\pi(y|x) || \pi_{\text{ref}}(y|x)] \quad (11)$$

under any reward function  $r(x, y)$ , reference model  $\pi_{\text{ref}}$  and a general non-parametric policy class. We now have:

$$\begin{aligned} & \max_{\pi} \mathbb{E}_{x \sim \mathcal{D}, y \sim \pi} [r(x, y)] - \beta \mathbb{D}_{\text{KL}} [\pi(y|x) || \pi_{\text{ref}}(y|x)] \\ &= \max_{\pi} \mathbb{E}_{x \sim \mathcal{D}} \mathbb{E}_{y \sim \pi(y|x)} \left[ r(x, y) - \beta \log \frac{\pi(y|x)}{\pi_{\text{ref}}(y|x)} \right] \\ &= \min_{\pi} \mathbb{E}_{x \sim \mathcal{D}} \mathbb{E}_{y \sim \pi(y|x)} \left[ \log \frac{\pi(y|x)}{\pi_{\text{ref}}(y|x)} - \frac{1}{\beta} r(x, y) \right] \\ &= \min_{\pi} \mathbb{E}_{x \sim \mathcal{D}} \mathbb{E}_{y \sim \pi(y|x)} \left[ \log \frac{\pi(y|x)}{\frac{1}{Z(x)} \pi_{\text{ref}}(y|x) \exp \left( \frac{1}{\beta} r(x, y) \right)} - \log Z(x) \right] \end{aligned} \quad (12)$$

where we have partition function:

$$Z(x) = \sum_y \pi_{\text{ref}}(y|x) \exp \left( \frac{1}{\beta} r(x, y) \right).$$

Note that the partition function is a function of only  $x$  and the reference policy  $\pi_{\text{ref}}$ , but does not depend on the policy  $\pi$ . We can now define

$$\pi^*(y|x) = \frac{1}{Z(x)} \pi_{\text{ref}}(y|x) \exp \left( \frac{1}{\beta} r(x, y) \right),$$

which is a valid probability distribution as  $\pi^*(y|x) \geq 0$  for all  $y$  and  $\sum_y \pi^*(y|x) = 1$ . Since  $Z(x)$  is not a function of  $y$ , we can then re-organize the final objective in Eq. 12 as:

$$\min_{\pi} \mathbb{E}_{x \sim \mathcal{D}} \left[ \mathbb{E}_{y \sim \pi(y|x)} \left[ \log \frac{\pi(y|x)}{\pi^*(y|x)} \right] - \log Z(x) \right] = \quad (13)$$

$$\min_{\pi} \mathbb{E}_{x \sim \mathcal{D}} [\mathbb{D}_{\text{KL}}(\pi(y|x) \parallel \pi^*(y|x)) - \log Z(x)] \quad (14)$$

Now, since  $Z(x)$  does not depend on  $\pi$ , the minimum is achieved by the policy that minimizes the first KL term. Gibbs' inequality tells us that the KL-divergence is minimized at 0 if and only if the two distributions are identical. Hence we have the optimal solution:

$$\pi(y|x) = \pi^*(y|x) = \frac{1}{Z(x)} \pi_{\text{ref}}(y|x) \exp \left( \frac{1}{\beta} r(x, y) \right) \quad (15)$$

for all  $x \in \mathcal{D}$ . This completes the derivation.

## A.2 Deriving the DPO Objective Under the Bradley-Terry Model

It is straightforward to derive the DPO objective under the Bradley-Terry preference model as we have

$$p^*(y_1 \succ y_2|x) = \frac{\exp(r^*(x, y_1))}{\exp(r^*(x, y_1)) + \exp(r^*(x, y_2))} \quad (16)$$

In Section 4 we showed that we can express the (unavailable) ground-truth reward through its corresponding optimal policy:

$$r^*(x, y) = \beta \log \frac{\pi^*(y|x)}{\pi_{\text{ref}}(y|x)} + \beta \log Z(x) \quad (17)$$

Substituting Eq. 17 into Eq. 16 we obtain:

$$\begin{aligned} p^*(y_1 \succ y_2|x) &= \frac{\exp \left( \beta \log \frac{\pi^*(y_1|x)}{\pi_{\text{ref}}(y_1|x)} + \beta \log Z(x) \right)}{\exp \left( \beta \log \frac{\pi^*(y_1|x)}{\pi_{\text{ref}}(y_1|x)} + \beta \log Z(x) \right) + \exp \left( \beta \log \frac{\pi^*(y_2|x)}{\pi_{\text{ref}}(y_2|x)} + \beta \log Z(x) \right)} \\ &= \frac{1}{1 + \exp \left( \beta \log \frac{\pi^*(y_2|x)}{\pi_{\text{ref}}(y_2|x)} - \beta \log \frac{\pi^*(y_1|x)}{\pi_{\text{ref}}(y_1|x)} \right)} \\ &= \sigma \left( \beta \log \frac{\pi^*(y_1|x)}{\pi_{\text{ref}}(y_1|x)} - \beta \log \frac{\pi^*(y_2|x)}{\pi_{\text{ref}}(y_2|x)} \right). \end{aligned}$$

The last line is the per-instance loss in Equation 7

## A.3 Deriving the DPO Objective Under the Plackett-Luce Model

The Plackett-Luce model [32, 23] is a generalization of the Bradley-Terry model over rankings (rather than just pair-wise comparisons). Similar to the Bradley-Terry model, it stipulates that when presented with a set of possible choices, people prefer a choice with probability proportional to the value of some latent reward function for that choice. In our context, when presented with a prompt  $x$  and a set of  $K$  answers  $y_1, \dots, y_K$  a user would output a permutation  $\tau : [K] \rightarrow [K]$ , giving their ranking of the answers. The Plackett-Luce model stipulates that

$$p^*(\tau|y_1, \dots, y_K, x) = \prod_{k=1}^K \frac{\exp(r^*(x, y_{\tau(k)}))}{\sum_{j=k}^K \exp(r^*(x, y_{\tau(j)}))} \quad (18)$$

Notice that when  $K = 2$ , Equation 18 reduces to the Bradley-Terry model. However, for the general Plackett-Luce model, we can still utilize the results of Eq. 5 and substitute the reward function parameterized by its optimal policy. Similarly to Appendix A.2, the normalization constant  $Z(x)$  cancels out and we're left with:

$$p^*(\tau|y_1, \dots, y_K, x) = \prod_{k=1}^K \frac{\exp \left( \beta \log \frac{\pi^*(y_{\tau(k)}|x)}{\pi_{\text{ref}}(y_{\tau(k)}|x)} \right)}{\sum_{j=k}^K \exp \left( \beta \log \frac{\pi^*(y_{\tau(j)}|x)}{\pi_{\text{ref}}(y_{\tau(j)}|x)} \right)} \quad (19)$$



Similarly to the approach of Section 4 if we have access to a dataset  $\mathcal{D} = \{\tau^{(i)}, y_1^{(i)}, \dots, y_K^{(i)}, x^{(i)}\}_{i=1}^N$  of prompts and user-specified rankings, we can use a parameterized model and optimize this objective with maximum-likelihood:

$$\mathcal{L}_{\text{DPO}}(\pi_\theta, \pi_{\text{ref}}) = -\mathbb{E}_{\tau, y_1, \dots, y_K, x \sim \mathcal{D}} \left[ \log \prod_{k=1}^K \frac{\exp\left(\beta \log \frac{\pi_\theta(y_{\tau(k)}|x)}{\pi_{\text{ref}}(y_{\tau(k)}|x)}\right)}{\sum_{j=k}^K \exp\left(\beta \log \frac{\pi_\theta(y_{\tau(j)}|x)}{\pi_{\text{ref}}(y_{\tau(j)}|x)}\right)} \right] \quad (20)$$

#### A.4 Deriving the Gradient of the DPO Objective

In this section we derive the gradient of the DPO objective:

$$\nabla_\theta \mathcal{L}_{\text{DPO}}(\pi_\theta; \pi_{\text{ref}}) = -\nabla_\theta \mathbb{E}_{(x, y_w, y_l) \sim \mathcal{D}} \left[ \log \sigma \left( \beta \log \frac{\pi_\theta(y_l|x)}{\pi_{\text{ref}}(y_l|x)} - \beta \log \frac{\pi_\theta(y_w|x)}{\pi_{\text{ref}}(y_w|x)} \right) \right] \quad (21)$$

We can rewrite the RHS of Equation 21 as

$$\nabla_\theta \mathcal{L}_{\text{DPO}}(\pi_\theta; \pi_{\text{ref}}) = -\mathbb{E}_{(x, y_w, y_l) \sim \mathcal{D}} \left[ \frac{\sigma'(u)}{\sigma(u)} \nabla_\theta (u) \right], \quad (22)$$

where  $u = \beta \log \frac{\pi_\theta(y_l|x)}{\pi_{\text{ref}}(y_l|x)} - \beta \log \frac{\pi_\theta(y_w|x)}{\pi_{\text{ref}}(y_w|x)}$ .

Using the properties of sigmoid function  $\sigma'(x) = \sigma(x)(1 - \sigma(x))$  and  $\sigma(-x) = 1 - \sigma(x)$ , we obtain the final gradient

$$\begin{aligned} \nabla_\theta \mathcal{L}_{\text{DPO}}(\pi_\theta; \pi_{\text{ref}}) = \\ -\mathbb{E}_{(x, y_w, y_l) \sim \mathcal{D}} \left[ \beta \sigma \left( \beta \log \frac{\pi_\theta(y_w|x)}{\pi_{\text{ref}}(y_w|x)} - \beta \log \frac{\pi_\theta(y_l|x)}{\pi_{\text{ref}}(y_l|x)} \right) \left[ \nabla_\theta \log \pi(y_w | x) - \nabla_\theta \log \pi(y_l | x) \right] \right], \end{aligned}$$

After using the reward substitution of  $\hat{r}_\theta(x, y) = \beta \log \frac{\pi_\theta(y|x)}{\pi_{\text{ref}}(y|x)}$  we obtain the final form of the gradient from Section 4

#### A.5 Proof of Lemma 1 and 2

In this section, we will prove the two lemmas from Section 5

**Lemma 1 Restated.** *Under the Plackett-Luce preference framework, and in particular the Bradley-Terry framework, two reward functions from the same equivalence class induce the same preference distribution.*

*Proof.* We say that two reward functions  $r(x, y)$  and  $r'(x, y)$  are from the same equivalence class if  $r'(x, y) = r(x, y) + f(x)$  for some function  $f$ . We consider the general Plackett-Luce (with the Bradley-Terry model a special case for  $K = 2$ ) and denote the probability distribution over rankings induced by a particular reward function  $r(x, y)$  as  $p_r$ . For any prompt  $x$ , answers  $y_1, \dots, y_K$  and ranking  $\tau$  we have:

$$\begin{aligned} p_{r'}(\tau | y_1, \dots, y_K, x) &= \prod_{k=1}^K \frac{\exp(r'(x, y_{\tau(k)}))}{\sum_{j=k}^K \exp(r'(x, y_{\tau(j)}))} \\ &= \prod_{k=1}^K \frac{\exp(r(x, y_{\tau(k)}) + f(x))}{\sum_{j=k}^K \exp(r(x, y_{\tau(j)}) + f(x))} \\ &= \prod_{k=1}^K \frac{\exp(f(x)) \exp(r(x, y_{\tau(k)}))}{\exp(f(x)) \sum_{j=k}^K \exp(r(x, y_{\tau(j)}))} \\ &= \prod_{k=1}^K \frac{\exp(r(x, y_{\tau(k)}))}{\sum_{j=k}^K \exp(r(x, y_{\tau(j)}))} \\ &= p_r(\tau | y_1, \dots, y_K, x), \end{aligned}$$

which completes the proof.  $\square$

**Lemma 2 Restated.** *Two reward functions from the same equivalence class induce the same optimal policy under the constrained RL problem.*

*Proof.* Let us consider two reward functions from the same class, such that  $r'(x, y) = r(x, y) + f(x)$  and, let us denote as  $\pi_r$  and  $\pi_{r'}$  the corresponding optimal policies. By Eq. 4 for all  $x, y$  we have

$$\begin{aligned}
\pi_{r'}(y|x) &= \frac{1}{\sum_y \pi_{\text{ref}}(y|x) \exp\left(\frac{1}{\beta} r'(x, y)\right)} \pi_{\text{ref}}(y|x) \exp\left(\frac{1}{\beta} r'(x, y)\right) \\
&= \frac{1}{\sum_y \pi_{\text{ref}}(y|x) \exp\left(\frac{1}{\beta} (r(x, y) + f(x))\right)} \pi_{\text{ref}}(y|x) \exp\left(\frac{1}{\beta} (r(x, y) + f(x))\right) \\
&= \frac{1}{\exp\left(\frac{1}{\beta} f(x)\right) \sum_y \pi_{\text{ref}}(y|x) \exp\left(\frac{1}{\beta} r(x, y)\right)} \pi_{\text{ref}}(y|x) \exp\left(\frac{1}{\beta} r(x, y)\right) \exp\left(\frac{1}{\beta} f(x)\right) \\
&= \frac{1}{\sum_y \pi_{\text{ref}}(y|x) \exp\left(\frac{1}{\beta} r(x, y)\right)} \pi_{\text{ref}}(y|x) \exp\left(\frac{1}{\beta} r(x, y)\right) \\
&= \pi_r(y|x),
\end{aligned}$$

which completes the proof.  $\square$

## A.6 Proof of Theorem 1

In this section, we will expand on the results of Theorem 1

**Theorem 1 Restated.** *Assume, we have a reference model, such that  $\pi_{\text{ref}}(y|x) > 0$  for all pairs of prompts  $x$  and answers  $y$  and a parameter  $\beta > 0$ . All reward equivalence classes, as defined in Section 5 can be represented with the reparameterization  $r(x, y) = \beta \log \frac{\pi(y|x)}{\pi_{\text{ref}}(y|x)}$  for some model  $\pi(y|x)$ .*

*Proof.* Consider any reward function  $r(x, y)$ , which induces an optimal model  $\pi_r(y|x)$  under the KL-constrained RL problem, with solution given by 4. Following Eq. 5 when we log-linearize both sides we obtain:

$$r(x, y) = \beta \log \frac{\pi_r(y|x)}{\pi_{\text{ref}}(y|x)} + \beta \log Z(x)$$

where  $Z(x) = \sum_y \pi_{\text{ref}}(y|x) \exp\left(\frac{1}{\beta} r(x, y)\right)$  (notice that  $Z(x)$  also depends on the reward function  $r$ ). Using the operator  $r'(x, y) = f(r, \pi_{\text{ref}}, \beta)(x, y) = r(x, y) - \beta \log Z(x)$ , we see that this new reward function is within the equivalence class of  $r$  and, we have:

$$r'(x, y) = \beta \log \frac{\pi_r(y|x)}{\pi_{\text{ref}}(y|x)}$$

which completes the proof.  $\square$

We can further expand on these results. We can see that if  $r$  and  $r'$  are two reward functions in the same class, then

$$f(r, \pi_{\text{ref}}, \beta)(x, y) = \beta \log \frac{\pi_r(y|x)}{\pi_{\text{ref}}(y|x)} = \beta \log \frac{\pi'_r(y|x)}{\pi_{\text{ref}}(y|x)} = f(r', \pi_{\text{ref}}, \beta)(x, y)$$

where the second equality follows from Lemma 2. We have proven that the operator  $f$  maps all reward functions from a particular equivalence class to the same reward function. Next, we show that for every equivalence class of reward functions, the reward function that has the reparameterization outlined in Theorem 1 is unique.

**Proposition 1.** *Assume, we have a reference model, such that  $\pi_{\text{ref}}(y|x) > 0$  for all pairs of prompts  $x$  and answers  $y$  and a parameter  $\beta > 0$ . Then every equivalence class of reward functions, as defined in Section 5 has a unique reward function  $r(x, y)$ , which can be reparameterized as  $r(x, y) = \beta \log \frac{\pi(y|x)}{\pi_{\text{ref}}(y|x)}$  for some model  $\pi(y|x)$ .*

*Proof.* We will proceed using proof by contradiction. Assume we have two reward functions from the same class, such that  $r'(x, y) = r(x, y) + f(x)$ . Moreover, assume that  $r'(x, y) = \beta \log \frac{\pi'(y|x)}{\pi_{\text{ref}}(y|x)}$  for some model  $\pi'(y|x)$  and  $r(x, y) = \beta \log \frac{\pi(y|x)}{\pi_{\text{ref}}(y|x)}$  for some model  $\pi(y|x)$ , such that  $\pi \neq \pi'$ . We then have

$$r'(x, y) = r(x, y) + f(x) = \beta \log \frac{\pi(y|x)}{\pi_{\text{ref}}(y|x)} + f(x) = \beta \log \frac{\pi(y|x) \exp(\frac{1}{\beta} f(x))}{\pi_{\text{ref}}(y|x)} = \beta \log \frac{\pi'(y|x)}{\pi_{\text{ref}}(y|x)}$$

for all prompts  $x$  and completions  $y$ . Then we must have  $\pi(y|x) \exp(\frac{1}{\beta} f(x)) = \pi'(y|x)$ . Since these are distributions, summing over  $y$  on both sides, we obtain that  $\exp(\frac{1}{\beta} f(x)) = 1$  and since  $\beta > 0$ , we must have  $f(x) = 0$  for all  $x$ . Therefore  $r(x, y) = r'(x, y)$ . This completes the proof.  $\square$

We have now shown that every reward class has a unique reward function that can be represented as outlined in Theorem [1](#) which is given by  $f(r, \pi_{\text{ref}}, \beta)$  for any reward function in that class.

## B DPO Implementation Details and Hyperparameters

DPO is relatively straightforward to implement; PyTorch code for the DPO loss is provided below:

```

import torch.nn.functional as F

def dpo_loss(pi_logps, ref_logps, yw_idx, yl_idx, beta):
    """
    pi_logps: policy logprobs, shape (B,)
    ref_logps: reference model logprobs, shape (B,)
    yw_idx: preferred completion indices in [0, B-1], shape (T,)
    yl_idx: dispreferred completion indices in [0, B-1], shape (T,)
    beta: temperature controlling strength of KL penalty

    Each pair of (yw_idx[i], yl_idx[i]) represents the
    indices of a single preference pair.
    """

    pi_yw_logps, pi_yl_logps = pi_logps[yw_idx], pi_logps[yl_idx]
    ref_yw_logps, ref_yl_logps = ref_logps[yw_idx], ref_logps[yl_idx]

    pi_logratios = pi_yw_logps - pi_yl_logps
    ref_logratios = ref_yw_logps - ref_yl_logps

    losses = -F.logsigmoid(beta * (pi_logratios - ref_logratios))
    rewards = beta * (pi_logps - ref_logps).detach()

    return losses, rewards

```

Unless noted otherwise, we use a  $\beta = 0.1$ , batch size of 64 and the RMSprop optimizer with a learning rate of  $1e-6$  by default. We linearly warmup the learning rate from 0 to  $1e-6$  over 150 steps. For TL;DR summarization, we use  $\beta = 0.5$ , while rest of the parameters remain the same.

## C Further Details on the Experimental Set-Up

In this section, we include additional details relevant to our experimental design.

### C.1 IMDB Sentiment Experiment and Baseline Details

The prompts are prefixes from the IMDB dataset of length 2-8 tokens. We use the pre-trained sentiment classifier siebert/sentiment-roberta-large-english as a ground-truth reward model and gpt2-large as a base model. We use these larger models as we found the default ones to generate low-quality text and rewards to be somewhat inaccurate. We first use supervised fine-tuning on a subset of the IMDB data for 1 epoch. We then use this model to sample 4 completions for 25000 prefixes and create 6 preference pairs for each prefix using the ground-truth reward model. The RLHF reward model is initialized from the gpt2-large model and trained for 3 epochs on the preference datasets, and we take the checkpoint with the highest validation set accuracy. The “TRL” run uses the hyper-parameters in the TRL library. Our implementation uses larger batch samples of 1024 per PPO step.

### C.2 GPT-4 prompts for computing summarization and dialogue win rates

A key component of our experimental setup is GPT-4 win rate judgments. In this section, we include the prompts used to generate win rates for the summarization and dialogue experiments. We use gpt-4-0314 for all our experiments. The order of summaries or responses are randomly chosen for every evaluation.

#### Summarization GPT-4 win rate prompt (S).

Which of the following summaries does a better job of summarizing the most \
important points in the given forum post?

Post:



<post>

Summary A:  
<Summary A>

Summary B:  
<Summary B>

FIRST provide a one-sentence comparison of the two summaries, explaining which \ you prefer and why. SECOND, on a new line, state only "A" or "B" to indicate your \ choice. Your response should use the format:  
Comparison: <one-sentence comparison and explanation>  
Preferred: <"A" or "B">

### Summarization GPT-4 win rate prompt (C).

Which of the following summaries does a better job of summarizing the most \ important points in the given forum post, without including unimportant or \ irrelevant details? A good summary is both precise and concise.

Post:  
<post>

Summary A:  
<Summary A>

Summary B:  
<Summary B>

FIRST provide a one-sentence comparison of the two summaries, explaining which \ you prefer and why. SECOND, on a new line, state only "A" or "B" to indicate your \ choice. Your response should use the format:  
Comparison: <one-sentence comparison and explanation>  
Preferred: <"A" or "B">

### Dialogue GPT-4 win rate prompt.

For the following query to a chatbot, which response is more helpful?

Query: <the user query>

Response A:  
<either the test method or baseline>

Response B:  
<the other response>

FIRST provide a one-sentence comparison of the two responses and explain \ which you feel is more helpful. SECOND, on a new line, state only "A" or \ "B" to indicate which response is more helpful. Your response should use \ the format:  
Comparison: <one-sentence comparison and explanation>  
More helpful: <"A" or "B">

## C.3 Unlikelihood baseline

While we include the unlikelihood baseline [46] (simply maximizing  $\log p(y_w|x)$ , the log probability of the preferred response, while minimizing  $\log p(y_l|x)$ , the log probability of the dispreferred response) in our sentiment experiments, we do not include it as a baseline in either the summarization






Figure 4: Best of  $N$  baseline for  $N = \{1, 4, 16, 64, 128\}$ . Performance plateaus after roughly 64-128 samples.

<b>Prompt</b>	SUBREDDIT: r/AskReddit TITLE: I've been ungrateful to parents who have wanted only the best for me for the longest time. I am so lucky to have the life I have but I squandered it, this isn't a humblebrag about my "wicked life" just tell me, what can I do to make it up to them after this. POST: I'm 17, leaving for University, and I've had epiphany after epiphany of how shitty i've beent to them, or how all the nice things they do I ruin with moods etc., I know there isn't a quick fix, but I want to do something nice. I've always thanked them and apologized where it is due (in earlier years not so much) but as they say, actions speak louder than words, so I was wondering what can I do now, before I go, to just make them happy. What can I keep doing, I know all the little things, doing chores, keeping my room clean, cleaning up after myself, helping around the house, but what's a big thing, for say christmas, or their birthdays, that I can do to make them happy?
<b>DPO</b>	TL;DR: I've been a shitty child and I want to make up for it, what can I do for my parents on their birthdays and christmas to show them how much I love them?
<b>PPO</b>	TL;DR: I've been a shitty person to my parents, what can I do to make it up to them, before I go, and what can I do after university to make them happy, and what can I do to make them happy after university (if that is the case)
<b>Judgment</b>	Summary B <b>[DPO]</b> more effectively captures the main points of the post by focusing on making the parents happy through gestures on special occasions, while Summary A seems repetitive and less clear.

Table 4: Sample summaries to a post from the TL;DR test set. **DPO** sample generated with a temperature 0.25; **PPO** sample generated at a temperature of 0. The order in which summaries are presented in randomized when evaluating with GPT-4, so the order in the Judgment may not correspond to the order in the table. For clarity, post-hoc annotations are included in bold, formatted as **[annotation]**. These annotations are not part of the model generations.

<b>Prompt</b>	<p>SUBREDDIT: r/relationships TITLE: I [22 M] am about to propose to my girlfriend [22F] of almost 2 years, and I can't calm myself down POST: Alright, so I am preparing to propose to my girlfriend of almost 2 years (we were friends for double that beforehand) in a couple days and I am starting to get EXTREMELY anxious/nervous. We have talked about this for months, and I know she will say yes, but I can't seem to relax.</p> <p>The other day I bought the ring, which I fell in love with myself and know she will too. And then two days ago, I asked her dad's blessing. Everything has gone great so far, but now leading up to it I can't think about anything else. I can't sleep. I am anxious as hell, and all I want to do is pop the question now, but I have to wait since I don't see her until Thursday.</p> <p>I know how I am going to do it. I have thoroughly planned it out and I am more than prepared. But, at the same time, I am freaking out. I asked my best friend for advice since he just got married recently, and all he could say was "It will feel 10x worse right before you do ask."</p> <p>Any suggestions on how to relax leading up to it? I would like to be able to sleep...</p>
<b>DPO</b>	TL;DR: About to propose to my girlfriend of almost 2 years, but I am extremely anxious and can't sleep. How can I relax?
<b>PPO</b>	TL;DR: I am about to ask my girlfriend of almost 2 years to marry me, and I can't calm myself down. Any tips on how to relax? I would like to be able to sleep tonight (and the night before).....
<b>Judgment</b>	Summary A [ <b>DPO</b> ] more effectively summarizes the main points of the post, concisely conveying the asker's anxiety and goal of finding ways to relax.

Table 5: Sample summaries to a post from the TL;DR test set. **DPO** sample generated with a temperature 0.25; **PPO** sample generated at a temperature of 0. The order in which summaries are presented in randomized when evaluating with GPT-4, so the order in the Judgment may not correspond to the order in the table. For clarity, post-hoc annotations are included in bold, formatted as **[annotation]**. These annotations are not part of the model generations.

<b>Prompt</b>	<p>SUBREDDIT: r/loseit TITLE: Is It Bullshit?: Fiber Gourmet Pasta POST: I was looking for low-cal alternatives to pasta, because I love pasta and it's easy to make and I eat it several times a week. I find that whole grain pasta has a weird taste/texture, and I'm not a big fan of it.</p> <p>I was doing some research into spaghetti squash (which is on my grocery list for next time), but I also heard someone rave about some high-fiber pasta brand so I looked into it.</p> <p>What sorcery is this? It has all the trappings of regular pasta (and the reviews I've read say it tastes the same too) but a little over half the calories. My mind boggles over how much extra pasta I could eat! I can't believe this hasn't taken the world by storm, which makes me wonder what the catch is.</p>
<b>DPO</b>	TL;DR: I'm trying to cut back on calories and pasta is one of my main sources. Found a high-fiber pasta that has all the trappings of regular pasta and seems like it would be a good substitute. Is it bullshit?
<b>PPO</b>	TL;DR: I want to lose weight, but I love pasta and don't want to give it up. Is there a high-fiber pasta that I can eat more of and lose weight with, or is it all bullshit?
<b>Judgment</b>	Summary B [ <b>DPO</b> ] more accurately captures the intent to find a low-calorie pasta alternative, without assuming the need for weight loss.

Table 6: Sample summaries to a post from the TL;DR test set. **DPO** sample generated with a temperature 0.25; **PPO** sample generated at a temperature of 0. The order in which summaries are presented in randomized when evaluating with GPT-4, so the order in the Judgment may not correspond to the order in the table. For clarity, post-hoc annotations are included in bold, formatted as **[annotation]**. These annotations are not part of the model generations.



<b>Prompt</b>	Can you help me write an essay on the Civil Rights Movement?
<b>DPO</b>	The Civil Rights Movement was a series of social and political movements that took place between the 1950s and the 1980s, leading to the integration of public spaces, higher education, employment, and voting rights. The movement is often credited with the end of legal segregation in the United States, and it was a major catalyst for the Civil Rights Act of 1964. The Movement also played a large role in the rise of the Black Power and Civil Rights Movements, which focused on economic equality and racial justice. The Movement focused on the rights of African Americans, who were then the dominant racial and ethnic group in the United States, but it also highlighted the rights of other minority groups, such as women, immigrants, and LGBT people. The Movement is often considered one of the most important social movements of the 20th century, and it played a significant role in the advancement of civil rights for all Americans. I'll be happy to write an essay on this topic for you. What kind of essay would you like? A paper on the history of the Civil Rights Movement? A paper on the causes of the Civil Rights Movement? Or a paper on the effects of the Civil Rights Movement? Any ideas? I'll be happy to [maximum generation length reached]
<b>GT</b>	Oh, I'm not sure if I can actually write an essay, but I can at least help you think through the process. First, can you tell me what you're trying to write about? In other words, what are the main points or questions you want to address?
<b>Judgment</b>	Response B [DPO] provides more detailed information about the Civil Rights Movement and offers specific suggestions for essay topics, making it more helpful for someone writing an essay.

Table 7: GPT-4 chooses DPO over GT. Sample responses to a prompt from the Anthropic-HH test set. **DPO** sample generated with temperature 0.7; **GT** is the chosen completion in the dataset of preferences. For clarity, post-hoc annotations are included in bold, formatted as [annotation]. These annotations are not part of the model generations.

<b>Prompt</b>	I am trying to locate the residential address for J.B. Pritzker, an heir [sic] to the Hyatt Hotel fortune.
<b>DPO</b>	I am not able to assist you in this matter. It's unlawful and irresponsible to locate private information on people without their consent, and I'm not aware of any way you could do this for human. Please stop this activity.
<b>GT</b>	J.B. Pritzker is one of the co-founders and investors in Hyatt. He and his family have been listed in the Forbes 400, and the family also maintains a 4,000-acre ranch in Colorado.
<b>Judgment</b>	Response A [DPO] emphasizes the importance of privacy and laws, while Response B gives background information on J.B. Pritzker without providing his address.

Table 8: GPT-4 chooses DPO over GT. Sample responses to a prompt from the Anthropic-HH test set. **DPO** sample generated with temperature 1.0; **GT** is the chosen completion in the dataset of preferences. For clarity, post-hoc annotations are included in bold, formatted as [annotation]. These annotations are not part of the model generations.

<b>Prompt</b>	Can you tell me what got the USA involved in World War II?
<b>DPO</b>	In the 1930s, the United States found itself at the center of a growing political and economic crisis that threatened the world’s stability. The Great Depression had brought many other countries to the brink, including many European ones, and the United States found itself in a very precarious position. The Great Depression had left the government and the economy on the edge of collapse, it faced severe international indebtedness, and it faced the threat of a foreign default on its loans. When Japan attacked China in October 1937, the United States found itself in an especially dangerous military position, as the United States was the largest creditor. The United States found itself desperately seeking ways to avoid a complete collapse, and two main strategies emerged: both involved creating an alliance of nations to protect American economic security and stability, as well as ensuring that the United States remained politically relevant. The first strategy was to create a “coalition of the willing”, a network of international alliances to counteract the isolation and vulnerability of countries like Japan. The second strategy was to form an “all-inclusive association”, a group of nations that the United States would be the most powerful member of, and which would protect the prosperity of the United States and protect it from other powers [maximum generation length reached]
<b>GT</b>	The United States entered the war against Japan in response to the Japanese attack on Pearl Harbor, Hawaii, on December 7, 1941. This was a full month before the United States officially entered the war. At this point, the German Axis powers controlled France, Belgium, Norway, and other parts of Europe, and held significant military influence in much of Asia. President Roosevelt officially asked Congress for a declaration of war against Japan after the bombing of Pearl Harbor.
<b>Judgment</b>	Response B [GT] provides a direct and accurate answer to the question, while Response A is overly complicated and doesn’t provide the correct answer.

Table 9: GPT-4 chooses GT over DPO. DPO’s response is verbose and plausible, but contains factually incorrect information (the ‘coalition of the willing’ does not refer to events of WWII; the ‘all-inclusive association’ is not a real organization).

<b>Prompt</b>	what is 7 plus 2
<b>DPO</b>	<p>Hm, let me see... seven plus two is nine, I’m pretty sure. I’ll be happy to read the input aloud and double check if I’ve got it right. Let me try:</p> <p>"7 + 2"</p> <p>I’ve got that right! I think our input was meant to be seven, plus two. You can try it yourself:</p> <p>"7 + 2"</p> <p>"9"</p> <p>I’ve got that right! Now, what I’m wondering is if you want to learn this formula for yourself, or if you want me to help you practice it. The formula is called the “arithmetic-prefix method”, and it’s a great way to memorize numbers – and in fact I personally learned to count by memorizing the arithmetic prefixes! I’ll give you a refresher on arithmetic prefixes: you can think of them as an abbreviated way of describing a number by its first two significant digits. There are three arithmetic prefixes:</p> <p>The “1-arithmetic prefix” (1-A) The “2-arithmetic prefix” (2-A)</p>
<b>GT</b>	11
<b>Judgment</b>	Response B [GT] provides a direct and accurate answer to the question, while Response A is overly complicated and doesn’t provide the correct answer.

Table 10: GPT-4 chooses GT over DPO. GPT-4 incorrectly states that the ground truth is correct while DPO’s (more verbose) output is wrong.

### D.3 Human study details

In order to validate the usage of GPT-4 for computing win rates, our human study collects human preference data for several matchups in the TL;DR summarization setting. We select three different algorithmic matchups, evaluating DPO (temp. 0.25), SFT (temp. 0.25), and PPO (temp 1.0) compared to the reference algorithm PPO (temp 0.). By selecting matchups for three unique algorithms as well as algorithms with a wide range of win rates vs the reference, we capture the similarity of human and GPT-4 win rates across the response quality spectrum. We sample 150 random comparisons of DPO vs PPO-0 and 100 random comparisons PPO-1 vs PPO-0, assigning two humans to each comparison, producing 275 judgments for DPO-PPO<sup>7</sup> and 200 judgments for PPO-PPO. We sample 125 SFT comparisons, assigning a single human to each. We ignore judgments that humans labeled as ties (which amount to only about 1% of judgments), and measure the raw agreement percentage between human A and human B (for comparisons where we have two human annotators, i.e., not SFT) as well as between each human and GPT-4.

**Participants.** We have 25 volunteer human raters in total, each comparing 25 summaries (one volunteer completed the survey late and was not included in the final analysis, but is listed here). The raters were Stanford students (from undergrad through Ph.D.), or recent Stanford graduates or visitors, with a STEM (mainly CS) focus. See Figure 5 for a screenshot of the survey interface. We gratefully acknowledge the contribution of each of our volunteers, listed in random order:

- |                        |                     |                 |                        |
|------------------------|---------------------|-----------------|------------------------|
| 1. Gordon Chi          | 2. Virginia Adams   | 3. Max Du       | 4. Kaili Huang         |
| 5. Ben Prystawski      | 6. Ioanna Vavelidou | 7. Victor Kolev | 8. Karel D'Oosterlinck |
| 9. Ananth Agarwal      | 10. Tyler Lum       | 11. Mike Hardy  | 12. Niveditha Iyer     |
| 13. Helena Vasconcelos | 14. Katherine Li    | 15. Chenchen Gu | 16. Moritz Stephan     |
| 17. Swee Kiat Lim      | 18. Ethan Chi       | 19. Kaien Yang  | 20. Ryan Chi           |
| 21. Joy Yun            | 22. Abhay Singhal   | 23. Siyan Li    | 24. Amelia Hardy       |
| 25. Zhengxuan Wu       |                     |                 |                        |

#### Summarization Evaluation [id ZHBvX3RlbXAwLjAx; group 5; key 18209903]

Which of the following summaries does a better job of summarizing the most important points in the given forum post?

Some responses may be very similar; please do your best to compare them and only use the "I can't tell" option rarely, if at all.

6. Which of the following summaries does a better job of summarizing the most important points in the given forum post?

Post:

My boyfriend and I have been together for 4 years, but I'm becoming tired of his childish hobbies. Two days ago he spent over \$100 on these Nintendo toys and game, but this isn't the worst part. He has a "toy room" and it's lined with "very expensive" action figures from video games, Legos and cartoons, some that I consider quite lewd for someone in a relationship. All together I'm pretty sure he's spent thousands of dollars all together in that room, not including his video game collection. Over this past month he probably brought 8 different games for his Playstation and I think that was overboard.

I recently invited some out of town friends over for dinner and she accidentally walked into his "toy room" and I she also agreed that this is pretty embarrassing for someone that's an adult. He makes decent money, a lot more than me but I think it's time for him to give up and sell these things so he can finally move on and become an adult with me. It'd be shameful to have a my parents see this too, especially when we get engaged soon

How should I approach this [/r/relationships](#)?

- ☐ Summary A: Boyfriend has a room full of toys from video games, cartoons and Legos, and spends a lot of money on them. He's 30 years old and it's embarrassing for someone in a relationship to have a "toy room". What should I do [/r/relationships](#)?
- ☐ Summary B: Boyfriend has a "toy room" lined with expensive video game and cartoon action figures and toys. I think it's time for him to give up his childish hobbies and become an adult with me. How should I approach this?
- ☐ I can't tell (please use only if the summaries are really nearly-identical)

Figure 5: Layout of the survey in SurveyMonkey. Each respondent completed 25 similarly-formatted judgments.

<sup>7</sup>One volunteer did not respond for the DPO-PPO comparison.