



Rancangan virtual, bukan topologi produksi

Lantai L1: Lantai 1 - Kerja & Kunjungan. Sumber: world.json ict + design/derived/ict-portmap.json

LEGENDA

- △

 Outlet data, tag Tnn
- Kamera opsional + arah konsep
- Riser ke lantai lain
- AP placeholder, tag APn
- Tray kabel +3,2 m
- Rack 42U (target)

OUTLET L1 (30 outlet, 55 port)

Tag	ID	Ruang	Port	Tag	ID	Ruang	Port
T1	TO-L1-001	LOBBY	2	T16	TO-L1-016	LAB	4
T2	TO-L1-002	LOBBY	1	T17	TO-L1-017	LAB	2
T3	TO-L1-003	MEET	2	T18	TO-L1-018	CEO	2
T4	TO-L1-004	MEET	1	T19	TO-L1-019	HUGO	2
T5	TO-L1-005	IMPL	2	T20	TO-L1-020	HUGO	2
T6	TO-L1-006	IMPL	2	T21	TO-L1-021	KEVIN	2
T7	TO-L1-007	IMPL	2	T22	TO-L1-022	BRUNO	2
T8	TO-L1-008	IMPL	2	T23	TO-L1-023	LOBBY	1
T9	TO-L1-009	IMPL	2	T24	TO-L1-024	IMPL	1
T10	TO-L1-010	IMPL	2	T25	TO-L1-025	CORR	1
T11	TO-L1-011	IMPL	1	T26	TO-L1-026	NCORR	1
T12	TO-L1-012	NOVA	2	T27	TO-L1-027	NCORR	1
T13	TO-L1-013	NOVA	2	T28	TO-L1-028	LOBBY	1
T14	TO-L1-014	LAB	4	T29	TO-L1-029	CORR	1
T15	TO-L1-015	LAB	4	T30	TO-L1-030	BRUNO	1

Domain dan endpoint per port: ICT-401.

PERANGKAT L1 (AP 5, kamera 3)

Tag	ID	Ruang	Outlet	z m	PoE
AP1	AP-L1-01	LOBBY	T23	3,0	4
AP2	AP-L1-02	IMPL	T24	3,0	4
AP3	AP-L1-03	CORR	T25	3,0	4
AP4	AP-L1-04	NCORR	T26	3,0	4
AP5	AP-L1-05	NCORR	T27	3,0	4
CAM1	CAM-L1-01	LOBBY	T28	2,8	3
CAM2	CAM-L1-02	CORR	T29	2,8	3
CAM3	CAM-L1-03	BRUNO	T30	2,8	3

Semua AP placeholder (AS-ICT-01); kamera opsional konsep, arah bukan FOV terukur. Lihat juga AS-ICT-02, AS-ICT-03, AS-NET-01 di A-001.

STATUS KONSEP

Bukan untuk konstruksi

kantor-rpg Proyek kantor-rpg · gedung K RPG-01

Outlet, AP dan kamera Lantai 1

Skala 1:100 @ A2 lanskap
Revisi P03 · 2026-10-01
Render 2026-10-02 00:29:26 UTC
Halaman 1/1
Digambar Claude Code cloud (generator)
Diperiksa Max (supervisor) belum review
Sumber world.json sha256 488597bb0552fbde

Huruf: KantorRPG Sans, turunan Alegreya Sans karya Juan Pablo del Peral (SIL OFL 1.1, paket Debian fonts-alegreya-sans), subset tertanam.

Nomor lembar

ICT-101

Rev P03 · 1/1

OUTLET, AP DAN KAMERA LANTAI 1 Skala 1:100 @ A2

Tag Tnn = outlet TO-L1-0nn, APn/CAMn = perangkat; ID lengkap di tabel panel. Tray di +3,2 m (AS-ICT-02). AP placeholder tanpa klaim radius Wi-Fi (AS-ICT-01).

