

	Name	Material/ Description	Used per Device	Supplier	Manufacturer	Link to RoHS Certificate	homogeneous	Amendment	Declaration	Directive 2011/65/EU	Directive (EU) 2015/863	IEC 62321:2008	Link to website	Address
1	MAIN PCB	Base Material: FR-4, Dimension: 92 mm* 78.5 mm, Layers: 4, Specify Stackup: JLC04161H-7628, PCB Thickness: 1.6mm, PCB Color: Blue, Silkscreen: White, Surface Finish: LeadFree HASL, Material Type: TG155, Outer Copper Weight: 1 oz, Inner Copper Weight: 0.5 oz	1	JLPCB	JLPCB / SHENZHEN JLC TECHNOLOGY GROUP CO.,LTD.	https://rs.jlpcb.com/static/file/rohs-certificate-of-conformity.pdf	Yes	Directive (EU) 2015/863	Lab CoC	Yes	Yes	Yes	https://jlpcb.com	27TH FLOOR, OLYMPIC BUILDING, SHANGBAO ROAD, FUTIAN DISTRICT, SHENZHEN CITY, GUANGDONG PROVINCE, CHINA
2	CL21A106KAYNNNE_C15 850	10uF, 25Vdc, +/-10%, X5R, 0805/2012 SMD MLCC, CL series, operating temperature -55C to +85C	5	LCSC	Samsung Electro-Mechanics Co., Ltd.	https://www.samsungsem.com/files/fileDownload.do?key=ed1dfdfa-645e-4252-b707-17f9b1502ad1	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.samsungsem.com/global/product/passive-component/mlcc-ds	Maeyoung-ro 150 Yeongtong-gu, Suwon, Gyeonggi-do 16674, Republic of Korea
3	CL05B104KO5NNNC	100nF, 16Vdc, +/-10%, X7R, 0402/1005 SMD MLCC, CL series, operating temperature -55C to +125C	42	LCSC	Samsung Electro-Mechanics Co., Ltd.	https://www.samsungsem.com/files/fileDownload.do?key=ed1dfdfa-645e-4252-b707-17f9b1502ad1	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.samsungsem.com/global/product/passive-component/mlcc-ds	Maeyoung-ro 150 Yeongtong-gu, Suwon, Gyeonggi-do 16674, Republic of Korea
4	CL05A105KA5NQNC	1uF, 25Vdc, +/-10%, X5R, 0402/1005 SMD MLCC, CL series, operating temperature -55C to +85C	14	LCSC	Samsung Electro-Mechanics Co., Ltd.	https://www.samsungsem.com/files/fileDownload.do?key=ed1dfdfa-645e-4252-b707-17f9b1502ad1	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.samsungsem.com/global/product/passive-component/mlcc-ds	Maeyoung-ro 150 Yeongtong-gu, Suwon, Gyeonggi-do 16674, Republic of Korea
5	CL21A475KAQNNNE	4.7uF, 25Vdc, +/-10%, X5R, 0805/2012 SMD MLCC, CL series, operating temperature -55C to +85C	2	LCSC	Samsung Electro-Mechanics Co., Ltd.	https://www.samsungsem.com/files/fileDownload.do?key=ed1dfdfa-645e-4252-b707-17f9b1502ad1	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.samsungsem.com/global/product/passive-component/mlcc-ds	Maeyoung-ro 150 Yeongtong-gu, Suwon, Gyeonggi-do 16674, Republic of Korea
6	CC0603KRX7R9BB104	100nF, 50Vdc, +/-10%, X7R, 0603/1608 SMD MLCC, CC series, tin termination, operating temperature -55C to +125C	4	LCSC	YAGEO Corporation	https://yageogroup.com/content/Resource%20Library/Product%20Environmental%20Compliance/RoHS%20Compliance_YA_GEO.pdf	Yes	Directive (EU) 2015/863	Other-Non-use certificate for RoHS	Yes	Yes	Other EN IEC 63000:2018	https://yageogroup.com/download/specsheet/CC0603KRX7R9BB104	3F, 233-1, Baoqiao Rd., Xindian Dist., New Taipei City 23145, Taiwan
7	GRM188B31H105KAALD	1uF, 50Vdc, +/-10%, temperature characteristic B (JIS), 0603/1608H Murata GRM series chip multilayer ceramic capacitor, operating temperature -25C to +85C	1	LCSC	Murata Manufacturing Co., Ltd.	https://www.murata.com/c-media/webinar/new_products/capacitor/ceramic/capacitor/certificate/rohs/peram/capacitor-eu-rohs-certificate.ashx?cvid=2023040401000000000&la=en	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.murata.com/en-us/products/productdetail/all?partno=GRM188B31H105KAALD	10-1, Higashikotari 1-chome, Nagaokakyoshi, Kyoto 617-8555, Japan
8	CL10B223KB8NNNC	22nF, 50Vdc, +/-10%, X7R, 0603/1608 SMD MLCC, CL series, operating temperature -55C to +125C	1	LCSC	Samsung Electro-Mechanics Co., Ltd.	https://www.samsungsem.com/files/fileDownload.do?key=ed1dfdfa-645e-4252-b707-17f9b1502ad1	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.samsungsem.com/global/product/passive-component/mlcc-ds	Maeyoung-ro 150 Yeongtong-gu, Suwon, Gyeonggi-do 16674, Republic of Korea
9	CL10A106KP8NNNC	10uF, 10Vdc, +/-10%, X5R, 0603/1608 SMD MLCC, CL series, operating temperature -55C to +85C	1	LCSC	Samsung Electro-Mechanics Co., Ltd.	https://www.samsungsem.com/files/fileDownload.do?key=ed1dfdfa-645e-4252-b707-17f9b1502ad1	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.samsungsem.com/global/product/passive-component/mlcc-ds	Maeyoung-ro 150 Yeongtong-gu, Suwon, Gyeonggi-do 16674, Republic of Korea
10	TH1620CTJ	SMD patch round nut / board spacer, M2*4.0.3+1.5, brass C3604 body, tin plated surface finish, tape reel package, RoHS compliant	4	LCSC	Shenzhen Sinho Science Technology Development Co., Ltd.	https://atta.szlsc.com/upload/public/pdf/source/20220525/26E6F223E9E2377D04E1A1E6AA348AF.pdf	No	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/C3604123.html	Shenzhen, Guangdong, China
11	MBR0530_C77336	MBR0530 Schottky barrier diode, SOD-123 package, 30V maximum DC reverse voltage, 500mA average rectified current, 550mV forward voltage at 500mA, 5.5A peak forward surge current, 80uA reverse leakage at 30V, lead-free finish and RoHS compliant	3	LCSC	Jiangsu Changling Electronics Technology Co., Ltd.	https://atta.szlsc.com/upload/public/pdf/source/20160702/1467448303432.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/C77336.html	No. 88, Jingyi Road, Jiangbei New Area, Nanjing, Jiangsu, China
12	B5819WS_C64886	B5819WS Schottky barrier diode, SOD-323 package, 40V maximum DC reverse voltage, 1A average rectified current, 900mV forward voltage at 3A, 25A peak forward surge current, 1mA reverse leakage at 40V, operating junction temperature -55C to +125C, RoHS III compliant	1	LCSC	MDD / Microdiode Semiconductor	https://atta.szlsc.com/upload/public/pdf/source/20241121/165544ED2364DF4F1DA9A28474F8D736.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.mddiodes.com/product/schottky-diode-sod-323-series-b5819ws/	Dongguan, Guangdong, China
13	LES5D5.0CT1G-ES	Bidirectional ESD/TVS protection diode, SOD-523 package, 5V reverse stand-off voltage, 5.8V breakdown voltage, 10V maximum clamping voltage, 8A peak pulse current, 80W peak pulse power, 1uA reverse leakage, 15pF typical capacitance, IEC 61000-4-2 level 4 ESD protection, operating temperature -40C to +125C, RoHS compliant	4	LCSC	ElecSuper	https://atta.szlsc.com/upload/public/pdf/source/20240905/10776531C4DE5F6ADA679023752259EC.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/C5198159.html	China
14	SF-0603F500-2	Fast acting thin film surface mount fuse, SingleFuse SF-0603F series, 0603/1608 miniature footprint, 5A current rating, 32Vdc voltage rating, 50A breaking capacity, UL 248-14 compliant, operating temperature -20C to +105C, RoHS compliant and halogen free	1	LCSC	Bourns, Inc.	https://www.bourns.com/docs/rohs-coc/sf_coc.pdf	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	No	https://www.bourns.com/products/circuit-protection/fuses/surface-mount-fuses	1200 Columbia Avenue, Riverside, CA 92507, USA
15	HC-FPC-05-09-24RLTAG	FFC/FPC connector assembly, 24 positions, 0.5mm pitch, right-angle surface mount, clamshell/flip-lock type, double-sided top and bottom contacts, 0.3mm FFC/FPC thickness, 1.0mm height above board, copper alloy contacts, operating temperature -55C to +85C	1	LCSC	Shenzhen Huacan Tianlu Electronics Co., Ltd.	https://www.lcsc.com/product-detail/FFC-FPC-Connectors_HCT1-HC-FPC-05-09-24RLTAG_C5213757.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://www.lcsc.com/product-detail/FFC-FPC-Connectors_HCT1-HC-FPC-05-09-24RLTAG_C5213757.html	2F, N+ Chuanghui Building, No. 15 Tian'an Road, Bantian Community, Bantian Street, Longgang District, Shenzhen, Guangdong, China
16	WPN4020H100MT	Shielded wire wound SMD power inductor, WPN4020H series, 10uH inductance, +/-20% tolerance, 4.0mm x 4.0 mm x 2.0mm package, ferrite core, 216mOhm max DC resistance, 11MHz self-resonant frequency, 2A rated current, 3.5A saturation current, operating temperature -40 C to +125C	1	LCSC	Shenzhen Sunlord Electronics Co., Ltd.	https://www.sunlordinc.com/uploadfiles/Declaration%20of%20Conformity.pdf	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	No	https://www.sunlordinc.com/uploadfiles/20221122/VP%2C%2ASeries%2C%2AAo%2C%2ASMD%2C%2ADPower%2C%2AInductor.pdf	Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110
17	KT-0603R	Red 0603 SMD LED, 1.6mm x 0.8mm x 0.6mm package, water clear transparent planar lens, 20mA forward current, 1.8V to 2.4V forward voltage, 615nm to 630nm dominant wavelength, 645nm peak wavelength, 300mcd luminous intensity, 120 degree viewing angle, 40mW power dissipation, operating temperature -40C to +85C, RoHS compliant green product	1	LCSC	Hubei Kento Electronic Stock Corporation	https://datasheet.lcsc.com/lcsc/1810231112_Hubei-KENTO-Elec-KT-0603R_C2286.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/C2286.html	No. 18, Jiandong Road, Maoping Town, Zigui County, Hubei Province, China

	Name	Material/Description	Used per Device	Supplier	Manufacturer	Link to RoHS Certificate	homogeneous	Amendment	Declaration	Directive 2011/65/EU	Directive (EU) 2015/863	IEC 62321:2008	Link to website	Address
18	BSS138LT1G	N-channel MOSFET, SOT-23 package, 50V drain-source voltage, 200mA continuous drain current, 800mA pulsed drain current, 225mW power dissipation, 3.5ohm max RDS(on) at 5V and 200mA, 5.6ohm max RDS(on) at 2.75 V, 0.85V to 1.5V gate threshold, 50pF max input capacitance, operating junction temperature -55C to +150C, Pb-free, halogen-free/BFR-free and RoHS compliant	1	LCSC	onsemi	https://www.onsemi.com/PowerSolutions/MaterialCompositi on.do?export=pdf&copid=BSS138LT1G	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	No	https://www.onsemi.com/pdf/datasheet/bss138lt1-d.pdf	5701 N. Pima Rd. Scottsdale, AZ 85250, USA
19	SI2301_C727151	P-channel MOSFET, SOT-23 package, 20V drain-source voltage, 2.8A continuous drain current, 10A pulsed drain current, 350mW power dissipation, 112mOhm max RDS (on) at 4.5V and 2.8A, 142mOhm max RDS(on) at 2.5V and 2.0A, 1V max gate threshold, 405pF input capacitance, 55pF reverse transfer capacitance, operating junction temperature up to +150C	1	LCSC	TWGMC	https://www.lcsc.com/product-detail/C727151.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://datasheet.lcsc.com/lcsc/2008301206_1TWGMCSi2301_C727151.pdf	Taiwan / China
20	S8050_C20069125	S8050 NPN bipolar transistor, SOT-23 package, 25V collector-emitter voltage, 500mA collector current, 300mW power dissipation, DC current gain 120 at 50mA and 1.0V, 100MHz transition frequency, 100nA collector cutoff current, 600mV VCE(sat), 5V emitter-base voltage, operating temperature -55C to +150C	1	LCSC	R+O / hongjiacheng	https://www.lcsc.com/product-detail/C20069125.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://datasheet.lcsc.com/lcsc/2504101957_hongjiacheng-S8050_C20069125.pdf	Zhuhai, Guangdong, China
21	0402WGF1002TCE	10 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	11	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25744.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
22	0402WGF0000TCE	0 Ohm jumper thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-800ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C17168.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
23	RC0402FR-0710KL	10 kOhm +/-1% thick film chip resistor, RC series, 0402/1005 SMD package, 0.063W (1/16W) at 70C, 50V maximum continuous voltage, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, 1in termination	3	LCSC	YAGEO Corporation	https://yageogroup.com/content/Resource%20Library/Product%20Environmental%20Compliance/RoHS-Compliance_YAGEO.pdf	Yes	Directive (EU) 2015/863	Other-Non-use certificate for RoHS	Yes	Yes	Other EN IEC 63000:2018	https://yageogroup.com/component:documentation/download/specialsheet/RC0402FR-0710KL	3F, 233-1, Baoqiao Rd., Xindian Dist., New Taipei City 23145, Taiwan
24	0402WGF220JTCE	22 Ohm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25092.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
25	0402WGF4701TCE	4.7 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25900.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
26	0402WGF2200TCE	220 Ohm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	10	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25091.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
27	0603WAF0000T5E	0 Ohm jumper thick film chip resistor, 0603 SMD package, 0.1W (1/10W), 75V voltage rating, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C21189.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
28	SCR0402JR470	470mOhm +/-5% thick film chip resistor, 0402 SMD package, 62.5mW power rating, 50V voltage rating, operating temperature -55C to +155C, RoHS compliant	1	LCSC	VO / Anhui VICO	https://www.lcsc.com/product-detail/C3017627.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://lccpcb.com/partdetail/VO-SCR0402JR470/C3017627	Anhui, China
29	0402WGFJ030JTCE	3 Ohm +/-5% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-200ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	1	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C273411.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
30	0402WGF1003TCE	100 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25741.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
31	0402WGF1001TCE	1 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C11702.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
32	0402WGF4702TCE	47 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25792.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
33	0402WGF5101TCE	5.1 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25905.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
34	0603WAF1004T5E	1 MOhm +/-1% thick film chip resistor, 0603 SMD package, 0.1W (1/10W), 75V maximum working voltage, 150V maximum overload voltage, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	1	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C22935.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
35	XL-1010RGB-C-WS2812B	1010 addressable RGB SMD LED with built-in WS2812B-compatible IC, 1.0mm x 1.0mm x 0.8mm package, transparent colloid, 4.5V to 5.5V VDD operating range, 800kbits single-wire data interface, 12mA/channel constant current, red/green/blue dominant wavelengths 620-630nm / 520-530nm / 465-475nm, 120 degree viewing angle, operating temperature -20C to +85C, MSL 5a	28	LCSC	Shenzhen Chengxing Electronic Technology Co., Ltd.	https://atta.szscs.com/upload/public/pdf/source/20240218/17D2B08F4295D202020F5662BF6E5539A.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/RGB-LEDs-Built-in-IC_XINGLIGHT-XL-1010RGBC-WS2812B_C5349953.html	1405-07, Building A, Jiaye Building, Huaqiangbei Street, Futian District, Shenzhen, Guangdong, China
36	GT-TC029B-H020-L1N	SPST tactile switch, SMD 4mm x 3mm package, 2.0mm switch height, round black actuator, 250gf operating force, 50mA contact current, 12Vdc voltage rating, 100MOhm insulation resistance, 100000 cycle mechanical life, MSL 1, operating temperature -40C to +85C, RoHS compliant	4	LCSC	G-Switch	https://www.lcsc.com/product-detail/C843665.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://lccpcb.com/partdetail/GSwitchGT_TC029B_H020L1N/C843665	Dongguan, Guangdong, China

	Name	Material/ Description	Used per Device	Supplier	Manufacturer	Link to RoHS Certificate	homogeneous	Amendment	Declaration	Directive 2011/65/EU	Directive (EU) 2015/863	IEC 62321:2008	Link to website	Address
37	XKTF-N02-N	MicroSD card (TF card) push-push SMD connector, self-bouncing card connection mode, 2mm maximum body height, copper alloy contacts with nickel plating, no additional card detection pins, operating temperature -25C to +85C, RoHS compliant	1	LCSC	XKB Connection	https://www.lcsc.com/product-detail/Electrical-Switches_XKB-Connectivty-XKTF-N02-N_C381084.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://lccpcb.com/partdetail/2689Connection-XKTF-N02N/C381084	No. 3 Second Hongye North Road Industrial Zone, Tangxia Town, Dongguan, Guangdong, China
38	ESP32-C6-WROOM-1-N8	MAIN WIFI MODULE; ESP32-C6 based Wi-Fi 6/Bluetooth LE/Zigbee/Thread module, 8 MB Quad SPI flash, on-board PCB antenna, 18.0 x 25.5 x 3.1 mm	1	LCSC	Espressif Systems (Shanghai) Co., Ltd.	https://documentation.espressif.com/api/resource/doc/file/zA7gV1n/FILE/Environmental_Compliance_Declaration_for_Espressif_Chips_and_Modules.pdf	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.espressif.com/en/products/modules/esp32-c6	690 Bibo Road Block 2 Suite 204, Zhangjiang Shanghai, China
39	ME6217C33M5G	Positive fixed LDO voltage regulator, 3.3V output, SOT-23-5 package, 2V to 6.5V operating voltage range, 800mA maximum output current, 180mV dropout voltage at 300mA, 65dB PSRR at 1kHz, +/-1% output voltage accuracy, 100uA typical operating current, 0.1uA typical shutdown current, thermal shutdown and overcurrent protection, operating temperature -40C to +85C, RoHS compliant	1	LCSC	Nanjing Micro One Electronics Inc.	https://www.lcsc.com/product-detail/C427602.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://datasheet.lcsc.com/lcsc/1912111437-MICRO-ONE-Elec-ME6217C33M5G_C427602.pdf	5F, 1st Building, No. 699-8 Xuanwu Avenue, Xuanwu District, Nanjing, Jiangsu, China
40	RT9193-33GB	Positive fixed ultra-low-noise CMOS LDO voltage regulator, 3.3V output, SOT-23-5/SOT-25 package, 2.5V to 5.5V operating voltage range, 300mA maximum output current, 220mV typical / 300mV maximum dropout voltage at 300mA, 70dB PSRR at 100Hz / 50dB at 10kHz, 90uA typical quiescent current, less than 0.01uA typical shutdown current, enable input, current limiting and thermal shutdown protection, low-ESR ceramic capacitor stable, operating temperature -40C to +85C, RoHS compliant and 100% Pb-free	1	LCSC	Richtek Technology Corporation	https://www.richtek.com/assets/product_file/RT9193/DS9193-18.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.richtek.com/product_detail.jsp?pe=RT9193	14F, No. 8, Tai Yuen 1st Street, Chupei City, Hsinchu, Taiwan, R.O.C.
41	BME680	Integrated environmental sensor for gas, pressure, humidity and temperature, 8-pin metal-lid LGA package, 3.0 x 3.0 x 0.93 mm, VDD 1.7V to 3.6V, VDDIO 1.2V to 3.6V, I2C and SPI interfaces, pressure range 300 hPa to 1100 hPa, humidity range 0% to 100% RH, temperature operating range -40C to +85C, RoHS compliant, halogen-free, MSL1	1	LCSC	Bosch Sensortec GmbH	https://www.bosch-sensortec.com/media/boschsensortec/downloads/datasheets/bst-bme680-ds001.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.bosch-sensortec.com/en/products/environmental-sensors/gas-sensors/bme680/	Gerhard-Kindler-Strasse 9, 72770 Reutlingen, Germany
42	SCD41-D-R2_C3659294	Photoacoustic NDIR CO2 sensor with integrated humidity and temperature compensation, SCD4x series, SMD LGA-20 module, 10.1 x 10.1 x 6.5 mm, I2C interface, CO2 output range 0 ppm to 40000 ppm, specified CO2 measurement range 400 ppm to 5000 ppm, supply voltage 2.4V to 5.5V, average supply current 15mA, maximum supply current 205mA, operating temperature -10C to +60C, operating relative humidity 0% to 95% RH, factory calibrated, RoHS and halogen-free	1	LCSC	Sensirion AG	https://sensirion.com/media/documents/54BDF766/69E07F5E/Sensirion_REACH-RoHS-HalFree_CO2-Sensors.pdf	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	No	https://sensirion.com/products/catalog/SCD41?show_inventory=SCD41-D-R2	Laubisruetistrasse 50, 8712 Staefa, Switzerland
43	TYPE-C 16P LTH6.8	USB Type-C female receptacle connector, 16 contacts, vertical surface-mount standing-paste type, USB 3.1 standard, 1 port, 5A maximum power current rating, 20V voltage rating, black insulator, 10000 mating cycles, operating temperature -40C to +85C, RoHS compliant per distributor product data	1	LCSC	Shenzhen Shouhan Technology Co., Ltd.	https://www.lcsc.com/product-detail/USB-Connectors_SHOUHAN-TYPE-C-16P-LTH6-8_C5187468.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://www.lcsc.com/product-detail/USB-Connectors_SHOUHAN-TYPE-C-16P-LTH6-8_C5187468.html	The entire 5th floor, Block B, Phase II, Huangfeng Youth Incubation Base, Haile Road, Bao'an District 39, Shenzhen, Guangdong, China
44	Insight 3D Printed Enclosure	3D printed enclosure material, Bambu PLA Basic filament, model A00-xx, PLA (polylactic acid) 99% by weight with additives 0-1%, CAS 26023-30-3, density 1.24 g/cm3, RoHS test report No. EGZ2303160195C00201R, MSDS No. EGZ2302280031C00102RM1	1	Bambu Lab	Bambu Lab / Shenzhen Tuozhu Technology Co., Ltd.	https://store.bblcdn.eu/s8/default/aa47437d032c445cba4aa6322674b1ee8/Bambu_PLA_Basic_RoHS.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://eu.store.bambulab.com/products/pla-basic-filament	Room 201, Building A, No. 1 First Qianwan Road, Qianhai Shengang Cooperation Zone, Shenzhen, China