

	Name	Material/ Description	Used per Device	Supplier	Manufacturer	Link to RoHS Certificate	homogeneous	Amendment	Declaration	Directive 2011/65/EU	Directive (EU) 2015/863	IEC 62321:2008	Link to website	Address
Urban PCB Base														
1	MAIN PCB	Base Material: FR-4, Dimension: 80.3 mm* 70.5 mm, Layers: 4, Specify Stackup: JLC04161H-7628, PCB Thickness: 1.6mm, PCB Color: Blue, Silkscreen: White, Surface Finish: LeadFree HASL, Material Type: TG155, Outer Copper Weight: 1 oz, Inner Copper Weight: 0.5 oz	1	JLPCPB	JLPCPB / SHENZHEN JLC TECHNOLOGY GROUP CO.,LTD.	https://rs.jlcpcb.com/static/file/rohs-certificate-of-conformity.pdf	Yes	Directive (EU) 2015/863	Lab CoC	Yes	Yes	Yes	https://jlcpcb.com	27TH FLOOR, OLYMPIC BUILDING, SHANGBAO ROAD, FUTIAN DISTRICT, SHENZHEN CITY, GUANGDONG PROVINCE, CHINA
2	ESP32-C6-WROOM-1-N8	MAIN WIFI MODULE; ESP32-C6 based Wi-Fi 6/Bluetooth LE/Zigbee/Thread module, 8 MB Quad SPI flash, on-board PCB antenna, 18.0 x 25.5 x 3.1 mm	1	LCSC	Espressif Systems (Shanghai) Co., Ltd.	https://documentation.espressif.com/api/resource/doc/file/ezA7gV1n/FiLE/Environmental_Compliance_Declaration_for_Espressif_Chips_and_Modules.pdf	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.espressif.com/en/products/modules/esp32-c6	690 Bibo Road Block 2 Suite 204, Zhangjiang Shanghai, China
3	TAJA226K010RNJ	22uF, 10V, +/-10%, TAJ Series standard SMD MnO2 tantalum capacitor, case A/3216, ESR 3 ohm @100kHz, operating temperature -55C to +125C	2	LCSC	KYOCERA AVX Components Corporation	https://www.kyocera-avx.com/docs/compliance/TAN/SMD-MnO2/TAJ-env-doc.zip	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.kyocera-avx.com/products/tantalum-smd-tantalum-mno2/taj-series/	San Bartolo, C. Cojutepeque 4-2, Ilopango, El Salvador
4	GRM188R61E106KA73D	10uF, 25Vdc, +/-10%, X5R, 0603/1608M chip multilayer ceramic capacitor, operating temperature -55C to +85C	2	LCSC	Murata Manufacturing Co., Ltd.	https://www.murata.com/-/media/webrenewal/products/capacitor/ceramic/capacitor/certificate/rohs/cerami capacitor-eu-rohs-certificate.ashx?cvid=2023040401000000000&la=en	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.murata.com/en-us/products/productdetail?partno=GRM188R61E106KA73D	10-1, Higashikotari 1-chome, Nagaokakyo-shi, Kyoto 617-8555, Japan
5	TAJD227K010RNJ	220uF, 10V, +/-10%, TAJ Series standard SMD MnO2 tantalum capacitor, case D/7343, ESR 500mOhm @100kHz, operating temperature -55C to +125C	1	LCSC	KYOCERA AVX Components Corporation	https://www.kyocera-avx.com/docs/compliance/TAN/SMD-MnO2/TAJ-env-doc.zip	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.kyocera-avx.com/products/tantalum-smd-tantalum-mno2/taj-series/	San Bartolo, C. Cojutepeque 4-2, Ilopango, El Salvador
6	CL10A105K08NNNC	1uF, 16Vdc, +/-10%, X5R, 0603/1608 MLCC, CL standard series, operating temperature -55C to +85C	2	LCSC	Samsung Electro-Mechanics Co., Ltd.	https://www.samsungsem.com/files/fileDownload.do?key=ed1dfdfa-645e-4252-b707-17f9b1502dd1	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://product.samsungsem.com/mlcc/CL10A105K08NNN.do	Maeyoung-ro 150 Yeongtong-gu, Suwon, Gyeonggi-do 16674, Republic of Korea
7	CC0603KRX7R9BB104	100nF, 50Vdc, +/-10%, X7R, 0603/1608 SMD MLCC, CC series, tin termination, operating temperature -55C to +125C	1	LCSC	YAGEO Corporation	https://yageogroup.com/content/Resource%20Library/Product%20Environmental%20Compliance/RoHS_Compliance_YAGEO.pdf	Yes	Directive (EU) 2015/863	Other-Non-use certificate for RoHS	Yes	Yes	Other EN IEC 63000:2018	https://yageogroup.com/download/spescheset/CC0603KRX7R9BB104	3F, 233-1, Baoqiao Rd., Xindian Dist., New Taipei City 23145, Taiwan
8	0402B104K500CT	100nF, 50Vdc, +/-10%, X7R, 0402/1005 SMD MLCC, lead-free termination, operating temperature -55C to +125C	1	LCSC	Walsin Technology Corporation	https://www.passivecomponent.com/download/reach_rohs_compliance_declaration-2/?wpdmdl=1343	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.passivecomponent.com/product-search/MLCC/	No.566-1, Kao-Shi Rd., Yangmei District, Taoyuan, Taiwan
9	CL10B104KB8NNNC	100nF, 50Vdc, +/-10%, X7R, 0603/1608 MLCC, CL standard series, operating temperature -55C to +125C	1	LCSC	Samsung Electro-Mechanics	https://www.samsungsem.com/files/fileDownload.do?key=ed1dfdfa-645e-4252-b707-17f9b1502dd1	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://product.samsungsem.com/mlcc/CL10A105K08NNN.do	Maeyoung-ro 150 Yeongtong-gu, Suwon, Gyeonggi-do 16674, Republic of Korea
10	HY-4P贴片	HY series 1x4P right-angle SMD wire-to-board connector, 2.0mm pitch, rated 2A, 250V AC/DC, phosphor bronze/brass contacts with tin plating, Nylon66/LCP housing, UL94V-0, operating temperature -25C to +85C	1	LCSC	BOOMELE / Zhejiang Boom Precision Electronic Co., Ltd.	https://jlcpcb.com/api/file/downloadByFileSystemAccessId/8588894496977666048	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://jlcpcb.com/partdetail/BOOMELE_Boom_Precision_Elec-HY_4P/C146060	West Industrial Zone, Hongqiao Town, Yueqing, Wenzhou, Zhejiang, China
11	X8821WR-05S-N0SN	1x5P XH series 2.5mm pitch right-angle through-hole wire-to-board header, brass contacts with tin plating, PA66 housing, UL94V-0, rated 3A, 250V, operating temperature -25C to +85C	1	LCSC	Guangdong XKB Technology Co., Ltd.	https://datasheet.lcsc.com/datasheet/pdf/158309a3ae20cabd855bb347881e7a9.pdf?productCode=C388742	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/Wire-To-Board-Wire-To-Wire-Connector_XKB-Enterprise-X8821WR-05S-N0SN_C388742.html	No. 3 Second Hongye North Road Industrial Zone, Tangxia Town, Dongguan, Guangdong, China
12	B2B-PH-K-K(LF)(SN)	PH series 1x2P 2.0mm pitch through-hole wire-to-board header, black PA66 housing, UL94V-0, brass/copper alloy contacts with tin plating, rated 2A, 100V, operating temperature -25C to +85C	1	LCSC	JST	https://atta.szlcsc.com/upload/public/pdf/source/20181010/C265101_22107ACC4D8714894FDA2DD97145FA81.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/Wire-To-Board-Wire-To-Wire-Connector_JST-Sales-America-B2B-PH-K-K-LF-SN_C265438.html	2-19-7 Yoyogi, Shibuya-ku, Tokyo 151-8543, Japan
13	HC-PM254-8.5H-2x7PS	2x7P 2.54mm pitch dual-row SMD female header, 14 positions, vertical top entry, 8.5mm insulation height, square holes, brass/copper contacts with gold plating, PA6T base, rated 3A, operating temperature -40C to +105C	1	LCSC	Shenzhen Hong Cheng Electronics Co., Ltd.	https://datasheet.lcsc.com/datasheet/pdf/c4d4929ab33c707dcdf55c4fcb4c76.pdf?productCode=C22373948	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/Female-Headers_Hong-Cheng-HC-PM254-8.5H-2x7PS_C22373948.html	Shenzhen, Guangdong, China
14	ZX-SH1.0-4PWT	SH1.0 series 1x4P 1.0mm pitch right-angle SMD wire-to-board header, LCP housing, brass contacts and solder tabs with tin plating, rated 1A, 50V AC/DC, operating temperature -25C to +85C	1	LCSC	Megastar Precision Electronic (Shenzhen) Co., Ltd.	https://atta.szlcsc.com/upload/public/pdf/source/20230619/390816C24B7A0EB1D042395C380CEA99.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/Wire-To-Board-Wire-To-Wire-Connector_Megastar-ZX-SH1.0-4PWT_C7430446.html	Shenzhen, Guangdong, China

	Name	Material/ Description	Used per Device	Supplier	Manufacturer	Link to RoHS Certificate	homogeneous	Amendment	Declaration	Directive 2011/65/EU	Directive (EU) 2015/863	IEC 62321:2008	Link to website	Address
15	HX ZH1.5-5PWT	ZH1.5mm series 1x5P 1.5mm pitch right-angle SMD wire-to-board header, LCP housing, brass/phosphor bronze contacts and solder tabs with tin plating, rated 1A, 50V AC/DC, operating temperature -25C to +85C	1	LCSC	Shenzhen Hanxia Electronic Co., Ltd.	https://atta.szlcsc.com/upload/public/pdf/source/20240606/4E1F4941E62B043884A0B12E20E18894.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/C22461274.html	Shenzhen, Guangdong, China
16	LESD5D5.0CT1G	Bidirectional ESD/TVS protection diode, SOD-523, 5V reverse stand-off voltage, 18.6V max clamping voltage, 9.4A peak pulse current @8/20us, 174W peak pulse power, IEC61000-4-2 level 4 ESD protection, operating temperature -40C to +125C	4	LCSC	Leshan Radio Company, LTD.	https://www.lrc.cn/Upload/PDF/Product/ESD/LESD5D5.0CT1G.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/LRC-LESD5D5-0CT1G_C383211.html	287 West People Road, Leshan, Sichuan 614000, China
17	1N5819WS_C191023	1N5819WS Schottky barrier diode, SOD-323, 40V maximum DC reverse voltage, 1A average rectified current, 600mV forward voltage @1A, 25A peak forward surge current, molded plastic UL94V-0 case	2	LCSC	Guangdong Hottech Industrial Co., Ltd.	https://atta.szlcsc.com/upload/public/pdf/source/20220428/3CB86FD8D28D653594B4E35F9D5AEFD9.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/C191023.html	No. 803, Building 7, Kangli City, No. 66 Pingli Avenue, Longgang District, Shenzhen, Guangdong, China
18	XL-1608SURC-06	0603/1608 red SMD LED, water clear lens, 1.6 x 0.8 x 0.6mm, 20mA forward current, 50mW max power, 1.9V to 2.2V forward voltage @20mA, 615nm to 630nm dominant wavelength, 625nm peak wavelength, 120 degree viewing angle, operating temperature -40C to +85C	1	LCSC	Shenzhen Chengxing Electronic Technology Co., Ltd.	https://atta.szlcsc.com/upload/public/pdf/source/20250213/F9766CE804FA391355DCDD48DB3E0DAB.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/Light-Emitting-Diodes-LED_XINGLIGHT-XL-1608SURC-06_C965799.html	1405-07, Building A, Jiahe Building, Huaqiangbei Street, Futian District, Shenzhen, Guangdong, China
19	AMS1117-3.3V_C5120796	SOT-89 fixed positive linear voltage regulator (LDO), 3.3V output, 1A max output current, 18V maximum input voltage, 1.4V dropout voltage @1A, 12mA quiescent current, operating temperature 0C to +125C	1	LCSC	Shenzhen Meisenke Electric Industrial Co., Ltd. / MSKSEMI	https://www.lcsc.com/product-detail/C5120796.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://www.maksemi.com/	Hsinchu City, Taiwan; offices in Shenzhen, Hong Kong and Singapore
20	RC0402FR-0710KL	10 kOhm +/-1% thick film chip resistor, RC series, 0402/1005 SMD package, 0.063W (1/16W) at 70C, 50V maximum continuous voltage, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, tin termination	3	LCSC	YAGEO Corporation	https://yageogroup.com/content/Resource%20Library/Product%20Environmental%20Compliance/RoHS_Compliance_YAGEO.pdf	Yes	Directive (EU) 2015/863	Other-Non-use certificate for RoHS	Yes	Yes	Other EN IEC 63000:2018	https://yageogroup.com/component-documentation/download/specsheet/RC0402FR-0710KL	3F, 233-1, Baoqiao Rd., Xindian Dist., New Taipei City 23145, Taiwan
21	0402WGF5101TCE	5.1 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25905.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
22	0402WGF3301TCE	3.3 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	1	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25890.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
23	0402WGF220JTCE	22 Ohm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	4	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25092.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
24	0402WGF4701TCE	4.7 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25900.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
25	0603WAF1004T5E	1 MOhm +/-1% thick film chip resistor, 0603 SMD package, 0.1W (1/10W), 75V maximum working voltage, 150V maximum overload voltage, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	1	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C22935.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
26	ZX-1.27BM-1PSMD	1-position SPST slide/recessed SMD DIP switch, 1.27mm pitch, 25mA at 24V DC switching rating, 100mA at 50V DC non-switching rating, 300V AC dielectric strength, 1000 cycle mechanical life, operating temperature -30C to +85C, black body	1	LCSC	Zhaoxing Precision Electronics (Shenzhen) Co., Ltd. / Megastar	https://atta.szlcsc.com/upload/public/pdf/source/20230821/CEAB8B442A6A36B2EC03530A42E8CA85.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/C7527751.html	Shenzhen, Guangdong, China
27	TYPE-C 16P QTWT	USB Type-C female receptacle connector, 16 contacts, surface mount right-angle/horizontal type, 1 port, 3A power current rating, 5V rating, operating temperature -25C to +85C, 5000 mating cycles, black insulator	1	LCSC	Shenzhen Shouhan Technology Co., Ltd.	https://www.lcsc.com/product-detail/USB-Connectors_SHOUHAN-TYPE-C-16P-QTWT_C5187472.html	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/USB-Connectors_SHOUHAN-TYPE-C-16P-QTWT_C5187472.html	The entire 5th floor, Block B, Phase II, Huafeng Youth Incubation Base, Haile Road, Bao'an District 39, Shenzhen, Guangdong, China
ICS-43434 Noise Sensor PCB														

	Name	Material/ Description	Used per Device	Supplier	Manufacturer	Link to RoHS Certificate	homogeneous	Amendment	Declaration	Directive 2011/65/EU	Directive (EU) 2015/863	IEC 62321:2008	Link to website	Address
28	Noize sensor PCB	FR-4 printed circuit board, 12.7mm x 11.6mm, 2 layers, 1.6mm PCB thickness, blue solder mask, white silkscreen, LeadFree HASL surface finish, TG155 material, 1 oz outer copper, 0.5 oz inner copper	1	JLPCPB	JLPCPB / SHENZHEN JLC TECHNOLOGY GROUP CO.,LTD.	https://rs.jlcpcb.com/static/file/rohs-certificate-of-conformity.pdf	Yes	Directive (EU) 2015/863	Lab CoC	Yes	Yes	Yes	https://jlcpcb.com	27TH FLOOR, OLYMPIC BUILDING, SHANGBAO ROAD, FUTIAN DISTRICT, SHENZHEN CITY, GUANGDONG PROVINCE, CHINA
29	0402B104K500CT	100nF, 50Vdc, +/-10%, X7R, 0402/1005 SMD MLCC, lead-free termination, operating temperature -55C to +125C	1	LCSC	Walsin Technology Corporation	https://www.passivecomponent.com/download/reach_rohs_compliance_declaration-2/?wpdmid=1343	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.passivecomponent.com/product-search/MLCC/	No.566-1, Kao-Shi Rd., Yangmei District, Taoyuan, Taiwan
30	ZX-ZH1.5-5PWT	1x5P ZH-series wire-to-board connector/header, 1.5mm pitch, horizontal/right-angle SMD mounting, 5 pins in 1 row, LCP natural insulator, brass contacts and solder tabs with tin plating, 1A current rating, 250V AC/DC voltage rating, operating temperature -25 C to +85C	1	LCSC	Zhaoxing Precision Electronics (Shenzhen) Co., Ltd. / Megastar	https://www.lcsc.com/product-detail/Wire-To-Board-Connector_Megastar-ZX-ZH1.5-5PWT_C19272408.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://www.lcsc.com/product-detail/Wire-To-Board-Connector_Megastar-ZX-ZH1.5-5PWT_C19272408.html	Shenzhen, Guangdong, China
31	0402WGF1003TCE	100 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	1	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25741.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
32	ICS-43434_C5656610	ICS-43434 bottom-port omnidirectional MEMS microphone with digital I2S output, 24-bit data, 1.65V to 3.63V supply range, 65dBA SNR typical, -26dB FS +/-1dB sensitivity, 120dB SPL acoustic overload point, 60Hz to 20kHz frequency response, 3.50mm x 2.65mm x 0.99mm SMD package	1	LCSC	TDK InvenSense / InvenSense Inc.	https://atta.szlcsc.com/upload/publicpdf/source/231023/D_S-000069-ICS-43434-v1-2-8194c7772d771e21a55310950270497.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://invensense.tdk.com/en-us/products/microphone/ics-43434	1745 Technology Drive, San Jose, CA 95110, U.S.A.
BME280 T/H/P Sensor PCB														
33	Temperature and Humidity Sensor PCB	FR-4 printed circuit board, 12.7mm x 11.6mm, 2 layers, 1.6mm PCB thickness, blue solder mask, white silkscreen, LeadFree HASL surface finish, TG155 material, 1 oz outer copper, 0.5 oz inner copper	1	JLPCPB	JLPCPB / SHENZHEN JLC TECHNOLOGY GROUP CO.,LTD.	https://rs.jlcpcb.com/static/file/rohs-certificate-of-conformity.pdf	Yes	Directive (EU) 2015/863	Lab CoC	Yes	Yes	Yes	https://jlcpcb.com	27TH FLOOR, OLYMPIC BUILDING, SHANGBAO ROAD, FUTIAN DISTRICT, SHENZHEN CITY, GUANGDONG PROVINCE, CHINA
34	CL05A105KA5NQNC	1uF, 25Vdc, +/-10%, X5R, 0402/1005 SMD MLCC, CL series, operating temperature -55C to +85C	1	LCSC	Samsung Electro-Mechanics Co., Ltd.	https://www.samsungsem.com/files/fileDownload.do?key=ed1dfdfa-645e-4252-b707-17f9b1502dd1	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.samsungsem.com/global/product/passive-component/mlcc-dg	Maeyoung-ro 150 Yeongtong-gu, Suwon, Gyeonggi-do 16674, Republic of Korea
35	0402B104K500CT	100nF, 50Vdc, +/-10%, X7R, 0402/1005 SMD MLCC, lead-free termination, operating temperature -55C to +125C	1	LCSC	Walsin Technology Corporation	https://www.passivecomponent.com/download/reach_rohs_compliance_declaration-2/?wpdmid=1343	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.passivecomponent.com/product-search/MLCC/	No.566-1, Kao-Shi Rd., Yangmei District, Taoyuan, Taiwan
36	0402WGF4701TCE	4.7 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	2	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25900.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
37	HY-4P贴片	HY series 1x4P right-angle SMD wire-to-board connector, 2.0mm pitch, rated 2A, 250V AC/DC, phosphor bronze/brass contacts with tin plating, Nylon66/LCP housing, UL94V-0, operating temperature -25C to +85C	2	LCSC	BOOMELE / Zhejiang Boom Precision Electronic Co., Ltd.	https://jlcpcb.com/api/file/downloadByFileSystemAccessId/8588894496977666048	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://jlcpcb.com/parddetail/BOOMELE_Boom_Precision_Elec-HY_4P/C146060	West Industrial Zone, Hongqiao Town, Yueqing, Wenzhou, Zhejiang, China
38	BME280	BME280 digital humidity, pressure and temperature sensor, 8-pin LGA metal-lid package 2.5mm x 2.5mm x 0.93mm, I2C/SPI interface, VDD 1.71V to 3.6V, VDDIO 1.2V to 3.6V, operating range -40 C to +85C, 0% to 100% RH, 300hPa to 1100hPa, MSL1	1	LCSC	Bosch Sensortec GmbH	https://www.bosch-sensortec.com/media/boschsensortec/downloads/datasheets/bst-bme280-ds002.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.bosch-sensortec.com/products/environmental-sensors/humidity-sensors-bme280	Gerhard-Kindler-Strasse 9, 72770 Reutlingen/Kusterdingen, Germany
Urban Button LED PCB														
39	Indicators PCB	FR-4 printed circuit board, 12.7mm x 11.6mm, 2 layers, 1.6mm PCB thickness, blue solder mask, white silkscreen, LeadFree HASL surface finish, TG155 material, 1 oz outer copper, 0.5 oz inner copper	1	JLPCPB	JLPCPB / SHENZHEN JLC TECHNOLOGY GROUP CO.,LTD.	https://rs.jlcpcb.com/static/file/rohs-certificate-of-conformity.pdf	Yes	Directive (EU) 2015/863	Lab CoC	Yes	Yes	Yes	https://jlcpcb.com	27TH FLOOR, OLYMPIC BUILDING, SHANGBAO ROAD, FUTIAN DISTRICT, SHENZHEN CITY, GUANGDONG PROVINCE, CHINA
40	CL05B104K05NNNC	100nF, 16Vdc, +/-10%, X7R, 0402/1005 SMD MLCC, CL series, operating temperature -55C to +125C	5	LCSC	Samsung Electro-Mechanics Co., Ltd.	https://www.samsungsem.com/files/fileDownload.do?key=ed1dfdfa-645e-4252-b707-17f9b1502dd1	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	Other EN IEC 63000:2018	https://www.samsungsem.com/global/product/passive-component/mlcc-dg	Maeyoung-ro 150 Yeongtong-gu, Suwon, Gyeonggi-do 16674, Republic of Korea

	Name	Material/ Description	Used per Device	Supplier	Manufacturer	Link to RoHS Certificate	homogeneous	Amendment	Declaration	Directive 2011/65/EU	Directive (EU) 2015/863	IEC 62321:2008	Link to website	Address
41	ZX-SH1.0-4PWT	SH1.0 series 1x4P 1.0mm pitch right-angle SMD wire-to-board header, LCP housing, brass contacts and solder tabs with tin plating, rated 1A, 50V AC/DC, operating temperature -25C to +85C	1	LCSC	Megastar Precision Electronic (Shenzhen) Co., Ltd.	https://atta.szlcsc.com/upload/public/pdf/source/20230619/390816C2487A0EB1D042395C380CEA99.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/Wire-To-Board-Wire-To-Wire-Connector_Megastar-ZX-SH1.0-4PWT_C7430446.html	Shenzhen, Guangdong, China
42	0402WGF2200TCE	220 Ohm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	1	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25091.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
43	0402WGF1002TCE	10 kOhm +/-1% thick film chip resistor, 0402 SMD package, 0.0625W (1/16W), 50V voltage rating, +/-100ppm/C temperature coefficient, operating temperature -55C to +155C, lead-free environmental protection type	1	LCSC	Uniroyal Electronics Industry Co., Ltd.	https://www.uni-royal.cn/images/userfile/file/1758332861b44461032e5e47fc.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://www.lcsc.com/product-detail/C25744.html	88 Longteng Road, Economic & Technical Development Zone, Kunshan City, Jiangsu, China
44	XL-1010RGBC-WS2812B	1010 addressable RGB SMD LED with built-in WS2812B-compatible IC, 1.0mm x 1.0mm x 0.8mm package, transparent colloid, 4.5V to 5.5V VDD operating range, 800kpbs single-wire data interface, 12mA/channel constant current, red/green/blue dominant wavelengths 620-630nm / 520-530nm / 465-475nm, 120 degree viewing angle, operating temperature -20C to +85C, MSL 5a	2	LCSC	Shenzhen Chengxing Electronic Technology Co., Ltd.	https://atta.szlcsc.com/upload/public/pdf/source/20240218/17D2BD8F4295D202E0F5662BF6E5539A.pdf	Yes	Directive (EU) 2015/863	Datasheet	Yes	Yes	No	https://www.lcsc.com/product-detail/RGB-LEDs-Built-in-IC_XINGLIGHT-XL-1010RGBC-WS2812B_C5349953.html	1405-07, Building A, Jiahe Building, Huaqiangbei Street, Futian District, Shenzhen, Guangdong, China
45	TS-1187A-C-H-B	SPST SMD tactile switch, 5.1mm x 5.1mm x 4.0mm, round actuator, 260gf operating force, 0.25mm travel, 50mA 12V DC contact rating, 100mOhm max contact resistance, 100MOhm min insulation resistance at 500V DC, 250V AC dielectric strength for 1 minute, operating temperature -30C to +85C	1	LCSC	XKB Industrial Precision Co., Limited	https://www.lcsc.com/product-detail/Tactile-Switches_XKB-Connectivity-TS-1187A-C-H-B_C528025.html	Yes	Directive (EU) 2015/863	Distributor CoC	Yes	Yes	No	https://www.lcsc.com/product-detail/Tactile-Switches_XKB-Connectivity-TS-1187A-C-H-B_C528025.html	No. 3 Second Hongye North Road Industrial Zone, Tangxia Town, Dongguan, Guangdong, China
46	XC6206P332MR-G_C5446	Positive fixed LDO voltage regulator, 3.3 V output, 200mA output current, SOT-23-3 package, 6.0V maximum operating voltage, low quiescent current 1uA typ, low ESR ceramic capacitor compatible, built-in current limit and short-circuit protection, +/-2% output voltage accuracy, operating ambient temperature -40C to +85C, EU RoHS compliant and Pb-free	1	LCSC	Torex Semiconductor Ltd.	https://www.torexsemi.com/sustainability/environment/hazardous-chemical	Yes	Directive (EU) 2015/863	Manufacturer CoC	Yes	Yes	No	https://product.torexsemi.com/en/series/xc6206	5F MEBKS TOYOSU 6-4-34 Toyosu, Koto-Ku, Tokyo 135-0061 Japan
3D Printed Enclosure														
47	Urban 3D Printed Enclosure	3D printed enclosure material, Bambu PLA Basic filament, model A00-xx, PLA (polylactic acid) 99% by weight with additives 0-1%, CAS 26023-30-3, density 1.24 g/cm3, RoHS test report No. EGZ2303160195C00201R, MSDS No. EGZ2302280031C00102RM1	1	Bambu Lab	Bambu Lab / Shenzhen Tuozhu Technology Co., Ltd.	https://store.bblcdn.eu/s8/default/aa47437d032c445cba4aa6322674b1e8/Bambu_PLA_Basic_RoHS.pdf	Yes	Directive (EU) 2015/863	Test Report	Yes	Yes	Yes	https://eu.store.bambulab.com/products/pla-basic-filament	Room 201, Building A, No. 1 First Qianwan Road, Qianhai Shengqiang Cooperation Zone, Shenzhen, China