

# Tools and Algorithms for Deciding Relations on Timed Automata

B Tech project, supervised by S Arun-Kumar, verification group

Mihir Mehta

Department of Computer Science and Engineering  
Indian Institute of Technology, Delhi  
[cs1090197@cse.iitd.ac.in](mailto:cs1090197@cse.iitd.ac.in)

May 12, 2013

# Outline

Automata without timing and relations on them

Timed automata and relations on them

Algorithms

# Labeled transition systems

## Definition

*Labelled Transition System*: A labelled transition system (LTS) [1] is an automaton which is described by

- ▶  $S$ , a set of *states*
- ▶  $Act$ , a set of *actions*
- ▶  $\rightarrow \subseteq S \times Act \times S$ , a *transition relation*.
- ▶ optionally,  $I \subseteq S$ , a set of initial states. If there is exactly one initial state, then the LTS is said to be *rooted*.

# Relations on LTS I

## Definition

*Strong bisimulation*: A binary relation  $R$  on the states of an LTS is a strong bisimulation if and only if, for all  $(s_1, s_2) \in R$  and  $a \in Act$ .

$$\forall s'_1 (s_1 \xrightarrow{a} s'_1 \Rightarrow \exists s'_2. (s_2 \xrightarrow{a} s'_2 \wedge (s'_1, s'_2) \in R)) \wedge$$

$$\forall s'_2 (s_2 \xrightarrow{a} s'_2 \Rightarrow \exists s'_1. (s_1 \xrightarrow{a} s'_1 \wedge (s'_1, s'_2) \in R))$$

## Definition

It can be shown that the union of all strong bisimulations over the set of states is a strong bisimulation. This binary relation is called *strong bisimilarity*, denoted by  $\sim$ .

# Outline

Automata without timing and relations on them

Timed automata and relations on them

Algorithms

# Timed Automata

## Definition

*Timed Automaton:* A timed automaton [2] over a finite set of clocks  $C$  and a finite set of actions  $Act$  is a 4-tuple  $(L, l_0, E, I)$ .

- ▶  $L$  is a finite set of locations.
- ▶  $l_0$  is the initial location.
- ▶  $E \subseteq L \times B(C) \times Act \times 2^C \times L$  is a finite set of edges.
- ▶  $I : L \rightarrow B(C)$  assigns invariants to each edge location.
- ▶  $B(C)$  is the set of clock constraints over  $C$ .

# Relations on timed automata I

## Definition

*Strong time abstracted bisimulation:* A binary relation  $R$  is a strong time abstracted bisimulation (STaB) if and only if, for all  $(s_1, s_2) \in R$ ,  $a \in \text{Act}$ ,  $d \in R_{\geq 0}$

$$\forall s'_1 (s_1 \xrightarrow{a} s'_1 \Rightarrow \exists s'_2. (s_2 \xrightarrow{a} s'_2 \wedge (s'_1, s'_2) \in R)) \wedge$$

$$\forall s'_2 (s_2 \xrightarrow{a} s'_2 \Rightarrow \exists s'_1. (s_1 \xrightarrow{a} s'_1 \wedge (s'_1, s'_2) \in R)) \wedge$$

$$\forall s'_1 (s_1 \xrightarrow{d} s'_1 \Rightarrow \exists (s'_2, d'). (s_2 \xrightarrow{d'} s'_2 \wedge (s'_1, s'_2) \in R)) \wedge$$

$$\forall s'_2 (s_2 \xrightarrow{d} s'_2 \Rightarrow \exists (s'_1, d'). (s_1 \xrightarrow{d'} s'_1 \wedge (s'_1, s'_2) \in R))$$

It can be shown that the union of all strong time abstracted bisimulations over the set of (location, valuation) pairs is a strong time abstracted bisimulation. This binary relation is called *strong time abstracted bisimilarity*.

## Definition

## Relations on timed automata II

*Time abstracted delay bisimulation:* A binary relation  $R$  is a time abstracted delay bisimulation (TadB) if and only if, for all  $(s_1, s_2) \in R$ ,  $a \in \text{Act}$ ,  $d \in R_{\geq 0}$

$$\forall s'_1 (s_1 \xrightarrow{a} s'_1 \Rightarrow \exists (s'_2, d). (s_2 \xrightarrow{d} \xrightarrow{a} s'_2 \wedge (s'_1, s'_2) \in R)) \wedge$$

$$\forall s'_2 (s_2 \xrightarrow{a} s'_2 \Rightarrow \exists (s'_1, d). (s_1 \xrightarrow{d} \xrightarrow{a} s'_1 \wedge (s'_1, s'_2) \in R)) \wedge$$

$$\forall s'_1 (s_1 \xrightarrow{d} s'_1 \Rightarrow \exists (s'_2, d'). (s_2 \xrightarrow{d'} s'_2 \wedge (s'_1, s'_2) \in R)) \wedge$$

$$\forall s'_2 (s_2 \xrightarrow{d} s'_2 \Rightarrow \exists (s'_1, d'). (s_1 \xrightarrow{d'} s'_1 \wedge (s'_1, s'_2) \in R))$$

It can be shown that the union of all time abstracted delay bisimulations over the set of (location, valuation) pairs is a time abstracted delay bisimulation. This binary relation is called *time abstracted delay bisimilarity*.

### Definition



## Relations on timed automata III

*Time abstracted observational bisimulation*: A binary relation  $R$  is a time abstracted observational bisimulation (TaoB) if and only if, for all  $(s_1, s_2) \in R$ ,  $a \in \text{Act}$ ,  $d \in R_{\geq 0}$

$$\forall s'_1 (s_1 \xrightarrow{a} s'_1 \Rightarrow \exists (s'_2, d, d'). (s_2 \xrightarrow{d} \xrightarrow{a} \xrightarrow{d'} s'_2 \wedge (s'_1, s'_2) \in R)) \wedge$$

$$\forall s'_2 (s_2 \xrightarrow{a} s'_2 \Rightarrow \exists (s'_1, d, d'). (s_1 \xrightarrow{d} \xrightarrow{a} \xrightarrow{d'} s'_1 \wedge (s'_1, s'_2) \in R)) \wedge$$

$$\forall s'_1 (s_1 \xrightarrow{d} s'_1 \Rightarrow \exists (s'_2, d'). (s_2 \xrightarrow{d'} s'_2 \wedge (s'_1, s'_2) \in R)) \wedge$$

$$\forall s'_2 (s_2 \xrightarrow{d} s'_2 \Rightarrow \exists (s'_1, d'). (s_1 \xrightarrow{d'} s'_1 \wedge (s'_1, s'_2) \in R))$$

It can be shown that the union of all time abstracted observational bisimulations over the set of (location, valuation) pairs is a time abstracted observational bisimulation. This binary relation is called *time abstracted observational bisimilarity*.

# Outline

Automata without timing and relations on them

Timed automata and relations on them

Algorithms

## Creating the zone valuation graph

Initialise the queue  $Q$  with a single element  $(null, null, l_0)$ ;

Initialise the graph  $zone\_graph$  with a single node  $(l_0, v_0 \uparrow)$  with an  $\epsilon$  self-loop;

**while**  $Q$  is not empty **do**

    Dequeue  $(l_{parent}, t, l_{child})$  from  $Q$ ;

**if**  $l_{parent} \neq null$  **then**

**foreach** zone  $Z_{parent}$  of  $l_{parent}$  **do**

            Add new zones to the zones of  $l_{child}$  so that all zones reachable from  $Z_{parent}$  are represented;

            Abstract if necessary;

            Update edges from  $Z_{parent}$  to the new zones of  $l_{child}$  **if**  
            new zones are created in  $l_{child}$  or  $l_{parent}$  is null **then**

**foreach** outgoing transition  $t'$  of  $l_{child}$  **do**

                    Enqueue  $(l_{child}, t', t'.target)$  in  $Q$ ;


**end**

**end**

**end**

**end**

## Zone valuation graph example



**Figure:** Timed automaton. Here, the states are  $\{0\}$ , the actions are  $\{a\}$ , and the clocks are  $\{X, Y\}$ .

## Zone valuation graph example




Figure: Zones after one iteration.

## Zone valuation graph example




Figure: Zones after two iterations.

## Zone valuation graph example




Figure: Zones after three iterations without abstraction.

## Zone valuation graph example




Figure: Zones after three iterations with abstraction.



# Zone valuation graph example




Figure: Zone graph with bisimilarity classes.

# Verifying relations on pairs of timed automata.

- ▶ Origin for this algorithm - [3]
- ▶ General method to compute  $(\rho, \sigma)$ -bisimilarities on two LTS, starting from their initial locations.
- ▶ Can be adapted for a certain class of timed and time abstracted relations by using zone valuation graphs.
- ▶ For every relation  $R$  satisfying this property, functions  $f_P$  and  $f_Q$  must exist such that the proposition  $s_P R s_Q$  resolves to one of these:
  - ▶ yes
  - ▶ no
  - ▶ if and only if

$$\begin{aligned} & \forall (s'_P, L'_Q) \in f_P(s_P) : \exists s'_Q \in L'_Q : s'_P R s'_Q \quad \wedge \\ & \forall (L'_P, s'_Q) \in f_Q(s_Q) : \exists s'_P \in L'_P : s'_P R s'_Q \end{aligned}$$

# Verifying relations on pairs of timed automata.

- For STaB, we define  $f_P$  and  $f_Q$  as

$$\begin{aligned}f_P(s_P) &= \{(s'_P, L'_Q) \mid s_P \xrightarrow{a} s'_P, L_Q = \{s'_Q \mid s_Q \xrightarrow{a} s'_Q\}\} \\ &\quad \cup \{(s'_P, L'_Q) \mid s_P \xrightarrow{\epsilon} s'_P, L_Q = \{s'_Q \mid s_Q \xrightarrow{\epsilon} s'_Q\}\} \\ f_Q(s_Q) &= \{(L'_P, s'_Q) \mid s_Q \xrightarrow{a} s'_Q, L_P = \{s'_P \mid s_P \xrightarrow{a} s'_P\}\} \\ &\quad \cup \{(L'_P, s'_Q) \mid s_Q \xrightarrow{\epsilon} s'_Q, L_P = \{s'_P \mid s_P \xrightarrow{\epsilon} s'_P\}\}\end{aligned}$$

- For TadB, we define  $f_P$  and  $f_Q$  as

$$\begin{aligned}f_P(s_P) &= \{(s'_P, L'_Q) \mid s_P \xrightarrow{a} s'_P, L_Q = \{s'_Q \mid s_Q \xrightarrow{\epsilon} \xrightarrow{a} s'_Q\}\} \\ &\quad \cup \{(s'_P, L'_Q) \mid s_P \xrightarrow{\epsilon} s'_P, L_Q = \{s'_Q \mid s_Q \xrightarrow{\epsilon} s'_Q\}\} \\ f_Q(s_Q) &= \{(L'_P, s'_Q) \mid s_Q \xrightarrow{a} s'_Q, L_P = \{s'_P \mid s_P \xrightarrow{\epsilon} \xrightarrow{a} s'_P\}\} \\ &\quad \cup \{(L'_P, s'_Q) \mid s_Q \xrightarrow{\epsilon} s'_Q, L_P = \{s'_P \mid s_P \xrightarrow{\epsilon} s'_P\}\}\end{aligned}$$

- For TaoB, we define  $f_P$  and  $f_Q$  as

$$\begin{aligned}f_P(s_P) &= \{(s'_P, L'_Q) \mid s_P \xrightarrow{a} s'_P, L_Q = \{s'_Q \mid s_Q \xrightarrow{\epsilon} \xrightarrow{a} \xrightarrow{\epsilon} s'_Q\}\} \\ &\quad \cup \{(s'_P, L'_Q) \mid s_P \xrightarrow{\epsilon} s'_P, L_Q = \{s'_Q \mid s_Q \xrightarrow{\epsilon} s'_Q\}\} \\ f_Q(s_Q) &= \{(L'_P, s'_Q) \mid s_Q \xrightarrow{a} s'_Q, L_P = \{s'_P \mid s_P \xrightarrow{\epsilon} \xrightarrow{a} \xrightarrow{\epsilon} s'_P\}\} \\ &\quad \cup \{(L'_P, s'_Q) \mid s_Q \xrightarrow{\epsilon} s'_Q, L_P = \{s'_P \mid s_P \xrightarrow{\epsilon} s'_P\}\}\end{aligned}$$

# Verifying relations on pairs of timed automata.

```
begin
  if lookup(yes_table, sp, sq) then
    return true;
  else
    if lookup(yes_table, sp, sq) then
      return false;
    else
      insert(yes_table, sp, sq);
      Set vp;
      foreach (s'_p, L'_Q) in f_P(sp) do
        Reset vp;
        foreach s'_Q in L'_Q do
          if CheckStatesRelation(P, Q, s'_p, s'_Q, yes_table, no_table) then
            Set vp;
          end
        end
      end
      Set vq;
      foreach (s'_Q, L'_P) in f_Q(sq) do
        Reset vq;
        foreach s'_p in L'_P do
          if CheckStatesRelation(P, Q, s'_p, s'_Q, yes_table, no_table) then
            Set vq;
          end
        end
      end
      if vp ∧ vq then
        return true;
      else
        remove(yes_table, sp, sq);
        insert(yes_table, sp, sq);
        return false;
      end
    end
  end
end
```

**Procedure** CheckStatesRelation( $P, Q, s_p, s_q, \text{yes\_table}, \text{no\_table}$ )

# Verifying relations on pairs of timed automata.


**begin**

Create zone valuation graphs  $G_P, G_Q$  of  $T_P, T_Q$ ;  
Find the zone  $s_P$  in  $G_P$  which contains the initial state of  $T_P$ ;  
Find the zone  $s_Q$  in  $G_Q$  which contains the initial state of  $T_Q$ ;  
Initialise *yes\_table* and *no\_table* to empty tables;  
**return** CheckStatesRelation( $G_P, G_Q, s_P, s_Q, \text{yes\_table}, \text{no\_table}$ );


**end**

**Procedure** CheckAutomataRelation( $T_P, T_Q$ )

# Verifying relations: example




(a) First




(b) Second

Figure: Timed automata.

# Verifying relations: example



(a) First



(b) Second

Figure: Zone valuation graphs.

# References I



Keller, R.M.:

Formal verification of parallel programs.

Commun. ACM **19**(7) (July 1976) 371–384



Alur, R., Dill, D.L.:

A theory of timed automata.

Theoretical Computer Science **126** (1994) 183–235



Arun-Kumar, S.:

On bisimilarities induced by relations on actions.

In: Software Engineering and Formal Methods, 2006. SEFM 2006. Fourth IEEE International Conference on, IEEE (2006) 41–49