

The Sen API

Interface Control Document

An example, generated from the data model by Sen. The reference that follows — every package, every type, every table — is written by the tool and is rewritten whenever the model changes.

This page is not. It is an ordinary Typst file included at a point the generated document leaves open, which is how a project puts its own cover, approvals and appendices around a reference it never has to edit.

Placeholder for your own project or product assets

Contents

About this document	3
Model overview	4
Reading the tables	5
components	6
ether	7
explorer	13
influx	14
jsonrpc	15
logmaster	26
py	27
recorder	28
replayer	30
rest	32
shell	38
db	43
kernel	44
log	75
Built-in types	78
Index	79

About this document

This is an example published with Sen's documentation. It was produced by running the model through `sen generate typst` and compiling the result, with no editing in between.

Everything from *Model overview* onwards is generated. It follows the model and only the model: if a type is added, renamed or given a new description, the next build says so, and nothing anyone wrote by hand is lost in the process.

This page, and the cover before it, are not generated. They are Typst files of your own that the document includes at points it leaves open for you:

<code>--front-matter</code>	A cover, before the contents.
<code>--before-reference</code>	Anything between the contents and the model — a scope, a set of conventions, an approvals table. This page.
<code>--after-reference</code>	Appendices, after the model.
<code>--style</code>	Every decision about how the document looks.

The generator does not read any of those files. It writes an `#raw("#include")` and Typst resolves it when the document is compiled, so a cover page can be anything Typst can set — and changing it never means regenerating the model.

Model overview

335 types in 13 packages. 13 classes in 11 independent hierarchies.

Packages

Package	Types	Object classes	Fixed records	Enumerations	Variant records	Arrays	Optionals
components	—	—	—	—	—	—	—
ether	31	—	20	1	3	4	3
explorer	1	—	1	—	—	—	—
influx	3	—	1	1	—	1	—
jsonrpc	41	2	17	—	1	8	13
logmaster	3	2	1	—	—	—	—
py	3	1	1	—	—	1	—
recorder	6	1	2	1	—	2	—
replayer	4	2	1	1	—	—	—
rest	37	—	20	5	—	9	3
shell	27	1	20	3	1	2	—
db	3	—	3	—	—	—	—
kernel	160	4	80	23	8	37	8
log	16	—	11	1	1	3	—

Class hierarchy across all packages

components.jsonrpc.JsonRpcServer	15
components.jsonrpc.StaticFileServer	18
components.logmaster.LogMaster	26
components.logmaster.Logger	26
components.py.PythonInterpreter	27
components.recorder.Recorder	28
components.replayer.Replay	30
components.replayer.Replayer	30
components.shell.Shell	38
kernel.KernelApi	44
kernel.VirtualClock	44
└─ kernel.VirtualKernelClock	44
└─ kernel.VirtualMasterClock	44

Reading the tables

Every property carries three flags, in this order.

Flag	Meaning
R0	Read-only: the value is published by whoever owns it and cannot be set from outside.
RW	Read-write: the value can be set as well as read.
D	Dynamic: the value changes over the life of an instance.
S	Static: the value is fixed once an instance exists.
C	Confirmed: delivery is acknowledged, and the update is retried until it arrives.
BE	Best effort: the update is sent once and may be lost.

components

ether

31 types.

Fixed records

BusConfig	Remember to set these to the same value in all related Sen instances	7
BusJoined		7
BusLeft		7
ByteRange	Range of values of a u8	8
Configuration	Overall component configuration	8
DiscoveryHubAddress	TCP-based discovery hub parameters	8
Endpoint		8
Ephemeral	Let the operating system select an ephemeral port	8
Hello		8
MulticastAddressRange	Inclusive IPv4 multicast address range	9
MulticastDiscovery	Multicast-based discovery parameters	9
PinnedPort	Bind exactly this port, fail closed if taken	9
PortConfig	This configuration is per process and does not need to match across Sen instances. Exclusions apply to a pinned port, not to an ephemeral one: an ephemeral bind asks the OS for any free port and does not learn which it was given. udpUnicast cannot be pinned. Its socket is per peer and UDP has no four-tuple to demultiplex on, so a second peer either fails to bind or silently takes the first peer's traffic.	9
PortRange	Inclusive port range	9
ProbePortRange	Bind within [min,max], random start, walk forward	10
ProtocolVersion		10
QueueConfig		10
Ready		10
SessionPresenceBeam		10
TcpDiscovery	TCP-based discovery parameters	10

BusConfig STRUCTURE

Remember to set these to the same value in all related Sen instances

Name	Type	Description
multicastRange	MulticastRange	Defaults to the Organization Local scope (RFC 2365): [239, [192-195], [0-255], [0-255] Remember to keep a range wide enough for avoiding collisions if you have many buses.
multicastExclusions	MulticastAddress Exclusions	Address ranges that must not be allocated
multicastPort	u16	Defaults to 50985 Change this in case you have limited control over the infrastructure.
multicastDisabled	bool	If true, no multicast traffic is performed and all the bus settings above become meaningless. Defaults to false.

Named by [Configuration](#).

BusJoined STRUCTURE

Name	Type	Description
participantId	u32	
busId	u32	
busName	string	

Named by [ControlMessage](#).

BusLeft STRUCTURE

Name	Type	Description
participantId	u32	
busId	u32	

Name	Type	Description
busName	string	

Named by [ControlMessage](#).

ByteRange STRUCTURE

Range of values of a u8

Name	Type	Description
min	u8	minimum range
max	u8	needs to be >= min

Named by [MulticastRange](#).

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
discovery	DiscoveryConfig	Discovery-related parameters
busOutQueue	QueueConfig	Queue for broadcasting to buses
processUdpOutQueue	QueueConfig	Queue for communicating with processes over UDP
processTcpOutQueue	QueueConfig	Queue for communicating with processes over TCP
busConfig	BusConfig	Bus transport configuration
portExclusions	PortExclusions	Port ranges that this process must not use
portConfig	PortConfig	If not present, all port bindings are Ephemeral
runDiscoveryHub	u16	If present, run the TCP discovery hub on this port
networkDevice	string	If present, the network device to use

DiscoveryHubAddress STRUCTURE

TCP-based discovery hub parameters

Name	Type	Description
port	u16	Port where the discovery hub is running
host	string	name or IP of the host where the discovery hub is running

Named by [TcpDiscovery](#).

Endpoint STRUCTURE

Name	Type	Description
ip	u32	
port	u16	

Named by [EndpointList](#).

Ephemeral STRUCTURE

Let the operating system select an ephemeral port

Named by [PortBinding](#).

Hello STRUCTURE

Name	Type	Description
info	sen.kernel.ProcessInfo	

Name	Type	Description
udpPort	u16	
version	ProtocolVersion	

Named by [ControlMessage](#).

MulticastAddressRange STRUCTURE

Inclusive IPv4 multicast address range

Name	Type	Description
min	string	
max	string	

Named by [MulticastAddressExclusions](#).

MulticastDiscovery STRUCTURE

Multicast-based discovery parameters

Name	Type	Description
beamPeriod	sen.Duration	How often are we beaming our presence
beamExpirationTime	sen.Duration	Expiry time used by the beam tracker
mcastGroup	string	Defaults to '239.255.0.44'
port	u16	Defaults to 60543
device	string	Device to use for the network communication
allowVirtual Interfaces	bool	If true, virtual (NO_CARRIER) interfaces are also considered

Named by [DiscoveryConfig](#).

PinnedPort STRUCTURE

Bind exactly this port, fail closed if taken

Name	Type	Description
port	u16	

Named by [PortBinding](#).

PortConfig STRUCTURE

This configuration is per process and does not need to match across Sen instances. Exclusions apply to a pinned port, not to an ephemeral one: an ephemeral bind asks the OS for any free port and does not learn which it was given. udpUnicast cannot be pinned. Its socket is per peer and UDP has no four-tuple to demultiplex on, so a second peer either fails to bind or silently takes the first peer's traffic.

Name	Type	Description
tcpAcceptor	PortBinding	inbound TCP listener
udpUnicast	PortBinding	per-peer UDP unicast; must be Ephemeral
tcpSource	PortBinding	outbound TCP source port

Named by [Configuration](#).

PortRange STRUCTURE

Inclusive port range

Name	Type	Description
min	u16	

Name	Type	Description
max	u16	

Named by [PortExclusions](#).

ProbePortRange STRUCTURE

Bind within [min,max], random start, walk forward

Name	Type	Description
min	u16	
max	u16	

Named by [PortBinding](#).

ProtocolVersion STRUCTURE

Name	Type	Description
kernel	u32	
ether	u32	

Named by [Hello](#).

QueueConfig STRUCTURE

Name	Type	Description
evictionPolicy	QueueEvictionPolicy	What to do when a queue is full
maxSize	u64	Maximum element count, 0 means unbounded
warningLevel	u64	Element count where warning will be issued, 0 means none

Named by [Configuration](#).

Ready STRUCTURE

Named by [ControlMessage](#).

SessionPresenceBeam STRUCTURE

Name	Type	Description
protocolVersion	u16	
info	sen.kernel.ProcessInfo	
beamPeriod	sen.Duration	
endpoints	EnpointList	

TcpDiscovery STRUCTURE

TCP-based discovery parameters

Name	Type	Description
beamPeriod	sen.Duration	How often are we beaming our presence
beamExpirationTime	sen.Duration	Expiry time used by the beam tracker
hubAddress	DiscoveryHubAddress	Where to find the discovery hub
allowVirtual Interfaces	bool	If true, virtual (NO_CARRIER) interfaces are also considered

Named by [DiscoveryConfig](#).

Enumerations

QueueEvictionPolicy

What to do when a queue is full

11

QueueEvictionPolicy

ENUMERATION

What to do when a queue is full

Held as u32.

dropOldest	0
dropNewest	1

Named by QueueConfig.

Variant records

ControlMessage

DiscoveryConfig

PortBinding

Configuration parameters related to the discovery protocol

11

11

11

ControlMessage

VARIANT

Type	Description
Hello	
Ready	
BusJoined	
BusLeft	

DiscoveryConfig

VARIANT

Configuration parameters related to the discovery protocol

Type	Description
MulticastDiscovery	
TcpDiscovery	

Named by Configuration.

PortBinding

VARIANT

Type	Description
Ephemeral	
PinnedPort	
ProbePortRange	

Named by PortConfig.

Arrays

EnpointList

MulticastAddressExclusions

MulticastRange

PortExclusions

Range of values of a IPv4 multicast address

11

12

12

12

EnpointList

SEQUENCE

```
sequence<Endpoint, 27> EnpointList;
```

Named by SessionPresenceBeam.

MulticastAddressExclusions

SEQUENCE

```
sequence<MulticastAddressRange> MulticastAddressExclusions;
```

Named by [BusConfig](#).

MulticastRange

SEQUENCE

Range of values of a IPv4 multicast address

```
array<ByteRange, 4> MulticastRange;
```

Named by [BusConfig](#).

PortExclusions

SEQUENCE

```
sequence<PortRange> PortExclusions;
```

Named by [Configuration](#).

Optionals

MaybeDeviceName	12
MaybeDiscoveryHubPort	12
MaybePortConfig	12

MaybeDeviceName

OPTIONAL

```
optional<string> MaybeDeviceName;
```

MaybeDiscoveryHubPort

OPTIONAL

```
optional<u16> MaybeDiscoveryHubPort;
```

MaybePortConfig

OPTIONAL

```
optional<PortConfig> MaybePortConfig;
```

explorer

1 types.

Fixed records

Configuration	Overall component configuration	13
-------------------------------	---------------------------------	----

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
layoutFile	string	the imgui layout file. Defaults to ""

influx

3 types.

Fixed records

[Configuration](#) Overall component configuration

14

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
samplingPeriod	sen.Duration	sampling period for the recordings
selections	SelectionList	objects to be monitored (using sql)
telegrafAddress	string	ip or name of the Telegraf server
telegrafPort	u16	port used by the Telegraf server
protocol	Protocol	protocol used
batchSize	u32	points to batch before emission (0 means no batching)

Enumerations

[Protocol](#)

14

Protocol ENUMERATION

Held as u8.

udp	0
tcp	1

Named by [Configuration](#).

Arrays

[SelectionList](#)

14

SelectionList SEQUENCE

```
sequence<string> SelectionList;
```

Named by [Configuration](#).

jsonrpc

41 types.

Object classes

JsonRpcServer	JsonRpcServer -- the JSON-RPC over WebSocket external API, expressed as a Sen class. One instance per connected client lives on `local.jsonrpc`. Methods are the RPC surface; events are the server-pushed notifications. Wire framing (envelope, id, error mapping) is the dispatcher's job, not this class's. Wire-shape convention: JSON-RPC named params (`"params": { ... }`) use the same field names as the STL method's argument list. The dispatcher treats every method's params object as `{ <argName>: <value>, ... }` and walks `method->getArgs()` to build the VarList in declaration order. That lets the inbound dispatch path go through Sen's meta machinery with no per-method translation.	15
StaticFileServer	Server-wide registry of in-memory static-file bundles, served alongside the WebSocket+JSON-RPC surface by the same uWS app. Internal-only: lives on the configurable control bus (defaults to `local.jsonrpc_control`), not on the data-plane bus that hosts authenticated per-connection JsonRpcServer instances. The component publishes exactly one instance.	18

JsonRpcServer CLASS

JsonRpcServer -- the JSON-RPC over WebSocket external API, expressed as a Sen class. One instance per connected client lives on `local.jsonrpc`. Methods are the RPC surface; events are the server-pushed notifications. Wire framing (envelope, id, error mapping) is the dispatcher's job, not this class's. Wire-shape convention: JSON-RPC named params (`"params": { ... }`) use the same field names as the STL method's argument list. The dispatcher treats every method's params object as `{ <argName>: <value>, ... }` and walks `method->getArgs()` to build the VarList in declaration order. That lets the inbound dispatch path go through Sen's meta machinery with no per-method translation.

Name	Type	Flags	Description
identity	Identity	RO S BE	Identity of the connected client.

Method	Signature	Description
ping	() → string	Liveness probe.
listTopology	() → SessionInfoList	Snapshot of the currently-detected sessions, each with the buses currently detected inside it. The kernel's discovery surface is asynchronous; this returns whatever was visible at the moment of the call. Use `subscribeTopology` for live updates.
subscribeTopology	()	Sticky subscription to topology changes. Idempotent per connection. Wires a `topologyChanged` push immediately with the current full snapshot, then again on every session or bus add/remove. Cancel with `unsubscribeTopology`; the subscription is also torn down automatically when the connection closes.
unsubscribeTopology	()	Cancel the topology subscription created by `subscribeTopology`. Idempotent.
getTypes	() → sen.kernel.StringList	Returns the qualified names of every custom type registered with the kernel. Catalog only -- pair with `getType` to fetch a chosen spec. The bundled-with-objects path on `interestUpdate.types` remains the primary way clients learn about types they observe.

Method	Signature	Description
getType	(qualifiedName: string , withSchema: bool) → TypeLookupResult	Look up one type by qualified name. Returns the CustomTypeSpec; when `withSchema` is true, also returns the JSON-Schema fragment for the type (empty string otherwise). Dependency chasing is the client's job: each schema fragment carries `ref` strings keyed by qualified name, resolved against whatever schema cache the client maintains.
createInterest	(interestName: string , query: string , subscribe: SubscribeBlock , withSchemas: bool)	Register a sticky interest defined by an STL query. Optional `subscribe` block pre-subscribes to properties/events on every matched object, including ones that arrive later. When `withSchemas` is true, every subsequent `interestUpdate` for this interest carries the JSON-Schema fragment for each previously-unseen type alongside the existing `CustomTypeSpec`. Re-registering the same name = invalidParams. Wire-ordering contract: the initial `interestUpdate.added` for the current match set is emitted <i>before</i> this RPC's response lands on the wire. Clients must accept pushes for an interest whose response has not yet been observed.
releaseInterest	(interestName: string)	Drop an interest and every subscription living under it.
listObjects	(interestName: string) → ObjectInfos	List the names and classes of objects currently in an interest's match set.
getProperty	(interestName: string , objectName: string , propertyName: string) → string	Read a property's current value, synchronously.
getObjectsBatchState	(interestName: string , objectNames: sen.kernel.StringList , propertyNames: sen.kernel.StringList) → ObjectStateList	Batched per-object snapshot. Walks the interest's match set in one pass instead of forcing the caller to issue N*M `getProperty` round-trips. Omitting `objectNames` reads every object currently matched; omitting `propertyNames` reads every property of each object (the class hierarchy is walked, so inherited members are included). Names from `objectNames` that aren't currently in the match set are silently skipped -- the caller compares its requested list against the returned `objectName`s to detect omissions. Names from `propertyNames` that don't exist on a given object's class are recorded per-object under `errors`, so a heterogeneous batch still returns useful partial results. Bounded: the call rejects with `invalidParams` when the resolved object set exceeds 512 entries (either via an explicit

Method	Signature	Description
setProperty	(interestName: <code>string</code> , objectName: <code>string</code> , propertyName: <code>string</code> , value: <code>string</code>)	<code>`objectNames`</code> list of that length, or via an implicit walk over a match set that has grown that large). Page the request by passing <code>`objectNames`</code>. Write a property's value (sugar over invoking the generated setter). Hand-routed in <code>`Dispatcher::handleSetProperty`</code>: the dispatcher issues <code>`invokeUntyped`</code> against the property's setter and wires the response through the kernel callback in a single tick. The typed <code>`setPropertyImpl`</code> override in the C++ <code>`Server`</code> exists only to satisfy the codegen-generated abstract base and is unreachable at runtime. See <code>`architecture.md`</code> "Method dispatch" for why this method (and <code>`invoke`</code>) bypass the generic meta path.
subscribeProperty	(interestName: <code>string</code> , objectName: <code>string</code> , propertyName: <code>string</code> , maxRateHz: <code>f64</code>)	Subscribe to <code>propertyChanged</code> notifications for one (interest, object, property). Sticky: persists across object churn; auto-rewires when the named object (re)enters the match set. Snapshot of the current value is delivered immediately after wiring. The throttle is per-object, shared across every property/event subscribed for the same object. An explicit <code>`maxRateHz`</code> overrides the current rate for the object; omitting it preserves whatever rate is already in effect (so adding a per-property sub doesn't accidentally retune existing subs back to unlimited).
unsubscribeProperty	(interestName: <code>string</code> , objectName: <code>string</code> , propertyName: <code>string</code>)	Cancel a property subscription previously created with <code>subscribeProperty</code>.
subscribeEvent	(interestName: <code>string</code> , objectName: <code>string</code> , eventName: <code>string</code>)	Subscribe to <code>eventTriggered</code> notifications for one (interest, object, event).
unsubscribeEvent	(interestName: <code>string</code> , objectName: <code>string</code> , eventName: <code>string</code>)	Cancel an event subscription previously created with <code>subscribeEvent</code>.
subscribeAll	(interestName: <code>string</code> , objectName: <code>string</code> , maxRateHz: <code>f64</code>)	Subscribe to every property and every event of one named object. Wildcard expansion against the object's actual class (including parent classes). Object must currently be in the match set; absent objects are <code>invalidParams</code>.
unsubscribeAll	(interestName: <code>string</code> , objectName: <code>string</code>)	Cancel an all-members subscription previously created with <code>subscribeAll</code>.
invoke	(interestName: <code>string</code> , objectName: <code>string</code> , methodName: <code>string</code> , argsJson: <code>string</code>) → <code>string</code>	Call a method on a kernel object and await its return value. Hand-routed in <code>`Dispatcher::handleInvoke`</code>: validates the args, issues <code>`invokeUntyped`</code>, and wires the response through the kernel callback in a single tick. The typed

Method	Signature	Description
		<code>`invokeImpl`</code> override in the C++ <code>`Server`</code> exists only to satisfy the codegen-generated abstract base and is unreachable at runtime. See <code>`architecture.md`</code> "Method dispatch".

Event	Payload	Description
propertyChanged	(interestName: <code>string</code> , objectName: <code>string</code> , values: <code>PropertyValueList</code> , timestamp: <code>sen.TimeStamp</code>)	Bundled per-object snapshot of changed properties. Per-object bundling, not per-property: any property change on one object lands in a single envelope.
eventTriggered	(interestName: <code>string</code> , objectName: <code>string</code> , eventName: <code>string</code> , args: <code>string</code> , timestamp: <code>sen.TimeStamp</code>)	An event fired on one object in one interest. The event signature is decided by the source object's class, not by JSON-RPC.
interestUpdate	(interestName: <code>string</code> , added: <code>AddedObjectList</code> , removed: <code>sen.kernel.StringList</code> , types: <code>sen.kernel.CustomTypeSpecList</code> , typeSchemas: <code>string</code>)	Match-set delta for one interest. The dispatcher tracks knownTypes / knownSchemas per connection and only re-sends specs / schemas new to the client.
topologyChanged	(sessions: <code>SessionInfoList</code>)	Full snapshot of the topology after a session or bus add/remove. Pushed once on <code>`subscribeTopology`</code> (with the current state) and again on every change. Snapshot form rather than deltas: topology changes are rare, and the snapshot keeps client logic trivial and idempotent.
notificationsDropped	(count: <code>u64</code>)	Sent once when outbound backpressure clears on this connection, reporting how many unreliable notifications were dropped while the buffer was above the high watermark. Emitted reliably on purpose: the notice about dropped messages must not be droppable. A client that receives this has an incomplete picture and cannot tell which updates it missed -- only that it missed some. The correct response is to re-read what it displays (<code>getObjectsBatchState</code> over the affected interests) rather than to wait for the next change, which may never come for a property that has stopped moving.

StaticFileServer CLASS

Server-wide registry of in-memory static-file bundles, served alongside the WebSocket+JSON-RPC surface by the same uWS app. Internal-only: lives on the configurable control bus (defaults to ``local.jsonrpc_control``), not on the data-plane bus that hosts authenticated per-connection `JsonRpcServer` instances. The component publishes exactly one instance.

Name	Type	Flags	Description
registeredBundles	<code>RegisteredBundleInfoList</code>	RO D C	Currently-registered bundles. Externally read-only; the component mutates this whenever a bundle is registered or unregistered. Subscribe to receive notifications on every change.

Method	Signature	Description
registerStaticBundle	(bundle: <code>StaticBundle</code>) → <code>u64</code>	Register a bundle. The bundle is copied into the registry; the caller may release the argument

Method	Signature	Description
unregisterStaticBundle	(bundleId: u64)	afterwards. Routes are wired up asynchronously on the uWS thread; the returned bundleId is stable and may be used immediately with <code>unregisterStaticBundle</code> . Stop serving the bundle. The slot in the registry is nulled; the underlying uWS route remains registered (uWS does not expose a clean route-removal API) but becomes inert and returns 404. No-op if <code>bundleId</code> is unknown.

Fixed records

AddedObjectEntry	One object newly entering an interest's match set.	19
Configuration	JSON-RPC over WebSocket component configuration. Only <code>address</code> and <code>port</code> are required; every other field falls back to a documented default.	20
ConnectionLimits	Per-connection buffer / timeout knobs consulted on the uWS thread for the lifetime of the server. Every field is optional; unset fields fall back to the defaults resolved inside <code>ws_server.cpp</code> at the use site.	20
Identity	Identity of the connected client. Set once on connect by the dispatcher from the WebSocket upgrade authenticator. Read-only externally. Other components / admin tools can <code>SELECT * FROM local.jsonrpc</code> to enumerate currently-connected clients.	20
NamedSelection	Named arm of <code>MemberSelector</code> : matches only the listed members. Wire shape: <code>{type: "NamedSelection", value: {memberNames: [...]}}</code> .	20
ObjectInfo	One entry of <code>listObjects</code> ' result.	20
ObjectState	Per-object snapshot returned by <code>getObjectsBatchState</code> . <code>properties</code> carries successful reads (one entry per property name resolved against the object's class hierarchy); <code>errors</code> is empty when nothing failed for this object.	21
PropertyError	Per-property read error. Used when the caller-supplied <code>propertyNames</code> includes a name that doesn't exist on a given object's class, or when the accessor itself throws. Carried in a separate list from successful reads so a property literally named <code>error</code> can never collide with the failure envelope.	21
PropertyValuePair	Per-property changed value. The value type is decided by the addressed kernel object, not by JSON-RPC, so STL can't statically describe it.	21
RegisteredBundleInfo	Summary record returned by <code>listRegisteredBundles</code> . Excludes the file bytes; just enough to answer "what is currently being served, and where".	21
SessionInfo	One discovered session and the buses currently detected inside it. Names are opaque strings from the kernel's session-discovery surface.	21
StaticBundle	One bundle of in-memory files served on a configurable URL prefix. The same bundle's files are served at <code><urlPrefix>/<file.path></code> . <code>indexFileName</code> is the SPA fallback served whenever a request under <code>urlPrefix</code> does not match any file (lets the client-side router handle paths the server does not know about).	22
StaticFile	One file inside a <code>StaticBundle</code> . Bytes are owned by the bundle; <code>path</code> is relative to the bundle's <code>urlPrefix</code> and uses forward slashes regardless of the producer's OS. <code>contentType</code> is the MIME type the server will return verbatim; the bundle producer decides it (no extension-based inference happens server-side).	22
SubscribeBlock	Pre-subscription block bundled into <code>createInterest</code> . Wires the listed property / event subscriptions on every matched object -- including ones that arrive later. Wire shape mirrors the typed STL representation exactly: each <code>MaybeMemberSelector</code> is either omitted (no auto-subscribe), <code>null</code> , or one of the typed variant arms (<code>{type: "WildcardSelection", value: {}}</code> or <code>{type: "NamedSelection", value: {memberNames: [...]}}</code>); <code>maxRateHz</code> is an optional positive number. Strict alignment with the typed surface lets the dispatcher's uniform meta-dispatch path consume the wire directly via <code>fromJson</code> , without a per-method translation step.	22
TlsConfig	TLS materials. The schema is reserved so configs stay forward-compatible, but the component fails to start if <code>tls</code> is set; full TLS support is not yet wired through the uWebSockets SSL backend.	22
TypeLookupResult	Bundled return of <code>getType</code> : always the <code>CustomTypeSpec</code> , plus the JSON-Schema fragment when the caller opted in. <code>schema</code> is empty when not requested.	22
WildcardSelection	Wildcard arm of <code>MemberSelector</code> : matches every member of the relevant kind. Wire shape: <code>{type: "WildcardSelection", value: {}}</code> .	23

AddedObjectEntry STRUCTURE

One object newly entering an interest's match set.

Name	Type	Description
objectName	string	name of the newly-matched object
qualifiedClassName	string	package-qualified class name of the object
currentValues	PropertyValueList	initial values of pre-subscribed properties (empty if none wired)

Named by [AddedObjectList](#).

Configuration STRUCTURE

JSON-RPC over WebSocket component configuration. Only `address` and `port` are required; every other field falls back to a documented default.

Name	Type	Description
address	string	The IP address or hostname the server will bind to
port	u16	The port number the server will listen on
updateFreqHz	f64	Run-loop frequency in Hz; defaults to 60
connectionLimits	ConnectionLimits	Per-connection uWS buffer / timeout knobs
tls	TlsConfig	schema placeholder; setting this fails component start
controlBusName	string	Control-plane bus on `local`; defaults to "jsonrpc_control"

ConnectionLimits STRUCTURE

Per-connection buffer / timeout knobs consulted on the uWS thread for the lifetime of the server. Every field is optional; unset fields fall back to the defaults resolved inside ws_server.cpp at the use site.

Name	Type	Description
idleTimeoutSeconds	u16	uWS idle close timeout; defaults to 120
maxPayloadBytes	u32	Max inbound frame size; defaults to 16 KiB
maxBackpressureBytes	u32	uWS hard outbound buffer ceiling; defaults to 64 KiB
highBackpressureBytes	u32	Soft trigger for the BackpressureUpdate signal; defaults to 32 KiB

Named by [Configuration](#).

Identity STRUCTURE

Identity of the connected client. Set once on connect by the dispatcher from the WebSocket upgrade authenticator. Read-only externally. Other components / admin tools can `SELECT * FROM local.jsonrpc` to enumerate currently-connected clients.

Name	Type	Description
subject	string	authenticated subject identifier (e.g. user / service principal)

Named by [JsonRpcServer](#).

NamedSelection STRUCTURE

Named arm of MemberSelector: matches only the listed members. Wire shape: `{type: "NamedSelection", value: {memberNames: [...]}}`.

Name	Type	Description
memberNames	sen.kernel.StringList	member names to match

Named by [MemberSelector](#).

ObjectInfo STRUCTURE

One entry of listObjects' result.

Name	Type	Description
objectName	string	object name within the interest's match set
qualifiedClassName	string	package-qualified class name of the object

Named by [ObjectInfos](#).

ObjectState STRUCTURE

Per-object snapshot returned by ``getObjectsBatchState``. ``properties`` carries successful reads (one entry per property name resolved against the object's class hierarchy); ``errors`` is empty when nothing failed for this object.

Name	Type	Description
objectName	string	object name within the interest's match set
qualifiedClassName	string	package-qualified class name at read time
properties	PropertyValueList	resolved property values; empty when caller's filter matched nothing
errors	PropertyErrorList	per-property failures; empty when none occurred

Named by [ObjectStateList](#).

PropertyError STRUCTURE

Per-property read error. Used when the caller-supplied ``propertyNames`` includes a name that doesn't exist on a given object's class, or when the accessor itself throws. Carried in a separate list from successful reads so a property literally named ``error`` can never collide with the failure envelope.

Name	Type	Description
propertyName	string	name from the caller's <code>`propertyNames`</code> list that could not be read
error	string	human-readable reason (e.g. "unknown property")

Named by [PropertyErrorList](#).

PropertyValuePair STRUCTURE

Per-property changed value. The value type is decided by the addressed kernel object, not by JSON-RPC, so STL can't statically describe it.

Name	Type	Description
propertyName	string	property member name
value	string	JSON-encoded SenValue

Named by [PropertyValueList](#).

RegisteredBundleInfo STRUCTURE

Summary record returned by ``listRegisteredBundles``. Excludes the file bytes; just enough to answer "what is currently being served, and where".

Name	Type	Description
bundleId	u64	opaque id assigned by the server, stable for the bundle's lifetime
urlPrefix	string	bundle's URL prefix
fileCount	u64	number of files in the bundle

Named by [RegisteredBundleInfoList](#).

SessionInfo STRUCTURE

One discovered session and the buses currently detected inside it. Names are opaque strings from the kernel's session-discovery surface.

Name	Type	Description
name	string	session name
buses	sen.kernel.StringList	bus names currently detected in this session

Named by [SessionInfoList](#).

StaticBundle STRUCTURE

One bundle of in-memory files served on a configurable URL prefix. The same bundle's files are served at ``<urlPrefix>/<file.path>``. `indexFileName` is the SPA fallback served whenever a request under `urlPrefix` does not match any file (lets the client-side router handle paths the server does not know about).

Name	Type	Description
<code>urlPrefix</code>	string	URL prefix, e.g. <code>"/explorer"</code> ; must start with <code>"/</code>
<code>indexFileName</code>	string	SPA fallback, e.g. <code>"index.html"</code> ; must match a <code>path</code> in <code>files</code>
<code>files</code>	StaticFileList	file set

Named by [StaticFileServer](#).

StaticFile STRUCTURE

One file inside a `StaticBundle`. Bytes are owned by the bundle; `path` is relative to the bundle's `urlPrefix` and uses forward slashes regardless of the producer's OS. `contentType` is the MIME type the server will return verbatim; the bundle producer decides it (no extension-based inference happens server-side).

Name	Type	Description
<code>path</code>	string	path within the bundle, e.g. <code>"assets/main.js"</code>
<code>contentType</code>	string	MIME type, e.g. <code>"text/html"</code>
<code>contents</code>	sen.kernel.Buffer	raw file bytes

Named by [StaticFileList](#).

SubscribeBlock STRUCTURE

Pre-subscription block bundled into `createInterest`. Wires the listed property / event subscriptions on every matched object -- including ones that arrive later. Wire shape mirrors the typed STL representation exactly: each `MaybeMemberSelector` is either omitted (no auto-subscribe), `null`, or one of the typed variant arms (`{type: "WildcardSelection", value: {}}` or `{type: "NamedSelection", value: {memberNames: [...]}}`); `maxRateHz` is an optional positive number. Strict alignment with the typed surface lets the dispatcher's uniform meta-dispatch path consume the wire directly via `fromJson`, without a per-method translation step.

Name	Type	Description
<code>properties</code>	MemberSelector	which properties to auto-subscribe to (or none)
<code>events</code>	MemberSelector	which events to auto-subscribe to (or none)
<code>maxRateHz</code>	f64	optional throttle cap shared across the wired subscriptions

Named by [JsonRpcServer](#).

TlsConfig STRUCTURE

TLS materials. The schema is reserved so configs stay forward-compatible, but the component fails to start if `tls` is set; full TLS support is not yet wired through the `uWebSockets` SSL backend.

Name	Type	Description
<code>certPath</code>	string	PEM-encoded server certificate
<code>keyPath</code>	string	PEM-encoded server private key

Named by [Configuration](#).

TypeLookupResult STRUCTURE

Bundled return of `getType`: always the `CustomTypeSpec`, plus the JSON-Schema fragment when the caller opted in. `schema` is empty when not requested.

Name	Type	Description
<code>spec</code>	sen.kernel.CustomTypeSpec	

Name	Type	Description
schema	string	JSON-encoded schema fragment; "" when withSchema=false

Named by [JsonRpcServer](#).

WildcardSelection STRUCTURE

Wildcard arm of MemberSelector: matches every member of the relevant kind. Wire shape: `{type: "WildcardSelection", value: {}}`.

Named by [MemberSelector](#).

Variant records

[MemberSelector](#) Selector for properties or events in a SubscribeBlock. Absent = no auto-subscribe; WildcardSelection = "*"; NamedSelection = explicit list. 23

MemberSelector VARIANT

Selector for properties or events in a SubscribeBlock. Absent = no auto-subscribe; WildcardSelection = "*"; NamedSelection = explicit list.

Type	Description
WildcardSelection	
NamedSelection	

Named by [SubscribeBlock](#).

Arrays

[AddedObjectList](#) 23
[ObjectInfos](#) 23
[ObjectStateList](#) 23
[PropertyErrorList](#) 23
[PropertyValueList](#) 24
[RegisteredBundleInfoList](#) 24
[SessionInfoList](#) 24
[StaticFileList](#) 24

AddedObjectList SEQUENCE

```
sequence<AddedObjectEntry> AddedObjectList;
```

Named by [JsonRpcServer](#).

ObjectInfos SEQUENCE

```
sequence<ObjectInfo> ObjectInfos;
```

Named by [JsonRpcServer](#).

ObjectStateList SEQUENCE

```
sequence<ObjectState> ObjectStateList;
```

Named by [JsonRpcServer](#).

PropertyErrorList SEQUENCE

```
sequence<PropertyError> PropertyErrorList;
```

Named by [ObjectState](#).

PropertyValueList

SEQUENCE

```
sequence<PropertyValuePair> PropertyValueList;
```

Named by [AddedObjectEntry](#), [JsonRpcServer](#), [ObjectState](#).

RegisteredBundleInfoList

SEQUENCE

```
sequence<RegisteredBundleInfo> RegisteredBundleInfoList;
```

Named by [StaticFileServer](#).

SessionInfoList

SEQUENCE

```
sequence<SessionInfo> SessionInfoList;
```

Named by [JsonRpcServer](#).

StaticFileList

SEQUENCE

```
sequence<StaticFile> StaticFileList;
```

Named by [StaticBundle](#).

Optionals

MaybeConnectionLimits	24
MaybeControlBusName	24
MaybeFlag	24
MaybeHighBackpressureBytes	24
MaybeIdleTimeoutSeconds	25
MaybeMaxBackpressureBytes	25
MaybeMaxPayloadBytes	25
MaybeMemberSelector	25
MaybeRateHz	25
MaybeStringList	25
Optional list of object names. Absent on the wire (or `null`) selects every object currently in the addressed interest's match set; present limits the read to the listed names.	
MaybeSubscribeBlock	25
MaybeTlsConfig	25
MaybeUpdateFreqHz	25

MaybeConnectionLimits

OPTIONAL

```
optional<ConnectionLimits> MaybeConnectionLimits;
```

MaybeControlBusName

OPTIONAL

```
optional<string> MaybeControlBusName;
```

MaybeFlag

OPTIONAL

```
optional<bool> MaybeFlag;
```

MaybeHighBackpressureBytes

OPTIONAL

```
optional<u32> MaybeHighBackpressureBytes;
```

MaybeIdleTimeoutSeconds OPTIONAL

```
optional<u16> MaybeIdleTimeoutSeconds;
```

MaybeMaxBackpressureBytes OPTIONAL

```
optional<u32> MaybeMaxBackpressureBytes;
```

MaybeMaxPayloadBytes OPTIONAL

```
optional<u32> MaybeMaxPayloadBytes;
```

MaybeMemberSelector OPTIONAL

```
optional<MemberSelector> MaybeMemberSelector;
```

MaybeRateHz OPTIONAL

```
optional<f64> MaybeRateHz;
```

MaybeStringList OPTIONAL

Optional list of object names. Absent on the wire (or `null`) selects every object currently in the addressed interest's match set; present limits the read to the listed names.

```
optional<sen.kernel.StringList> MaybeStringList;
```

MaybeSubscribeBlock OPTIONAL

```
optional<SubscribeBlock> MaybeSubscribeBlock;
```

MaybeTlsConfig OPTIONAL

```
optional<TlsConfig> MaybeTlsConfig;
```

MaybeUpdateFreqHz OPTIONAL

```
optional<f64> MaybeUpdateFreqHz;
```

logmaster

3 types.

Object classes

[LogMaster](#) allows controlling the loggers
[Logger](#) represents a logger

26

26

LogMaster CLASS

allows controlling the loggers

Name	Type	Flags	Description
targetBus	string	RO S BE	

Method	Signature	Description
muteAll	()	mute all the loggers
unmuteAll	()	un-mutes all the muted loggers
toggleMuteAll	()	toggles the muting of all loggers
setLevel	(level: sen.kernel.log.LogLevel)	sets all the loggers to a given level

Logger CLASS

represents a logger

Name	Type	Flags	Description
level	sen.kernel.log.LogLevel	RO D BE	the current log level of this logger
pattern	string	RO D C	the pattern used by this logger
muted	bool	RO D BE	true if muted

Method	Signature	Description
mute	()	mute this logger
unmute	()	unmute this logger
setLevel	(level: sen.kernel.log.LogLevel)	unmute this logger
setPattern	(pattern: string)	sets the pattern for this logger

Fixed records

[Config](#) component configuration

26

Config STRUCTURE

component configuration

Name	Type	Description
targetBus	string	defaults to "local.log"
period	sen.Duration	defaults to 500 milliseconds

py

3 types.

Object classes

[PythonInterpreter](#) represents the embedded Python interpreter

27

PythonInterpreter CLASS

represents the embedded Python interpreter

Method	Signature	Description
eval	(expr: string) → string	evaluates a Python expression
exec	(code: string)	executes a Python code block
execFile	(file: string)	executes a Python file

Fixed records

[Configuration](#) Overall component configuration

27

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
freqHz	f32	update frequency in Hertz
module	string	python module to use (name of a python script, without the .py)
imports	StringList	sen packages to import
bus	string	bus where to publish the interpreter object (none by default)

Arrays

[StringList](#)

27

StringList SEQUENCE

```
sequence<string> StringList;
```

Named by [Configuration](#).

recorder

6 types.

Object classes

[Recorder](#) represents an recording session

28

Recorder CLASS

represents an recording session

Name	Type	Flags	Description
settings	RecordingSettings	RO S BE	
state	RecorderState	RO D C	

Method	Signature	Description
start	()	starts (or resumes) recording
stop	()	stops recording
fetchStats	() → sen.db.OutStats	sample the output statistics

Fixed records

[Configuration](#) Overall component configuration

28

[RecordingSettings](#) Configuration of a predefined recording

28

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
samplingPeriod	sen.Duration	sampling period for the recordings
recordings	RecordingSettingsList	predefined recordings
bus	string	bus to publish the object (local.rec by default)

RecordingSettings STRUCTURE

Configuration of a predefined recording

Name	Type	Description
name	string	name of the recording (cannot be empty)
folder	string	storage folder
selections	SelectionList	which objects shall be recorded
keyframePeriod	sen.Duration	period between keyframes (0 means no keyframes)
indexKeyframes	bool	should we create indexes for keyframes
indexObjects	bool	should we create indexes for objects
autoStart	bool	should we start recording automatically

Named by [Recorder](#), [RecordingSettingsList](#).

Enumerations

[RecorderState](#) the state of a recording session

28

RecorderState ENUMERATION

the state of a recording session

Held as u8.

stopped	0	error	2
recording	1		

Named by [Recorder](#).

Arrays

RecordingSettingsList	List of predefined recordings	29
SelectionList	List of selection queries	29

RecordingSettingsList SEQUENCE

List of predefined recordings

```
sequence<RecordingSettings> RecordingSettingsList;
```

Named by [Configuration](#).

SelectionList SEQUENCE

List of selection queries

```
sequence<string> SelectionList;
```

Named by [RecordingSettings](#).

replayer

4 types.

Object classes

Replay	controls the replay of a given archive	30
Replayer	represents the replayer component and manages Replay objects.	30

Replay CLASS

controls the replay of a given archive

Name	Type	Flags	Description
archiveInfo	sen.db.Summary	RO S BE	information about the archive being replayed
archivePath	string	RO S BE	file path to the archive
status	ReplayStatus	RO D C	playback status
playbackTime	sen.Timestamp	RO D BE	playback time

Method	Signature	Description
play	()	starts the playback from the current position
pause	()	hold the playback position, if playing
stop	()	goes to the start of the playback, erasing all objects
seek	(time: sen.Timestamp)	restores the playback to the keyframe that's closest to a given time
advance	(time: sen.Duration)	if paused or stopped, advances the playback a given time delta

Replayer CLASS

represents the replayer component and manages Replay objects.

Name	Type	Flags	Description
autoPlay	bool	RO S BE	if true, automatically calls play when opening a replay

Method	Signature	Description
open	(name: string , path: string)	opens an archive in a given path, and creates a named Replay object.
close	(name: string)	closes the named Replay object, if any.
closeAll	()	closes all previously opened replays

Fixed records

Configuration	Overall component configuration	30
-------------------------------	---------------------------------	----

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
bus	string	bus to publish the object (local.replay by default)
samplingPeriod	sen.Duration	max sampling period for flushing the replayed data
autoOpen	string	optional archive path to auto open on start-up (empty by default)
autoPlay	bool	if autoOpen is not empty, try to play it on start-up (false by default)

Enumerations

[ReplayStatus](#) the state in which a Replay can be

31

ReplayStatus ENUMERATION

the state in which a Replay can be

Held as u8.

stopped	0
paused	1
playing	2

Named by [Replay](#).

rest

37 types.

Fixed records

Argument	32
Bus	32
BusSummary	32
ClientAuth	32
Configuration	33
Error	33
Interest	33
InterestSummary	33
Link	33
Notification	33
Object	33
ObjectEvent	34
ObjectMethod	34
ObjectSummary	34
Session	34
SessionSummary	34
SubscriptionOptions	34
Subscriptions	34
Success	35
Version	35

Argument STRUCTURE

Name	Type	Description
name	string	
description	string	
type	string	

Named by [Arguments](#).

Bus STRUCTURE

Name	Type	Description
id	string	
status	Status	
objects	ObjectsSummary	

BusSummary STRUCTURE

Name	Type	Description
id	string	
status	Status	

Named by [Buses](#).

ClientAuth STRUCTURE

Name	Type	Description
id	string	

Configuration STRUCTURE

Name	Type	Description
address	string	The IP address or hostname the server will bind to
port	u16	The port number the server will listen on
freqHz	f32	Update frequency in Hertz

Error STRUCTURE

Name	Type	Description
error	string	

Interest STRUCTURE

Name	Type	Description
query	string	
name	string	

InterestSummary STRUCTURE

Name	Type	Description
name	string	
session	string	
bus	string	

Named by [InterestsSummary](#).

Link STRUCTURE

Name	Type	Description
rel	RelType	
href	string	
method	HttpMethod	

Named by [Links](#), [ObjectSummary](#).

Notification STRUCTURE

Name	Type	Description
type	NotificationType	
interest	string	
time	sen.TimeStamp	
data	string	

Object STRUCTURE

Name	Type	Description
objectId	u32	
name	string	
className	string	
localName	string	

Name	Type	Description
description	string	
links	Links	

ObjectEvent STRUCTURE

Name	Type	Description
name	string	
description	string	

ObjectMethod STRUCTURE

Name	Type	Description
name	string	
description	string	
retType	string	
args	Arguments	

ObjectSummary STRUCTURE

Name	Type	Description
objectId	u32	
name	string	
className	string	
localName	string	
link	Link	

Named by [ObjectsSummary](#).

Session STRUCTURE

Name	Type	Description
name	string	

SessionSummary STRUCTURE

Name	Type	Description
name	string	
buses	BusNames	

SubscriptionOptions STRUCTURE

Name	Type	Description
maxUpdateTime	sen.Duration	Max. update time

Subscriptions STRUCTURE

Name	Type	Description
properties	Properties	
events	Events	

Success STRUCTURE

Name	Type	Description
msg	string	

Version STRUCTURE

Name	Type	Description
version	string	

Enumerations

HttpMethod	35
InvokeStatus	35
NotificationType	35
RelType	35
Status	36

HttpMethod ENUMERATION

Held as u8.

httpGet	0
httpPost	1
httpPut	2
httpDelete	3
httpOption	4

Named by [Link](#).

InvokeStatus ENUMERATION

Held as u8.

pending	0
finished	1
failed	2

NotificationType ENUMERATION

Held as u8.

evt	0
invoke	1
property	2
objectAdded	3
objectRemoved	4
count	5

Named by [Notification](#).

RelType ENUMERATION

Held as u8.

method	0
setter	1
getter	2
evt	3
property	4
propertySubscribe	5
propertyUnsubscribe	6
def	7

Named by [Link](#).

Status

ENUMERATION

Held as u8.

open	0
close	1

Named by [Bus](#), [BusSummary](#).

Arrays

Arguments	36
BusNames	36
Buses	36
Events	36
InterestsSummary	36
Links	36
ObjectsSummary	36
Properties	37
Sessions	37

Arguments

SEQUENCE

```
sequence<Argument> Arguments;
```

Named by [ObjectMethod](#).

BusNames

SEQUENCE

```
sequence<string> BusNames;
```

Named by [SessionSummary](#).

Buses

SEQUENCE

```
sequence<BusSummary> Buses;
```

Events

SEQUENCE

```
sequence<string> Events;
```

Named by [Subscriptions](#).

InterestsSummary

SEQUENCE

```
sequence<InterestSummary> InterestsSummary;
```

Links

SEQUENCE

```
sequence<Link> Links;
```

Named by [Object](#).

ObjectsSummary

SEQUENCE

```
sequence<ObjectSummary> ObjectsSummary;
```

Named by [Bus](#).

Properties SEQUENCE

```
sequence<string> Properties;
```

Named by [Subscriptions](#).

Sessions SEQUENCE

```
sequence<string> Sessions;
```

Optionals

ThreadPoolSize	37
UpdateFrequency	37
UpdateTime	37

ThreadPoolSize OPTIONAL

```
optional<u16> ThreadPoolSize;
```

UpdateFrequency OPTIONAL

```
optional<f32> UpdateFrequency;
```

UpdateTime OPTIONAL

```
optional<sen.Duration> UpdateTime;
```

shell

27 types.

Object classes

[Shell](#) Provides a text-based interface to interact with the a sen kernel

38

Shell CLASS

Provides a text-based interface to interact with the a sen kernel

Name	Type	Flags	Description
config	Configuration	RO S BE	service configuration

Method	Signature	Description
clear	()	clears the screen
help	()	basic usage help
history	()	lists previous commands
ls	()	lists all the existing objects and sources.
open	(source: string)	opens a source (bus or session) without any condition
query	(name: string , condition: string)	opens a named source using a condition expression
close	(source: string)	closes a previously-opened source (session, bus or query)
info	(term: string)	prints information about a type or instance
shutdown	()	requests the kernel to be shut-down
src	()	lists the current sources

Fixed records

CPrint		38
ClearCurrentLine		39
ClearRemainingCurrentLine		39
ClearScreen		39
Configuration	Configuration params for the shell	39
HideCursor		39
MoveCursorAllLeft		39
MoveCursorDown		39
MoveCursorLeft		39
MoveCursorRight		39
MoveCursorUp		40
NewLine		40
Print		40
Query	Holds information about a named query	40
RestoreCursorPosition		40
SaveCursorPosition		40
SetBgColor		40
SetFgColor		40
SetWindowTitle		40
ShowCursor		41

CPrint STRUCTURE

Name	Type	Description
flags	u32	
color	u32	
text	string	

Named by [TerminalCmd](#).

ClearCurrentLine STRUCTURE

Named by [TerminalCmd](#).

ClearRemainingCurrentLine STRUCTURE

Named by [TerminalCmd](#).

ClearScreen STRUCTURE

Named by [TerminalCmd](#).

Configuration STRUCTURE

Configuration params for the shell

Name	Type	Description
prompt	string	defaults to 'sen> '
timeStyle	TimeStyle	how to display time
bufferStyle	BufferStyle	how to display buffers
serverEnabled	bool	enables remote shell access (false by default)
serverPort	u16	0 means default
noLogo	bool	true if you don't want a welcoming logo
open	SourcesList	list of sources to open automatically
query	QueryList	list of queries to create automatically
logBus	string	where to find the logmaster, if any (default: local.log)

Named by [Shell](#).

HideCursor STRUCTURE

Named by [TerminalCmd](#).

MoveCursorAllLeft STRUCTURE

Named by [TerminalCmd](#).

MoveCursorDown STRUCTURE

Name	Type	Description
cells	u32	

Named by [TerminalCmd](#).

MoveCursorLeft STRUCTURE

Name	Type	Description
cells	u32	

Named by [TerminalCmd](#).

MoveCursorRight STRUCTURE

Name	Type	Description
cells	u32	

Named by [TerminalCmd](#).

MoveCursorUp STRUCTURE

Name	Type	Description
cells	u32	

Named by [TerminalCmd](#).

NewLine STRUCTURE

Named by [TerminalCmd](#).

Print STRUCTURE

Name	Type	Description
text	string	

Named by [TerminalCmd](#).

Query STRUCTURE

Holds information about a named query

Name	Type	Description
name	string	the name of the query (cannot contain spaces or dots)
selection	string	the query expression

Named by [QueryList](#).

RestoreCursorPosition STRUCTURE

Named by [TerminalCmd](#).

SaveCursorPosition STRUCTURE

Named by [TerminalCmd](#).

SetBgColor STRUCTURE

Name	Type	Description
color	u32	

Named by [TerminalCmd](#).

SetFgColor STRUCTURE

Name	Type	Description
color	u32	

Named by [TerminalCmd](#).

SetWindowTitle STRUCTURE

Name	Type	Description
text	string	

Named by [TerminalCmd](#).

ShowCursor

STRUCTURE

Named by [TerminalCmd](#).

Enumerations

BufferStyle	How buffers should be printed	41
ListStyle	How lists should be printed	41
TimeStyle	How timestamps should be printed	41

BufferStyle

ENUMERATION

How buffers should be printed

Held as u8.

size	0
hexdump	1

Named by [Configuration](#).

ListStyle

ENUMERATION

How lists should be printed

Held as u8.

treeStyle	0
plainStyle	1

TimeStyle

ENUMERATION

How timestamps should be printed

Held as u8.

timestampUTC	0
timestampLocal	1

Named by [Configuration](#).

Variant records

TerminalCmd	41
-----------------------------	----

TerminalCmd

VARIANT

Type	Description
Print	
CPrint	
NewLine	
MoveCursorLeft	
MoveCursorRight	
MoveCursorUp	
MoveCursorDown	
MoveCursorAllLeft	
SetFgColor	
SetBgColor	
ClearCurrentLine	
ClearRemainingCurrentLine	
HideCursor	
ShowCursor	
SaveCursorPosition	

Type	Description
RestoreCursorPosition	
ClearScreen	
SetWindowTitle	

Arrays

QueryList	42
SourcesList	42

QueryList SEQUENCE

```
sequence<Query> QueryList;
```

Named by [Configuration](#).

SourcesList SEQUENCE

```
sequence<string> SourcesList;
```

Named by [Configuration](#).

db

3 types.

Fixed records

OutSettings	Settings for outputs	43
OutStats	Statistics of writing	43
Summary	Summary of an archive	43

OutSettings STRUCTURE

Settings for outputs

Name	Type	Description
name	string	name of the archive (cannot be empty)
folder	string	storage folder
indexKeyframes	bool	should we create indexes for keyframes

OutStats STRUCTURE

Statistics of writing

Name	Type	Description
maxQueueSize	u64	in bytes

Named by [sen.components.recorder.Recorder](#).

Summary STRUCTURE

Summary of an archive

Name	Type	Description
firstTime	sen.TimeStamp	the time of the first event
lastTime	sen.TimeStamp	the time of the last event
keyframeCount	u32	number of written keyframes
objectCount	u32	number of recorded objects
typeCount	u32	number of types written
annotationCount	u32	number of annotations
indexedObjectCount	u32	number of indexed objects

Named by [sen.components.replayer.Replay](#).

kernel

160 types.

Object classes

KernelApi	Represents the kernel	44
VirtualClock	Allows inspecting and controlling the advance of virtual time and associated component iteration	44
VirtualKernelClock	A clock for all the components loaded by the kernel	44
VirtualMasterClock	Controls all the VirtualKernelClock that it discovers in the bus where it's published. One step reaches the next component due to run: each clock reports how long until its own next one, and the soonest wins	44

KernelApi CLASS

Represents the kernel

Name	Type	Flags	Description
buildInfo	BuildInfo	RO S BE	kernel build information

Method	Signature	Description
shutdown	()	requests the kernel to shut down
getUnits	() → UnitList	registered units
getTypes	() → StringList	registered types, by name
getConfig	() → KernelParams	configuration of the kernel execution
getRuntimeNetworkFootprint	() → NetworkFootprint	actual network addresses and ports currently used by this process

VirtualClock CLASS

Allows inspecting and controlling the advance of virtual time and associated component iteration

Name	Type	Flags	Description
time	sen.Timestamp	RO D BE	the current virtual time

VirtualKernelClock CLASS

A clock for all the components loaded by the kernel

Method	Signature	Description
processNoFlush	(delta: sen.Duration) → sen.Duration	updates the time, drains the inputs, and cycles components - doesn't flush outputs
flushOutputs	() → sen.Duration	makes component outputs visible to other components and returns the next step duration

VirtualMasterClock CLASS

Controls all the VirtualKernelClock that it discovers in the bus where it's published. One step reaches the next component due to run: each clock reports how long until its own next one, and the soonest wins

Method	Signature	Description
advanceTime	(duration: sen.Duration) → sen.Duration	steps until the virtual time advanced reaches duration, rounding up to a whole step. Returns the wall time the call took
step	() → sen.Duration	single step forward
steps	(count: u64) → sen.Duration	perform 'count' steps forward

Fixed records

AliasTypeSpec	data of an aliased type	46
-------------------------------	-------------------------	----

AliasTypeSpecV4		46
AliasTypeSpecV5		46
ArgSpec	an argument of a callable (methods and events)	46
ArgSpecV4		46
ArgSpecV5		47
BuildInfo	Build-related information	47
BuiltComponentParams	Parameters related to components build by the kernel	47
BusAddress	Address to connect to a bus	47
ClassTypeSpec	spec of a class	47
ClassTypeSpecV4		48
ClassTypeSpecV5		48
ComponentConfig	Basic runtime configuration for a component	48
ComponentInfo	Basic information of a kernel component	48
CustomTypeSpec	spec of a custom type	49
CustomTypeSpecV4		49
CustomTypeSpecV5		49
EnumTypeSpec	spec of an enum type	49
EnumTypeSpecV4		49
EnumTypeSpecV5		50
EnumeratorSpec	an enumerator	50
EnumeratorSpecV4		50
EnumeratorSpecV5		50
EnvVar	Information about an environment variable	50
ErrorData	Information related to the error	50
ErrorReport	Information about a detected error	51
EventSpec	spec for an event	51
EventSpecV4		51
EventSpecV5		51
ExecError	Holds details of an execution error	51
KernelParams	Parameters to configure kernel execution	51
LoadedComponentParams	Parameters related to a component that will be loaded by the kernel	52
MethodSpec	spec for methods	52
MethodSpecV4		52
MethodSpecV5		53
NetworkFootprint	Network endpoints predicted offline or observed at runtime for one process	53
NetworkFootprintAddressRange	Inclusive IPv4 address range excluded from multicast allocation	53
NetworkFootprintBus	Multicast endpoint allocated to a bus	53
NetworkFootprintBusIdentity	Names and IDs that identify a bus	54
NetworkFootprintCollision	Multicast allocation capacity and collision information	54
NetworkFootprintMulticast	Multicast information in the network footprint	54
NetworkFootprintPort	Socket type, port selection mode and port value	54
NetworkFootprintPortExclusions	Port ranges that cannot be used	55
NetworkFootprintPortRange	Inclusive range from which a port may be selected	55
NetworkFootprintSelfCollision	Two buses allocated to the same multicast group	55
OpFinished	An operation is complete	55
OpNotFinished	An operation is not complete	55
OptionalTypeSpec	data of an optional type	55
OptionalTypeSpecV4		56
OptionalTypeSpecV5		56
PrecisionSleep	Be more precise at the expense of some CPU cycles.	56
ProcessData	Information about the process	56
ProcessInfo	Basic information about a process	56
PropertySpec	spec of a property	57
PropertySpecV4		57
PropertySpecV5		57
QuantityTypeSpec	spec of a quantity type	57
QuantityTypeSpecV4		58
QuantityTypeSpecV5		58
QueueConfig		58
SenData	Information about Sen	58
SequenceTypeSpec	spec of a sequence type	58
SequenceTypeSpecV4		59
SequenceTypeSpecV5		59
SignalData	Information about an unhandled signal	59
StructTypeFieldSpec	a field of a struct	59
StructTypeFieldSpecV4		59
StructTypeFieldSpecV5		60

StructTypeSpec	spec of an struct type	60
StructTypeSpecV4		60
StructTypeSpecV5		60
SystemSleep	Use the native system sleep	60
UncaughtException	Information about an unhandled exception	60
UnitInfo	Describes a unit	60
VariantTypeFieldSpec	a field of a variant	61
VariantTypeFieldSpecV4		61
VariantTypeFieldSpecV5		61
VariantTypeSpec	spec of an struct type	61
VariantTypeSpecV4		61
VariantTypeSpecV5		62

AliasTypeSpec STRUCTURE

data of an aliased type

Name	Type	Description
aliasedType	string	qualified type name being aliased

Named by [CustomTypeData](#).

AliasTypeSpecV4 STRUCTURE

Name	Type	Description
aliasedType	string	qualified type name being aliased

Named by [CustomTypeDataV4](#).

AliasTypeSpecV5 STRUCTURE

Name	Type	Description
aliasedType	string	qualified type name being aliased
hash	u32	unique hash

Named by [CustomTypeDataV5](#).

ArgSpec STRUCTURE

an argument of a callable (methods and events)

Name	Type	Description
name	string	argument name
description	string	documentation
type	string	qualified type name of the argument

Named by [ArgSpecList](#).

ArgSpecV4 STRUCTURE

Name	Type	Description
name	string	argument name
description	string	documentation
type	string	qualified type name of the argument

Named by [ArgSpecListV4](#).

ArgSpecV5 STRUCTURE

Name	Type	Description
name	string	argument name
nameHash	u32	hash computed with the argument name
description	string	documentation
type	string	qualified type name of the argument
hash	u32	unique hash

Named by [ArgSpecListV5](#).

BuildInfo STRUCTURE

Build-related information

Name	Type	Description
maintainer	string	principal maintainer of the software
version	string	version string (format-agnostic)
compiler	string	vendor-specific compiler string
debugMode	bool	compiled in debug mode or not
buildTime	string	the commit's timestamp, ISO-8601; not the compiler's clock
wordSize	WordSize	architecture
gitRef	string	git ref spec
gitHash	string	git hash
gitStatus	GitStatus	git status

Named by [ComponentInfo](#), [KernelApi](#).

BuiltComponentParams STRUCTURE

Parameters related to components build by the kernel

Name	Type	Description
name	string	the name of the component
period	sen.Duration	the execution period
config	ComponentConfig	the configuration of the component
imports	StringList	the imported packages

Named by [BuiltComponentList](#).

BusAddress STRUCTURE

Address to connect to a bus

Name	Type	Description
sessionName	string	
busName	string	

ClassTypeSpec STRUCTURE

spec of a class

Name	Type	Description
properties	PropertySpecList	
methods	MethodSpecList	
events	EventSpecList	
constructor	MethodSpec	

Name	Type	Description
parents	StringList	
isInterface	bool	

Named by [CustomTypeData](#).

ClassTypeSpecV4 STRUCTURE

Name	Type	Description
properties	PropertySpecListV4	
methods	MethodSpecListV4	
events	EventSpecListV4	
isInterface	bool	
id	u32	
constructor	MethodSpecV4	
parents	StringList	

Named by [CustomTypeDataV4](#).

ClassTypeSpecV5 STRUCTURE

Name	Type	Description
properties	PropertySpecListV5	
methods	MethodSpecListV5	
events	EventSpecListV5	
isInterface	bool	
id	u32	
constructor	MethodSpecV5	
parents	StringList	
hash	u32	

Named by [CustomTypeDataV5](#).

ComponentConfig STRUCTURE

Basic runtime configuration for a component

Name	Type	Description
priority	Priority	thread priority
stackSize	u32	thread stack size in bytes, 0 means default
group	u32	the group where to run the component
cpuAffinity	u64	CPU affinity mask
inQueue	QueueConfig	queuing of inbound information
outQueue	QueueConfig	queuing of outbound information
sleepPolicy	SleepPolicy	configurable component sleep policy

Named by [BuiltComponentParams](#), [LoadedComponentParams](#).

ComponentInfo STRUCTURE

Basic information of a kernel component

Name	Type	Description
name	string	
description	string	

Name	Type	Description
buildInfo	BuildInfo	

CustomTypeSpec STRUCTURE

spec of a custom type

Name	Type	Description
name	string	name of the type
qualifiedName	string	package-qualified name
description	string	documentation
data	CustomTypeData	spec data

Named by [sen.components.jsonrpc.TypeLookupResult](#), [CustomTypeSpecList](#).

CustomTypeSpecV4 STRUCTURE

Name	Type	Description
name	string	name of the type
qualifiedName	string	package-qualified name
description	string	documentation
data	CustomTypeDataV4	spec data

Named by [CustomTypeSpecListV4](#).

CustomTypeSpecV5 STRUCTURE

Name	Type	Description
name	string	name of the type
qualifiedName	string	package-qualified name
description	string	documentation
data	CustomTypeDataV5	spec data

Named by [CustomTypeSpecListV5](#).

EnumTypeSpec STRUCTURE

spec of an enum type

Name	Type	Description
enums	EnumeratorSpecList	enumerators
storageType	IntegralType	type used to store the value

Named by [CustomTypeData](#).

EnumTypeSpecV4 STRUCTURE

Name	Type	Description
enums	EnumeratorSpecListV4	enumerators
storageType	IntegralType	type used to store the value

Named by [CustomTypeDataV4](#).

EnumTypeSpecV5 STRUCTURE

Name	Type	Description
enums	EnumeratorSpecListV5	enumerators
storageType	IntegralType	type used to store the value
hash	u32	unique hash

Named by [CustomTypeDataV5](#).

EnumeratorSpec STRUCTURE

an enumerator

Name	Type	Description
name	string	enumerator name
key	u32	enumerator value
description	string	enumerator description

Named by [EnumeratorSpecList](#).

EnumeratorSpecV4 STRUCTURE

Name	Type	Description
name	string	enumerator name
key	u64	enumerator value

Named by [EnumeratorSpecListV4](#).

EnumeratorSpecV5 STRUCTURE

Name	Type	Description
name	string	enumerator name
key	u64	enumerator value
hash	u32	unique hash

Named by [EnumeratorSpecListV5](#).

EnvVar STRUCTURE

Information about an environment variable

Name	Type	Description
name	string	name of the variable
value	string	value of the variable

Named by [EnvironmentVarList](#).

ErrorData STRUCTURE

Information related to the error

Name	Type	Description
time	sen.TimeStamp	time of the error
errorMessage	StringList	message presented to the user
exceptionData	UncaughtException	information about the unhandled exception (if any)
signalData	SignalData	information about the received signal (if any)

Named by [ErrorReport](#).

ErrorReport STRUCTURE

Information about a detected error

Name	Type	Description
senData	SenData	information related to Sen
processData	ProcessData	information related to the process
errorData	ErrorData	information related to the error

EventSpec STRUCTURE

spec for an event

Name	Type	Description
name	string	name of the type
description	string	documentation
args	ArgSpecList	arguments
transportMode	TransportModeSpec	transport mode

Named by [EventSpecList](#).

EventSpecV4 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
args	ArgSpecListV4	arguments
transportMode	TransportModeSpec	transport mode

Named by [EventSpecListV4](#).

EventSpecV5 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
args	ArgSpecListV5	arguments
transportMode	TransportModeSpec	transport mode
hash	u32	unique hash

Named by [EventSpecListV5](#).

ExecError STRUCTURE

Holds details of an execution error

Name	Type	Description
category	ErrorCategory	general problem
explanation	string	human-readable explanation

KernelParams STRUCTURE

Parameters to configure kernel execution

Name	Type	Description
runMode	RunMode	how to run the kernel
appName	string	optional name of the application
bus	string	where to publish the kernel objects (defaults to local.kernel)
clockBus	string	where to publish the virtual clock (if any), defaults to bus
clockName	string	the name of the virtual clock (if any), defaults to 'clock'
clockMaster	bool	if time is virtualized, publish a master clock to clockBus
logConfig	log.Config	logging configuration
crashReportDir	string	where to store crash reports (defaults to the temp dir)
crashReportDisabled	bool	if true, no reports are generated
lockMemoryPages	bool	keep process pages memory-resident
sleepPolicy	SleepPolicy	configurable sleep policy of the kernel component
compatibilityMode	CompatibilityMode	what to do with a remote type that does not match
limitCpuIdleLatency	bool	This struct is reachable over the wire through <code>Kernel.getConfig()</code> and is embedded in <code>SenData</code> , and the encoding is positional, so adding a field here shifts what follows it either way. keep the CPUs out of the deep idle states they are slow to leave

Named by [KernelApi](#), [SenData](#).

LoadedComponentParams STRUCTURE

Parameters related to a component that will be loaded by the kernel

Name	Type	Description
name	string	the name of the component
config	ComponentConfig	the configuration of the component

Named by [LoadedComponentList](#).

MethodSpec STRUCTURE

spec for methods

Name	Type	Description
name	string	name of the type
description	string	documentation
args	ArgSpecList	arguments
transportMode	TransportModeSpec	transport mode
constness	MethodConstnessSpec	if it changes the state of the object
deferred	bool	if the execution of the method is deferred
returnType	string	qualified return type name
propertyRelation	PropertyRelationSpec	property relation of the method
localOnly	bool	true if the method can only be called locally

Named by [ClassTypeSpec](#), [MethodSpecList](#).

MethodSpecV4 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
args	ArgSpecListV4	arguments

Name	Type	Description
transportMode	TransportModeSpec	transport mode
constness	MethodConstnessSpec	if it changes the state of the object
deferred	bool	true if the method is marked as deferred
returnTypeId	string	qualified return type name (empty for none)

Named by [ClassTypeSpecV4](#), [MethodSpecListV4](#).

MethodSpecV5 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
args	ArgSpecListV5	arguments
transportMode	TransportModeSpec	transport mode
constness	MethodConstnessSpec	if it changes the state of the object
localOnly	bool	true if the method can only be called locally
returnTypeId	string	qualified return type name (empty for none)
hash	u32	unique hash

Named by [ClassTypeSpecV5](#), [MethodSpecListV5](#).

NetworkFootprint STRUCTURE

Network endpoints predicted offline or observed at runtime for one process

Name	Type	Description
discoveryPort	u16	Discovery port used to calculate multicast addresses
multicast	NetworkFootprintMulticast	Multicast allocation details
ports	NetworkFootprintPortList	Port settings
portExclusions	NetworkFootprintPortExclusions	Port ranges that cannot be used

Named by [KernelApi](#).

NetworkFootprintAddressRange STRUCTURE

Inclusive IPv4 address range excluded from multicast allocation

Name	Type	Description
min	string	
max	string	

Named by [NetworkFootprintAddressRangeList](#).

NetworkFootprintBus STRUCTURE

Multicast endpoint allocated to a bus

Name	Type	Description
sessionName	string	
busName	string	

Name	Type	Description
sessionId	u32	
busId	u32	
groupAddress	string	
source	NetworkFootprintBus Source	

Named by [NetworkFootprintBusList](#).

NetworkFootprintBusIdentity STRUCTURE

Names and IDs that identify a bus

Name	Type	Description
sessionName	string	
busName	string	
sessionId	u32	
busId	u32	

Named by [NetworkFootprintSelfCollision](#).

NetworkFootprintCollision STRUCTURE

Multicast allocation capacity and collision information

Name	Type	Description
usableSpaceSize	u64	Number of addresses available
busCount	u64	Number of reported buses
probability	f64	Estimated conflict from 0 to 1
selfCollisions	NetworkFootprintSelf CollisionList	Collisions in the reported buses

Named by [NetworkFootprintMulticast](#).

NetworkFootprintMulticast STRUCTURE

Multicast information in the network footprint

Name	Type	Description
port	u16	Shared multicast port used by every bus
buses	NetworkFootprintBus List	Multicast address used by each bus
exclusions	NetworkFootprint AddressRangeList	Addresses that cannot be used
collision	NetworkFootprint Collision	Available addresses and conflict information

Named by [NetworkFootprint](#).

NetworkFootprintPort STRUCTURE

Socket type, port selection mode and port value

Name	Type	Description
kind	NetworkFootprintPort Kind	
mode	NetworkFootprintPort Mode	

Name	Type	Description
value	NetworkFootprintPortValue	

Named by [NetworkFootprintPortList](#).

NetworkFootprintPortExclusions STRUCTURE

Port ranges that cannot be used

Name	Type	Description
builtIn	NetworkFootprintPortRangeList	
configured	NetworkFootprintPortRangeList	
operatingSystem	NetworkFootprintPortRangeList	

Named by [NetworkFootprint](#).

NetworkFootprintPortRange STRUCTURE

Inclusive range from which a port may be selected

Name	Type	Description
min	u16	
max	u16	

Named by [NetworkFootprintPortRangeList](#), [NetworkFootprintPortValue](#).

NetworkFootprintSelfCollision STRUCTURE

Two buses allocated to the same multicast group

Name	Type	Description
firstBus	NetworkFootprintBusIdentity	
secondBus	NetworkFootprintBusIdentity	
groupAddress	string	

Named by [NetworkFootprintSelfCollisionList](#).

OpFinished STRUCTURE

An operation is complete

Named by [OpState](#).

OpNotFinished STRUCTURE

An operation is not complete

Name	Type	Description
waitHint	sen.Duration	How long to wait until the next try

Named by [OpState](#).

OptionalTypeSpec STRUCTURE

data of an optional type

Name	Type	Description
type	string	qualified type name

Named by [CustomTypeData](#).

OptionalTypeSpecV4 STRUCTURE

Name	Type	Description
type	string	qualified type name

Named by [CustomTypeDataV4](#).

OptionalTypeSpecV5 STRUCTURE

Name	Type	Description
type	string	qualified type name
hash	u32	unique hash

Named by [CustomTypeDataV5](#).

PrecisionSleep STRUCTURE

Be more precise at the expense of some CPU cycles.

Name	Type	Description
veryCoarseGrainSleepTime	sen.Duration	First set of sleeps. If 0 defaults to 7ms
coarseGrainSleepTime	sen.Duration	Second set of sleeps. If 0 defaults to 1ms

Named by [SleepPolicy](#).

ProcessData STRUCTURE

Information about the process

Name	Type	Description
processInfo	ProcessInfo	general process information
environment	EnvironmentVarList	list of environment variables
stacktrace	StringList	the stack trace (if any)
recentLogs	StringList	the last logs emitted by the process

Named by [ErrorReport](#).

ProcessInfo STRUCTURE

Basic information about a process

Name	Type	Description
hostId	u32	
processId	u32	
sessionId	u32	
sessionName	string	
appName	string	
hostName	string	
osKind	OsKind	
osName	string	
cpuArch	CpuArch	

Named by [sen.components.ether.Hello](#), [sen.components.ether.SessionPresenceBeam](#), [ProcessData](#), [Processes](#).

PropertySpec STRUCTURE

spec of a property

Name	Type	Description
name	string	name of the type
description	string	documentation
category	PropertyCategorySpec	category
type	string	qualified type name of the property
transportMode	TransportModeSpec	how to transport the data
tags	StringList	user-defined tags
checkedSet	bool	if setting the property is checked

Named by [PropertySpecList](#).

PropertySpecV4 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
category	PropertyCategorySpec	category
type	string	qualified type name of the property
transportMode	TransportModeSpec	how to transport the data
tags	StringList	user-defined tags

Named by [PropertySpecListV4](#).

PropertySpecV5 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
category	PropertyCategorySpec	category
type	string	qualified type name of the property
transportMode	TransportModeSpec	how to transport the data
tags	StringList	user-defined tags
hash	u32	unique hash

Named by [PropertySpecListV5](#).

QuantityTypeSpec STRUCTURE

spec of a quantity type

Name	Type	Description
elementType	NumericType	type used to store the value
unit	UnitInfo	used unit
minValue	f64	discarded if $\geq$ maxValue
maxValue	f64	discarded if $\leq$ minValue

Named by [CustomTypeData](#).

QuantityTypeSpecV4 STRUCTURE

Name	Type	Description
numericType	NumericType	type used to store the value
unit	UnitInfo	used unit
minValue	f64	discarded if >= maxValue
maxValue	f64	discarded if <= minValue

Named by [CustomTypeDataV4](#).

QuantityTypeSpecV5 STRUCTURE

Name	Type	Description
numericType	NumericType	type used to store the value
unit	UnitInfo	used unit
minValue	f64	discarded if >= maxValue
maxValue	f64	discarded if <= minValue
hash	u32	unique hash

Named by [CustomTypeDataV5](#).

QueueConfig STRUCTURE

Name	Type	Description
evictionPolicy	QueueEvictionPolicy	what to do when the queue is full
maxSize	u64	0 means unbounded

Named by [ComponentConfig](#).

SenData STRUCTURE

Information about Sen

Name	Type	Description
version	string	the Sen version
compiler	string	the compiler used to build Sen
debugMode	bool	true if it was build in debug mode
buildTime	string	the commit's timestamp, not the compiler's clock
wordSize	WordSize	architecture
gitRef	string	git ref
gitHash	string	git hash
gitStatus	GitStatus	status of the branch when build
kernelParams	KernelParams	Sen kernel parameters
kernelProtocol	u32	version of the kernel protocol
transportProtocol	u32	version of the transport protocol (if present)
loadedComponents	LoadedComponentList	components to load
builtComponents	BuiltComponentList	components to build

Named by [ErrorReport](#).

SequenceTypeSpec STRUCTURE

spec of a sequence type

Name	Type	Description
elementType	string	qualified type name for stored values
maxSize	u64	discarded when 0
fixedSize	bool	

Named by [CustomTypeData](#).

SequenceTypeSpecV4 STRUCTURE

Name	Type	Description
elementType	string	qualified type name for stored values
maxSize	u64	discarded when 0

Named by [CustomTypeDataV4](#).

SequenceTypeSpecV5 STRUCTURE

Name	Type	Description
elementType	string	qualified type name for stored values
maxSize	u64	discarded when 0
fixedSize	bool	
hash	u32	unique hash

Named by [CustomTypeDataV5](#).

SignalData STRUCTURE

Information about an unhandled signal

Name	Type	Description
signalNumber	i32	signal number
signalName	string	human-readable name

Named by [ErrorData](#).

StructTypeFieldSpec STRUCTURE

a field of a struct

Name	Type	Description
name	string	field name
description	string	documentation
type	string	qualified type name held by this field

Named by [StructTypeFieldSpecList](#).

StructTypeFieldSpecV4 STRUCTURE

Name	Type	Description
name	string	field name
description	string	documentation
type	string	qualified type name held by this field

Named by [StructTypeFieldSpecListV4](#).

StructTypeFieldSpecV5 STRUCTURE

Name	Type	Description
name	string	field name
description	string	documentation
type	string	qualified type name held by this field
hash	u32	unique hash

Named by [StructTypeFieldSpecListV5](#).

StructTypeSpec STRUCTURE

spec of an struct type

Name	Type	Description
fields	StructTypeFieldSpecList	fields
parent	string	qualified type name the parent struct, empty means none

Named by [CustomTypeData](#).

StructTypeSpecV4 STRUCTURE

Name	Type	Description
fields	StructTypeFieldSpecListV4	fields
parent	string	qualified type name the parent struct, empty means none

Named by [CustomTypeDataV4](#).

StructTypeSpecV5 STRUCTURE

Name	Type	Description
fields	StructTypeFieldSpecListV5	fields
parent	string	qualified type name the parent struct, empty means none
hash	u32	unique hash

Named by [CustomTypeDataV5](#).

SystemSleep STRUCTURE

Use the native system sleep

Named by [SleepPolicy](#).

UncaughtException STRUCTURE

Information about an unhandled exception

Name	Type	Description
exceptionKind	ExceptionKind	kind of exception
message	string	message it provides (if any)

Named by [ErrorData](#).

UnitInfo STRUCTURE

Describes a unit

Name	Type	Description
name	string	
abbreviation	string	
category	UnitCat	

Named by [QuantityTypeSpec](#), [QuantityTypeSpecV4](#), [QuantityTypeSpecV5](#), [UnitList](#).

VariantTypeFieldSpec STRUCTURE

a field of a variant

Name	Type	Description
key	u32	key/index of this type within the variant
description	string	documentation
type	string	qualified type name held by this field

Named by [VariantTypeFieldSpecList](#).

VariantTypeFieldSpecV4 STRUCTURE

Name	Type	Description
key	u32	key/index of this type within the variant
description	string	documentation
type	string	qualified type name held by this field

Named by [VariantTypeFieldSpecListV4](#).

VariantTypeFieldSpecV5 STRUCTURE

Name	Type	Description
key	u32	key/index of this type within the variant
description	string	documentation
type	string	qualified type name held by this field
hash	u32	unique hash

Named by [VariantTypeFieldSpecListV5](#).

VariantTypeSpec STRUCTURE

spec of an struct type

Name	Type	Description
fields	VariantTypeFieldSpecList	

Named by [CustomTypeData](#).

VariantTypeSpecV4 STRUCTURE

Name	Type	Description
fields	VariantTypeFieldSpecListV4	

Named by [CustomTypeDataV4](#).

VariantTypeSpecV5 STRUCTURE

Name	Type	Description
fields	VariantTypeFieldSpec ListV5	
hash	u32	

Named by [CustomTypeDataV5](#).

Enumerations

BasicType	built-in others	62
CompatibilityMode	What to do when a type published by another kernel does not match the local one	62
ComponentState	State of a kernel component	62
CpuArch	Type of CPU	63
ErrorCategory	Category of a problem during component execution	63
ExceptionKind	Types of exceptions that can occur.	63
GitStatus	Status of git	63
IntegralType	built-in integrals	64
MethodConstnessSpec	method constness	64
NetworkFootprintBusSource	Bus source	64
NetworkFootprintPortKind	Type of socket opened by the process	64
NetworkFootprintPortMode	Port allocation policy	64
OsKind	Type of operating system	64
Priority	Thread execution priorities	65
PropertyCategorySpec	how a property is seen by others	65
PropertyRelationSpec	method property relation	65
QueueEvictionPolicy	Component queue eviction policy	65
RealType	built-in reals	65
RunMode	Run modes for the kernel	65
ThreadCreateErr	What can go wrong when creating a thread	66
TransportModeSpec	how to transport information	66
UnitCat	Type of measurement	66
WordSize	Native processor word size	66

BasicType ENUMERATION

built-in others

Held as u8.

booleanType	0
stringType	1
durationType	2
timestampType	3

Named by [BuiltInType](#).

CompatibilityMode ENUMERATION

What to do when a type published by another kernel does not match the local one

Held as u8.

relaxed	0
strict	1
disabled	2

Named by [KernelParams](#).

ComponentState ENUMERATION

State of a kernel component

Held as u8.

unloaded	0	loaded	3	running	6
preloaded	1	initializing	4	stopping	7
loading	2	initialized	5	stopped	8

unloading	9
error	10

CpuArch ENUMERATION

Type of CPU

Held as u8.

x86	0
x64	1
arm2	2
arm3	3
arm4T	4
arm5	5
arm6T2	6
arm6	7
arm7	8
arm7a	9
arm7r	10
arm7s	11
arm64	12
mips	13
superH	14
ppc	15
ppc64	16
sparc	17
m68k	18
otherArch	19

Named by [ProcessInfo](#).

ErrorCategory ENUMERATION

Category of a problem during component execution

Held as u8.

runtimeError	0
logicError	1
expectationsNotMet	2
ioError	3
other	4

Named by [ExecError](#).

ExceptionKind ENUMERATION

Types of exceptions that can occur.

Held as u8.

runtime	0
logic	1
standard	2
unknown	3

Named by [UncaughtException](#).

GitStatus ENUMERATION

Status of git

Held as u8.

clean	0
modified	1
unknown	2

Named by [BuildInfo](#), [SenData](#).

IntegralType ENUMERATION

built-in integrals

Held as u8.

uint8Type	0
int16Type	1
uint16Type	2
int32Type	3
uint32Type	4
int64Type	5
uint64Type	6

Named by [EnumTypeSpec](#), [EnumTypeSpecV4](#), [EnumTypeSpecV5](#), [NumericType](#).

MethodConstnessSpec ENUMERATION

method constness

Held as u8.

constant	0
nonConstant	1

Named by [MethodSpec](#), [MethodSpecV4](#), [MethodSpecV5](#).

NetworkFootprintBusSource ENUMERATION

Bus source

Held as u8.

configured	0
supplied	1
runtime	2

Named by [NetworkFootprintBus](#).

NetworkFootprintPortKind ENUMERATION

Type of socket opened by the process

Held as u8.

tcpAcceptor	0
udpUnicast	1
tcpSource	2

Named by [NetworkFootprintPort](#).

NetworkFootprintPortMode ENUMERATION

Port allocation policy

Held as u8.

ephemeral	0
probe	1
pinned	2

Named by [NetworkFootprintPort](#).

OsKind ENUMERATION

Type of operating system

Held as u8.

windowsOs	0	posixOs	5
linuxOs	1	otherOs	6
androidOs	2		
appleOs	3		
unixOs	4		

Named by [ProcessInfo](#).

Priority ENUMERATION

Thread execution priorities

Held as u32.

lowest	0
nominalMin	1
nominalMax	2
highest	3

Named by [ComponentConfig](#).

PropertyCategorySpec ENUMERATION

how a property is seen by others

Held as u8.

staticRW	0
staticRO	1
dynamicRW	2
dynamicRO	3

Named by [PropertySpec](#), [PropertySpecV4](#), [PropertySpecV5](#).

PropertyRelationSpec ENUMERATION

method property relation

Held as u8.

nonPropertyRelated	0
propertyGetter	1
propertySetter	2

Named by [MethodSpec](#).

QueueEvictionPolicy ENUMERATION

Component queue eviction policy

Held as u32.

dropOldest	0
dropNewest	1

Named by [QueueConfig](#).

RealType ENUMERATION

built-in reals

Held as u8.

float32Type	0
float64Type	1

Named by [NumericType](#).

RunMode ENUMERATION

Run modes for the kernel

Held as u8.

realTime	0
virtualTime	1
virtualTimeRunning	2
startAndStop	3

Named by [KernelParams](#).

ThreadCreateErr ENUMERATION

What can go wrong when creating a thread

Held as u32.

schedulerAlreadyStarted	0
invalidStackSize	1
invalidThreadFunction	2
invalidThreadFunctionArgument	3
invalidAffinity	4
tooManyThreads	5
internalOsError	6

TransportModeSpec ENUMERATION

how to transport information

Held as u8.

unicast	0
multicast	1
confirmed	2

Named by [EventSpec](#), [EventSpecV4](#), [EventSpecV5](#), [MethodSpec](#), [MethodSpecV4](#), [MethodSpecV5](#), [PropertySpec](#), [PropertySpecV4](#), [PropertySpecV5](#).

UnitCat ENUMERATION

Type of measurement

Held as u8.

length	0
mass	1
time	2
angle	3
temperature	4
frequency	5
velocity	6
angularVelocity	7
acceleration	8
angularAcceleration	9
density	10
pressure	11
area	12
force	13
torque	14

Named by [UnitInfo](#).

WordSize ENUMERATION

Native processor word size

Held as u32.

bits32	0
bits64	1

Named by [BuildInfo](#), [SenData](#).

Variant records

BuiltInType	all built-in types	67
CustomTypeData	all custom types	67
CustomTypeDataV4		67
CustomTypeDataV5		67
NetworkFootprintPortValue	Known port number or range	67
NumericType	all built-in numeric types	68
OpState	The status of an operation	68
SleepPolicy	Component sleep policy	68

BuiltInType VARIANT

all built-in types

Type	Description
NumericType	
BasicType	

CustomTypeData VARIANT

all custom types

Type	Description
EnumTypeSpec	
QuantityTypeSpec	
SequenceTypeSpec	
StructTypeSpec	
VariantTypeSpec	
AliasTypeSpec	
OptionalTypeSpec	
ClassTypeSpec	

Named by [CustomTypeSpec](#).

CustomTypeDataV4 VARIANT

Type	Description
EnumTypeSpecV4	
QuantityTypeSpecV4	
SequenceTypeSpecV4	
StructTypeSpecV4	
VariantTypeSpecV4	
AliasTypeSpecV4	
OptionalTypeSpecV4	
ClassTypeSpecV4	

Named by [CustomTypeSpecV4](#).

CustomTypeDataV5 VARIANT

Type	Description
EnumTypeSpecV5	
QuantityTypeSpecV5	
SequenceTypeSpecV5	
StructTypeSpecV5	
VariantTypeSpecV5	
AliasTypeSpecV5	
OptionalTypeSpecV5	
ClassTypeSpecV5	

Named by [CustomTypeSpecV5](#).

NetworkFootprintPortValue VARIANT

Known port number or range

Type	Description
u16	
NetworkFootprintPort	
Range	

Named by [NetworkFootprintPort](#).

NumericType VARIANT

all built-in numeric types

Type	Description
IntegralType	
RealType	

Named by [BuiltInType](#), [QuantityTypeSpec](#), [QuantityTypeSpecV4](#), [QuantityTypeSpecV5](#).

OpState VARIANT

The status of an operation

Type	Description
OpFinished	done
OpNotFinished	not done

SleepPolicy VARIANT

Component sleep policy

Type	Description
PrecisionSleep	
SystemSleep	

Named by [ComponentConfig](#), [KernelParams](#).

Arrays

ArgSpecList	list of argument specs	69
ArgSpecListV4		69
ArgSpecListV5		69
Buffer	A general-purpose unbounded buffer	69
BuiltComponentList		69
CustomTypeSpecList	list of custom types	69
CustomTypeSpecListV4		69
CustomTypeSpecListV5		69
EnumeratorSpecList	list of enumerators	70
EnumeratorSpecListV4		70
EnumeratorSpecListV5		70
EnvironmentVarList		70
EventSpecList	list of event specs	70
EventSpecListV4		70
EventSpecListV5		70
LoadedComponentList		70
MethodSpecList	list of method specs	70
MethodSpecListV4		71
MethodSpecListV5		71
NetworkFootprintAddressRangeList		71
NetworkFootprintBusList	Buses included in a network footprint	71
NetworkFootprintPortList	Ports used by the process	71
NetworkFootprintPortRangeList		71
NetworkFootprintSelfCollisionList	Multicast address conflicts found in the reported buses	71
Processes	Unbounded sequence of ProcessInfo	71
PropertySpecList	list of property specs	71
PropertySpecListV4		72

PropertySpecListV5		72
StringList	Unbounded sequence of strings for general purpose	72
StructTypeFieldSpecList	list of struct fields	72
StructTypeFieldSpecListV4		72
StructTypeFieldSpecListV5		72
U32List		72
UnitList	Unbounded sequence of unit information structs	72
VariantTypeFieldSpecList	list of variant fields	72
VariantTypeFieldSpecListV4		73
VariantTypeFieldSpecListV5		73

ArgSpecList SEQUENCE

list of argument specs

```
sequence<ArgSpec> ArgSpecList;
```

Named by [EventSpec](#), [MethodSpec](#).

ArgSpecListV4 SEQUENCE

```
sequence<ArgSpecV4> ArgSpecListV4;
```

Named by [EventSpecV4](#), [MethodSpecV4](#).

ArgSpecListV5 SEQUENCE

```
sequence<ArgSpecV5> ArgSpecListV5;
```

Named by [EventSpecV5](#), [MethodSpecV5](#).

Buffer SEQUENCE

A general-purpose unbounded buffer

```
sequence<u8> Buffer;
```

Named by [sen.components.jsonrpc.StaticFile](#).

BuiltComponentList SEQUENCE

```
sequence<BuiltComponentParams> BuiltComponentList;
```

Named by [SenData](#).

CustomTypeSpecList SEQUENCE

list of custom types

```
sequence<CustomTypeSpec> CustomTypeSpecList;
```

Named by [sen.components.jsonrpc.JsonRpcServer](#).

CustomTypeSpecListV4 SEQUENCE

```
sequence<CustomTypeSpecV4> CustomTypeSpecListV4;
```

CustomTypeSpecListV5 SEQUENCE

```
sequence<CustomTypeSpecV5> CustomTypeSpecListV5;
```

EnumeratorSpecList SEQUENCE

list of enumerators

```
sequence<EnumeratorSpec> EnumeratorSpecList;
```

Named by [EnumTypeSpec](#).

EnumeratorSpecListV4 SEQUENCE

```
sequence<EnumeratorSpecV4> EnumeratorSpecListV4;
```

Named by [EnumTypeSpecV4](#).

EnumeratorSpecListV5 SEQUENCE

```
sequence<EnumeratorSpecV5> EnumeratorSpecListV5;
```

Named by [EnumTypeSpecV5](#).

EnvironmentVarList SEQUENCE

```
sequence<EnvVar> EnvironmentVarList;
```

Named by [ProcessData](#).

EventSpecList SEQUENCE

list of event specs

```
sequence<EventSpec> EventSpecList;
```

Named by [ClassTypeSpec](#).

EventSpecListV4 SEQUENCE

```
sequence<EventSpecV4> EventSpecListV4;
```

Named by [ClassTypeSpecV4](#).

EventSpecListV5 SEQUENCE

```
sequence<EventSpecV5> EventSpecListV5;
```

Named by [ClassTypeSpecV5](#).

LoadedComponentList SEQUENCE

```
sequence<LoadedComponentParams> LoadedComponentList;
```

Named by [SenData](#).

MethodSpecList SEQUENCE

list of method specs

```
sequence<MethodSpec> MethodSpecList;
```

Named by [ClassTypeSpec](#).

MethodSpecListV4 SEQUENCE

```
sequence<MethodSpecV4> MethodSpecListV4;
```

Named by [ClassTypeSpecV4](#).

MethodSpecListV5 SEQUENCE

```
sequence<MethodSpecV5> MethodSpecListV5;
```

Named by [ClassTypeSpecV5](#).

NetworkFootprintAddressRangeList SEQUENCE

```
sequence<NetworkFootprintAddressRange> NetworkFootprintAddressRangeList;
```

Named by [NetworkFootprintMulticast](#).

NetworkFootprintBusList SEQUENCE

Buses included in a network footprint

```
sequence<NetworkFootprintBus> NetworkFootprintBusList;
```

Named by [NetworkFootprintMulticast](#).

NetworkFootprintPortList SEQUENCE

Ports used by the process

```
sequence<NetworkFootprintPort> NetworkFootprintPortList;
```

Named by [NetworkFootprint](#).

NetworkFootprintPortRangeList SEQUENCE

```
sequence<NetworkFootprintPortRange> NetworkFootprintPortRangeList;
```

Named by [NetworkFootprintPortExclusions](#).

NetworkFootprintSelfCollisionList SEQUENCE

Multicast address conflicts found in the reported buses

```
sequence<NetworkFootprintSelfCollision> NetworkFootprintSelfCollisionList;
```

Named by [NetworkFootprintCollision](#).

Processes SEQUENCE

Unbounded sequence of ProcessInfo

```
sequence<ProcessInfo> Processes;
```

PropertySpecList SEQUENCE

list of property specs

```
sequence<PropertySpec> PropertySpecList;
```

Named by [ClassTypeSpec](#).

PropertySpecListV4 SEQUENCE

```
sequence<PropertySpecV4> PropertySpecListV4;
```

Named by [ClassTypeSpecV4](#).

PropertySpecListV5 SEQUENCE

```
sequence<PropertySpecV5> PropertySpecListV5;
```

Named by [ClassTypeSpecV5](#).

StringList SEQUENCE

Unbounded sequence of strings for general purpose

```
sequence<string> StringList;
```

Named by [sen.components.jsonrpc.JsonRpcServer](#), [sen.components.jsonrpc.NamedSelection](#), [sen.components.jsonrpc.SessionInfo](#), [BuiltComponentParams](#), [ClassTypeSpec](#), [ClassTypeSpecV4](#), [ClassTypeSpecV5](#), [ErrorData](#), [KernelApi](#), [ProcessData](#), [PropertySpec](#), [PropertySpecV4](#), [PropertySpecV5](#).

StructTypeFieldSpecList SEQUENCE

list of struct fields

```
sequence<StructTypeFieldSpec> StructTypeFieldSpecList;
```

Named by [StructTypeSpec](#).

StructTypeFieldSpecListV4 SEQUENCE

```
sequence<StructTypeFieldSpecV4> StructTypeFieldSpecListV4;
```

Named by [StructTypeSpecV4](#).

StructTypeFieldSpecListV5 SEQUENCE

```
sequence<StructTypeFieldSpecV5> StructTypeFieldSpecListV5;
```

Named by [StructTypeSpecV5](#).

U32List SEQUENCE

```
sequence<u32> U32List;
```

UnitList SEQUENCE

Unbounded sequence of unit information structs

```
sequence<UnitInfo> UnitList;
```

Named by [KernelApi](#).

VariantTypeFieldSpecList SEQUENCE

list of variant fields

```
sequence<VariantTypeFieldSpec> VariantTypeFieldSpecList;
```

Named by [VariantTypeSpec](#).

VariantTypeFieldSpecListV4

SEQUENCE

```
sequence<VariantTypeFieldSpecV4> VariantTypeFieldSpecListV4;
```

Named by [VariantTypeSpecV4](#).

VariantTypeFieldSpecListV5

SEQUENCE

```
sequence<VariantTypeFieldSpecV5> VariantTypeFieldSpecListV5;
```

Named by [VariantTypeSpecV5](#).

Optionals

MaybeException		73
MaybeF64	optional value for a f64	73
MaybeNetworkFootprintMulticast		73
MaybeNetworkFootprintPortValue	The value is not present when the port number is not known	73
MaybeSignal		73
MaybeStacktrace		73
MaybeTransportProtocol		73
MaybeU64	optional value for a u64	74

MaybeException

OPTIONAL

```
optional<UncaughtException> MaybeException;
```

MaybeF64

OPTIONAL

optional value for a f64

```
optional<f64> MaybeF64;
```

MaybeNetworkFootprintMulticast

OPTIONAL

```
optional<NetworkFootprintMulticast> MaybeNetworkFootprintMulticast;
```

MaybeNetworkFootprintPortValue

OPTIONAL

The value is not present when the port number is not known

```
optional<NetworkFootprintPortValue> MaybeNetworkFootprintPortValue;
```

MaybeSignal

OPTIONAL

```
optional<SignalData> MaybeSignal;
```

MaybeStacktrace

OPTIONAL

```
optional<StringList> MaybeStacktrace;
```

MaybeTransportProtocol

OPTIONAL

```
optional<u32> MaybeTransportProtocol;
```

MaybeU64 OPTIONAL

optional value for a u64

```
optional<u64> MaybeU64;
```

log

16 types.

Fixed records

BasicFile	Basic file sink	75
ColorStderr	Colored stderr sink	75
ColorStdout	Colored stdout sink	75
Config	Overall component configuration	75
LoggerConfig	Configuration used for a given spdlog logger.	75
Null	Single-threaded null sink	76
RotatingFile	Rotating file sink	76
SinkConfig	Configuration used for a given spdlog Sink.	76
Stderr	stderr sink	76
Stdout	stdout sink	76
Syslog	Syslog sink (only in linux)	76

BasicFile STRUCTURE

Basic file sink

Name	Type	Description
fileName	string	file to log to
truncate	bool	defaults to false
createParentDir	bool	true if we should create the parent dir first

Named by [SinkType](#).

ColorStderr STRUCTURE

Colored stderr sink

Named by [SinkType](#).

ColorStdout STRUCTURE

Colored stdout sink

Named by [SinkType](#).

Config STRUCTURE

Overall component configuration

Name	Type	Description
pattern	string	default format (empty means default)
level	LogLevel	default global level for all
sinks	SinkConfigList	sinks to configure
loggers	LoggerConfigList	loggers to configure
backtrace	bool	log backtrace is printed on failure

Named by [sen.kernel.KernelParams](#).

LoggerConfig STRUCTURE

Configuration used for a given spdlog logger.

Name	Type	Description
name	string	name of the logger
sinks	SinkNameList	name of the sinks to connect the logger to
level	LogLevel	default log level for this logger

Name	Type	Description
pattern	string	Formatting for the sinks in this logger. Does nothing if empty. Note that this replaces the format of the associated sinks, and this could affect other loggers using those sinks. The config is applied following the order of the Config.loggers field.

Named by [LoggerConfigList](#).

Null STRUCTURE

Single-threaded null sink

Named by [SinkType](#).

RotatingFile STRUCTURE

Rotating file sink

Name	Type	Description
baseFileName	string	
maxSize	u32	0 means use defaults
maxFiles	u32	0 means use defaults

Named by [SinkType](#).

SinkConfig STRUCTURE

Configuration used for a given spdlog Sink.

Name	Type	Description
name	string	name of the sink
singleThreaded	bool	if true, single-threaded (defaults to false)
pattern	string	the pattern used for the formatting (empty means default).
level	LogLevel	default log level for this sink
config	SinkType	the type-specific configuration parameters

Named by [SinkConfigList](#).

Stderr STRUCTURE

stderr sink

Named by [SinkType](#).

Stdout STRUCTURE

stdout sink

Named by [SinkType](#).

Syslog STRUCTURE

Syslog sink (only in linux)

Name	Type	Description
identity	string	
option	u32	
enableFormatting	bool	

Named by [SinkType](#).

Enumerations

[LogLevel](#)

Severity/importance of a log message.

77

LogLevel ENUMERATION

Severity/importance of a log message.

Held as u8.

warn	0
err	1
critical	2
trace	3
debug	4
info	5
off	6

Named by [sen.components.logmaster.LogMaster](#), [sen.components.logmaster.Logger](#), [Config](#), [LoggerConfig](#), [SinkConfig](#).

Variant records

[SinkType](#)

The type-specific configuration of the used spdlog Sink.

77

SinkType VARIANT

The type-specific configuration of the used spdlog Sink.

Type	Description
ColorStdout	
ColorStderr	
Stdout	
Stderr	
BasicFile	
RotatingFile	
Null	
Syslog	

Named by [SinkConfig](#).

Arrays

[LoggerConfigList](#)

77

[SinkConfigList](#)

77

[SinkNameList](#)

77

LoggerConfigList SEQUENCE

```
sequence<LoggerConfig> LoggerConfigList;
```

Named by [Config](#).

SinkConfigList SEQUENCE

```
sequence<SinkConfig> SinkConfigList;
```

Named by [Config](#).

SinkNameList SEQUENCE

```
sequence<string> SinkNameList;
```

Named by [LoggerConfig](#).

Built-in types

The types the language provides. Every one is written the same way on the wire wherever it appears.

Type	Meaning
<code>bool</code>	classic boolean
<code>f32</code>	32 bit floating point number
<code>f64</code>	64 bit floating point number
<code>i32</code>	32 bit signed integer
<code>sen.Duration</code>	a time duration
<code>sen.TimeStamp</code>	a point in time
<code>string</code>	unbounded string
<code>u16</code>	16 bit unsigned integer
<code>u32</code>	32 bit unsigned integer
<code>u64</code>	64 bit unsigned integer
<code>u8</code>	8 bit unsigned integer

Index

components.ether.BusConfig	7	components.logmaster.Config	26	kernel.BasicType	62
components.ether.BusJoined	7	components.logmaster.LogMaster	26	kernel.Buffer	69
components.ether.BusLeft	7	components.logmaster.Logger	26	kernel.BuildInfo	47
components.ether.ByteRange	8	components.py.Configuration	27	kernel.BuiltComponentList	69
components.ether.Configuration	8	components.py.PythonInterpreter	27	kernel.BuiltComponentParams	47
components.ether.ControlMessage	11	components.py.StringList	27	kernel.BuiltInType	67
components.ether.DiscoveryConfig	11	components.recorder.Configuration	28	kernel.BusAddress	47
components.ether.DiscoveryHubAddress	8	components.recorder.Recorder	28	kernel.ClassTypeSpec	47
components.ether.Endpoint	8	components.recorder.RecorderState	28	kernel.ClassTypeSpecV4	48
components.ether.EnpointList	11	components.recorder.RecordingSettings	28	kernel.ClassTypeSpecV5	48
components.ether.Ephemeral	8			kernel.CompatibilityMode	62
components.ether.Hello	8			kernel.ComponentConfig	48
components.ether.MaybeDeviceName	12	components.recorder.RecordingSettings	29	kernel.ComponentInfo	48
components.ether.MaybeDiscoveryHub	12	List	29	kernel.ComponentState	62
Port	12	components.recorder.SelectionList	29	kernel.CpuArch	63
components.ether.MaybePortConfig	12	components.replayer.Configuration	30	kernel.CustomTypeData	67
components.ether.MulticastAddress	12	components.replayer.Replay	30	kernel.CustomTypeDataV4	67
Exclusions	12	components.replayer.ReplayStatus	31	kernel.CustomTypeDataV5	67
components.ether.MulticastAddress	12	components.replayer.Replayer	30	kernel.CustomTypeSpec	49
Range	9	components.rest.Argument	32	kernel.CustomTypeSpecList	69
components.ether.MulticastDiscovery	9	components.rest.Arguments	36	kernel.CustomTypeSpecListV4	69
components.ether.MulticastRange	12	components.rest.Bus	32	kernel.CustomTypeSpecListV5	69
components.ether.PinnedPort	9	components.rest.BusNames	36	kernel.CustomTypeSpecV4	49
components.ether.PortBinding	11	components.rest.BusSummary	32	kernel.CustomTypeSpecV5	49
components.ether.PortConfig	9	components.rest.Buses	36	kernel.EnumTypeSpec	49
components.ether.PortExclusions	12	components.rest.ClientAuth	32	kernel.EnumTypeSpecV4	49
components.ether.PortRange	9	components.rest.Configuration	33	kernel.EnumTypeSpecV5	50
components.ether.ProbePortRange	10	components.rest.Error	33	kernel.EnumeratorSpec	50
components.ether.ProtocolVersion	10	components.rest.Events	36	kernel.EnumeratorSpecList	70
components.ether.QueueConfig	10	components.rest.HttpMethod	35	kernel.EnumeratorSpecListV4	70
components.ether.QueueEvictionPolicy	11	components.rest.Interest	33	kernel.EnumeratorSpecListV5	70
components.ether.Ready	10	components.rest.InterestSummary	33	kernel.EnumeratorSpecV4	50
components.ether.SessionPresenceBeam	10	components.rest.InterestsSummary	36	kernel.EnumeratorSpecV5	50
components.ether.TcpDiscovery	10	components.rest.InvokeStatus	35	kernel.EnvVar	50
components.explorer.Configuration	13	components.rest.Link	33	kernel.EnvironmentVarList	70
components.influx.Configuration	14	components.rest.Links	36	kernel.ErrorCategory	63
components.influx.Protocol	14	components.rest.Notification	33	kernel.ErrorData	50
components.influx.SelectionList	14	components.rest.NotificationType	35	kernel.ErrorReport	51
components.jsonrpc.AddedObjectEntry	19	components.rest.Object	33	kernel.EventSpec	51
components.jsonrpc.AddedObjectList	23	components.rest.ObjectEvent	34	kernel.EventSpecList	70
components.jsonrpc.Configuration	20	components.rest.ObjectMethod	34	kernel.EventSpecListV4	70
components.jsonrpc.ConnectionLimits	20	components.rest.ObjectSummary	34	kernel.EventSpecListV5	70
components.jsonrpc.Identity	20	components.rest.ObjectsSummary	36	kernel.EventSpecV4	51
components.jsonrpc.JsonRpcServer	15	components.rest.Properties	37	kernel.EventSpecV5	51
components.jsonrpc.MaybeConnection	15	components.rest.RelType	35	kernel.ExceptionKind	63
Limits	24	components.rest.Session	34	kernel.ExecError	51
components.jsonrpc.MaybeControlBus	24	components.rest.SessionSummary	34	kernel.GitStatus	63
Name	24	components.rest.Sessions	37	kernel.IntegralType	64
components.jsonrpc.MaybeFlag	24	components.rest.Status	36	kernel.KernelApi	44
components.jsonrpc.MaybeHigh	24	components.rest.SubscriptionOptions	34	kernel.KernelParams	51
BackpressureBytes	24	components.rest.Subscriptions	34	kernel.LoadedComponentList	70
components.jsonrpc.MaybeIdleTimeout	24	components.rest.Success	35	kernel.LoadedComponentParams	52
Seconds	25	components.rest.ThreadPoolSize	37	kernel.MaybeException	73
BackpressureBytes	25	components.rest.UpdateFrequency	37	kernel.MaybeF64	73
components.jsonrpc.MaybeMaxPayload	25	components.rest.UpdateTime	37	kernel.MaybeNetworkFootprintMulticast	73
Bytes	25	components.rest.Version	35	kernel.MaybeNetworkFootprintPortValue	73
components.jsonrpc.MaybeMember	25	components.shell.BufferStyle	41		
Selector	25	components.shell.CPrint	38	kernel.MaybeSignal	73
components.jsonrpc.MaybeRateHz	25	components.shell.ClearCurrentLine	39	kernel.MaybeStackTrace	73
components.jsonrpc.MaybeStringList	25	components.shell.ClearRemainingCurrent	39	kernel.MaybeTransportProtocol	73
components.jsonrpc.MaybeSubscribe	25	Line	39	kernel.MaybeU64	74
Block	25	components.shell.ClearScreen	39	kernel.MethodConstnessSpec	64
components.jsonrpc.MaybeTlsConfig	25	components.shell.Configuration	39	kernel.MethodSpec	52
components.jsonrpc.MaybeUpdateFreqHz	25	components.shell.HideCursor	39	kernel.MethodSpecList	70
components.jsonrpc.MemberSelector	23	components.shell.ListStyle	41	kernel.MethodSpecListV4	71
components.jsonrpc.NamedSelection	20	components.shell.MoveCursorAllLeft	39	kernel.MethodSpecListV5	71
components.jsonrpc.ObjectInfo	20	components.shell.MoveCursorDown	39	kernel.MethodSpecV4	52
components.jsonrpc.ObjectInfos	23	components.shell.MoveCursorLeft	39	kernel.MethodSpecV5	53
components.jsonrpc.ObjectState	21	components.shell.MoveCursorRight	39	kernel.NetworkFootprint	53
components.jsonrpc.ObjectStateList	23	components.shell.MoveCursorUp	40	kernel.NetworkFootprintAddressRange	53
components.jsonrpc.PropertyError	21	components.shell.NewLine	40	kernel.NetworkFootprintAddressRange	53
components.jsonrpc.PropertyErrorList	23	components.shell.Print	40	List	71
components.jsonrpc.PropertyValueList	24	components.shell.Query	40	kernel.NetworkFootprintBus	53
components.jsonrpc.PropertyValuePair	21	components.shell.QueryList	42	kernel.NetworkFootprintBusIdentity	54
components.jsonrpc.RegisteredBundle	21	components.shell.RestoreCursorPosition	42	kernel.NetworkFootprintBusList	71
Info	21			kernel.NetworkFootprintBusSource	64
components.jsonrpc.RegisteredBundle	21	components.shell.SaveCursorPosition	40	kernel.NetworkFootprintCollision	54
InfoList	24	components.shell.SetBgColor	40	kernel.NetworkFootprintMulticast	54
components.jsonrpc.SessionInfo	21	components.shell.SetFgColor	40	kernel.NetworkFootprintPort	54
components.jsonrpc.SessionInfoList	24	components.shell.SetWindowTitle	40	kernel.NetworkFootprintPortExclusions	55
components.jsonrpc.StaticBundle	22	components.shell.Shell	38	kernel.NetworkFootprintPortKind	64
components.jsonrpc.StaticFile	22	components.shell.ShowCursor	41	kernel.NetworkFootprintPortList	71
components.jsonrpc.StaticFileList	24	components.shell.SourcesList	42	kernel.NetworkFootprintPortMode	64
components.jsonrpc.StaticFileServer	18	components.shell.TerminalCmd	41	kernel.NetworkFootprintPortRange	55
components.jsonrpc.SubscribeBlock	22	components.shell.TimeStyle	41	kernel.NetworkFootprintPortRangeList	71
components.jsonrpc.TlsConfig	22	db.OutSettings	43	kernel.NetworkFootprintPortValue	67
components.jsonrpc.TypeLookupResult	22	db.OutStats	43	kernel.NetworkFootprintSelfCollision	55
components.jsonrpc.WildcardSelection	23	db.Summary	43	kernel.NetworkFootprintSelfCollisionList	55
		kernel.AliasTypeSpec	46		
		kernel.AliasTypeSpecV4	46	71	
		kernel.AliasTypeSpecV5	46	kernel.NumericType	68
		kernel.ArgSpec	46	kernel.OpFinished	55
		kernel.ArgSpecList	69	kernel.OpNotFinished	55
		kernel.ArgSpecListV4	69	kernel.OpState	68
		kernel.ArgSpecListV5	69	kernel.OptionalTypeSpec	55
		kernel.ArgSpecV4	46	kernel.OptionalTypeSpecV4	56
		kernel.ArgSpecV5	47	kernel.OptionalTypeSpecV5	56

kernel.OsKind	64
kernel.PrecisionSleep	56
kernel.Priority	65
kernel.ProcessData	56
kernel.ProcessInfo	56
kernel.Processes	71
kernel.PropertyCategorySpec	65
kernel.PropertyRelationSpec	65
kernel.PropertySpec	57
kernel.PropertySpecList	71
kernel.PropertySpecListV4	72
kernel.PropertySpecListV5	72
kernel.PropertySpecV4	57
kernel.PropertySpecV5	57
kernel.QuantityTypeSpec	57
kernel.QuantityTypeSpecV4	58
kernel.QuantityTypeSpecV5	58
kernel.QueueConfig	58
kernel.QueueEvictionPolicy	65
kernel.RealType	65
kernel.RunMode	65
kernel.SenData	58
kernel.SequenceTypeSpec	58
kernel.SequenceTypeSpecV4	59
kernel.SequenceTypeSpecV5	59
kernel.SignalData	59
kernel.SleepPolicy	68
kernel.StringList	72
kernel.StructTypeFieldSpec	59
kernel.StructTypeFieldSpecList	72
kernel.StructTypeFieldSpecListV4	72
kernel.StructTypeFieldSpecListV5	72
kernel.StructTypeFieldSpecV4	59
kernel.StructTypeFieldSpecV5	60
kernel.StructTypeSpec	60
kernel.StructTypeSpecV4	60
kernel.StructTypeSpecV5	60
kernel.SystemSleep	60
kernel.ThreadCreateErr	66
kernel.TransportModeSpec	66
kernel.U32List	72
kernel.UncaughtException	60
kernel.UnitCat	66
kernel.UnitInfo	60
kernel.UnitList	72
kernel.VariantTypeFieldSpec	61
kernel.VariantTypeFieldSpecList	72
kernel.VariantTypeFieldSpecListV4	73
kernel.VariantTypeFieldSpecListV5	73
kernel.VariantTypeFieldSpecV4	61
kernel.VariantTypeFieldSpecV5	61
kernel.VariantTypeSpec	61
kernel.VariantTypeSpecV4	61
kernel.VariantTypeSpecV5	62
kernel.VirtualClock	44
kernel.VirtualKernelClock	44
kernel.VirtualMasterClock	44
kernel.WordSize	66
kernel.log.BasicFile	75
kernel.log.ColorStderr	75
kernel.log.ColorStdout	75
kernel.log.Config	75
kernel.log.LogLevel	77
kernel.log.LoggerConfig	75
kernel.log.LoggerConfigList	77
kernel.log.Null	76
kernel.log.RotatingFile	76
kernel.log.SinkConfig	76
kernel.log.SinkConfigList	77
kernel.log.SinkNameList	77
kernel.log.SinkType	77
kernel.log.Stderr	76
kernel.log.Stdout	76
kernel.log.Syslog	76