FAN CHAMBERS
Technical Specifications

VANTERM



Fan Chamber incl. silencer

Motor power: 75 kW
Air capacity: 50 000 m³/h

EASY TO ASSEMBLE & OPERATE

WHERE TO USE

- VANTERM Fan chambers are used as a complementary part of the filtration projects with VANTERM dust collectors. They are mostly used to control and capture the smoke and dust in production halls.

STANDART FEATURES

- High efficiency backward curved radial ventilators are used in the fan chambers.
- The ventilators used in the VANTERM fan chambers, are statically and dynamically balanced in G2.5 or G6.3 quality according to ISO 1940 standard by VANTERM talented craftsman.

ENERGY SAVING & MAXIMUM SAFETY

- VFD driven and automatic PID control of the fan speed with pressure transmitter enables energy saving.
- The fan chamber service door is equipped with safety switch, which avoids unauthorized personnel to enter in during operation.
- The ventilator is equipped with vibration sensor to guarantee a long life-time for the ventilator and the bearings.

EASY SERVICE & MAINTENANCE

- All the components used in the fan chambers (bearings, pulleys, belts …etc.) are from internationally well-known companies and available world-wide such as SKF, FAG etc.



Fan Chamber incl. silencer

Motor power: 18,5 kW
Air capacity: 12 000 m³/h



Fan Chamber incl. silencer

Motor power: 11,0 kW
Air capacity: 15 000 m³/h