NOTES:

Note:
1) Due to continuous research development, specifications features may change without prior notice
2) Weight data mentioned above is provided considering tolerance of ±2kg due to uncontrollable factors

Panasonic

store.in.panasonic.com

REACH US ON: 9311211333

Third party laboratory test conditions have confirmed that nanoe technology inhibits bacteria and viruses & removes 99% PM 2.5 after 4 hours continuous use & cleaning efficiency may differ during actual usage. Visual representation and images are for illustration purposes only and actual may vary. India's 1st matter-enabled room air conditioner from a leading brand*. #Source: Euromonitor International Limited, Consumer Appliances 2025 edition, per Consumer Appliances definition, retail unit volume, 2024 data. Any pictorial representation is for reference only & actual may vary. All trademarks are the property of their respective owners. For more details, visit Panasonic.com/in

@panasonicindia | Panasonicin | @panasonic_india | @Panasonicindia | www.panasonic.com/in

GT Version 2026

Panasonic | JAPAN'S NO.1 CONSUMER APPLIANCES BRAND*

INDIA KA CaptAIn Cool

TRUSTED AC FOR SMART INDIA

MirAIle Connected Living | INDIA'S 1st matter ENABLED RAC* | AI | nanoe | converti 8™

— ODU AUTO CLEAN — DUSTBUSTER™ COOLING | EFFICIENCY | RELIABILITY

*Source: Euromonitor International Limited, Consumer Appliances 2025 edition., per Consumer Appliances definition, retail unit volume, 2024 data.

TRUSTED QUALITY COOLING

SYMBOL OF ABSOLUTE T.R.U.S.T

- **T** TECHNOLOGY: matter, MirAIle Connected Living, AQI Air Quality Index, Proximity control, nanoeX, nanoe-G
- **R** RELIABILITY: ecoTOUCH, Shield Blu+, Blue Fin Condenser, 100% COPPER
- **U** ULTRA EFFICIENT: ODU AUTO CLEAN DUSTBUSTER™, CRYSTAL CLEAN, AI converti 8™
- **S** SUPERIOR COOLING: COOLS EVEN AT 55°, POWERFUL MODE, HIGHER AIRFLOW, 4 WAY SWING
- **T** TRUSTED QUALITY: JAPAN'S NO.1 CONSUMER APPLIANCES BRAND*, 67+ YEARS OF AC LEGACY

ONE TOUCH CONVENIENCE FOR YOUR HOME

MirAIle Connected Living

AVAILABLE IN 9 LANGUAGES NOW

INDIA'S 1st matter ENABLED RAC*

Our Matter-enabled air conditioners are built to change and adapt as technology does, making sure they work with new gadgets and innovations and future-proofing your smart home setup. It offers interoperability, helping you choose from a wider range of options without worrying about compatibility problems. It also comes with enhanced security and a simple set-up procedure.

- **INTEROPERABLE** — Devices from Multiple Brands Work Natively Together
- **SIMPLE** — Easy Setup & Control of Your Smart Devices with Multiple Ecosystems
- **SECURE** — User Authentication and Encryption to Transfer Data
- **RELIABLE** — Consistent & Responsive Local Connectivity Without Internet

#Certified by Euromonitor

EUROMONITOR INTERNATIONAL

Scan to know more

*Source: Euromonitor International Limited, leading brands considered account for over 90% of retail value sales in India in 2022, claim for room ACs only, all retail channels, research as of 01/12/2023.

EFFICIENT COOLING WITH ODU AUTO CLEAN

— ODU AUTO CLEAN — DUSTBUSTER™ COOLING | EFFICIENCY | RELIABILITY

FIGHTS DUST, COOLS CONSISTENTLY

Auto cleans the outdoor unit coils every 8 hours*

- Steady Cooling
- Better Efficiency
- Longer Life

In DustBuster™ mode, ODU fan rotates in reverse direction for 3 minutes after every 8 hours* of running.

*Available in selected models only. *T&C Apply

BREATH CLEAN AIR WITH ACTIVE AIR PURIFICATION

nanoe™ TECHNOLOGY

7 benefits of nanoe™ X

- Repels allergens* effectively
- Averts pollen* with ease
- Inhibits bacteria* & viruses
- Blocks hazardous* substances
- Deodourises* & get rid of foul odour
- Moisturises* your skin & hair
- Prevents mold*

nanoe-G

KEEPS THE AIR HEALTHY & CLEAN

Remove dust particle from the air

AQI SENSOR INSIDE — Removes 99%* PM 2.5

Air Quality Index

Panasonic's advanced Active Purification System

99% clean air

PM 0.1 FILTER

ADAPTIVE COOLING WITH AI

All MirAIle enabled inverter range of Air Conditioners come with AI

MirAIle Connected Living | AI

BASED ON THE AMBIENT CONDITIONS THE AI MODE CONTROLS

TEMPERATURE | MODE | FAN SPEED

ADAPTIVE THERMAL COMFORT MODEL

- AI Mode uses Adaptive Thermal Comfort Model to maintain the ambience of the room within a comfortable range.
- It automatically manages temperature profile, mode and fan speed of AC based on indoor & outdoor temperature and external humidity.

ENSURE COMFORT & EFFICIENCY WITH PROXIMITY CONTROL

Get Notifications on the MirAIle App to Turn Your AC On/Off as You Enter/Exit a Custom Range (100 m – 35 km)*

SELF CLEANING MODE THAT ENSURES LONG LIFE OF YOUR AC

Longer life & better air quality | Removal of dust & pollutants

Start the Automated cleaning process with the clean mode button

8-STAGES OF COOLING PERFORMANCE

converti 8™

Super convertible with 8 stages of cooling performance*

Allows the user to save energy with adjustment of cooling performance using remote controller or MirAIle App

Manually adjust the AC for upto 8 stages of cooling performance from 40%* to more than 100%*

Efficiently adjusts the cooling performance by detecting your room's temperature and changing the fan speed.

*Only inverter models

ULTIMATE COOLING COMFORT

COOLING COMFORT AND ENERGY EFFICIENCY ENABLED

Auto-convertible INVERTER

- Precise temperature control*
- 100% capacity even at 48°C for 5 Star Split Inverter AC*
- Minimal temperature fluctuations*

FASTER COOLING: Delivers powerful air at start-up.

STABLE TEMPERATURE: High rotation for smooth, stable, and uniform operation

For 4 Star Inverter Split: 100%* Capacity at 46°C
For 3 Star Inverter Split: 100%* Capacity at 43°C

ULTIMATE COOLING COMFORT

FASTER AND EFFICIENT COOLING

POWERFUL MODE

- Powerful operation that maximises cooling
- Cools your room faster and quicker

ACHIEVES DESIRED TEMPERATURE QUICKER

Internal setting decreases set temperature by 2°C in, (-2°C) instantly once the Powerful button is pressed. Fan speed will be super high and it will remain so for 60 mins (1 hour).

DESERT SERIES

Escape the heat with high performance cooling

Bigger indoor unit	High capacity	Higher airflow
of 1.1 meter	up to 2.75 TR	up to 851 CFM

*In selected models only

HOT & COLD SERIES

Our air conditioners are designed factoring in local weather conditions and are used in a wide range of extreme hot & cold regions.

*For EZ Series

PREMIUM JAPANESE DESIGN

SLIM AND SLEEK DESIGN — Elegantly crafted design seamlessly integrates into any interior.

BIGGER INDOOR UNIT — Wide Indoor unit with Higher Airflow for ultimate cooling & comfort

CRAFTED FOR LONG LASTING DURABILITY

HIGHER* AIRFLOW



BUILT TO WITHSTAND TOUGH CONDITIONS

Shield-Blu+ — 2X Increased Heat Xchanger Lifespan

- "Blue Fin" technology with hydrophilic properties
- Protects from air, water and other corrosives
- Anti corrosive blue coating on copper U-Bend

2x the life of Heat Exchanger

ALL-WEATHER ENDURANCE

ecoTOUCH Outdoor Unit

Exceptionally crafted to resist tough weather conditions like rain, direct sunlight and strong winds

Longer life and 5-year warranty on outdoor casing

100%* GROOVED COPPER TUBING

Faster heat transfer — better heat transfer and easy to maintain and repair

STABILIZER-FREE* OPERATION

100-290V : All Inverter Series
145-280V : Window XU & LU Model
170-265V : Fixed Speed - KN Series

Stable voltage output even when power fluctuation occurs

Blue Fin Condenser

Durability & long-term performance

Blue Fin anti-rust coating extends the condenser's life and increases durability

*Refer to detailed specification table for all models

5 STAR Auto Convertible* INVERTER

AMAZE SERIES



SPECIFICATIONS

Model		[50Hz]	CS/CU-HU2CKY5FM-P	CS/CU-HU18CKY5XFMH-P
Type			Cooling Only	Cooling Only
Tonnage Class		TR	1.0	1.5
Cooling Capacity Standard [Min. - Max.]		Btu/h	9772 [5297 - 12949]	18406 [8107 - 19818]
		W	3450 [1553 - 3795]	5280 [2376 - 5808]
Heating Capacity Standard [Min. - Max.]		Btu/h	-	-
		W	-	-
ISEER		-	5.80	5.80
Annual Power Consumption		kWh	460.65	704.45
Star Rating			5★	5★
Electrical Data	Voltage	V-AC	230	230
	Phase	Φ	Single Phase	Single Phase
	Running Current	A	3.7	5.6
	Power Input, Standard Cooling [Min. - Max.]	W	810 [254 - 1094]	1220 [363 - 1647]
	Power Input, Standard Heating [Min. - Max.]	W	-	-
Moisture Removal Rate		l/h	1.0	1.2
		Pt/h	21	2.5
Air Circulation (Indoor)		m³/min	14.0	19.9
		ft³/min	494	703
		m/s	8.60	11.94
Net Dimensions of the Indoor Unit	Length (L)	cm	87.0	104.0
	Breadth (B)	cm	22.9	24.4
	Height (H)	cm	29.5	29.6
Gross Dimensions of the Indoor Unit	Length (L)	cm	95.2	114.8
	Breadth (B)	cm	28.3	31.4
	Height (H)	cm	37.4	38.3
Net Dimensions of the Outdoor Unit	Length (L)	cm	78.0	78.0
	Breadth (B)	cm	28.8	28.8
	Height (H)	cm	54.2	54.2
Gross Dimensions of the Outdoor Unit	Length (L)	cm	90.0	90.0
	Breadth (B)	cm	40.5	40.5
	Height (H)	cm	60.7	60.7
Noise Level	Indoor (H/Q)	[dB-A]	44.72	47.54
	Outdoor	[dB-A]	53	54
Net Weight	IDU [ODU]	kg	10 [23]	12 [26]
Gross Weight	IDU [ODU]	kg	11 [27]	14 [30]
Refrigerant		-	R-32	R-32
Operating Temperature Range		°C	16 - 55	16 - 55
Operating Voltage Range		V	100-290	100-290
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635	Ø0.635
	Gas Side	cm	Ø0.952	Ø1.270
Pipe Extension	Chargeless Pipe Length *	m	7.5	7.5
	Maximum Pipe Length *	m	10	15
	Maximum Elevation Length *	m	5	10
	Additional Refrigerant Gas *	g/m	10	15
Power Supply Source		-	Indoor	Indoor

WARRANTY 10 YEARS COMPRESSOR, 5 YEARS PCB, 5 YEARS PANEL

*T&C Apply

OUTDOOR

AMAZE SERIES



SPECIFICATIONS

Model		[50Hz]	CS/CU-EU2CKY5FM	CS/CU-EU18CKY5XFM
Type			Cooling Only	Cooling Only
Tonnage Class		TR	1.0	1.5
Cooling Capacity Standard [Min. - Max.]		Btu/h	9772 [5297 - 12949]	17402 [7831 - 19142]
		W	3450 [1553 - 3795]	5100 [2295 - 5610]
Heating Capacity Standard [Min. - Max.]		Btu/h	-	-
		W	-	-
ISEER		-	5.80	5.80
Annual Power Consumption		kWh	460.65	681.01
Star Rating			5★	5★
Electrical Data	Voltage	V-AC	230	230
	Phase	Φ	Single Phase	Single Phase
	Running Current	A	3.7	5.4
	Power Input, Standard Cooling [Min. - Max.]	W	810 [254 - 1094]	1178 [351 - 1590]
	Power Input, Standard Heating [Min. - Max.]	W	-	-
Moisture Removal Rate		l/h	1.0	1.2
		Pt/h	21	2.5
Air Circulation (Indoor)		m³/min	14.0	19.9
		ft³/min	494	703
		m/s	8.60	11.94
Net Dimensions of the Indoor Unit	Length (L)	cm	87.0	104.0
	Breadth (B)	cm	22.9	24.4
	Height (H)	cm	29.5	29.6
Gross Dimensions of the Indoor Unit	Length (L)	cm	95.2	114.8
	Breadth (B)	cm	28.3	31.4
	Height (H)	cm	37.4	38.3
Net Dimensions of the Outdoor Unit	Length (L)	cm	78.0	78.0
	Breadth (B)	cm	28.8	28.8
	Height (H)	cm	54.2	54.2
Gross Dimensions of the Outdoor Unit	Length (L)	cm	90.0	90.0
	Breadth (B)	cm	40.5	40.5
	Height (H)	cm	60.7	60.7
Noise Level	Indoor (H/Q)	[dB-A]	44.72	47.54
	Outdoor	[dB-A]	53	54
Net Weight	IDU [ODU]	kg	10 (23)	12 (26)
Gross Weight	IDU [ODU]	kg	11 (27)	14 (30)
Refrigerant		-	R-32	R-32
Operating Temperature Range		°C	16 - 55	16 - 55
Operating Voltage Range		V	100-290	100-290
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635	Ø0.635
	Gas Side	cm	Ø0.952	Ø1.270
Pipe Extension	Chargeless Pipe Length *	m	7.5	7.5
	Maximum Pipe Length *	m	10	15
	Maximum Elevation Length *	m	5	10
	Additional Refrigerant Gas *	g/m	10	15
Power Supply Source		-	Indoor	Indoor

WARRANTY 10 YEARS COMPRESSOR, 5 YEARS PCB, 5 YEARS PANEL

*T&C Apply

OUTDOOR

AMAZE SERIES

SPECIFICATIONS

Model		[50Hz]	CS/CU-EU2CKY5F	CS/CU-EU18CKY5XF
Type			Cooling Only	Cooling Only
Tonnage Class		TR	1.0	1.5
Cooling Capacity Standard [Min. - Max.]		Btu/h	9772 [5297 - 12949]	17402 [7831 - 19142]
		W	3450 [1553 - 3795]	5100 [2295 - 5610]
Heating Capacity Standard [Min. - Max.]		Btu/h	-	-
		W	-	-
ISEER		-	5.80	5.80
Annual Power Consumption		kWh	460.65	681.01
Star Rating			5★	5★
Electrical Data	Voltage	V-AC	230	230
	Phase	Φ	Single Phase	Single Phase
	Running Current	A	3.7	5.4
	Power Input, Standard Cooling [Min. - Max.]	W	810 [254 - 1094]	1178 [351 - 1590]
	Power Input, Standard Heating [Min. - Max.]	W	-	-
Moisture Removal Rate		l/h	1.0	1.2
		Pt/h	21	2.5
Air Circulation (Indoor)		m³/min	14.0	19.9
		ft³/min	494	703
		m/s	8.60	11.94
Net Dimensions of the Indoor Unit	Length (L)	cm	87.0	104.0
	Breadth (B)	cm	22.9	24.4
	Height (H)	cm	29.5	29.6
Gross Dimensions of the Indoor Unit	Length (L)	cm	95.2	114.8
	Breadth (B)	cm	28.3	31.4
	Height (H)	cm	37.4	38.3
Net Dimensions of the Outdoor Unit	Length (L)	cm	78.0	78.0
	Breadth (B)	cm	28.8	28.8
	Height (H)	cm	54.2	54.2
Gross Dimensions of the Outdoor Unit	Length (L)	cm	90.0	90.0
	Breadth (B)	cm	40.5	40.5
	Height (H)	cm	60.7	60.7
Noise Level	Indoor (H/Q)	[dB-A]	44.72	47.54
	Outdoor	[dB-A]	53	54
Net Weight	IDU [ODU]	kg	10 (23)	12 (26)
Gross Weight	IDU [ODU]	kg	11 (27)	14 (30)
Refrigerant		-	R-32	R-32
Operating Temperature Range		°C	16 - 55	16 - 55
Operating Voltage Range		V	100-290	100-290
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635	Ø0.635
	Gas Side	cm	Ø0.952	Ø1.270
Pipe Extension	Chargeless Pipe Length *	m	7.5	7.5
	Maximum Pipe Length *	m	10	15
	Maximum Elevation Length *	m	5	10
	Additional Refrigerant Gas *	g/m	10	15
Power Supply Source		-	Indoor	Indoor

WARRANTY 10 YEARS COMPRESSOR, 5 YEARS PCB, 5 YEARS PANEL

*T&C Apply

OUTDOOR

ACE+ SERIES

SPECIFICATIONS

Model		[50Hz]	CS/CU-EU24CKY5FM
Type			Cooling Only
Tonnage Class		TR	2.0
Cooling Capacity Standard [Min. - Max.]		Btu/h	22520 [10154 - 24772]
		W	6600 [2970 - 7260]
Heating Capacity Standard [Min. - Max.]		Btu/h	-
		W	-
ISEER		-	5.80
Annual Power Consumption		kWh	881.19
Star Rating			5★
Electrical Data	Voltage	V-AC	230
	Phase	Φ	Single Phase
	Running Current	A	6.7
	Power Input, Standard Cooling [Min. - Max.]	W	1470 [469 - 1985]
	Power Input, Standard Heating [Min. - Max.]	W	-
Moisture Removal Rate		l/h	3.0
		Pt/h	6.3
Air Circulation (Indoor)		m³/min	24.1
		ft³/min	851
		m/s	14.46
Net Dimensions of the Indoor Unit	Length (L)	cm	110.0
	Breadth (B)	cm	25.0
	Height (H)	cm	33.0
Gross Dimensions of the Indoor Unit	Length (L)	cm	118.4
	Breadth (B)	cm	32.0
	Height (H)	cm	40.0
Net Dimensions of the Outdoor Unit	Length (L)	cm	87.5
	Breadth (B)	cm	32.0
	Height (H)	cm	75.0
Gross Dimensions of the Outdoor Unit	Length (L)	cm	104.9
	Breadth (B)	cm	48.5
	Height (H)	cm	83.3
Noise Level	Indoor (H/Q)	[dB-A]	52.46
	Outdoor	[dB-A]	62
Net Weight	IDU [ODU]	kg	15 (40.5)
Gross Weight	IDU [ODU]	kg	17.5 (48)
Refrigerant		-	R-32
Operating Temperature Range		°C	16 - 55
Operating Voltage Range		V	100-290
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635
	Gas Side	cm	Ø1.588
Pipe Extension	Chargeless Pipe Length *	m	7.5
	Maximum Pipe Length *	m	15
	Maximum Elevation Length *	m	10
	Additional Refrigerant Gas *	g/m	20
Power Supply Source		-	Indoor

WARRANTY 10 YEARS COMPRESSOR, 5 YEARS PCB, 5 YEARS PANEL

*T&C Apply

OUTDOOR

4 STAR Auto Convertible* INVERTER

AMAZE SERIES

SPECIFICATIONS

Model		[50Hz]	CS/CU-WU18CKY4XFM-P
Type			Cooling Only
Tonnage Class		TR	1.5
Cooling Capacity Standard [Min. - Max.]		Btu/h	17402 [7831 - 19142]
		W	5100 [2295 - 5610]
Heating Capacity Standard [Min. - Max.]		Btu/h	-
		W	-
ISEER		-	5.20
Annual Power Consumption		kWh	759.55
Star Rating			4★
Electrical Data	Voltage	V-AC	230
	Phase	Φ	Single Phase
	Running Current	A	5.8
	Power Input, Standard Cooling [Min. - Max.]	W	1270 [403 - 1715]
	Power Input, Standard Heating [Min. - Max.]	W	-
Moisture Removal Rate		l/h	1.2
		Pt/h	2.5
Air Circulation (Indoor)		m³/min	19.9
		ft³/min	703
		m/s	11.94
Net Dimensions of the Indoor Unit	Length (L)	cm	104.0
	Breadth (B)	cm	24.4
	Height (H)	cm	29.6
Gross Dimensions of the Indoor Unit	Length (L)	cm	114.8
	Breadth (B)	cm	31.4
	Height (H)	cm	38.3
Net Dimensions of the Outdoor Unit	Length (L)	cm	78.0
	Breadth (B)	cm	28.8
	Height (H)	cm	54.2
Gross Dimensions of the Outdoor Unit	Length (L)	cm	90.0
	Breadth (B)	cm	40.5
	Height (H)	cm	60.7
Noise Level	Indoor (H/Q)	[dB-A]	49.76
	Outdoor	[dB-A]	54
Net Weight	IDU [ODU]	kg	12 (24)
Gross Weight	IDU [ODU]	kg	14 (28)
Refrigerant		-	R-32
Operating Temperature Range		°C	16 - 55
Operating Voltage Range		V	100-290
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635
	Gas Side	cm	Ø1.270
Pipe Extension	Chargeless Pipe Length *	m	7.5
	Maximum Pipe Length *	m	15
	Maximum Elevation Length *	m	10
	Additional Refrigerant Gas *	g/m	15
Power Supply Source		-	Indoor

WARRANTY 10 YEARS COMPRESSOR, 5 YEARS PCB, 5 YEARS PANEL

*T&C Apply

OUTDOOR

AMAZE SERIES



SPECIFICATIONS

Model		[50Hz]	CS/CU-EU12CKY4FM	CS/CU-EU18CKY4XFM	CS/CU-EU24CKY4FM
Type			Cooling Only	Cooling Only	Cooling Only
Tonnage Class		TR	1.0	1.5	2.0
Cooling Capacity Standard [Min. - Max.]		Btu/h	9772 [5297 - 12949]	17402 [7831 - 19142]	21884 [9366 - 22895]
		W	3450 [1553 - 3795]	5100 [2295 - 5610]	6100 [2745 - 6710]
Heating Capacity Standard [Min. - Max.]		Btu/h	-	-	-
		W	-	-	-
ISEER		-	5.20	5.20	5.20
Annual Power Consumption		kWh	845.00	759.55	908.90
Star Rating			4★	4★	4★
Electrical Data	Voltage	V-AC	230	230	230
	Phase	Φ	Single Phase	Single Phase	Single Phase
	Running Current	A	4.0	5.8	7.0
	Power Input, Standard Cooling [Min. - Max.]	W	870 [270 - 1175]	1270 [403 - 1715]	1530 [480 - 2066]
	Power Input, Standard Heating [Min. - Max.]	W	-	-	-
Moisture Removal Rate		l/h	1.0	1.2	2.3
		Pt/h	2.1	2.5	4.8
Air Circulation (Indoor)		m³/min	14.0	19.9	20.4
		ft³/min	494	703	720
		m/s	8.60	11.94	12.24
Net Dimensions of the Indoor Unit	Length (L)	cm	87.0	104.0	104.0
	Breadth (B)	cm	22.9	24.4	24.4
	Height (H)	cm	29.5	29.6	29.6
Gross Dimensions of the Indoor Unit	Length (L)	cm	95.2	114.8	114.8
	Breadth (B)	cm	28.3	31.4	31.4
	Height (H)	cm	37.4	38.3	38.3
Net Dimensions of the Outdoor Unit	Length (L)	cm	78.0	78.0	78.0
	Breadth (B)	cm	28.8	28.8	29.9
	Height (H)	cm	54.2	54.2	61.9
Gross Dimensions of the Outdoor Unit	Length (L)	cm	90.0	90.0	97.0
	Breadth (B)	cm	40.5	40.5	46.6
	Height (H)	cm	60.7	60.7	70.0
Noise Level	Indoor (H/Q)	[dB-A]	47.75	49.76	49.76
	Outdoor	[dB-A]	53	56	56
Net Weight	IDU [ODU]	kg	12 (25.5)	12 (30.5)	12 (30.5)
Gross Weight	IDU [ODU]	kg	14 (29.5)	14 (35)	14 (35)
Refrigerant		-	R-32	R-32	R-32
Operating Temperature Range		°C	10 - 55	16 - 55	16 - 55
Operating Voltage Range		V	100-290	100-290	100-290
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635	Ø0.635	Ø0.635
	Gas Side	cm	Ø1.270	Ø1.270	Ø1.270
Pipe Extension	Chargeless Pipe Length *	m	7.5	7.5	7.5
	Maximum Pipe Length *	m	15	15	15
	Maximum Elevation Length *	m	10	10	10
	Additional Refrigerant Gas *	g/m	15	15	15
Power Supply Source		-	Indoor	Indoor	Indoor

WARRANTY 10 YEARS COMPRESSOR, 5 YEARS PCB, 5 YEARS PANEL

*T&C Apply

OUTDOOR

3 STAR Auto Convertible* INVERTER

ACE+ SERIES

SPECIFICATIONS

Model		[50Hz]	CS/CU-GU30CKY5FM
Type			Cooling Only
Tonnage Class		TR	2.5
Cooling Capacity Standard [Min. - Max.]		Btu/h	30027 [13152 - 33030]
		W	8800 [3960 - 9680]
Heating Capacity Standard [Min. - Max.]		Btu/h	-
		W	-
ISEER		-	4.50
Annual Power Consumption		kWh	1514.70
Star Rating			3★
Electrical Data	Voltage	V-AC	230
	Phase	Φ	Single Phase
	Running Current	A	11.6
	Power Input, Standard Cooling [Min. - Max.]	W	2534 [804 - 3421]
	Power Input, Standard Heating [Min. - Max.]	W	-
Moisture Removal Rate		l/h	3.0
		Pt/h	6.3
Air Circulation (Indoor)		m³/min	24.1
		ft³/min	851
		m/s	14.46
Net Dimensions of the Indoor Unit	Length (L)	cm	110.0
	Breadth (B)	cm	25.0
	Height (H)	cm	33.0
Gross Dimensions of the Indoor Unit	Length (L)	cm	118.4
	Breadth (B)	cm	32.0
	Height (H)	cm	40.0
Net Dimensions of the Outdoor Unit	Length (L)	cm	87.5
	Breadth (B)	cm	32.0
	Height (H)	cm	75.0
Gross Dimensions of the Outdoor Unit	Length (L)	cm	104.9
	Breadth (B)	cm	48.5
	Height (H)	cm	83.3
Noise Level	Indoor (H/Q)	[dB-A]	50.44
	Outdoor	[dB-A]	61
Net Weight	IDU [ODU]	kg	15 (40.5)
Gross Weight	IDU [ODU]	kg	17.5 (49)
Refrigerant		-	R-32
Operating Temperature Range		°C	16 - 55
Operating Voltage Range		V	100-290
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635
	Gas Side	cm	Ø1.588
Pipe Extension	Chargeless Pipe Length *	m	7.5
	Maximum Pipe Length *	m	15
	Maximum Elevation Length *	m	10
	Additional Refrigerant Gas *	g/m	20
Power Supply Source		-	Indoor

WARRANTY 10 YEARS COMPRESSOR, 5 YEARS PCB, 5 YEARS PANEL

*T&C Apply

OUTDOOR

AMAZE SERIES

SPECIFICATIONS

Model		[50Hz]	CS/CU-EZ12CKYF	CS/CU-EZ18CKYF
Type			Heating & Cooling Both	Heating & Cooling Both
Tonnage Class		TR	1.0	1.5
Cooling Capacity Standard [Min. - Max.]		Btu/h	11260 [5067 - 12386]	16267 [7677 - 18767]
		W	3300 [1485 - 3630]	5000 [2250 - 5500]
Heating Capacity Standard [Min. - Max.]		Btu/h	12454 [9604 - 13700]	18084 [8188 - 19893]
		W	3650 [1445 - 4015]	5300 [2385 - 5830]
ISEER		-	4.50	4.50
Annual Power Consumption		kWh	567.60	859.27
Star Rating			3★	3★
Electrical Data	Voltage	V-AC	230	230
	Phase	Φ	Single Phase	Single Phase
	Running Current	A	4.4	6.5
	Power Input, Standard Cooling [Min. - Max.]	W	965 [297 - 1303]	1410 [464 - 1904]
	Power Input, Standard Heating [Min. - Max.]	W	915 [290 - 1235]	1350 [432 - 1823]
Moisture Removal Rate		l/h	1.0	1.2
		Pt/h	2.1	2.5
Air Circulation (Indoor)		m³/min	14.0	19.9
		ft³/min	494	576
		m/s	8.60	9.76
Net Dimensions of the Indoor Unit	Length (L)	cm	87.0	87.0
	Breadth (B)	cm	22.9	22.9
	Height (H)	cm	29.5	29.5
Gross Dimensions of the Indoor Unit	Length (L)	cm	95.2	95.2
	Breadth (B)	cm	28.3	28.3
	Height (H)	cm	37.4	37.4
Net Dimensions of the Outdoor Unit	Length (L)	cm	78.0	78.0
	Breadth (B)	cm	28.8	28.8
	Height (H)	cm	54.2	54.2
Gross Dimensions of the Outdoor Unit	Length (L)	cm	90.0	90.0
	Breadth (B)	cm	40.5	40.5
	Height (H)	cm	60.7	60.7
Noise Level	Indoor (H/Q)	[dB-A]	44.72	47.54
	Outdoor	[dB-A]	53	54
Net Weight	IDU [ODU]	kg	11 (24)	11 (32.5)
Gross Weight	IDU [ODU]	kg	13 (26)	13 (35)
Refrigerant		-	R-32	R-32
Operating Temperature Range		°C	16 - 55	16 - 55
Operating Voltage Range		V	100-290	100-290
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635	Ø0.635
	Gas Side	cm	Ø1.270	Ø1.270
Pipe Extension	Chargeless Pipe Length *	m	7.5	7.5
	Maximum Pipe Length *	m	15	15
	Maximum Elevation Length *	m	10	10
	Additional Refrigerant Gas *	g/m	15	20
Power Supply Source		-	Indoor	Indoor

WARRANTY 10 YEARS COMPRESSOR, 5 YEARS PCB, 5 YEARS PANEL

*T&C Apply

OUTDOOR

3 STAR Auto Convertible* INVERTER

AMAZE SERIES



SPECIFICATIONS

Model		[50Hz]	CS/CU-EZ18CKYFM	CS/CU-EZ24CKYFM
Type			Heating & Cooling Both	Heating & Cooling Both
Tonnage Class		TR	1.5	2.0
Cooling Capacity Standard [Min. - Max.]		Btu/h	17402 [9520 - 21270]	21884 [10288 - 23547]
		W	5100 [2295 - 5610]	6200 [2790 - 6820]
Heating Capacity Standard [Min. - Max.]		Btu/h	19426 [8392 - 20968]	22520 [10154 - 24772]
		W	5400 [2430 - 5940]	6600 [2970 - 7260]
ISEER		-	4.50	4.50
Annual Power Consumption		kWh	877.71	1067.19
Star Rating			3★	3★
Electrical Data	Voltage	V-AC	230	230
	Phase	Φ	Single Phase	Single Phase
	Running Current	A	6.7	8.5
	Power Input, Standard Cooling [Min. - Max.]	W	1460 [469-1971]	1845 [549 - 2498]
	Power Input, Standard Heating [Min. - Max.]	W	1350 [432 - 1823]	1700 [544 - 2295]
Moisture Removal Rate		l/h	1.2	2.3
		Pt/h	2.5	4.8
Air Circulation (Indoor)		m³/min	19.9	20.4
		ft³/min	703	720
		m/s	11.94	12.24
Net Dimensions of the Indoor Unit	Length (L)	cm	104.0	104.0
	Breadth (B)	cm	24.4	24.4
	Height (H)	cm	29.6	29.6
Gross Dimensions of the Indoor Unit	Length (L)	cm	114.8	114.8
	Breadth (B)	cm	31.4	31.4
	Height (H)	cm	38.3	38.3
Net Dimensions of the Outdoor Unit	Length (L)	cm	78.0	82.4
	Breadth (B)	cm	28.8	29.9
	Height (H)	cm	54.2	61.9
Gross Dimensions of the Outdoor Unit	Length (L)	cm	90.0	97.0
	Breadth (B)	cm	40.5	46.6
	Height (H)	cm	60.7	70.0
Noise Level	Indoor (H/Q)	[dB-A]	47.75	49.76
	Outdoor	[dB-A]	53	56
Net Weight	IDU [ODU]	kg	12 (25.5)	12 (30.5)
Gross Weight	IDU [ODU]	kg	14 (29.5)	14 (35)
Refrigerant		-	R-32	R-32
Operating Temperature Range		°C	10 - 55	16 - 55
Operating Voltage Range		V	100-290	100-290
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635	Ø0.635
	Gas Side	cm	Ø1.270	Ø1.270
Pipe Extension	Chargeless Pipe Length *	m	7.5	7.5
	Maximum Pipe Length *	m	15	15
	Maximum Elevation Length *	m	10	10
	Additional Refrigerant Gas *	g/m	15	20
Power Supply Source		-	Indoor	Indoor

WARRANTY 10 YEARS COMPRESSOR, 5 YEARS PCB, 5 YEARS PANEL

*T&C Apply

OUTDOOR

AMAZE SERIES



SPECIFICATIONS

Model		[50Hz]	CS/CU-EU12CKY3FM	CS/CU-EU18CKY3XFMH	CS/CU-EU24CKY3FM
Type			Cooling Only	Cooling Only	Cooling Only
Tonnage Class		TR	1.0	1.5	2.0
Cooling Capacity Standard [Min. - Max.]		Btu/h	9772 [5297 - 12949]	17402 [7831 - 19142]	21884 [9366 - 22895]
		W	3450 [1553 - 3795]	5280 [2376 - 5808]	6700 [3015 - 7370]
Heating Capacity Standard [Min. - Max.]		Btu/h	-	-	-
		W	-	-	-
ISEER		-	4.50	4.50	4.50
Annual Power Consumption		kWh	591.89	908.48	1153.74
Star Rating			3★	3★	3★
Electrical Data	Voltage	V-AC	230	230	230
	Phase	Φ	Single Phase	Single Phase	Single Phase
	Running Current	A	4.8	7.3	8.7
	Power Input, Standard Cooling [Min. - Max.]	W	1045 [302 - 1411]	1600 [461 - 2160]	1898 [621 - 2562]
	Power Input, Standard Heating [Min. - Max.]	W	-	-	-
Moisture Removal Rate		l/h	1.0	1.2	2.3
		Pt/h	2.1	2.5	4.8
Air Circulation (Indoor)		m³/min	14.0	19.9	20.4
		ft³/min	494	703	720
		m/s	8.60	11.94	12.24
Net Dimensions of the Indoor Unit	Length (L)	cm	87.0	104.0	104.0
	Breadth (B)	cm	22.9	24.4	24.4
	Height (H)	cm	29.5	29.6	29.6
Gross Dimensions of the Indoor Unit	Length (L)	cm	95.2	114.8	114.8
	Breadth (B)	cm	28.3	31.4	31.4
	Height (H)	cm	37.4	38.3	38.3
Net Dimensions of the Outdoor Unit	Length (L)	cm	67.2	78.0	82.4
	Breadth (B)	cm	24.0	28.8	29.9
	Height (H)	cm	52.0	54.2	61.9
Gross Dimensions of the Outdoor Unit	Length (L)	cm	79.5	90.0	97.0
	Breadth (B)	cm	37.0	40.5	46.6
	Height (H)	cm	57.5	60.7	70.0
Noise Level	Indoor (H/Q)	[dB-A]	44.72	47.54	49.76
	Outdoor	[dB-A]	53	53	54
Net Weight	IDU [ODU]	kg	9 (20)	11 (22)	11 (28)
Gross Weight	IDU [ODU]	kg	11 (24)	13 (26)	13 (32.5)
Refrigerant		-	R-32	R-32	R-32
Operating Temperature Range		°C	16 - 55	16 - 55	16 - 55
Operating Voltage Range		V	100-290	100-290	100-290
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635	Ø0.635	Ø0.635
	Gas Side	cm	Ø0.952	Ø1.270	Ø1.270
Pipe Extension	Chargeless Pipe Length *	m	7.5	7.5	7.5
	Maximum Pipe Length *	m	10	15	15
	Maximum Elevation Length *	m	5	10	10
	Additional Refrigerant Gas *	g/m	10	15	20
Power Supply Source		-	Indoor	Indoor	Indoor

WARRANTY 10 YEARS COMPRESSOR, 5 YEARS PCB, 5 YEARS PANEL

*T&C Apply

OUTDOOR

AMAZE SERIES



SPECIFICATIONS

Model		[50Hz]	CS/CU-EU12CKY3F	CS/CU-EU18CKY3F
Type			Cooling Only	Cooling Only
Tonnage Class		TR	1.0	1.5
Cooling Capacity Standard [Min. - Max.]		Btu/h	9772 [5297 - 12949]	17402 [7831 - 19142]
		W	3450 [1553 - 3795]	5100 [2295 - 5610]
Heating Capacity Standard [Min. - Max.]		Btu/h	-	-
		W	-	-
ISEER		-	4.50	4.50
Annual Power Consumption		kWh	591.89	893.74
Star Rating			3★	3★
Electrical Data	Voltage	V-AC	230	230
	Phase	Φ	Single Phase	Single Phase
	Running Current	A	4.8	6.9
	Power Input, Standard Cooling [Min. - Max.]	W	1045 [302 - 1411]	1595 [454 - 2045]
	Power Input, Standard Heating [Min. - Max.]	W	-	-
Moisture Removal Rate		l/h	1.0	1.2
		Pt/h	2.1	2.5
Air Circulation (Indoor)		m³/min	14.0	19.9
		ft³/min	494	576
		m/s	8.60	9.76
Net Dimensions of the Indoor Unit	Length (L)	cm	87.0	87.0
	Breadth (B)	cm	22.9	22.9
	Height (H)	cm	29.5	29.5
Gross Dimensions of the Indoor Unit	Length (L)	cm	95.2	95.2
	Breadth (B)	cm	28.3	28.3
	Height (H)	cm	37.4	37.4
Net Dimensions of the Outdoor Unit	Length (L)	cm	67.2	78.0
	Breadth (B)	cm	24.0	28.8
	Height (H)	cm	52.0	54.2
Gross Dimensions of the Outdoor Unit	Length (L)	cm	79.5	90.0
	Breadth (B)	cm	37.0	40.5