

National University of Computer and Emerging Sciences



Laboratory Manual

for

Data Structures Lab

Course Instructor	Mr. Saad Farooq
Lab Instructor(s)	Mr. Hasnain Iqbal Mr. Usama Hassan
Section	CS-E
Date	29-Nov-2021
Semester	Fall 2021

Department of Computer Science

FAST-NU, Lahore, Pakistan

Objectives:

In this lab, students will practice:

1. Binary Search Trees
2. Recursive insert operation, recursive inorder traversal, and some other recursive operations on BST
3. Iterative insert and Iterative inorder traversal using stack

Question 1

Implement the following Tree Node:

```
template <typename k, typename v>
struct TNode
{
    k key;
    v value;
    TNode<k, v> *leftChild;
    TNode<k, v> *rightChild;
}
```

Now implement a binary search tree class “BST” which contains root of type TNode as data member. You have to implement the following member functions for your binary search tree:

- a. A default Constructor which sets the root to nullptr.
- b. A recursive “insertRec” function which is passed as parameter a key and a corresponding value. It then uses **recursion** to insert the <key, value> pair while considering the insertion rules. If the key already exists in the BST, it simply replaces the value.
`void insertRec(k const key, v const value)`
- c. A function “search” which is passed as parameter a key. The function then uses **recursion** to return pointer to the corresponding value. If the key does not exist, the function returns null.
`v* search(k key)`
- d. A function “inorderPrintkeys” which prints the keys using **recursive** inorder traversal.
`void inorderPrintKeysRec() const`
- e. A function “preOrderPrintkeys” which prints the keys using **recursive** preOrder traversal.
`void preOrderPrintKeys() const`
- f. A function “postOrderPrintkeys” which prints the keys using **recursive** postOrder traversal.
`void postOrderPrintKeys() const`
- g. A function “length” which uses **recursion** to return the count of total nodes in BST.
`int length() const`
- h. A function “deleteNode” which is passed as parameter a key. The function then delete the node containing that key. If the node isn’t a leaf than replace the value with inorder predecessor.
`void deleteNode(k const key) const`

- i. A function "inorderPredecessor" which is passed as parameter a pointer to node. The function then search the inorderPredecessor and return its value. node containing that key. If the node isn't a leaf than replace the value with inorder predecessor.

v printAllAncestors(TNode *) const

- j. Provide the destructor which delete all the nodes from the tree

- k. bool isPerfect()

Question 2: Now run the following main program.

```
int main()
{
    BST<int, int> tree; //the key and value both are of type int

    tree.insertRec(500, 500);
    tree.insertRec(1000, 1000);
    tree.insertRec(1, 1);
    tree.insertRec(600, 600);
    tree.insertRec(700, 700);
    tree.insertRec(10, 10);
    tree.insertRec(30, 30);
    tree.insertRec(9000, 9000);
    tree.insertRec(50000, 50000);
    tree.insertRec(20, 20);

    cout << "Printing keys using inorder traversal: ";
    tree.inorderPrintKeys();

    cout << endl << endl << "Printing keys using recursive inorder traversal: ";
    tree.inorderPrintKeysRec();

    cout << endl << endl << "Tree Length: " << tree.length() << endl << endl;

    int *val = tree.search(123);
    if (val != nullptr){
        cout << "123 found" << endl;}

    val = tree.search(123);
    if (val == nullptr){
        cout << "123 not found" << endl;}

    cout << endl << "Printing the keys using preOrder traversal: ";
    tree.preOrderPrintKeys();

    cout << endl << "Printing the keys of ancestor nodes of 20";
    tree.printAllAncestors(20);
    tree.delete(1);
    cout << "Post order traversal: "; tree.postOrderPrintKeys();

    cout << tree.isPerfect();
    system("pause");
}
```