

CORE VSI 1300R & 1400R

get more with core ...

Salient features:



Exotic material of construction for rotor wear parts :

Critical rotor wear components are made with high quality steel (high Chromium); rotor tips fabricated with Hi grade Tungsten Carbide – significantly reduces wear costs and suitable for more abrasive stones such as granite, quartz.

By-pass system for greater flexibility:

By-pass system at the top shell. This eliminates need to change the conveyor/plant layout and allows for greater flexibility in the overall plant design.



Well-balanced rotor:

Well-balanced rotor that can operate seamlessly at higher speeds.

Rolled shells with high mechanical strength:

Completely rolled top, middle and bottom shells which yield higher strength compared to conventional fabricated shells with sharp edges.





Oil lubrication panel for bearings:

Unlike conventional VSIs which require repeated manual greasing, we provide an automated oil lubrication panel for the spherical roller bearings. This reduces your maintenance costs - lesser manpower, no grease requirement.

Standard supply includes: Complete VSI with chassis, platform & handrail, oil lubrication panel & other accessories,

pulleys.

Optional extras:

Motor, bare rotor, wear carriers, liners and tip plates, D-cones.

Recommended feed:

0-40 mm.

Technical Specification & Capacity Chart

Model	1300R	1400R
Max. Capacity	90-160 TPH	200-400 TPH
Max. Power	90-160 kW	200-400 kW

For more information, Contact:



Mumba

104, Terminal-9, Near Vile Parle Police Station, Nehru road, Vile Parle (E), Mumbai - 400057, Maharastra, India.

Tel: +91 22 6611 5702 / +91 95949 40004

Email: info@coreengg.co.in

Hyderabad

Plot No.H-10 & H-11, IDA, Uppal, Hyderabad-500039, Telangana, India. Ph: +91 40 2720 5115 / 5119 / 6199 Email: core@corecrushtech.com