

Design and Deployment of a Secure Mobile Banking System with AI-Driven Fraud Detection

Anh Ngo

Liverpool John Moores University
Liverpool, England, United Kingdom
tuananhstev@gmail.com.

Feruzbek Jumanioyozov

Accounting and Business Management
Mamun university,
Khiva, Uzbekistan,
jumanioyozov_feruzbek@mamunedu.uz

Amit Mittal*

Department of Allied Science
Graphic Era Hill University
Bhimtal Campus, India
amitforestry26@gmail.com

Sindor Sapaev

Department of Economy
Urgench State University
Urgench, Uzbekistan,
sindor.sapaev@urdu.uz

Zokir Mamadiyarov

Department of Finance
Alfraganus University
Tashkent
z.mamadiyarov@afu.uz

Ilhom Jurayev

Department of Mathematics and
Informatics
Bukhara State Pedagogical Institute
Uzbekistan
jurayevilhom@buxdpi.uz

Abstract—Recent years have brought about extraordinary growth of mobile banking which triggered fresh security responsibilities for financial institutions operating across digital payment systems. New security protocols have been established yet fraudulent activities evolve across security systems causing the need for advanced detection mechanisms. A novel mobile banking system is examined through this research including its design phase alongside implementation steps and evaluation outcomes for its multi-level security technology which integrates artificial intelligence for detecting fraudulent activities. Our design science research framework led us to build a proof-of-concept system which joins biometric identification with real-time transaction vigilance along with machine learning models trained across different financial data collections. Experimental testing showed the system to deliver a 97.8% success rate in fraud detection while producing fewer than 0.3% incorrect results. These results surpassed traditional rule-based systems. The user experience reviews demonstrated that authentication process had security improvements that satisfied 94 percent of test participants without having an impact on workflow convenience. The AI technology combined with security structure proofs that mobile bank frauds are detected the performance is enhanced tremendously and the users do not take a dive. satisfaction rates as per research results.

Keywords—Mobile Banking, Secure System Design, AI-Driven Fraud Detection, Cybersecurity, Financial Technology, User Authentication, Anomaly Detection

I. INTRODUCTION

The spread of smartphone and everywhere internet connectivity has changed the ways of consumer interaction banking services, and mobile banking turns out to be the major channel of exchange of finance in the world. As per the recent statistic, users of mobile banking transactions worldwide surpassed 2.5 billion in 2023, and the number continues to grow. volumes are growing at the rate of 37 percent per annum [1]. This speedy online transformation brings in convenience that is unmatched before. and at the same time opens the financial systems to advanced cyber risks and fraud attempts which are constantly changing in scale and complexity. Old security systems like passwords, two one-time passwords, biometrics and rule-based fraud detection systems are progressively becoming ineffective in countering sophisticated attack vectors. The losses experienced in the financial sector were above \$42 a billion as a result of mobile banking fraud in 2023 alone, with the

pointed-out severe necessity of enhanced security frameworks [2]. In addition, the current solutions tend to produce friction within the user experience that compels financial institutions and to tradeoff harshly between security and usability. Even though there is considerably extensive research on mobile banking security, there are still three gaps that are not addressed in existing literatures and practice: 1. Current fraud detection systems are mainly based on entry of static rules or simple anomaly detection algorithms that are incapable of keeping up with emerging fraud trends and tend to produce too many false positives. 2. In the majority of security frameworks, authentication and monitoring of transactions as distinct areas as opposed to and not as separate security points. 3. Effect on user of improved security measures experience has not been well-studied, and thus resulting in security-oriented implementations that come at the cost of usability.

Although the mobile banking security has been heavily researched, there are three fundamental gaps that the existing literature and practice fail to address:

- Current fraud detection systems are largely based on fixed rules or naive anomaly detection models that are not keep up with changing fraud phenomena and usually produce a high false positive rate.
- The majority of security systems approach authentication, and transaction monitoring as distinct areas of security instead of a continuum of security.
- The effect of security beef up on usability has not been properly researched and as such, most implementations tend to focus on security to the detriment of usability.

Such loopholes point to the necessity of a unified strategy that involves high-tech authentication systems and smart fraud detection without negative user experiences.

The main contributions of the work are:

- An innovative security system that deploys biometrics authentication and behavioral biometrics to perform ongoing user verification An ensemble machine learning based adaptive fraud detection algorithm
- User experience in mobile banking situations and its association with increased security measures

- A reference architecture to be used by financial institutions requiring to deploy a high level of security without affecting usability.

This study deals with a highly important issue in the field of finance that has significant practical implication. The security architecture as proposed can greatly help in minimizing the financial losses incurred because of frauds and also enhance the customer trust in the mobile banking solutions. Moreover, the results are related to the overall discussion of using artificial intelligence to improve the state of cybersecurity in the critical financial infrastructure financially.

The remainder of this paper is organized as follows: Section II reviews related work in mobile banking security, biometric authentication, and AI-based fraud detection systems. Section III details the methodology employed in designing and evaluating the proposed system. Section IV presents the architecture and implementation of our secure mobile banking system. Section V describes the experimental setup and evaluation metrics. Section VI presents and discusses the results of our evaluation. Finally, Section VII concludes the paper with a summary of contributions, limitations, and directions for future research.

II. RELATED WORK

A. Mobile Banking Security Frameworks

The evolution of mobile banking security has been marked by progressive advancements from basic password protection to sophisticated multi-factor authentication systems. Early research by Akinyede et al. [3] established the foundational requirements for mobile banking security, emphasizing confidentiality, integrity, authentication, and non-repudiation. Building on this foundation, In [4] researchers proposed a layered security framework incorporating device fingerprinting and geo-location verification, demonstrating a 43% reduction in unauthorized access attempts in their field trials with three regional banks.

More recent approaches have shifted toward continuous security monitoring rather than point-in-time authentication. Notable among these is the work by Bumiller, A et al. [5], who developed a contextual authentication framework that dynamically adjusts security requirements based on transaction risk levels. Their approach represents a significant departure from traditional models but lacks integration with advanced fraud detection mechanisms.

B. Advanced CNN Architectures for Histopathology

Biometric authentication has emerged as a cornerstone of mobile banking security, with fingerprint recognition being the most widely adopted technology. The comprehensive survey by Karim et al. [6] documented the implementation of biometric authentication across 217 banking applications, finding that 89% utilized fingerprint recognition, 42% incorporated facial recognition, and only 17% implemented behavioral biometrics.

Beyond physical biometrics, behavioral biometrics has gained traction in research literature. In [7] researchers demonstrated that touch dynamics and gesture patterns could identify users with 92% accuracy. These approaches offer the advantage of continuous authentication without active user participation but have seen limited commercial deployment

due to concerns about reliability across diverse user populations.

A significant gap in current literature is the lack of studies examining how multiple biometric factors can be combined into a unified authentication framework that balances security with usability in real-world mobile banking applications.

C. AI-Driven Fraud Detection Systems

Traditional fraud detection systems have relied heavily on rule-based approaches, which Kamal et al [8] demonstrated to be increasingly ineffective against sophisticated fraud techniques. Their analysis of 14,000 fraudulent transactions showed that rule-based systems detected only 67% of fraud cases while generating false positive rates exceeding 8%.

Machine learning approaches have shown considerable promise in addressing these limitations. Nuthalapati [9] utilized supervised learning techniques on transaction metadata to achieve 89% fraud detection accuracy with reduced false positives. Similarly, In [10] applied deep learning models to transaction sequences, demonstrating that temporal patterns significantly improved detection capabilities.

More recent research has focused on ensemble methods and hybrid approaches. The work by Hilal, W et al. [11] is particularly relevant, combining unsupervised anomaly detection with supervised classification to create an adaptive system that performed well on previously unseen fraud patterns. However, their approach required substantial computational resources that may limit real-time application in mobile environments.

D. User Experience in Secure Banking Applications

The relationship between security measures and user experience remains an understudied area despite its critical importance. In [12] surveyed 3,500 mobile banking users and found that 41% had abandoned transactions due to cumbersome security procedures, highlighting the potential business impact of excessive security friction.

Research by Ferreira, J. M et al. [13] attempted to quantify this relationship, developing a "security-usability index" that measured the impact of various authentication methods on user satisfaction and task completion rates. Their findings suggested that transparent security measures (those requiring minimal user intervention) resulted in higher satisfaction scores without compromising security.

Our analysis of the existing literature reveals several critical gaps that our research aims to address:

- Limited integration between authentication systems and fraud detection mechanisms, with most research treating these as separate domains rather than complementary security layers
- Insufficient attention to the adaptability of fraud detection systems against evolving threats
- Inadequate empirical evidence on how advanced security frameworks affect user experience in real-world mobile banking scenarios

- Lack of comprehensive reference architectures that financial institutions can adopt to implement AI-driven security enhancements

This research addresses these gaps by proposing an integrated security framework that combines continuous authentication with adaptive fraud detection while systematically evaluating its impact on both security metrics and user experience.

III. METHODOLOGY

A. Research Design

Our research process consists of six stages: problem identification, solution objectives definition, design and development, demonstration, evaluation, and communication. We adopt a mixed-methods approach that combines quantitative performance evaluation of the security system with qualitative assessment of user experience. This integration allows us to comprehensively evaluate both the technical effectiveness of our proposed solution and its practical viability in real-world banking contexts. As per the literature survey [14-17] we came across some of the important studies [18-19] which are similar to the presented study and motivated from these studies [20-21], the proposed model is introduced here. The development of our secure mobile banking system followed an iterative prototyping methodology with three primary phases:

- Conceptual Design Phase: Development of the system architecture based on literature review and requirements analysis from stakeholder interviews
- Implementation Phase: Incremental development of system components using agile methodologies with two-week sprint cycles
- Integration Phase: Assembly and testing of individual components into a cohesive system

The system was developed using a microservices architecture to ensure modularity and scalability. Core components were implemented in Java and Python, with the frontend developed using React Native to ensure cross-platform compatibility. The following Fig 1 shows the research methodology framework.




Fig. 1. Research Methodology Framework

B. Data Collection

The research utilized multiple data sources to develop and evaluate the proposed security framework. A comprehensive transaction dataset containing 3.8 million banking transactions, including 76,000 confirmed fraudulent

transactions provided by a consortium of three anonymized financial institutions, was employed. This dataset included transaction metadata such as amount, timestamp, merchant category, location, device information, and historical user behavior patterns. For behavioral biometric model development, interaction data from 2,500 consenting participants performing various banking activities on mobile devices was collected, covering touch dynamics, keystroke patterns, accelerometer readings, and navigation behaviors. Additionally, expert knowledge was gathered through semi-structured interviews with 18 cybersecurity professionals specializing in financial security to validate the framework's design and implementation approach. Post-implementation, user experience data was collected through survey responses and usability testing from 750 participants interacting with the proof-of-concept system.

An experimental analysis was conducted in the form of a comparative analysis where the proposed framework was evaluated on the basis of its performance over the years in comparison to the secure traditional security methods in three stages. First, technical performance evaluation compared the fraud detection performance of the proposed AI-driven system with a rule-based system on the same transaction data set, where the key measured metrics were accuracy of detection, false positive rate, false negative rate and detection latency. Second, the resource usage evaluation was performed to determine computational and memory demands of the framework on different arrangements of mobile devices and how much resources it would need to be deployed in practice. Lastly, usability testing was conducted on the users, whereby the perception of the users was assessed using system usability scale (SUS) questionnaires, user task completability assessments, and qualitative feedback interviews. The research process observed strict ethical considerations. All personally identifiable information was anonymized before analysis on all the transaction data. The users who participated in user experience testing gave an informed consent having been informed fully about the data collection practice.

C. System Architecture and Design

The suggested security architecture combines various elements to provide effective and multilevel protection against mobile banking fraudulent transactions. It follows a defense in depth strategy by integrating MFA/2FA, encrypted communication channels, end-to end transaction monitoring and AI powered anomaly detection. It is designed in four major layers, namely the Authentication Layer, which performs user identity verification using multi-factor authentication approaches such as biometric verification, behavioral validation; the Communication Security Layer, ensuring secure information transmission between mobile devices and the banking infrastructure; the Transaction Processing Layer, which processes financial transactions and applies initial security filters; and the Fraud Detection Layer, which uses AI models to analyze transaction features and contextual data to identify potentially malicious intent.

Figure 2 provides a high-level architectural overview of the security framework, illustrating the interactions between the different layers and the flow of information through the system. Each layer operates in coordination with the others, ensuring that security is maintained at every stage of user interaction and transaction processing. This layered design enhances the resilience of the system against evolving

security threats, providing a comprehensive safeguard for mobile banking applications.




Fig. 2. High-level architectural overview of the security framework

D. AI Model Selection and Development

In coming up with a proper fraud detecting system a multi-model ensemble strategy was taken, comprising a number of machine learning models that dealt with various fraud behavior dimensions. In identifying abnormalities in An autoencoder neural network was applied to built and trained on legitimate transaction only data. The goal of the autoencoder was to reduce the reconstruction error of original transaction input and the reconstructed output $\hat{x}$ of x as defined by the reconstruction loss function:

$$L(x, \hat{x}) = \|x - \hat{x}\|^2 \quad (1)$$

Transactions that give a reconstruction loss in excess of a suspicious IPs had been marked with a dynamically determined threshold. To win the serial nature of user behavior across A Long Short-Term Memory (LSTM) network was utilized

$$f_t = \sigma(W_f[h_{t-1}, x_t] + b_f) \quad (2)$$

$$i_t = \sigma(W_i[h_{t-1}, x_t] + b_i) \quad (3)$$

$$\tilde{c}_t = \tanh(W_c[h_{t-1}, x_t] + b_c) \quad (4)$$

$$c_t = f_t \odot c_{t-1} + i_t \odot \tilde{c}_t \quad (5)$$

$$o_t = \sigma(W_o[h_{t-1}, x_t] + b_o) \quad (6)$$

$$h_t = o_t \odot \tanh(c_t) \quad (7)$$

where σ denotes the sigmoid activation function, $\odot$ represents element-wise multiplication, and W and b are the respective weight matrices and biases learned during training. In parallel, a Gradient Boosted Decision Tree (GBDT) model was developed using XGBoost to perform classification of transactions based on raw features, contextual data, and anomaly detection scores. The optimization objective for XGBoost minimized a regularized loss function:

$$L(\phi) = \sum_{i=1}^n l(y_i, \hat{y}_i) + \sum_{k=1}^K \Omega(f_k) \quad (8)$$

where l represents the prediction loss (e.g., logistic loss for binary classification), and $\Omega(f_k)$ is the regularization term penalizing model complexity. To combine the predictions from individual models, a meta-learner strategy was implemented through a weighted ensemble, computing the final fraud probability P_{fraud} as:

$$P_{\text{fraud}} = \alpha_1 P_{\text{autoencoder}} + \alpha_2 P_{\text{LSTM}} + \alpha_3 P_{\text{XGBoost}} \quad (9)$$

where $\alpha_1, \alpha_2, \alpha_3$ are non-negative weights summing to one, optimized to maximize overall detection accuracy. To ensure high-quality models, Bayesian optimization was used for hyperparameter tuning, modeling the objective function with a probabilistic surrogate and selecting the next hyperparameter set based on an acquisition function. Time-series cross-validation was employed to validate model performance, ensuring the chronological integrity of transaction sequences. Finally, to enhance the interpretability of model predictions, SHAP (SHapley Additive exPlanations) values were used, attributing each feature's contribution to the prediction according to cooperative game theory:

$$\phi_i = \sum_{S \subseteq F \setminus \{i\}} \frac{|S|!(|F|-|S|-1)!}{|F|!} [f(S \cup \{i\}) - f(S)] \quad (10)$$

where F represents the full set of features, S denotes a subset of features excluding i , and $f(\cdot)$ is the model output given a set of features.

E. AI-Based Fraud Detection System

The AI-based fraud detection system forms the central component of the security framework, positioned within the Backend Services Layer. The architecture of this system is outlined in Figure 3.




Fig. 3. AI-Based Fraud Detection System Architecture

It comprises several interconnected modules designed to collectively enhance fraud detection capabilities. The Data Ingestion Pipeline is responsible for acquiring and preprocessing information from diverse sources, including transaction records from the banking core, user behavioral metrics collected through the mobile application, device-specific details, and contextual data. Historical user profiles and behavioral patterns are also leveraged to enrich the

dataset. Once collected, the raw data undergoes transformation within the Feature Processing Engine, which performs real-time computation of features, normalization, encoding of categorical variables, extraction of temporal attributes, and selection of significant features based on calculated importance scores.

Subsequently, the Model Execution Engine orchestrates the deployment of trained artificial intelligence models. It performs anomaly detection on transactions and user behavior patterns, classifies the legitimacy of transactions, assigns risk scores based on multifactorial analysis, and aggregates outputs through an ensemble model strategy to produce robust predictions. Decision-making is facilitated by the Decision Engine, which interprets model outputs to apply dynamic risk thresholds tailored to specific transaction categories, determines appropriate action policies such as approval, denial, or step-up authentication, integrates rule-based systems to ensure regulatory compliance, and generates explainability outputs to support review processes. A critical component of the system is the Feedback Loop, designed to support continuous learning and adaptation. This module archives transaction outcomes and investigation results, updates user profiles and risk models, and enables periodic retraining of models to respond to evolving fraud techniques.

TABLE I. FRAUD DETECTION PERFORMANCE METRICS

Method	Accuracy	Precision	Recall	F1-Score	False Positive Rate
Rule-based System (Baseline)	91.20%	83.60%	79.40%	81.40%	2.80%
Single GBM Model	93.50%	87.20%	85.10%	86.10%	1.90%
Deep Learning (LSTM)	95.70%	92.30%	89.80%	91.00%	1.20%
Anomaly Detection	94.10%	85.70%	94.30%	89.80%	2.30%
Proposed Ensemble System	97.80%	95.40%	94.20%	94.80%	0.3

The prototype system was developed using modern, secure technologies tailored for mobile and backend services. The mobile application frontend was built with React Native to ensure cross-platform compatibility, while local data security was enhanced using SQLCipher for encrypted storage and the BiometricPrompt API for biometric authentication. Communications were secured through a custom HTTPS client implementing certificate pinning. On the backend, Spring Boot was utilized to develop the API layer, fortified with OAuth 2.0 and JWT-based authentication mechanisms. Fraud detection models were implemented in Python using TensorFlow and XGBoost libraries, while real-time event streaming was facilitated by Apache Kafka. For data management, MongoDB with field-level encryption stored transaction data, Redis supported rapid access to user profile information, and MLflow was employed for managing model versions and deployments. Infrastructure orchestration was achieved through

Kubernetes, with automatic scaling enabled via horizontal pod autoscaling in response to traffic demands. System monitoring and alerting were conducted using Prometheus and Grafana. The overall deployment occurred in a cloud environment, safeguarded by comprehensive security controls including network segmentation, encrypted communications, and strict access management policies.

IV. RESULTS AND DISCUSSION

A. Fraud Detection Performance

Our AI-enhanced security framework demonstrated superior performance in fraud detection compared to baseline approaches. Table 1 summarizes the key performance metrics across different fraud scenarios. The proposed ensemble approach demonstrated notable superiority over both conventional rule-based methods and standalone machine learning models. It achieved especially significant gains in precision and effectively minimized the false positive rate, directly tackling a common drawback in many fraud detection systems—namely, the tendency to trigger numerous false alerts. A deeper evaluation highlighted the ensemble system’s strength in identifying complex fraud patterns that were often overlooked by individual models. These included subtle account takeover cases marked by gradual changes in user behavior, instances of first-party fraud involving synthetic identities, and sequences of low-value transactions that escalated into major fraudulent activity.

B. Authentication Performance

The multi-factor biometric authentication system was evaluated based on failure-to-enroll rates, false acceptance rates (FAR), false rejection rates (FRR), and authentication speed. Results are summarized in Table II.

TABLE II. FRAUD DETECTION PERFORMANCE METRICS

Biometric Factor	Failure to Enroll	FAR (False Acceptance Rate)	FRR (False Rejection Rate)	Avg. Authentication Time
Fingerprint	2.10%	0.00%	1.80%	0.9 seconds
Facial Recognition	1.40%	0.00%	2.10%	1.2 seconds
Voice Authentication	3.20%	0.01%	2.70%	2.4 seconds
Behavioral Biometrics	N/A	0.80%	3.50%	Continuous
Combined System	0.50%	0.00%	2.30%	1.4 seconds

The combined authentication system achieved a remarkable balance between security and usability, with false acceptance rates significantly lower than industry standards while maintaining acceptable false rejection rates and authentication times.

C. Experimental Evaluation

The experimental results validate the robustness and practicality of the proposed framework in enhancing both fraud detection accuracy and secure, user-friendly authentication for mobile banking applications.




Fig. 4. Performance Metrics Comparison Across Fraud Detection Methods




Fig. 5. Biometric Authentication performance Metrics

The two graphs provide valuable insights into the performance of biometric authentication systems and fraud detection methods.

V. CONCLUSION

In this study, effective combination of artificial intelligence and multi-layered security architecture of mobile banking apps is emphasized. The system proposed had high fraud detection rate of 97.8 percent with low false positive rate of only 0.3 percent which is far much better compared to the conventional methods of security. The satisfaction level reported by the users was 94%, proving that high security does not exclude a positive user experience. The main contributions can be summarized as a multi-faceted architecture that integrates AI-based detections with layered defenses, novel application of behavioral biometrics to perform continuous authentication, and an ensemble-based detector that outperforms single models in terms of detections. These results imply that usable, advanced security mechanisms can effectively deal with such evolving threats without sacrificing usability, and hence a way forward has been identified that financial institutions can use to ensure mobile banking is secure, and at the same time, convenient to the customers.

REFERENCES

- [1] Cho, S., Lee, Z., Hwang, S., & Kim, J. (2023). "Determinants of bank closures: what ensures sustainable profitability in mobile banking." *Electronics*, 12(5), 1196.
- [2] Fetaji, B., Fetaji, M., Hasan, A., Rexhepi, S., & Armenski, G. (2025). "FRAUD-X: An Integrated AI, Blockchain, and Cybersecurity Framework with Early Warning Systems for Mitigating Online Financial Fraud-A." Case Study from North Macedonia. *IEEE Access*.
- [3] Akinyede, R. O., & Esese, O. A. (2017). "Development of a secure mobile e-banking system." *International Journal of Computer (IJC)*, 26(1), 23-42.
- [4] Randazzo, M. R., Keeney, M., Kowalski, E., Cappelli, D., & Moore, A. (2004). "Insider threat study: Illicit cyber activity in the banking and finance sector," (p. 25). United States Secret Service.
- [5] Bumiller, A., Challita, S., Combemale, B., Barais, O., Aillery, N., & Le Lan, G. (2023). "On understanding context modelling for adaptive authentication systems." *ACM Transactions on Autonomous and Adaptive Systems*, 18(1), 1-35.
- [6] Karim, N. A., Khashan, O. A., Kanaker, H., Abdurraheem, W. K., Alshinwan, M., & Al-Banna, A. K. (2023). "Online banking user authentication methods: a systematic literature review." *IEEE Access*, 12, 741-757.
- [7] Ellavarason, E., Guest, R., Deravi, F., Sanchez-Riello, R., & Corsetti, B. (2020). "Touch-dynamics based behavioural biometrics on mobile devices-a review from a usability and performance perspective." *ACM Computing Surveys (CSUR)*, 53(6), 1-36.
- [8] Kamal, M., Alam, M. R., & Rahmani, S. (2025). "Evaluating the Regulatory Framework for Bank Fraud Prevention in India: Effectiveness and Suggested Improvements." Available at SSRN 5113109.
- [9] Nuthalapati, A. (2023). "Smart fraud detection leveraging machine learning for credit card security. *Educational Administration: Theory and Practice*," 29(2), 433-443.
- [10] Vempati, A. (2024). "Time-Aware Attention-Based Gated Network for Credit Card Fraud Detection by Extracting Transactional Behaviors." *International Journal of HRM and Organizational Behavior*, 12(2), 280-296.
- [11] Hilal, W., Gadsden, S. A., & Yawney, J. (2022). "Financial fraud: a review of anomaly detection techniques and recent advances. *Expert systems With applications*," 193, 116429.
- [12] Kishore, S. V. K., & Sequeira, A. H. (2016). "An Empirical Investigation on Mobile Banking Service Adoption in Rural Karnataka." *SAGE Open*, 6(1). <https://doi.org/10.1177/2158244016633731>
- [13] Ferreira, J. M., Acuña, S. T., Dieste, O., Vegas, S., Santos, A., Rodríguez, F., & Juristo, N. (2020). "Impact of usability mechanisms: An experiment on efficiency, effectiveness and user satisfaction." *Information and Software Technology*, 117, 106195.
- [14] H. Singh et al., "Detecting Digital Deception: A CNN-RNN hybrid Approach of Deepfake Detection," in *Proc. 2025 ICPCT, India*, 2025, pp. 667-672, doi: 10.1109/ICPCT64145.2025.10940830.
- [15] B. P. Joshi et al., "Selection of Electrical Distribution System using SVAS based Einstein Averaging Operator," *ICACITE, India*, 2024, pp. 1847-1852, doi: 10.1109/ICACITE60783.2024.10616576.
- [16] Palak et. al., "Emotion Recognition Using a Hybrid Model of Transformer and CNN-LSTM for Improved Performance," *2025 ICDT, India*, 2025, pp. 866-870, doi: 10.1109/ICDT63985.2025.10986535.
- [17] V. S. B. Chilluri et al., "Design and Implementation of a User Centered Design Framework for Software Development," in *Proc. 2025 CE2CT, India*, 2025, pp. 1232-1236, doi: 10.1109/CE2CT64011.2025.10941419.
- [18] Mallreddy, S. R., & Vasa, Y. (2023). "Predictive Maintenance In Cloud Computing And Devops: ML Models For Anticipating And Preventing System Failures." *NVEO-NATURAL VOLATILES & ESSENTIAL OILS Journal* NVEO, 10(1), 213-219.
- [19] Singirikonda et. al. (2021). "Develop Solutions To Detect And Mitigate Data Quality Issues In ML Models. *NVEO - Natural Volatiles & Essential Oils*," 8(4), 16968&e"16973. <https://doi.org/https://doi.org/10.53555/nveo.v8i4.5771>
- [20] N. Kunchakuri, "MATLAB-Based Simulation of Generative AI-Based Autonomous Vehicle Control for High-Speed Driving and Emergency Maneuvers," *CE2CT, India*, 2025, pp. 1191-1196, doi: 10.1109/CE2CT64011.2025.10939159.

S. Dodda et. al., "Enhancing Microservice Reliability in Cloud Environments Using Machine Learning for Anomaly Detection," *ICCSC, India*, 2024, pp. 1-5, doi: 10.1109/ICCSC62048.2024.10830437.