

SELECT with various clauses – WHERE, pattern matching

```
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> create database collegedb;
Query OK, 1 row affected (0.10 sec)

mysql> use collegedb;
Database changed
mysql> create table student(regno bigint primary key,stuname varchar(30),department varchar(20),marks int);
Query OK, 0 rows affected (0.14 sec)

mysql> insert into student values (191711341,'sonu','CSE',85),(191711342,'Pranathi','ECE',90),(191711343,'roops','EEE',75),(191711344,'abhighna','CSE',88),(
191711345,'tabassum','ECE',80);
Query OK, 5 rows affected (0.07 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql> select*from student;
+-----+-----+-----+-----+
| regno | stuname | department | marks |
+-----+-----+-----+-----+
| 191711341 | sonu | CSE | 85 |
| 191711342 | Pranathi | ECE | 90 |
| 191711343 | roops | EEE | 75 |
| 191711344 | abhighna | CSE | 88 |
| 191711345 | tabassum | ECE | 80 |
+-----+-----+-----+-----+
5 rows in set (0.01 sec)

mysql> select*from student where department='CSE';
+-----+-----+-----+-----+
| regno | stuname | department | marks |
+-----+-----+-----+-----+
| 191711341 | sonu | CSE | 85 |
| 191711344 | abhighna | CSE | 88 |
+-----+-----+-----+-----+
2 rows in set (0.01 sec)

mysql> select*from student where marks>80;
+-----+-----+-----+-----+
| regno | stuname | department | marks |
+-----+-----+-----+-----+
| 191711341 | sonu | CSE | 85 |
| 191711342 | Pranathi | ECE | 90 |
| 191711344 | abhighna | CSE | 88 |
+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

```
mysql> select*from student where marks>80;
+-----+-----+-----+-----+
| regno | stuname | department | marks |
+-----+-----+-----+-----+
| 191711341 | sonu | CSE | 85 |
| 191711342 | Pranathi | ECE | 90 |
| 191711344 | abhighna | CSE | 88 |
+-----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> select*from student where stuname like 'P%';
+-----+-----+-----+-----+
| regno | stuname | department | marks |
+-----+-----+-----+-----+
| 191711342 | Pranathi | ECE | 90 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)

mysql> select*from student where stuname like '%i';
+-----+-----+-----+-----+
| regno | stuname | department | marks |
+-----+-----+-----+-----+
| 191711342 | Pranathi | ECE | 90 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)

mysql> select*from student where stuname like '%a%';
+-----+-----+-----+-----+
| regno | stuname | department | marks |
+-----+-----+-----+-----+
| 191711342 | Pranathi | ECE | 90 |
| 191711344 | abhighna | CSE | 88 |
| 191711345 | tabassum | ECE | 80 |
+-----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> select*from student where department='CSE';
+-----+-----+-----+-----+
| regno | stuname | department | marks |
+-----+-----+-----+-----+
| 191711341 | sonu | CSE | 85 |
| 191711344 | abhighna | CSE | 88 |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

```
mysql> select*from student where department='CSE';
```

regno	stuname	department	marks
191711341	sonu	CSE	85
191711344	abhighna	CSE	88

```
2 rows in set (0.00 sec)
```

```
mysql> select*from student where marks>80;
```

regno	stuname	department	marks
191711341	sonu	CSE	85
191711342	Pranathi	ECE	90
191711344	abhighna	CSE	88

```
3 rows in set (0.00 sec)
```

```
mysql> select*from student where stuname like 'p%';
```

regno	stuname	department	marks
191711342	Pranathi	ECE	90

```
1 row in set (0.00 sec)
```

```
mysql> select*from student where stuname like '%i';
```

regno	stuname	department	marks
191711342	Pranathi	ECE	90

```
1 row in set (0.00 sec)
```

```
mysql> select*from student where stuname like '%a%';
```

regno	stuname	department	marks
191711342	Pranathi	ECE	90
191711344	abhighna	CSE	88
191711345	tabassum	ECE	80

```
3 rows in set (0.00 sec)
```