



Full Name:	Aishwarya S
Email:	aishwaryasriramu@gmail.com
Test Name:	Mock Test
Taken On:	24 Aug 2025 18:03:03 IST
Time Taken:	12 min 43 sec/ 90 min
Invited by:	Ankush
Invited on:	24 Aug 2025 18:02:43 IST
Skills Score:	
Tags Score:	Algorithms280/280 Core CS280/280 Data Structures105/105 Easy280/280 LCM105/105 Least Common Multiple105/105 Math105/105 Problem Solving105/105 Strings175/175 gcd105/105 greatest common divisor105/105 problem-solving280/280 sets105/105

100%
280/280

scored in **Mock Test** in 12 min 43 sec on 24 Aug 2025 18:03:03 IST

Recruiter/Team Comments:

No Comments.

Plagiarism flagged

We have marked questions with suspected plagiarism below. Please review it in detail here -

	Question Description	Time Taken	Score	Status
Q1	Palindrome Index > Coding	4 min 6 sec	105/ 105	⚠
Q2	Between Two Sets > Coding	5 min 3 sec	105/ 105	⚠
Q3	Anagram > Coding	3 min 13 sec	70/ 70	⚠

QUESTION 1



Needs Review

Score 105

Palindrome Index > Coding

Strings

Algorithms

Easy

problem-solving

Core CS

Problem Solving

QUESTION DESCRIPTION

Given a string of lowercase letters in the range `ascii[a-z]`, determine the index of a character that can be removed to make the string a **palindrome**. There may be more than one solution, but any will do. If the word is already a palindrome or there is no solution, return `-1`. Otherwise, return the index of a character to remove.

Example

 $s = \text{"bcbc"}$

Either remove `'b'` at index **0** or `'c'` at index **3**.

Function Description

Complete the `palindromeIndex` function in the editor below.

`palindromeIndex` has the following parameter(s):

- `string s`: a string to analyze

Returns

- `int`: the index of the character to remove or **`-1`**

Input Format

The first line contains an integer **q** , the number of queries.

Each of the next **q** lines contains a query string **s** .

Constraints

- $1 \leq q \leq 20$
- $1 \leq \text{length of } s \leq 10^5 + 5$
- All characters are in the range `ascii[a-z]`.

Sample Input

STDIN	Function
-----	-----
3	$q = 3$
aaab	$s = \text{'aaab'}$ (first query)
baa	$s = \text{'baa'}$ (second query)
aaa	$s = \text{'aaa'}$ (third query)

Sample Output

```
3
0
-1
```

Explanation

Query 1: "aaab"

Removing `'b'` at index **3** results in a palindrome, so return **3**.

Query 2: "baa"

Removing `'b'` at index **0** results in a palindrome, so return **0**.

Query 3: "aaa"

This string is already a palindrome, so return **`-1`**. Removing any one of the characters would result in a palindrome, but this test comes first.

Note: The custom checker logic for this challenge is available [here](#).

CANDIDATE ANSWER

Language used: C

```

1
2  /*
3   * Complete the 'palindromeIndex' function below.
4   *
5   * The function is expected to return an INTEGER.
6   * The function accepts STRING s as parameter.
7   */
8
9  bool isPalindromeRange(char* s, int left, int right){
10     while(left < right){
11         if(s[left] != s[right]){
12             return false;
13         }
14         left++;
15         right--;
16     }
17     return true;
18 }
19
20 int palindromeIndex(char* s) {
21     int len = strlen(s);
22     int left = 0;
23     int right = len - 1;
24
25     while(left < right){
26         if(s[left] != s[right]){
27             if(isPalindromeRange(s, left + 1, right)){
28                 return left;
29             }
30             if(isPalindromeRange(s, left, right - 1)){
31                 return right;
32             }
33             return -1;
34         }
35         left++;
36         right--;
37     }
38     return -1;
39 }
40

```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
Testcase 1	Easy	Sample case	✔ Success	0	0.0166 sec	7.25 KB
Testcase 2	Medium	Hidden case	✔ Success	5	0.0098 sec	7.13 KB
Testcase 3	Medium	Hidden case	✔ Success	5	0.0091 sec	7.25 KB
Testcase 4	Medium	Hidden case	✔ Success	5	0.0068 sec	7 KB
Testcase 5	Medium	Hidden case	✔ Success	5	0.0088 sec	6.75 KB
Testcase 6	Medium	Hidden case	✔ Success	5	0.0075 sec	7.25 KB
Testcase 7	Medium	Hidden case	✔ Success	5	0.0083 sec	7.25 KB
Testcase 8	Medium	Hidden case	✔ Success	5	0.013 sec	7.5 KB
Testcase 9	Hard	Hidden case	✔ Success	10	0.0076 sec	7 KB

Testcase 10	Hard	Hidden case	✔ Success	10	0.0075 sec	7.38 KB
Testcase 11	Hard	Hidden case	✔ Success	10	0.009 sec	7.13 KB
Testcase 12	Hard	Hidden case	✔ Success	10	0.0084 sec	7 KB
Testcase 13	Hard	Hidden case	✔ Success	10	0.0121 sec	7.38 KB
Testcase 14	Hard	Hidden case	✔ Success	10	0.0082 sec	7.25 KB
Testcase 15	Hard	Hidden case	✔ Success	10	0.0092 sec	7 KB

No Comments

QUESTION 2



Needs Review

Score 105

Between Two Sets >

Coding

Math

Algorithms

Easy

gcd

Data Structures

LCM

sets

problem-solving

Core CS

greatest common divisor

Least Common Multiple

QUESTION DESCRIPTION

There will be two arrays of integers. Determine all integers that satisfy the following two conditions:

1. The elements of the first array are all factors of the integer being considered
2. The integer being considered is a factor of all elements of the second array

These numbers are referred to as being *between* the two arrays. Determine how many such numbers exist.

Example

$a = [2, 6]$

$b = [24, 36]$

There are two numbers between the arrays: **6** and **12**.

$6\%2 = 0$, $6\%6 = 0$, $24\%6 = 0$ and $36\%6 = 0$ for the first value.

$12\%2 = 0$, $12\%6 = 0$ and $24\%12 = 0$, $36\%12 = 0$ for the second value. Return **2**.

Function Description

Complete the `getTotalX` function in the editor below. It should return the number of integers that are between the sets.

`getTotalX` has the following parameter(s):

- `int a[n]`: an array of integers
- `int b[m]`: an array of integers

Returns

- `int`: the number of integers that are between the sets

Input Format

The first line contains two space-separated integers, n and m , the number of elements in arrays a and b .

The second line contains n distinct space-separated integers $a[i]$ where $0 \leq i < n$.

The third line contains m distinct space-separated integers $b[j]$ where $0 \leq j < m$.

Constraints

- $1 \leq n, m \leq 10$
- $1 \leq a[i] \leq 100$
- $1 \leq b[j] \leq 100$

Sample Input

```
2 3
2 4
16 32 96
```

Sample Output

Explanation

2 and 4 divide evenly into 4, 8, 12 and 16.

4, 8 and 16 divide evenly into 16, 32, 96.

4, 8 and 16 are the only three numbers for which each element of a is a factor and each is a factor of all elements of b.

CANDIDATE ANSWER

Language used: C

```

1
2  /*
3   * Complete the 'getTotalX' function below.
4   *
5   * The function is expected to return an INTEGER.
6   * The function accepts following parameters:
7   * 1. INTEGER_ARRAY a
8   * 2. INTEGER_ARRAY b
9   */
10
11 int getTotalX(int a_count, int* a, int b_count, int* b) {
12     int count = 0;
13
14     int max_b = b[0];
15     for(int i=1; i<b_count; i++){
16         if(b[i]>max_b){
17             max_b = b[i];
18         }
19     }
20
21     for(int x=1; x<=max_b; x++){
22         bool valid = true;
23         for(int i=0; i<a_count; i++){
24             if(x % a[i] != 0){
25                 valid = false;
26                 break;
27             }
28         }
29         if(valid){
30             for(int j=0; j<b_count; j++){
31                 if(b[j] % x != 0){
32                     valid = false;
33                     break;
34                 }
35             }
36         }
37         if(valid){
38             count++;
39         }
40     }
41     return count;
42 }
43

```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
----------	------------	------	--------	-------	------------	-------------

Testcase 1	Easy	Sample case	✔ Success	0	0.0074 sec	6.88 KB
Testcase 2	Easy	Hidden case	✔ Success	15	0.0099 sec	6.88 KB
Testcase 3	Easy	Hidden case	✔ Success	15	0.0066 sec	6.88 KB
Testcase 4	Easy	Hidden case	✔ Success	15	0.0119 sec	7.25 KB
Testcase 5	Easy	Hidden case	✔ Success	15	0.0081 sec	7.13 KB
Testcase 6	Easy	Hidden case	✔ Success	15	0.007 sec	7.13 KB
Testcase 7	Easy	Hidden case	✔ Success	15	0.0091 sec	7.13 KB
Testcase 8	Easy	Hidden case	✔ Success	15	0.0083 sec	7.13 KB
Testcase 9	Easy	Sample case	✔ Success	0	0.0083 sec	7.25 KB

No Comments

QUESTION 3



Needs Review

Score 70

Anagram > Coding

Strings

Algorithms

Easy

problem-solving

Core CS

QUESTION DESCRIPTION

Two words are *anagrams* of one another if their letters can be rearranged to form the other word.

Given a string, split it into two contiguous substrings of equal length. Determine the minimum number of characters to change to make the two substrings into anagrams of one another.

Example

$s = \text{abccde}$

Break s into two parts: 'abc' and 'cde'. Note that all letters have been used, the substrings are contiguous and their lengths are equal. Now you can change 'a' and 'b' in the first substring to 'd' and 'e' to have 'dec' and 'cde' which are anagrams. Two changes were necessary.

Function Description

Complete the *anagram* function in the editor below.

anagram has the following parameter(s):

- *string s*: a string

Returns

- *int*: the minimum number of characters to change or -1.

Input Format

The first line will contain an integer, q , the number of test cases.

Each test case will contain a string s .

Constraints

- $1 \leq q \leq 100$
- $1 \leq |s| \leq 10^4$
- s consists only of characters in the range `ascii[a-z]`.

Sample Input

```
6
aaabbb
ab
abc
mnop
xyyx
xaxbbbx
```

Sample Output

```
3
1
-1
2
0
1
```

Explanation

Test Case #01: We split s into two strings $S1='aaa'$ and $S2='bbb'$. We have to replace all three characters from the first string with 'b' to make the strings anagrams.

Test Case #02: You have to replace 'a' with 'b', which will generate "bb".

Test Case #03: It is not possible for two strings of unequal length to be anagrams of one another.

Test Case #04: We have to replace both the characters of first string ("mn") to make it an anagram of the other one.

Test Case #05: $S1$ and $S2$ are already anagrams of one another.

Test Case #06: Here $S1 = "xaxb"$ and $S2 = "bbxx"$. You must replace 'a' from $S1$ with 'b' so that $S1 = "xbxb"$.

CANDIDATE ANSWER

Language used: C

```
1
2  /*
3   * Complete the 'anagram' function below.
4   *
5   * The function is expected to return an INTEGER.
6   * The function accepts STRING s as parameter.
7   */
8
9  int anagram(char* s) {
10     int len = strlen(s);
11     if(len % 2 != 0){
12         return -1;
13     }
14     int half = len / 2;
15     int freq[26] = {0};
16     for(int i = 0; i<half; i++){
17         freq[s[i] - 'a']++;
18     }
19     for(int i=half; i<len;i++){
20         freq[s[i] - 'a']--;
21     }
22     int changes =0;
23     for(int i = 0; i<26; i++){
24         if(freq[i] > 0){
25             changes += freq[i];
26         }
27     }
28     return changes;
29 }
30
```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
Testcase 1	Easy	Hidden case	✔ Success	5	0.0073 sec	6.75 KB
Testcase 2	Easy	Hidden case	✔ Success	5	0.007 sec	7 KB
Testcase 3	Easy	Hidden case	✔ Success	5	0.0073 sec	6.88 KB
Testcase 4	Easy	Hidden case	✔ Success	5	0.0074 sec	7.38 KB
Testcase 5	Easy	Hidden case	✔ Success	5	0.0102 sec	6.75 KB
Testcase 6	Easy	Hidden case	✔ Success	5	0.0096 sec	7.88 KB
Testcase 7	Easy	Hidden case	✔ Success	5	0.008 sec	7.63 KB
Testcase 8	Easy	Hidden case	✔ Success	5	0.0107 sec	7.88 KB
Testcase 9	Easy	Hidden case	✔ Success	5	0.0124 sec	7.5 KB
Testcase 10	Easy	Hidden case	✔ Success	5	0.0095 sec	7.88 KB
Testcase 11	Easy	Hidden case	✔ Success	5	0.0283 sec	7.25 KB
Testcase 12	Easy	Hidden case	✔ Success	5	0.0194 sec	7.88 KB
Testcase 13	Easy	Hidden case	✔ Success	5	0.0097 sec	7.75 KB
Testcase 14	Easy	Hidden case	✔ Success	5	0.0125 sec	7.88 KB
Testcase 15	Easy	Sample case	✔ Success	0	0.0083 sec	7 KB
Testcase 16	Easy	Sample case	✔ Success	0	0.0084 sec	7.13 KB
No Comments						