

40

1. B ✓
2. C ✓
3. B ✗
4. A ✓
5. B ✓
6. B ✗
7. B ✗
8. C ✓
9. C ✓
10. B ✓
11. B ✓
12. C ✓
13. B ✓
14. C ✓
15. B ✓
16. C ✓
17. B ✓
18. C ✓
19. B ✓
20. B ✓

V

21.	Supervised learning is a type of machine learning that required supervision to learn. It is trained using <u>labeled dataset</u> and it is <u>mainly</u> used for <u>classification</u> and <u>regression</u> problems.
22.	Model M1 gives 99% of accuracy for training dataset and it gives 30% of accuracy for testing dataset so the model is Overfitting.
23.	Regression analysis is the process of predicting a <u>numerical value</u> (target variables) based on a <u>single</u> or <u>multiple independent</u> variables
24.	Two challenges of machine learning: - Finding dataset = very tedious process that starts from <u>data mining</u> → <u>data preprocessing</u> - <u>Training a fit model</u> (No overfitting nor underfitting)
25.	Major applications of data science: - Healthcare = diabetes checker, diagnosing diseases - <u>Business</u> = <u>chatbot</u> , stock prediction

26. structured data: data that are ~~read~~ readable by people and usually are in the form of tables. Example = Records in database

Semi-structured data: data that readable by programmers and machine. Example = data in Json Format.

There are 3 common ways in finding outlier :

27. Visualization
- Z-score
- IQR

28. Data preprocessing is the proper process of cleansing, transforming and enriching data to prepare a dataset that can be used more effectively in training machine learning models.

29. Data normalization is required in K-NN is due to the algorithm used in K-NN. We need to scale the data points so that scatter K datapoints won't be so far wide from each other.

30. Continuous attributes are discretized using normalization techniques

33. Gradient descent is used to optimize the algorithm parameters for better performance. For example, In SVM, it used to maximized marginal value.

31. k in k -means algorithm refer to datapoints within clusters.

34. A. Acceptable result but can not be considered a good performance
B. Unacceptable, either the model is overfit or underfit
C. Very good result because the marginal value is high.

35. Radial Basis Function Kernel is a function that generate hyper planes based on the dimensions.

32. Hyper parameters =

- max - pool
- entropy