

# Scripts Implementation

Project Development Phase | Import Data Using Transform Maps

## 1. Objective

Add scripts to the Transform Map for validation, value conversion and logging. Scripts are kept short and commented. Create them under the Transform Map in the **Transform Scripts** related list (onStart, onBefore, onAfter, onComplete) and in the field map for u\_status.

## 2. onStart Script

```
// Runs once before the first row is processed
log.info('Import Users Map: transform started');
```

## 3. onBefore Script (validate and clean each row)

```
// source = staging row, target = target record, ignore = skip row flag
var email = source.u_email.toString().trim().toLowerCase();

if (email == '') {
    ignore = true; // skip rows with no email
    log.warn('Row skipped: missing email');
} else if (source.u_first_name.nil() || source.u_last_name.nil()) {
    ignore = true; // skip rows with missing name
    log.warn('Row skipped: missing name for ' + email);
} else {
    source.u_email = email; // store cleaned email
}

if (!ignore && source.u_department.nil()) {
    log.warn('No department supplied for ' + email);
}
```

## 4. Field Map Script (u\_status to active)

Open the field map for u\_status to active, check **Use source script** and enter:

```
// Convert text status to true / false
answer = (source.u_status.toString().trim().toLowerCase() == 'active');
```

## 5. onAfter Script (log each result)

```
// Runs after each row is saved
var action = (isUpdate) ? 'Updated' : 'Inserted';
log.info(action + ' user: ' + target.email);
```

## 6. onComplete Script

```
// Runs once after all rows are processed
log.info('Import Users Map: transform completed');
```

## 7. Script Review

| Script           | Purpose                               | Requirement   |
|------------------|---------------------------------------|---------------|
| onStart          | Log start of run                      | FR-12         |
| onBefore         | Validate email and names, clean email | FR-09, NFR-01 |
| Field map script | Convert status to true / false        | FR-07         |

| Script     | Purpose                      | Requirement  |
|------------|------------------------------|--------------|
| onAfter    | Log inserted or updated user | FR-11, FR-12 |
| onComplete | Log end of run               | FR-12        |

## 8. Coding Standards Followed

- Every script has a comment describing its purpose.
- Values are trimmed and lower-cased before matching.
- No hard-coded sys\_ids; reference lookups use field names.
- Logging uses log.info and log.warn to explain skipped rows.