


```
import { type Page, type Locator } from '@playwright/test';

export class SalesforceLoginPage {
  readonly usernameInput: Locator;
  readonly loginButton: Locator;

  constructor(private readonly page: Page) {
    // Email input - fallback to ID selector as no accessible label is present
    this.usernameInput = page.locator('#username');

    // Submit button - accessible name comes from the input's value attribute
    this.loginButton = page.getByRole('button', { name: 'Log In' });
  }

  /** Fill the username (email) field */
  async enterUsername(username: string): Promise<void> {
    await this.usernameInput.fill(username);
  }

  /** Click the Log In button */
  async clickLogin(): Promise<void> {
    await this.loginButton.click();
  }

  /** Complete login action with the given username */
  async login(username: string): Promise<void> {
    await this.enterUsername(username);
    await this.clickLogin();
  }
}
```



Salesforce login

Username

Log In

☐ Remember me

[Forgot Your Password?](#) [Use Custom Domain](#)

or

 Log In with Email

Not a customer?

Try for Free

© 2026 Salesforce, Inc. All rights reserved. | [Privacy](#)

AI Browser Extension for Code Generation

Code GeneratorSettings

☐ Feature File☒ Page Class

Reset Chat

Copy

```
import { type Page, type Locator } from '@playwright/test';

export class SalesforceLoginPage {
  readonly usernameInput: Locator;
  readonly loginButton: Locator;

  constructor(private readonly page: Page) {
    // Email input - fallback to ID selector as no accessible label is present
    this.usernameInput = page.locator('#username');

    // Submit button - accessible name comes from the input's value attribute
    this.loginButton = page.getByRole('button', { name: 'Log In' });
  }

  /** Fill the username (email) field */
  async enterUsername(username: string): Promise<void> {
    await this.usernameInput.fill(username);
  }
}
```