Richco

CLEANING GUIDE

CLEANING GUIDE

RICHCO RESIN FLOORING SYSTEM

To maintain an optimal performance of Richco Resin Flooring System, establishing an appropriate cleaning regime is crucial. Richco recommends a daily cleaning in these high trafficked areas.

SCRUBBER / DRYER MACHINE METHOD OF CLEANING

The use of a Scrubber / Dryer Machine is Richco's preferred method of cleaning large internal spaces on our Richco Resin Flooring System. This method of cleaning is easier, quicker, and more hygienic than manual floor cleaning and provides the best result on our flooring systems.

Prior to using the scrubber / dryer machine, sweep or vacuum the floor to remove loose debris or dirt.

It is important that the Scrubber / Dryer Machine is filled with water and the correct diluted cleaning fluids are used as per the manufacturer's instructions. We recommend the use of a PH neutral cleaner (on matte finishes) or a diluted citrus based cleaning agent, detergent, deodorizer, degreaser, or emulsifier (diluted into water as per the manufactures instructions). It is essential that a soft cleaning pad is used (which is normally a white pad), ensuring that the pad is fitted flat and even (not at an angle).

MANUAL METHOD OF CLEANING

1. Sweep or vacuum the floor to remove loose debris or dirt.
2. We would recommend the use of a PH neutral cleaner (on matte finishes) or a citrus based cleaning agent, detergent, deodorizer, degreaser, or emulsifier diluted into water as per manufacturer's instructions.
3. Place the solution onto floor surface and agitate by hand using a stiff brush (by scrubbing motion).
4. Flood the surface with clean water and scrub.
5. Remove dirty water with squeegee (or with wet vacuum).
6. Dispose of contaminated water whilst paying special attention to the by-law regulations which prohibit the introduction of certain chemicals into surface water drains or sewer systems.

WARNING: The use of a mop and bucket method for routine cleaning of the floors should only be used when dealing with spillages or spot cleaning (see below). Applying this method in normal everyday usage may remove heavy soiling but will often result in the floor being mopped with dirty water, creating a film of dirt spread uniformly across the floor that will build and over time causes a matte surface.

For floors with a matte finish only use a PH Neutral Cleaner!

Disclaimer: Richco will not be held responsible for the incorrect cleaning procedures resulting in damage to the Richco Resin Flooring System.

SPOT CLEANING/ SPILLAGES	It is important that spillages are immediately cleaned from the surface as follows: 1. Wipe up spillage with towels or paper towels and dispose of properly. It is important to not allow spillages to sit on the floor surface for too long. 2. Vacuum / Wet Vacuum or Sweep the small area of floor that has the spillage or needs spot cleaning. 3. For stubborn stains clean with a PH Neutral cleaner (diluted as per the manufacturer's instructions). 4. Clean the small area with a mop and clean warm water to spot clean or remove the residue from the spillage.
CHEWING GUM REMOVAL *(THIS SHOULD BE BANNED FROM THE PARKS)*	If chewing gum is found on the floor surface - this should be removed immediately (whilst it is still in its soft / pliable state) or during the nightly clean. Use a chewing gum removal product (typically a citrus based product) which is spray applied onto the chewing gum and cleaning cloth. Leave the cloth (saturated with the chewing gum removal product) on top of the chewing gum to soak. Use a soft plastic scraper (DO NOT USE A METAL SCRAPER ON THE SURFACE) to remove the chewing gum. Use a clean cloth to remove any remaining residue of the gum and cleaning product. After removal of the chewing gum – use water with a PH neutral cleaner and clean the surface as normal. *DO NOT use a zero-point power washing to remove chewing gum – this will result in damages to our flooring systems*
CLEANING CHEMICALS	Richco recommends the use of a citrus based cleaner for routine cleaning. ***Important***: Dilute chemicals as per manufacturer guidelines. If used in wrong concentrations, could cause an adverse effect on the floor. Harsh detergents and bleach are **not recommended**, as it will cause the color to fade after a period of prolonged use. Avoid soap-based cleaners as they will leave a haze on the resin flooring that builds up over time. **Never use** solvents on the floor surface.
POLISHING	For a durable gloss finish Richco recommends a 25% solids metalized floor polish. To maintain a gloss finish, periodically apply a high solids metalized floor polish. Apply to surface per manufacturer's instructions to medium/ heavy traffic areas where a hard-wearing deep lustrous finish is required. There is no need for buffing the surface as the matalized polish dries to a high gloss finish.
POLYMER CLEANER	Some floors benefit from having Stone Grip applied over a polished surface; cleaning polished floors and leaving a slip resistant polymer finish. Richco would recommend that Stone Grip is applied to a polished floor surface periodically as per the manufacturer's instructions. Stone Grip is a detergent with cleaning properties which also leaves behind a low molecular weight polymer. Stone Grip by Slip Doctors or other equivalent products are acceptable.

Richco
INTERNATIONAL

www.richcogroup.com
info@richcogroup.com
+1 888 848 4157