

Homework - Neural networks - Part C (25 points)

A neural network model of semantic cognition

by *Brenden Lake* and *Todd Gureckis*

Computational Cognitive Modeling


NYU class webpage: <https://brendenlake.github.io/CCM-site/>

This homework is due before midnight on Feb. 15, 2024.

In this assignment, you will help implement and analyze a neural network model of semantic cognition. Semantic cognition is our intuitive understanding of objects and their properties. Semantic knowledge includes observations of which objects have which properties, and storage of these facts in long term memory. It also includes the ability to generalize, or predict which properties apply to which objects although they have not been directly observed.

This notebook explores a neural network model of semantic cognition developed by Rogers and McClelland (R&M). R&M sought to model aspects of semantic cognition with a multi-layer neural network, which contrasts with classic symbolic approaches for organizing semantic knowledge. They model the cognitive development of semantic representation as gradient descent (the backpropagation algorithm), using a neural network trained to map objects to their corresponding properties. R&M also modeled the deterioration of semantic knowledge in dementia by adding noise to the learned representations.

The network architecture is illustrated below.



There are two input layers ("Item Layer" and "Relation Layer"), which pass through intermediate layers to produce an output pattern on the "Attribute Layer." In this example, dark green is used to indicate active nodes (activation 1) and light green for inactive nodes (activation 0). The network is trained to answer queries involving an item (e.g., "Canary") and a relation (e.g., "CAN"), outputting all attributes that are true of the item/relation pair (e.g., "grow, move, fly, sing").

For this assignment, you will set up the network architecture in PyTorch and train it. The dataset and code for training has been provided. You will then analyze how its semantic knowledge develops over the course of training. While the original model used logistic (sigmoid) activation functions for all of the intermediate and output layers, we will use the ReLu activation for the Representation and Hidden Layers, with a sigmoid activation for the Attribute Layer.

Completing this assignment requires knowledge of setting up a neural network architecture in PyTorch. Please review your notes from lab and the following [PyTorch tutorial](#).

Reference (available for download on Brightspace):

McClelland, J. L., & Rogers, T. T. (2003). The parallel distributed processing approach to semantic cognition. *Nature Reviews Neuroscience*, 4(4), 310.

```
In [ ]: # Import Libraries
from __future__ import print_function
import matplotlib
%matplotlib inline
import matplotlib.pyplot as plt
import numpy as np
import torch
import torch.nn as nn
from torch.nn.functional import sigmoid, relu
from scipy.cluster.hierarchy import dendrogram, linkage
```

Let's first load in the names of all the items, attributes, and relations into Python lists.

```
In [ ]: with open('data/sem_items.txt', 'r') as fid:
    names_items = np.array([l.strip() for l in fid.readlines()])
with open('data/sem_relations.txt', 'r') as fid:
    names_relations = np.array([l.strip() for l in fid.readlines()])
with open('data/sem_attributes.txt', 'r') as fid:
    names_attributes = np.array([l.strip() for l in fid.readlines()])

nobj = len(names_items)
nrel = len(names_relations)
nattributes = len(names_attributes)
print('List of items:')
print(names_items)
print("List of relations:")
print(names_relations)
print("List of attributes:")
print(names_attributes)
```

List of items:

['Pine' 'Oak' 'Rose' 'Daisy' 'Robin' 'Canary' 'Sunfish' 'Salmon']

List of relations:

['ISA' 'Is' 'Can' 'Has']

List of attributes:

['Living thing' 'Plant' 'Animal' 'Tree' 'Flower' 'Bird' 'Fish' 'Pine'
'Oak' 'Rose' 'Daisy' 'Robin' 'Canary' 'Sunfish' 'Salmon' 'Pretty' 'Big'
'Living' 'Green' 'Red' 'Yellow' 'Grow' 'Move' 'Swim' 'Fly' 'Sing' 'Skin'
'Roots' 'Leaves' 'Bark' 'Branch' 'Petals' 'Wings' 'Feathers' 'Gills'
'Scales']

Next, let's load in the data matrix from a text file too. The matrix `D` has a row for each training pattern. It is split into a matrix of input patterns `input_pats` (item and relation) and their corresponding output patterns `output_pats` (attributes). The are `N` patterns total in the set.

For each input pattern, the first 8 elements indicate which item is being presented, and the next 4 indicate which relation is being queried. Each element of the output pattern corresponds to a different attribute. All patterns use 1-hot encoding.

```
In [ ]: D = np.loadtxt('data/sem_data.txt')
input_pats = D[:, :nobj+nrel]
input_pats = torch.tensor(input_pats, dtype=torch.float)
```

```

output_pats = D[:,nobj+nrel:]
output_pats = torch.tensor(output_pats,dtype=torch.float)
N = input_pats.shape[0] # number of training patterns
input_v = input_pats[0,:].numpy().astype('bool')
output_v = output_pats[0,:].numpy().astype('bool')
print('Example input pattern:')
print(input_v.astype('int'))
print('Example output pattern:')
print(output_v.astype('int'))
print("")
print("Which encodes...")
print('Item ',end='')
print(names_items[input_v[:8]])
print('Relation ',end='')
print(names_relations[input_v[8:]])
print('Attributes ',end='')
print(names_attributes[output_v])

```

Example input pattern:

```
[1 0 0 0 0 0 0 1 0 0 0]
```

Example output pattern:

```
[1 1 0 1 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0]
```

Which encodes...

Item ['Pine']

Relation ['ISA']

Attributes ['Living thing' 'Plant' 'Tree' 'Pine']

Problem 1 (20 points)

Your assignment is to create the neural network architecture shown in the figure above. Fill in the missing pieces of the "Net" class in the code below. For an example, refer to the PyTorch tutorial on ["Neural Networks"](#).

Use the ReLu activation function ("relu") for the Representation and Hidden Layers, with a Logistic/Sigmoid activation function for the Attribute Layer ("sigmoid").

You will need PyTorch's "nn.Linear" function for constructing the layers, and the "relu" and "sigmoid" activation functions.

```

In [ ]: class Net(nn.Module):
    def __init__(self, rep_size, hidden_size):
        super(Net, self).__init__()
        self.rep_layer = nn.Linear(nobj, rep_size)
        self.hid_layer = nn.Linear(rep_size + nrel, hidden_size)
        self.out_layer = nn.Linear(hidden_size, nattributes)

    def forward(self, x):
        # Defines forward pass for the network on input patterns x
        #
        # Input can take these two forms:
        #
        # x: [nobj+nrel 1D Tensor], which is a single input pattern as a 1D te

```

```

#         (containing both object and relation 1-hot identifier) (batch size)
# OR
# x : [B x (nobj+nrel) Tensor], which is a batch of B input patterns (
#
# Output
# output [B x nattribute Tensor], which is the output pattern for each
# hidden [B x hidden_size Tensor], which are activations in the Hidden
# rep [B x rep_size Tensor], which are the activations in the Representa
x = x.view(-1, nobj + nrel) # reshape as size [B x (nobj+nrel) Tensor] i
x_pat_item = x[:, :nobj] # input to Item Layer [B x nobj Tensor]
x_pat_rel = x[:, nobj:] # input to Relation Layer [B x nrel Tensor]
x_pat_rep = nn.ReLU()(self.rep_layer(x_pat_item))
x_pat_hid = nn.ReLU()(self.hid_layer(torch.cat([x_pat_rep, x_pat_rel], d
x_pat_out = nn.Sigmoid()(self.out_layer(x_pat_hid))
output, hidden, rep = x_pat_out, x_pat_hid, x_pat_rep
return output, hidden, rep

```

We provide a completed function `train` for stochastic gradient descent. The network makes online (rather than batch) updates, adjusting its weights after the presentation of each input pattern.

```

In [ ]: def train(mynet, epoch_count, nepochs_additional=5000):
# Input
# mynet : Net class object
# epoch_count : (scalar) how many epochs have been completed so far
# nepochs_additional : (scalar) how many more epochs we want to run
mynet.train()
for e in range(nepochs_additional): # for each epoch
    error_epoch = 0.
    perm = np.random.permutation(N)
    for p in perm: # iterate through input patterns in random order
        mynet.zero_grad() # reset gradient
        output, hidden, rep = mynet(input_pats[p,:]) # forward pass
        target = output_pats[p,:]
        loss = criterion(output, target) # compute loss
        loss.backward() # compute gradient
        optimizer.step() # update network parameters
        error_epoch += loss.item()
    error_epoch = error_epoch / float(N)
    if e % 50 == 0:
        print('epoch ' + str(epoch_count+e) + ' loss ' + str(round(error_epo
return epoch_count + nepochs_additional

```

We provide some useful functions for extracting the activation pattern on the Representation Layer for each possible item. We provide two functions `plot_rep` and `plot_dendo` for visualizing these activation patterns.

```

In [ ]: def get_rep(mynet):
# Extract the hidden activations on the Representation Layer for each item
#
# Input
# mynet : Net class object
#
# Output
# rep : [nitem x rep_size numpy array], where each row is an item
input_clean = torch.zeros(nobj, nobj+nrel)
for idx, name in enumerate(names_items):

```

```

        input_clean[idx, idx] = 1. # 1-hot encoding of each object (while Relati
output, hidden, rep = mynet(input_clean)
return rep.detach().numpy()

def plot_rep(rep1, rep2, rep3, names):
    # Compares Representation Layer activations of Items at three different tim
    # using bar graphs
    #
    # Each rep1, rep2, rep3 is a [nitem x rep_size numpy array]
    # names : [nitem list] of item names
    #
    nepochs_list = [ nepochs_phase1, nepochs_phase2, nepochs_phase3 ]
    nrows = nobj
    R = np.dstack((rep1, rep2, rep3))
    mx = R.max()
    mn = R.min()
    depth = R.shape[2]
    count = 1
    plt.figure(1,figsize=(4.2, 8.4))
    for i in range(nrows):
        for d in range(R.shape[2]):
            plt.subplot(nrows, depth, count)
            rep = R[i, :, d]
            plt.bar(range(rep.size), rep)
            plt.ylim([mn, mx])
            plt.xticks([])
            plt.yticks([])
            if d==0:
                plt.ylabel(names[i])
            if i==0:
                plt.title("epoch " + str(nepochs_list[d]))
            count += 1
    plt.show()

def plot_dendo(rep1, rep2, rep3, names):
    # Compares Representation Layer activations of Items at three different tim
    # using hierarchical clustering
    #
    # Each rep1, rep2, rep3 is a [nitem x rep_size numpy array]
    # names : [nitem list] of item names
    #
    nepochs_list = [ nepochs_phase1, nepochs_phase2, nepochs_phase3 ]
    linked1 = linkage(rep1, "single")
    linked2 = linkage(rep2, "single")
    linked3 = linkage(rep3, "single")
    mx = np.dstack((linked1[:,2], linked2[:,2], linked3[:,2])).max() + 0.1
    plt.figure(2, figsize=(7, 12))
    plt.subplot(3, 1, 1)
    dendrogram(linked1, labels=names, color_threshold=0)
    plt.ylim([0, mx])
    plt.title("Hierarchical clustering; " + "epoch " + str(nepochs_list[0]))
    plt.ylabel("Euclidean distance")
    plt.subplot(3, 1, 2)
    plt.title("epoch " + str(nepochs_list[1]))
    dendrogram(linked2, labels=names, color_threshold=0)
    plt.ylim([0, mx])
    plt.subplot(3, 1, 3)
    plt.title("epoch " + str(nepochs_list[2]))
    dendrogram(linked3, labels=names, color_threshold=0)

```

```
plt.ylim([0, mx])  
plt.show()
```


The next script initializes the neural network and trains it for 2500 epochs total. It trains in three stages, and the item representations (on the Representation Layer) are extracted after 500 epochs, 1000 epochs, and then at the end of training (2500 epochs).


```
In [ ]: learning_rate = 0.1  
criterion = nn.MSELoss() # mean squared error loss function  
mynet = Net(rep_size=8, hidden_size=15)  
optimizer = torch.optim.SGD(mynet.parameters(), lr=learning_rate) # stochastic g  
  
nepochs_phase1 = 500  
nepochs_phase2 = 1000  
nepochs_phase3 = 2500  
epoch_count = 0  
epoch_count = train(mynet, epoch_count, nepochs_additional=nepochs_phase1)  
rep1 = get_rep(mynet)  
epoch_count = train(mynet, epoch_count, nepochs_additional=nepochs_phase2-nepoch  
rep2 = get_rep(mynet)  
epoch_count = train(mynet, epoch_count, nepochs_additional=nepochs_phase3-nepoch  
rep3 = get_rep(mynet)
```

```
epoch 0 loss 0.241
epoch 50 loss 0.07
epoch 100 loss 0.067
epoch 150 loss 0.064
epoch 200 loss 0.059
epoch 250 loss 0.055
epoch 300 loss 0.052
epoch 350 loss 0.049
epoch 400 loss 0.047
epoch 450 loss 0.045
epoch 500 loss 0.043
epoch 550 loss 0.041
epoch 600 loss 0.039
epoch 650 loss 0.036
epoch 700 loss 0.033
epoch 750 loss 0.03
epoch 800 loss 0.028
epoch 850 loss 0.026
epoch 900 loss 0.025
epoch 950 loss 0.024
epoch 1000 loss 0.023
epoch 1050 loss 0.022
epoch 1100 loss 0.02
epoch 1150 loss 0.018
epoch 1200 loss 0.016
epoch 1250 loss 0.015
epoch 1300 loss 0.014
epoch 1350 loss 0.013
epoch 1400 loss 0.012
epoch 1450 loss 0.011
epoch 1500 loss 0.01
epoch 1550 loss 0.01
epoch 1600 loss 0.009
epoch 1650 loss 0.009
epoch 1700 loss 0.009
epoch 1750 loss 0.008
epoch 1800 loss 0.008
epoch 1850 loss 0.008
epoch 1900 loss 0.007
epoch 1950 loss 0.007
epoch 2000 loss 0.007
epoch 2050 loss 0.007
epoch 2100 loss 0.006
epoch 2150 loss 0.006
epoch 2200 loss 0.005
epoch 2250 loss 0.005
epoch 2300 loss 0.005
epoch 2350 loss 0.004
epoch 2400 loss 0.004
epoch 2450 loss 0.004
```

Finally, let's visualize the Representation Layer at the different stages of learning.

```
In [ ]: plot_rep( rep1, rep2, rep3, names_items)
        plot_dendo(rep1, rep2, rep3, names_items)
```



Problem 2 (5 points)

Based on your plots, write a short analysis (4-5 sentences) of how the internal representations of the network develop over the course of learning. How does learning progress? Does the network start by differentiating certain classes of patterns from each other, and then differentiate others in later stages?

Hint: You can refer to your lecture slides and notes for the R&M model for help with your analysis. Your network should broadly replicate their findings, but since the training patterns and activation function aren't identical, don't expect the exact same results.

My Answer:

From the representation graph, we can observe that at epoch 500, the net have divided items into two parts, plants and animals.

I.e., we can see the distinction in the patterns of plants and animals.

Then at epoch 1000, the net is able to classify trees, flowers, birds, and fishes.

Last, at epoch 2500, except for Canary and Robin, the representations of each item have become very unlike from each other.

The reason that the representations of Canary and Robin are quite similar could be that they don't have too many differences. (They are only different at name, color, and that Canary can sing.)