


Time Series Analysis

Candle stick



TSA- Supervised Regression Problem

Time Series -Regression

Vs

Machine Learning- Regression

Training and Test should
be series




```
#trendslist.append(td)
model = AutoReg(X_train, lags=i,trend=td)
model_fit = model.fit()
# make prediction
y_pred= model_fit.predict(len(X_train), len(data1)-1)
```

Training and Test should
be random

```
loaded_model=pickle.load(open("finalized_model_Mul_linear.sav",'rb'))
result=loaded_model.predict([[2344,345,435,0,1]])
```




3. SUPER EASY COMPARISON TABLE



Feature	Time Series Regression	Machine Learning Regression
Time order important?	 Yes	 No
Inputs	Past values (lags)	Independent features
Output example	Predict next hour/day value	Predict price/score/quantity
Model types	ARIMA, Prophet, LSTM	Linear, RF, XGBoost
Suitable for	Stock price, weather, sales forecasting 	House price, medical prediction, score prediction

Time series graph

- Original = Seasonal + Trend + Noise









Time Series Analysis



Seasonal/cyclic unit

Time series Assumption Stationarity

- Mean and Variance is same over the period of time




Stationarity


- mean and variance do not vary with time.
- Absence of trend, seasonality, etc.,

Non-Stationarity


- mean and variance vary with time
- Presence of trend, seasonality, etc.,




Stationary Data



Nonstationary Data




Stationary Data (Variance is constant with time)




Non-stationary Data (Variance is varying with time)

ADDITIVE AND MULTIPLICATIVE TIME SERIES

Additive



MULTIPLICATIVE



How to Check Stationarity

- Augmented Dickey-Fuller Test ✓

ADF test is conducted with the following assumptions.

Null Hypothesis (H₀): Series is non-stationary or series has a unit root.

Alternate Hypothesis(H_A): Series is stationary or series has no unit root.

If the null hypothesis is failed to be rejected, this test may provide evidence that the series is non-stationary.

Conditions to Reject Null Hypothesis(H₀)

If Test statistic < Critical Value and p-value < 0.05 – Reject Null Hypothesis(H₀) i.e., time series does not have a unit root, meaning it is stationary. It does not have a time-dependent structure.


~~Hypothesis~~
Null: There is
Alt: There is


```

from statsmodels.tsa.stattools import adfuller
def adf_test(timeseries):
    print ('Results of Dickey-Fuller Test:')
    dfctest = adfuller(timeseries, autolag='AIC')
    dfcoutput = pd.Series(dfctest[0:4], index=['Test Statistic','p-value','#Lags Used','Number of Observations Used'])
    for key,value in dfctest[4].items():
        dfcoutput['Critical Value (%s)'%key] = value
    print (dfcoutput)
    ans=dfcoutput
    if(ans['Test Statistic']<ans["Critical Value (1%)"] or ans['Test Statistic']<ans["Critical Value (5%)"] or ans['Test Statistic']<ans["Critical Value (10%)"]):
        print("Condition: statistic < any critical value and p-value <0.05 to reject null hypothesis")
        print("Reject null hypothesis:Non Stationarity")
        print("Accept Alternate hypothesis:Stationarity ")
    else:
        print("Condition: statistic < any critical value and p-value <0.05 to reject null hypothesis")
        print("Accept null hypothesis:Non Stationarity" )
        print("Reject Alternate hypothesis:Stationarity ")
    return dfcoutput

```

Non-Stationary → *Model X*



```

Results of Dickey-Fuller Test:
Test Statistic      -3.394032
p-value             0.011164
#Lags Used          27.000000
Number of Observations Used 2468.000000
Critical Value (1%) -3.433002
Critical Value (5%) -2.862712
Critical Value (10%) -2.567394
dtype: float64
Condition: statistic < any critical value and p-value <0.05 to reject null hypothesis
Reject null hypothesis:Non Stationarity
Accept Alternate hypothesis:Stationarity

```

Non stationary to stationary

- Difference
- Log

Time Series Analysis

Lag

Date	Value	Value _{t-1}	Value _{t-2}
1/1/2017	200	NA	NA
1/2/2017	220	200	NA
1/3/2017	215	220	200
1/4/2017	230	215	220
1/5/2017	235	230	215
1/6/2017	225	235	230
1/7/2017	220	225	235
1/8/2017	225	220	225
1/9/2017	240	225	220
1/10/2017	245	240	225


Time Series Analysis

What is White Noise?

White Noise

- No pattern (does not use for forecasting)

Completely random with



Time Series Forecasting methods

- Autoregression (AR)
- Moving Average (MA)
- Autoregressive Moving Average (ARMA)
- Autoregressive Integrated Moving Average (ARIMA)
- Seasonal Autoregressive Integrated Moving-Average (SARIMA)
- Seasonal Autoregressive Integrated Moving-Average with Exogenous Regressors (SARIMAX)
- Vector Autoregression (VAR)
- Vector Autoregression Moving-Average (VARMA)
- Vector Autoregression Moving-Average with Exogenous Regressors (VARMAX)
- Simple Exponential Smoothing (SES)


Auto Regression (AR)

lag

The term *Auto Regression* indicates that it is a regression of the variable against itself.

Autoregressive Model: AR(p)

- The autoregressive model uses observations from previous time steps as input to a regression equations to predict the value at the next step.
- The order, p , of the autoregressive model can be determined by looking at the **partial autocorrelation function (PACF)**. The PACF gives the partial correlation of a stationary time series with its own lagged values, regressed of the time series at all shorter lags.





```
from sklearn.preprocessing import MinMaxScaler
Ms = MinMaxScaler()
data1= Ms.fit_transform(stk_data[[column]])
print("Len:",data1.shape)
```

Times
↓
univariate
colse

Len: (145, 1)

```
training_size = round(len(data1 ) * 0.80)
print(training_size)
X_train=data1[:training_size]
X_test=data1[training_size:]
print("X_train length:",X_train.shape)
print("X_test length:",X_test.shape)
y_train=data1[:training_size]
y_test=data1[training_size:]
print("y_train length:",y_train.shape)
print("y_test length:",y_test.shape)
```



✓ Lag=1, Trend=n ✓

RMSE-Testset: 0.2868932436955159 ✓

maPe-Testset: 0.43360580238884344 ✓

***** ✓

Lag=1, Trend=t

RMSE-Testset: 0.16951470088008333

maPe-Testset: 0.2820005995613298

Time series → ↓ ✓

Moving Average(MA) →

IG

● EUR/USD



```
] : import warnings
warnings.filterwarnings("ignore")
```

```
] : from sklearn.metrics import mean_squared_error
trends=['n','t','c','ct']
orders=[(0,0,1),(0,0,2)]
from statsmodels.tsa.arima.model import ARIMA
for td in trends:

    #print(td)
    #trendslst.append(td)
    model = ARIMA(X_train, order=(0,0,10),trend=td,)
    model_fit = model.fit()
    # make prediction
    y_pred= model_fit.predict(len(X_train), len(data1)-1)
    #print(y_pred)
    from sklearn.metrics import r2_score
    mse=mean_squared_error(y_test,y_pred,squared=False)
    from stockFunctions import rmseape
    print("Trend={}".format(td))
    rmseape(y_test,y_pred)
    print("*****")
```

MA
ARMA
ARIMA

Autoregressive Integrated Moving Average (ARIMA)


Log

difference
↓

MA

Non Stationarity
↓

$$\text{AR} + \text{I} + \text{MA} = \text{ARIMA}$$



$$\text{AR} + \text{I} + \text{MA}$$

AR(Autoregression) - Uses the past values to predict the future.

I(Integrated) - The use of differencing of raw observations in order to make the time series stationary.

MA(Moving Average) - Uses the past error terms in the given series to predict the future


```
from sklearn.metrics import mean_squared_error
trends=['n','t','c','ct']
orders=[(0,0,1),(0,0,2)]
from statsmodels.tsa.arima.model import ARIMA
for td in trends:

    #print(td)
    #trendslst.append(td)
    model = ARIMA(X_train, order=(0,0,10), trend=td,)
    model_fit = model.fit()
    # make prediction
    y_pred= model_fit.predict(len(X_train), len(data1)-1)
    #print(y_pred)

from sklearn.metrics import r2_score
mse=mean_squared_error(y_test,y_pred,squared=False)
from stockFunctions import rmsemape
print("Trend={}".format(td))
rmsemape(y_test,y_pred)
print("*****")
```

MA

```
: from sklearn.metrics import mean_squared_error
trends=['n','t','c','ct']
orders=[(0,0,1),(0,0,2)]
from statsmodels.tsa.arima.model import ARIMA
for td in trends:

    #print(td)
    #trendslst.append(td)
    model = ARIMA(X_train, order=(0,0,10),trend=td,)
    model_fit = model.fit()
    # make prediction
    y_pred= model_fit.predict(len(X_train), len(data1)-1)
    #print(y_pred)

    from sklearn.metrics import r2_score
    mse=mean_squared_error(y_test,y_pred,squared=False)
    from stockFunctions import rmseape
    print("Trend={}".format(td))
    rmseape(y_test,y_pred)
    print("*****")
```

Time Series Analysis

ARIMA(p,d,q)



p



Lag order

**No of lag
observations**

d



**Degree of
differencing**

**No of times that the
raw observations
are differenced.**

q



**Order of moving
average**

**The size of the
moving average
window**

Seasonal Autoregressive Integrated Moving-Average (SARIMA)

Seasonal ARIMA is an extension of ARIMA that explicitly supports univariate time series data with a seasonal component.

$SARIMA(p,d,q)(P,D,Q)m$

P: Seasonal autoregressive order.

D: Seasonal difference order.

Q: Seasonal moving average order.

m: The number of time steps for a single seasonal period.

Seasonal Autoregressive Integrated Moving-Average with Exogenous Regressors (SARIMAX)

SARIMAX is an updated version of the ARIMA model. It includes seasonal effects and exogenous factors with the autoregressive and moving average component in the model.

X – Exogenous
variable(external
factor)

Eg: In farming, production forecast is based on factors like area of land, quality of seed etc. but in this rainfall is an exogenous variable whose value will be determined by other factors like humidity, air speed etc.

Multi Variate Vector Auto-Regression (VAR)


- ❑ Vector Autoregression (**VAR**) is a **multivariate** forecasting algorithm that is used when two or more time series influence each other.
- ❑ In the VAR model, each variable is modeled as a **linear combination of past values of itself and the past values of other variables in the system.**



VAR different from other Autoregressive models like AR, ARMA or ARIMA?

The primary difference is those models are **uni-directional**. Whereas, Vector Auto Regression (VAR) is **bi-directional**. That is, the variables influence each other.

Vector Auto Regression Moving-Average (VARMA)



VARMA model where both lag order and order of moving average (p and q) is used in the modelling and also we can convert the VARMA model in VAR by setting the moving average as zero and in VMA by setting the lag order as zero in the modelling.

NOTE: It is used for multivariate time series forecasting.