

<!DOCTYPE html>

ETSI GS QKD 004 push mode specification, KMS server

etsi004

postendpoint to push key material to.

API docs by Redocly

ETSI GS QKD 004 push mode specification, KMS server (1.0.0)

Download OpenAPI specification:Download

URL: <https://qkd-kms.ait.ac.at>

Server description of the KMS endpoint processing ETSI GS QKD 004 push mode requests

etsi004

endpoint to push key material to.

According to the sequence, after a successful `get_key`, the QKD can push the corresponding key material to this endpoint, whenever it created a new key.

Request Body schema: `application/json`

status

required

integer or 1 (integer) or 2 (integer) or 3 (integer) or 4 (integer) or 5 (integer) or 6 (integer) or 7 (integer) or 8 (integer) (status)

index

required

integer <uint32>

increasing index of the key chunk in the key stream. Wrapping at `UINT_MAX`.

key_buffer

required

string <base64>

metadata

object

Responses

201

Key successfully received

post/key-material

https://qkd_server/api/v1/qkd/etsi004/key-material

Request samples

Payload

Content type

`application/json`

Copy

Expand all

Collapse all

{

“status”: 0,

```
“index”: 0,  
“key_buffer”: ”string”,  
“metadata”: {  
“size”: 57,  
“buffer”: {  
“key_stream_id”: ”4eb81a5c-031f-4d1f-881d-309bee44fc20”  
}  
}  
}
```

Response samples

201

Content type

application/json

Copy

Expand all

Collapse all

```
{  
“status”: 0,  
“metadata”: {  
“size”: 0,  
“buffer”: ””  
}  
}
```