

API Reference

ETSI GS QKD 004 push mode specification, QKD server

API Version: 1.0.1

Server description of the QKD endpoint for processing ETSI GS QKD 004 push mode requests

CONTACT

URL: <https://qkd-kms.ait.ac.at>

INDEX

1. ETSI004	3
1.1 POST /open-connect	3
1.2 GET /get-key	5
1.3 PUT /close	7

API

1. ETSI004

1.1 POST /open-connect

open key stream

The open-connect message connects a KMS to the QKD Device. As per sequence definition, the QKD device will assign the key_stream_id at the source node, therefore null has to be given as key_stream_id parameter. The QKD can suggest alternative QoS due to its capabilities. At the destination, the key_stream_id has to be specified to the same given at the source.

REQUEST

REQUEST BODY - application/json

NAME	TYPE	DESCRIPTION
source*	string	the source URI of the request.
destination*	string	the destination URI of the request.
key_stream_id	string	key stream ID. If `null` specified it is up to the QKD device to define the UUID
qos*	object	
key_chunk_size	integer	length of key chunks in Byte.
max_bps	integer	in bit per second
min_bps	integer	in bit per second
jitter	integer	in bit per second
priority	integer	Meaning up to implementation.
timeout	integer	Timeout in msec after which the call will be aborted, returning an error.
ttl	integer	Time in seconds after which the keys for this key stream ID shall be erased from the kms key store.
metadata_mimetype	string	MIME type of the metadata of the `get` request

RESPONSE

STATUS CODE - 201: Key stream successfully created

RESPONSE MODEL - application/json

NAME	TYPE	DESCRIPTION
OBJECT WITH BELOW STRUCTURE		
key_stream_id	string	key stream ID. If not specified it is up to the QKD device to define the UUID
qos*	object	
key_chunk_size	integer	length of key chunks in Byte.
max_bps	integer	in bit per second
min_bps	integer	in bit per second
jitter	integer	in bit per second
priority	integer	Meaning up to implementation.
timeout	integer	Timeout in msec after which the call will be aborted, returning an error.

NAME	TYPE	DESCRIPTION
ttl	integer	Time in seconds after which the keys for this key stream ID shall be erased from the kms key store.
metadata_mimetype	string	MIME type of the metadata of the `get` request
status	enum	ALLOWED: 0, 1, 2, 3, 4, 5, 6, 7, 8 Status code: 0 = Successful; HTTP code 200 1 = Successful connection, but peer not connected; HTTP code 200 2 = GET_KEY failed because insufficient key available; HTTP code 500 3 = GET_KEY failed because peer application is not yet connected; HTTP code 400 4 = No QKD connection available; HTTP code 500 5 = OPEN_CONNECT failed because the KSID is already in use; HTTP code 400 6 = TIMEOUT_ERROR: The call failed because the specified TIMEOUT; HTTP code 500 7 = OPEN failed because requested QoS settings could not be met, counter proposal included in return has occurred; HTTP code 500 8 = GET_KEY failed because metadata field size insufficient. Returned Metadata_size value holds minimum needed size of metadata; HTTP code 400

STATUS CODE - 400: Client sent a malformed input

RESPONSE MODEL - application/json

NAME	TYPE	DESCRIPTION
OBJECT WITH BELOW STRUCTURE		
status*	enum	ALLOWED: 0, 1, 2, 3, 4, 5, 6, 7, 8 Status code: 0 = Successful; HTTP code 200 1 = Successful connection, but peer not connected; HTTP code 200 2 = GET_KEY failed because insufficient key available; HTTP code 500 3 = GET_KEY failed because peer application is not yet connected; HTTP code 400 4 = No QKD connection available; HTTP code 500 5 = OPEN_CONNECT failed because the KSID is already in use; HTTP code 400 6 = TIMEOUT_ERROR: The call failed because the specified TIMEOUT; HTTP code 500 7 = OPEN failed because requested QoS settings could not be met, counter proposal included in return has occurred; HTTP code 500 8 = GET_KEY failed because metadata field size insufficient. Returned Metadata_size value holds minimum needed size of metadata; HTTP code 400

STATUS CODE - 500: The server experienced an internal error

RESPONSE MODEL - application/json

NAME	TYPE	DESCRIPTION
OBJECT WITH BELOW STRUCTURE		

NAME	TYPE	DESCRIPTION
status*	enum	ALLOWED:0, 1, 2, 3, 4, 5, 6, 7, 8 Status code: 0 = Successful; HTTP code 200 1 = Successful connection, but peer not connected; HTTP code 200 2 = GET_KEY failed because insufficient key available; HTTP code 500 3 = GET_KEY failed because peer application is not yet connected; HTTP code 400 4 = No QKD connection available; HTTP code 500 5 = OPEN_CONNECT failed because the KSID is already in use; HTTP code 400 6 = TIMEOUT_ERROR: The call failed because the specified TIMEOUT; HTTP code 500 7 = OPEN failed because requested QoS settings could not be met, counter proposal included in return has occurred; HTTP code 500 8 = GET_KEY failed because metadata field size insufficient. Returned Metadata_size value holds minimum needed size of metadata; HTTP code 400

1.2 GET /get-key

Start the pushed key retrieval process

The get-key message informs the QKD device that it can start pushing keys.

REQUEST

REQUEST BODY - application/json

NAME	TYPE	DESCRIPTION
key_stream_id*	string	corresponding to the one given in `open_connect`
index	integer	increasing index of the key chunk in the key stream. Wrapping at UINT_MAX.
metadata	object	
size	integer	size of buffer in characters
buffer	string	metadata in json format.

RESPONSE

STATUS CODE - 205: Successful registration

RESPONSE MODEL - application/json

NAME	TYPE	DESCRIPTION
OBJECT WITH BELOW STRUCTURE		

NAME	TYPE	DESCRIPTION
status*	enum	ALLOWED: 0, 1, 2, 3, 4, 5, 6, 7, 8 Status code: 0 = Successful; HTTP code 200 1 = Successful connection, but peer not connected; HTTP code 200 2 = GET_KEY failed because insufficient key available; HTTP code 500 3 = GET_KEY failed because peer application is not yet connected; HTTP code 400 4 = No QKD connection available; HTTP code 500 5 = OPEN_CONNECT failed because the KSID is already in use; HTTP code 400 6 = TIMEOUT_ERROR: The call failed because the specified TIMEOUT; HTTP code 500 7 = OPEN failed because requested QoS settings could not be met, counter proposal included in return has occurred; HTTP code 500 8 = GET_KEY failed because metadata field size insufficient. Returned Metadata_size value holds minimum needed size of metadata; HTTP code 400
metadata	object	
size	integer	size of buffer in characters
buffer	string	metadata in json format.

STATUS CODE - 400: Client sent a malformed input

RESPONSE MODEL - application/json

NAME	TYPE	DESCRIPTION
OBJECT WITH BELOW STRUCTURE		
status*	enum	ALLOWED: 0, 1, 2, 3, 4, 5, 6, 7, 8 Status code: 0 = Successful; HTTP code 200 1 = Successful connection, but peer not connected; HTTP code 200 2 = GET_KEY failed because insufficient key available; HTTP code 500 3 = GET_KEY failed because peer application is not yet connected; HTTP code 400 4 = No QKD connection available; HTTP code 500 5 = OPEN_CONNECT failed because the KSID is already in use; HTTP code 400 6 = TIMEOUT_ERROR: The call failed because the specified TIMEOUT; HTTP code 500 7 = OPEN failed because requested QoS settings could not be met, counter proposal included in return has occurred; HTTP code 500 8 = GET_KEY failed because metadata field size insufficient. Returned Metadata_size value holds minimum needed size of metadata; HTTP code 400
metadata	object	
size	integer	size of buffer in characters
buffer	string	metadata in json format.

STATUS CODE - 500: The server experienced an internal error

RESPONSE MODEL - application/json

NAME	TYPE	DESCRIPTION
OBJECT WITH BELOW STRUCTURE		

NAME	TYPE	DESCRIPTION
status*	enum	ALLOWED: 0, 1, 2, 3, 4, 5, 6, 7, 8 Status code: 0 = Successful; HTTP code 200 1 = Successful connection, but peer not connected; HTTP code 200 2 = GET_KEY failed because insufficient key available; HTTP code 500 3 = GET_KEY failed because peer application is not yet connected; HTTP code 400 4 = No QKD connection available; HTTP code 500 5 = OPEN_CONNECT failed because the KSID is already in use; HTTP code 400 6 = TIMEOUT_ERROR: The call failed because the specified TIMEOUT; HTTP code 500 7 = OPEN failed because requested QoS settings could not be met, counter proposal included in return has occurred; HTTP code 500 8 = GET_KEY failed because metadata field size insufficient. Returned Metadata_size value holds minimum needed size of metadata; HTTP code 400
metadata	object	
size	integer	size of buffer in characters
buffer	string	metadata in json format.

1.3 PUT /close

close the key stream

The close message disconnects the KMS from the QKD device.

REQUEST

REQUEST BODY - application/json

NAME	TYPE	DESCRIPTION
key_stream_id*	string	corresponding to the one given in `open_connect`

RESPONSE

STATUS CODE - 204: Key stream successfully closed

RESPONSE MODEL - application/json

NAME	TYPE	DESCRIPTION
OBJECT WITH BELOW STRUCTURE		

NAME	TYPE	DESCRIPTION
status*	enum	ALLOWED:0, 1, 2, 3, 4, 5, 6, 7, 8 Status code: 0 = Successful; HTTP code 200 1 = Successful connection, but peer not connected; HTTP code 200 2 = GET_KEY failed because insufficient key available; HTTP code 500 3 = GET_KEY failed because peer application is not yet connected; HTTP code 400 4 = No QKD connection available; HTTP code 500 5 = OPEN_CONNECT failed because the KSID is already in use; HTTP code 400 6 = TIMEOUT_ERROR: The call failed because the specified TIMEOUT; HTTP code 500 7 = OPEN failed because requested QoS settings could not be met, counter proposal included in return has occurred; HTTP code 500 8 = GET_KEY failed because metadata field size insufficient. Returned Metadata_size value holds minimum needed size of metadata; HTTP code 400

STATUS CODE - 400: Client sent a malformed input

RESPONSE MODEL - application/json

NAME	TYPE	DESCRIPTION
OBJECT WITH BELOW STRUCTURE		
status*	enum	ALLOWED:0, 1, 2, 3, 4, 5, 6, 7, 8 Status code: 0 = Successful; HTTP code 200 1 = Successful connection, but peer not connected; HTTP code 200 2 = GET_KEY failed because insufficient key available; HTTP code 500 3 = GET_KEY failed because peer application is not yet connected; HTTP code 400 4 = No QKD connection available; HTTP code 500 5 = OPEN_CONNECT failed because the KSID is already in use; HTTP code 400 6 = TIMEOUT_ERROR: The call failed because the specified TIMEOUT; HTTP code 500 7 = OPEN failed because requested QoS settings could not be met, counter proposal included in return has occurred; HTTP code 500 8 = GET_KEY failed because metadata field size insufficient. Returned Metadata_size value holds minimum needed size of metadata; HTTP code 400

STATUS CODE - 500: The server experienced an internal error

RESPONSE MODEL - application/json

NAME	TYPE	DESCRIPTION
OBJECT WITH BELOW STRUCTURE		

NAME	TYPE	DESCRIPTION
status*	enum	ALLOWED:0, 1, 2, 3, 4, 5, 6, 7, 8 Status code: 0 = Successful; HTTP code 200 1 = Successful connection, but peer not connected; HTTP code 200 2 = GET_KEY failed because insufficient key available; HTTP code 500 3 = GET_KEY failed because peer application is not yet connected; HTTP code 400 4 = No QKD connection available; HTTP code 500 5 = OPEN_CONNECT failed because the KSID is already in use; HTTP code 400 6 = TIMEOUT_ERROR: The call failed because the specified TIMEOUT; HTTP code 500 7 = OPEN failed because requested QoS settings could not be met, counter proposal included in return has occurred; HTTP code 500 8 = GET_KEY failed because metadata field size insufficient. Returned Metadata_size value holds minimum needed size of metadata; HTTP code 400