

Documentation for ETSI GS QKD 004 push mode specification, KMS server

Documentation for API Endpoints

All URIs are relative to *https://qkd_server/api/v1/qkd/etsi004*

Class	Method	HTTP request	Description
<i>Etsi004Api</i>	postKeyMaterial	POST /key-material	endpoint to push key material to.

Documentation for Models

- `post_key_material_201_response`
- `post_key_material_201_response_metadata`
- `post_key_material_request`
- `post_key_material_request_metadata`
- `post_key_material_request_metadata_buffer`

Documentation for Authorization

All endpoints do not require authorization. # Etsi004Api

All URIs are relative to *https://qkd_server/api/v1/qkd/etsi004*

Method	HTTP request	Description
postKeyMaterial	POST /key-material	endpoint to push key material to.

postKeyMaterial > `post_key_material_201_response postKeyMaterial(post_key_material_request)`
endpoint to push key material to.

According to the sequence, after a successful ``get_key`;`, the QKD can push the corresponding k

Parameters

Name	Type	Description	Notes
post_key_material_request	post_key_material_request		

Return type

`post_key_material_201_response`

Authorization

No authorization required

HTTP request headers

- **Content-Type:** application/json
- **Accept:** application/json

post_key_material_201_response

Properties

Name	Type	Description	Notes
status	Integer		[default to null]
metadata	post_key_material_201_response_metadata		[optional] [default to null]

Name	Type	Description	Notes
------	------	-------------	-------

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

post__key__material__201__response__metadata

Properties

Name	Type	Description	Notes
size	Integer	size of buffer in characters	[optional] [default to null]
buffer	String	metadata in json format.	[optional] [default to null]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

post__key__material__request

Properties

Name	Type	Description	Notes
status	Integer		[default to null]
index	Integer	increasing index of the key chunk in the key stream. Wrapping at UINT_MAX.	[default to null]
key__buffer	String		[default to null]
metadata	post__key__material__request__metadata		[optional] [default to null]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

post__key__material__request__metadata

Properties

Name	Type	Description	Notes
size	Integer	size of buffer in characters	[optional] [default to null]
buffer	post__key__material__request__metadata__buffer		[optional] [default to null]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

post__key__material__request__metadata__buffer

Properties

Name	Type	Description	Notes
key__stream__id	UUID	key stream ID to which the value belongs (required for KMS in case of multiple open key streams)	[default to null]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)