

Browser Automation with AttackMate

AttackMate includes a **browser** command type backed by [Playwright](#), a browser automation library. It lets you drive a real Chromium browser from a playbook, navigating pages, clicking elements, filling forms, and taking screenshots.

The **browser** Command

```
- type: browser
  cmd: <action>
  # action-specific fields follow
```

Actions

cmd value	What it does	Required fields
visit	Navigate to a URL	url
click	Click a DOM element	selector
type	Type text into a field	selector, text
screenshot	Save a PNG screenshot	screenshot_path

Selectors

selector uses standard CSS selector syntax, the same syntax used in browser DevTools:

```
selector: "input[name='username']" # by attribute
selector: "button[type='submit']"  # submit button
selector: "#login-btn"             # by ID
selector: ".btn-primary"           # by class
```

Sessions

By default each **browser** command opens a fresh browser context (no cookies, no state) and destroys it when done. To keep state across multiple commands, for example to log in and then navigate to a protected page, use named sessions.

```
# Open a browser, visit the login page, keep the session open
- type: browser
  cmd: visit
  url: http://192.168.1.100/login
  creates_session: my_browser
```

```
# Still in the same browser window: fill username
- type: browser
  cmd: type
  selector: "input[name='username']"
  text: "admin"
  session: my_browser

# Fill password
- type: browser
  cmd: type
  selector: "input[name='password']"
  text: "password123"
  session: my_browser

# Click submit
- type: browser
  cmd: click
  selector: "button[type='submit']"
  session: my_browser

# Screenshot the result
- type: browser
  cmd: screenshot
  screenshot_path: /tmp/after_login.png
  session: my_browser
```

If a session named in `creates_session` already exists, it is automatically closed and replaced.

Headless Mode

By default the browser window is visible (`headless: false`). On servers or CI without a display, set `headless: true`:

```
- type: browser
  cmd: visit
  url: http://10.0.0.1
  headless: true
  creates_session: ci_session
```

Background Mode

Background mode (`background: true`) is **not supported** for browser commands.

Key Fields Reference

Field	Type	Default	Description
<code>cmd</code>	str	<code>visit</code>	Action to perform
<code>url</code>	str		Target URL (required for <code>visit</code>)

Field	Type	Default	Description
selector	str		CSS selector (required for <code>click/type</code>)
text	str		Text to enter (required for <code>type</code>)
screenshot_path	str		Output path (required for <code>screenshot</code>)
creates_session	str		Name for a new persistent browser session
session	str		Name of an existing session to reuse
headless	bool	false	Run without visible window