

# DATABASE SYSTEMS COURSE 2021/2022

SESSION 6



# SESSION 6

- •NULL TREATMENT
- •OR OPERATOR
- DATA INSERTION FROM QUERIES



# ONE NULL value checking Syntax

```
MySQL
```

SELECT IFNULL (Value1, Value2)

FROM table

#### Oracle

**SELECT NVL (**Value1, Value2)

**FROM** table



# ONE NULL value checking Example

#### **MySQL**

```
SELECT datecrash, location, summary,
IFNULL(summary, location)
FROM crash
WHERE location = 'Newark, New Jersey';
```

	datecrash	location	summary	ifnull(summary; location)
٠	3/30/1920	Newark, New Jersey	{null}	Newark, New Jersey
	4/10/1920	Newark, New Jersey	{null}	Newark, New Jersey
3/17/1929 Newark, New J		Newark, New Jersey	ey The plane The plane was making th	The plane was making the last of a number of sightse
	1/14/1933	Newark, New Jersey	Went into a	Went into a vertical bank and crashed and burned.
	4/18/1979	Newark, New Jersey	Tail rotor s	Tail rotor separated in flight shortly after takeoff. The
	3/30/1983	Newark, New Jersey	While atte	While attempting to land, the cargo plane came in too

#### Oracle

```
SELECT datecrash, location, summary,
NVL(summary, location)
FROM crash
WHERE location = 'Newark, New Jersey';
```

				♦ NVL(SUMMARY,LOCATION)
1	3/17/1929	Newark, New Jerse	y The plane was	The plane was making t
2	3/30/1920	Newark, New Jerse	y (null)	Newark, New Jersey
3	4/10/1920	Newark, New Jerse	y (null)	Newark, New Jersey
4	1/14/1933	Newark, New Jerse	y Went into a ve	Went into a vertical b
5	3/30/1983	Newark, New Jersey	y While attempti	While attempting to la
6	4/18/1979	Newark, New Jersey	y Tail rotor sep	Tail rotor separated i



# SEVERAL NULL values checking Syntax

#### MySQL/Oracle ——

SELECT COALESCE (Field1, Field2, Field3)

FROM table

WHERE Field1 = Value1

NOTE: COALESCE looks for the first NOT NULL argument.



# SEVERAL NULL values checking example

#### MySQL/ Oracle

```
SELECT summary, location, operator,
COALESCE(summary, location, operator)
FROM crash WHERE type = 'Junkers JU-53/3m';
```

SUMMARY		<b>♦ LOCATION</b>	♦ OPERATOR			
1	1 (null) (null		Deutsche Lufthansa	Deutsche Lufthansa		
2	Missing	(null)	(null)	Missing on an evacuation flight fro		



# SEVERAL NULL values checking Example

#### MySQL/ Oracle -

```
SELECT summary, location, operator,
COALESCE(summary, location, 'No detail')
FROM crash WHERE type = 'Junkers JU-53/3m'
```

		<b>♦ LOCATION</b>	♦ OPERATOR	♦ COALESCE(SUMMARY,LOCATION,'NODETAIL')		
1	(null)	(null)	Deutsche Lufthansa	No detail		
2	Missing on an	(null)	(null)	Missing on an evacuation flight fr		



# IS NULL/IS NOT NULL Syntax

#### MySQL/Oracle —

• SELECT Field1, Field2, Field3
FROM table
WHERE Field1 IS NULL

• SELECT Field1, Field2, Field3
FROM table
WHERE Field1 IS NOT NULL



# IS NULL/IS NOT NULL Example

#### MySQL/Oracle \_\_\_\_\_

SELECT datecrash, time, location
 FROM crash
 WHERE time IS NOT NULL;

datecrash	time	location
17/09/1908 0:00:00	17:18	Fort Myer, Virginia
12/07/1912 0:00:00	6:30	AtlantiCity, New Jersey
09/09/1913 0:00:00	18:30	Over the North Sea
17/10/1913 0:00:00	10:30	Near Johannisthal, Germany
05/03/1915 0:00:00	1:00	Tienen, Belgium
03/09/1915 0:00:00	15:20	Off Cuxhaven, Germany
24/09/1916 0:00:00	1:00	Billericay, England

#### MySQL/Oracle

SELECT datecrash, type, locationFROM crashWHERE type IS NULL;

datecrash	type	location
06/04/1921 0:00:00	{null}	Point Cook, Australia
17/05/1921 0:00:00	{null}	Rock Springs, Wyoming
08/04/1922 0:00:00	{null}	Pao Ting Fou, China
06/11/1924 0:00:00	{null}	Cabrerolles, France
07/09/1925 0:00:00	{null}	Toul, France
15/04/1927 0:00:00	{null}	King Hill, Idaho



# SESSION 6

- NULL TREATMENT
- •OR OPERATOR
- DATA INSERTION FROM QUERIES

### OR OPERATOR



# OR Syntax

# MySQL/Oracle -

## OR OPERATOR



# OR Example

#### MySQL/Oracle -

SELECT title , popularity, vote\_average
FROM movie

WHERE popularity > 50 OR vote average > 7

∯ TITLE	POPULARITY	♦ VOTE_AVERAGE
1 The Big Lebowski	49,230089	7,8
2 Match Point	30,669913	7,3
3 The Untouchables	38,272889	7,6
4 Charlie and the Chocolate Factory	53,905592	6,7
5 The Lord of the Rings: The Fellowship of the Ring	138,049577	8
6 The Lord of the Rings: The Two Towers	106,914973	8
7 The Lord of the Rings: The Return of the King	123,630332	8,1



# SESSION 6

- •NULL TREATMENT
- •OR OPERATOR
- •DATA INSERTION FROM QUERIES



## CREATE TABLE AS SELECT Syntax

```
MySQL/Oracle _____
```

CREATE TABLE NewTable AS

SELECT Field1, Field2, Field3, ..., FieldN

FROM table

WHERE Field1 = Value1 AND

• • • •



# CREATE TABLE AS SELECT Example

#### MySQL/Oracle

```
CREATE TABLE expensive_movies AS
SELECT movie_id, title, budget, revenue
FROM movie WHERE budget > 1000000000;
```

SI	ELECT * FROM expensive_movies;		
Salida o	de Script X Resultado de la Consulta X Resultado de la Consulta 1 X		
4	SQL   Todas las Filas Recuperadas: 279 en 0,043 segundos		
1	MOVIE_ID # TITLE	⊕ BUDGET	REVENUE
277	150540 Inside Out	175000000	857611174
278	188927 Star Trek Beyond	185000000	343471816
279	117251 White House Down	150000000	205366737



# INSERT INTO SELECT Syntax

```
- MySQL/Oracle

INSERT INTO ExistentTable

SELECT Field1, Field2, ..., FieldN FROM table

WHERE Field1 = Value1 AND
```



# INSERT INTO SELECT Example

#### MySQL/Oracle

```
INSERT INTO expensive_movies
SELECT movie_id, title, budget, revenue
FROM movie WHERE budget BETWEEN 50000000 AND 100000000;
```

