

Prover9 Unleashed: Automated Configuration for Enhanced Proof Discovery

Kristina Aleksandrova² Jan Jakubův^{1,2} Cezary Kaliszyk²

AITP'24, Aussois, France, 3rd September 2024

¹Czech Technical University in Prague, Prague, Czech Republic

²University of Innsbruck, Innsbruck, Austria

Automated Theorem Proving and Prover9

Grackle Strategy Invention

Experiments on AIM Problems

Experiments on TPTP Problems

Automated Theorem Proving and Prover9

Grackle Strategy Invention

Experiments on AIM Problems

Experiments on TPTP Problems

Prover9: Legendary Theorem Prover

- Prover9 is an **automated theorem prover** for first-order logic
- ...based on resolution and paramodulation.

Prover9: Legendary Theorem Prover

- Prover9 is an **automated theorem prover** for first-order logic
- ...based on resolution and paramodulation.
- Not developed since 2009 but ...
- ...still actively and successfully used by its users.
- ...still used in the CASC competition (as a reference).

Our Goal

- Prover9 contains a rich language for strategy configuration.
- As opposed to the state-of-the-art theorem provers,
... does not have an automated strategy selection mechanism.

Our Goal

- Prover9 contains a **rich language for strategy configuration**.
- As opposed to the state-of-the-art theorem provers,
... does not have an automated strategy selection mechanism.
- Goal: Use Grackle automated strategy invention on Prover9.

Our Goal

- Prover9 contains a **rich language for strategy configuration**.
- As opposed to the state-of-the-art theorem provers,
... does not have an automated strategy selection mechanism.
- Goal: Use Grackle automated strategy invention on Prover9.
- Question: Can Prover9 still compete with state-of-the-art?

Prover9: Proof Search Strategy Configuration

- Supports more than 100 basic options
... (booleans, numerical, categorical).

```
set(binary_resolution).  
set(expand_relational_defs).  
clear(back_subsume).  
assign(order, kbo).  
assign(not_weight, -2).  
assign(or_weight, 200).  
assign(prop_atom_weight, 9999).
```

Prover9: Given Clause Selection Configuration

- Prover9 processes one **given** clause a time.
- Allows to define which clauses should be preferred,
... using priority queues where clauses are sorted (age/weight)

```
list(given_selection).  
  part(queue1, high, age    , weight < 500 & -horn  ) = 50.  
  part(queue2, high, weight, depth < 15              ) = 50.  
  part(queue3, low , weight, -false                  ) = 5.  
  part(rest   , low , random, all                     ) = 1.  
end_of_list.
```

Prover9: Action Rules

- **action** rules: Change options values on the fly, ...when certain event occur.

```
list(actions).  
  generated=5000  -> assign(pick_given_ratio, 4).  
end_of_list.
```

Prover9: Keep/Delete Rules

- **keep/delete** rules: Delete generated clauses (incomplete), ...satisfying a delete condition unless kept is satisfied.

```
list(delete).  
    weight > 20 & variables > 4.  
    weight > 30.  
end_of_list.
```

```
list(keep).  
    horn & variables<3.  
end_of_list.
```

Automated Theorem Proving and Prover9

Grackle Strategy Invention

Experiments on AIM Problems

Experiments on TPTP Problems

Grackle: Algorithm Motivation

- **Grackles** are passerine birds native to North and South America.



Grackle: Algorithm Motivation

- **Grackles** are passerine birds native to North and South America.
- During evolution, different grackle species developed different bill sizes to be able to feed on different types of nutrients.



Grackle: Algorithm Motivation

- **Grackles** are passerine birds native to North and South America.
- During evolution, different grackle species developed different bill sizes to be able to feed on different types of nutrients.
- This decreases competition between different species and increases the chances of their survival.



Grackle: Algorithm Overview

- Successor/generalization of BliStr/Tune tools.
 - **Grackle** utilizes existing algorithm configuration frameworks
 - ParamILS: Iterative Local Search (Hutter et al.)
 - SMAC3: Bayesian Optimization (Lindauer et al.)
- to improve a strategy on a given set of problems.

Grackle: Algorithm Overview

- Successor/generalization of BliStr/Tune tools.
- **Grackle** utilizes existing algorithm configuration frameworks
 - ParamILS: Iterative Local Search (Hutter et al.)
 - SMAC3: Bayesian Optimization (Lindauer et al.)to improve a strategy on a given set of problems.
- Grackle input:
 - initial set of strategies
 - input problems
 - **strategy space parametrization**: parameters and their values
 - solver wrapper

Grackle: Algorithm Overview

- Successor/generalization of BliStr/Tune tools.
- **Grackle** utilizes existing algorithm configuration frameworks
 - ParamILS: Iterative Local Search (Hutter et al.)
 - SMAC3: Bayesian Optimization (Lindauer et al.)

to improve a strategy on a given set of problems.

- Grackle input:
 - initial set of strategies
 - input problems
 - **strategy space parametrization**: parameters and their values
 - solver wrapper
- Grackle output:
 - portfolio of strategies complementary on input problems

Grackle: Invent Portfolio of Strategies

Repeat the following:

1. Evaluate all strategies on all problems P
2. Select one strategy S to be improved
3. Specialize strategy S for the problems where it performs best
4. Go to 1

Terminate when:

- all strategies has been improved, or ...
- time limit is reached.

Grackle: Encoding advanced Prover9 features

To describe a given clause selection queue:

```
part(queue1, high, age , weight < 500 & -horn ) = 50.
```

we introduce a set of parameters

while fixing the maximal count of parts in the condition (j)

Grackle: Encoding advanced Prover9 features

To describe a given clause selection queue:

```
part(queue1, high, age , weight < 500 & -horn ) = 50.
```

we introduce a set of parameters

while fixing the maximal count of parts in the condition (j)

1. *H^{order}*: select the sorting criterion (age,weight,random)

Grackle: Encoding advanced Prover9 features

To describe a given clause selection queue:

`part(queue1, high, age , weight < 500 & -horn) = 50.`

we introduce a set of parameters

while fixing the maximal count of parts in the condition (j)

1. H^{order} : select the sorting criterion (age,weight,random)
2. H_j^{cond} : the property of the j -th part in the condition

Grackle: Encoding advanced Prover9 features

To describe a given clause selection queue:

`part(queue1, high, age , weight < 500 & -horn) = 50.`

we introduce a set of parameters

while fixing the maximal count of parts in the condition (j)

1. H^{order} : select the sorting criterion (age,weight,random)
2. H_j^{cond} : the property of the j -th part in the condition
3. $H_j^{connect}$: the logical connective between condition parts

Grackle: Encoding advanced Prover9 features

To describe a given clause selection queue:

```
part(queue1, high, age , weight < 500 & -horn ) = 50.
```

we introduce a set of parameters

while fixing the maximal count of parts in the condition (j)

1. H^{order} : select the sorting criterion (age,weight,random)
2. H_j^{cond} : the property of the j -th part in the condition
3. $H_j^{connect}$: the logical connective between condition parts
4. H_j^{val} : the numeric value to compare the property with

Grackle: Encoding advanced Prover9 features

To describe a given clause selection queue:

```
part(queue1, high, age , weight < 500 & -horn ) = 50.
```

we introduce a set of parameters

while fixing the maximal count of parts in the condition (j)

1. H^{order} : select the sorting criterion (age,weight,random)
2. H_j^{cond} : the property of the j -th part in the condition
3. $H_j^{connect}$: the logical connective between condition parts
4. H_j^{val} : the numeric value to compare the property with
5. H_j^{neg} : is the condition negated (yes or no)

Grackle: Encoding advanced Prover9 features

To describe a given clause selection queue:

`part(queue1, high, age , weight < 500 & -horn) = 50.`

we introduce a set of parameters

while fixing the maximal count of parts in the condition (j)

1. H^{order} : select the sorting criterion (age,weight,random)
2. H_j^{cond} : the property of the j -th part in the condition
3. $H_j^{connect}$: the logical connective between condition parts
4. H_j^{val} : the numeric value to compare the property with
5. H_j^{neg} : is the condition negated (yes or no)
6. H^{ratio} : the queue selection ratio

Grackle: Encoding advanced Prover9 features

Similarly, we encode other Prover9 advanced features:

- keep/delete rules: deleting generated clauses (incomplete)
- actions: dynamic changing of parameter values

Grackle: Encoding advanced Prover9 features

Similarly, we encode other Prover9 advanced features:

- keep/delete rules: deleting generated clauses (incomplete)
- actions: dynamic changing of parameter values

This gives rise to 2 Grackle domains:

- **default domain**: only basic options (value-based)
- **full domain**: basic + advanced features

Automated Theorem Proving and Prover9

Grackle Strategy Invention

Experiments on AIM Problems

Experiments on TPTP Problems

Experiments Setup

- AIM benchmark used in the CASC 2016 ATP competition
 - ...divided into 1020 training and 200 testing problems
 - ...from a large theorem proving project in loop theory.

Experiments Setup

- AIM benchmark used in the CASC 2016 ATP competition
...divided into 1020 training and 200 testing problems
...from a large theorem proving project in loop theory.
- We start with 5 simple Prover9 strategies.

Experiments Setup

- AIM benchmark used in the CASC 2016 ATP competition
...divided into 1020 training and 200 testing problems
...from a large theorem proving project in loop theory.
- We start with 5 simple Prover9 strategies.
- We run Grackle for 24 hours on **training** problems.


Experiments Setup

- AIM benchmark used in the CASC 2016 ATP competition
...divided into 1020 training and 200 testing problems
...from a large theorem proving project in loop theory.
- We start with 5 simple Prover9 strategies.
- We run Grackle for 24 hours on **training** problems.
- The 10 best strategies are evaluated on **testing** problems,
...each with a time limit of 30 seconds ($30 * 10 = 300$).

Experiments Setup

- AIM benchmark used in the CASC 2016 ATP competition
...divided into 1020 training and 200 testing problems
...from a large theorem proving project in loop theory.
- We start with 5 simple Prover9 strategies.
- We run Grackle for 24 hours on **training** problems.
- The 10 best strategies are evaluated on **testing** problems,
...each with a time limit of 30 seconds ($30 * 10 = 300$).
- This portfolio is compared with E and Vampire's portfolios
...with a compatible time limit of 300 seconds.

Grackle run on AIM train problems




Results on AIM test problems

<i>prover</i>	<i>solves</i>
Prover9/Grackle	91
Vampire/casc-mode	50
E/auto-schedule	36

Results on AIM test problems

<i>prover</i>	<i>solves</i>
Prover9/Grackle	91
Vampire/casc-mode	50
E/auto-schedule	36
<i>Prover9/auto</i>	<i>41</i>

Results on 200 AIM testing problems



Automated Theorem Proving and Prover9


Grackle Strategy Invention

Experiments on AIM Problems

Experiments on TPTP Problems


Initial Evaluation on Whole TPTP

- Q: On which TPTP category Prover9/auto performs best?




Initial Evaluation on Whole TPTP

- Q: On which TPTP category Prover9/auto performs best?



- A: On **TPTP/NUM** category.

Grackle run on TPTP/NUM problems




Results on TPTP/NUM problems

<i>prover</i>	<i>solves</i>
Prover9/Grackle	618
Vampire/casc-mode	611
E/auto-schedule	541

Results on TPTP/NUM problems

<i>prover</i>	<i>solves</i>
Prover9/Grackle	618
Vampire/casc-mode	611
E/auto-schedule	541
<i>Prover9/auto</i>	<i>519</i>

Results on TPTP/NUM problems



Thank you for listening.

Future work:

- Run Grackle for Prover9 on other TPTP categories.
- Intelligent problem-based strategy selection.
- Grackle strategy invention with Prover9 hints.

Grackle is available at GitHub:

`http://github.com/ai4reason/grackle`

Questions?