🏠 Home
👩‍💻 Author

GB English
IT Italiano

1. Configure user and avatar
2. Command aliases
Command usage
3. Fixed responses
4. Abbreviations
5. Storing data
6. Opening files
7. Launching programs
8. Opening web pages
General notes
Folder structure
Add a new language

Assistant .json Configuration Manual

Updated to release 2.2

Web page [Personal desktop assistant]
Download the program from the [GitLab project]

1️⃣ Configure user and avatar

Open the file:

📁 _dati/configurazione.json

```
"nome_avatar": "Alice",
"nome_utente": "Emanuele",
"avatar_iniziale": "benvenuto",
"avatar_random": [ "sorridente", "soddisfatto" ],
"avatar_finale": "ciao.mp4",
"frase_finale": "See you soon!",
"lingua": "en"
```

It is recommended to customize the assistant name and your name.

Example:
If you don't, the assistant will say: `"Ciao utente"`.

All avatar images and the video can be modified inside:

📁 _dati/asset/avatar/

The `lingua` field indicates the initial language.
The assistant automatically detects all languages present in the **_dati** folder.

- lang_it.json
- lang_en.json

2️⃣ Command aliases

Configurable in:

📁 _dati/configurazione.json

🏠 Home
👩‍💻 Author

GB English
IT Italiano

1. Configure user and avatar
2. Command aliases
Command usage
3. Fixed responses
4. Abbreviations
5. Storing data
6. Opening files
7. Launching programs
8. Opening web pages
General notes
Folder structure
Add a new language

```
"dammi": [ "recall" ]
```

If you don't need an alias, leave it empty:

```
"copia": []
```

List of commands with aliases

```
"alias_comandi": {
  "dammi": [ "ricorda" ],
  "apri": [ "launch" ],
  "aiuto": [ "help" ],
  "esci": [ "close", "bye" ],
  "ricorda": [ "record" ],
  "modifica": [ "change" ],
  "elimina": [ "erease" ],
  "cerca": [],
  "impara": [],
  "elenca": [],
  "copia": []
}
```

📜 Availabe commands

Command	Description (lang_en.json)
`get <name>`	Retrieves data
`open <name>`	Opens file, link or program
`search <query>`	Searches memory
`list memory`	Shows all entries
`help`	Shows commands
`exit`	Closes the assistant
`MANAGE MEMORY`	
`learn`	Guided input
`remember <name> <data>`	Saves information
`remember imagine <name> <data>`	Saves images
`edit <name>`	Modifies an entry
`delete <name>`	Deletes an entry
`copy <name>`	Copies to clipboard
`SHORTCUT`	
List of your personalized shortcut	
`LANGUAGE`	
`language name <code>`	Changes language

🏠 Home

👩‍🏫 Author

GB English

IT Italiano

1. Configure user and avatar
2. Command aliases
Command usage
3. Fixed responses
4. Abbreviations
5. Storing data
6. Opening files
7. Launching programs
8. Opening web pages
General notes
Folder structure
Add a new language

3️⃣ Fixed responses

```
"risposte_fisse": {
  "thanks": "You are welcome {nome_utente}!",
  "ciao": "Ciao {nome_utente}!",
  "How are you": "Fine, thanks!"
}
```

4️⃣ Abbreviations (quick buttons)

```
"shortcut": [
  {
    "etichetta": "Mail",
    "comando": "apri posta"
  },
  {
    "etichetta": "Browser",
    "comando": "apri web"
  }
]
```

5️⃣ Storing data

```
{
 "nome": "Tax code",
 "alias": "code",
 "soggetto": "Andrea",
 "dati": "ANDRRS99A30L424X",
 "tag": "information",
 "avatar": "magazziniere"
}
```

6️⃣ Opening files or folders

```
"dati": "D:\\Documents\\excel\\fileUPDATED.ods"
```

7️⃣ Launching programs

```
"dati": "D:\\mail\\ThunderbirdPortable.exe"
```

8️⃣ Opening web pages

```
"dati": "https://www.steppa.net/cassani/business_card.htm"
```

⚠️ General notes

🏠 Home

👩‍💻 Author

GB English

IT Italiano

1. Configure user and avatar
2. Command aliases
Command usage
3. Fixed responses
4. Abbreviations
5. Storing data
6. Opening files
7. Launching programs
8. Opening web pages
General notes
Folder structure
Add a new language

- The last field inside { } and [] must not have a comma
- All others must have one

📁 Folder structure

```
assistenteVOICE.py
assistente.ico
assistente.png

_dati/
  configurazione.json
  memoria.json
  memoria.json.bak
  lang_it.json
  lang_en.json

  asset/
    avatar/
```

🌍 Add a new language

1. Copy `_dati/lang_en.json`
2. Rename it (e.g. `lang_fr.json`)
3. Translate values, not keys
4. Set `lingua_stt`
5. Restart the assistant

Personal Desktop Assistant Toolkit

Author's website

© 2026 Emanuele Cassani