

©Bennet Becker, 2019

IP of the Max-Planck-Institute for Physics of Complex Systems (mpipks),
Nöthnitzer Straße 38, 01187 Dresden

DO NOT USE OUTSIDE THE MPI PKS

Images Copyrighted by their owners

Theme Metropolis CC-BY-SA 4.0 by github.com/matze



MPI PKS C++ Lecture


Bennet Becker

2019-09-09

MPI PKS

Git - Versioning your Code


What the git?? Version Control 🤔!??




A directory view showing a list of C++ source files. Each file name is preceded by a small icon representing a C++ source file (a document with a blue header and 'C++' text). The files are listed vertically:

- mycode.cpp
- mycode_final.cpp
- mycode_final1.cpp
- mycode_final_new.cpp
- mycode_v2.cpp
- mycode_v3.cpp
- mycode_v3new.cpp

What the git?? Version Control 🤔!??



What the git?? Version Control 🤔!??



```
* commit 88a69495fa0a038a118f59cf5d2a74a20badf8ce (HEAD -> master, develop)
Author: Bennet Becker <bbecker@pks.mpg.de>
Date:   Fri Oct 19 08:55:58 2018 +0200

    modifying the code to add awesome new functionality


* commit e01ee11dc84976667b9e03a5df558dc14927eab2
Author: Bennet Becker <bbecker@pks.mpg.de>
Date:   Fri Oct 19 08:54:18 2018 +0200

    adding my initial code skeleton

* commit 5848c1445fc090eefe8feae1b28a692aea60a060
Author: Bennet Becker <bbecker@pks.mpg.de>
Date:   Fri Oct 19 08:52:55 2018 +0200

    Initializing Repo
```


What the git?? Version Control 🤔!??




What the git?? Version Control 🤔!??



In an ideal World



Git - the whole story



Pro Git, Scott Chacon and Ben Straub

Print ISBN 978-1-4842-0077-3

Online ISBN 978-1-4842-0076-6

Free E-book

[https://doi.org/10.1007/](https://doi.org/10.1007/978-1-4842-0076-6)

978-1-4842-0076-6



Git Versioning

- Keep track of changes to files, managed by Git

Git Versioning

- Keep track of changes to files, managed by Git
- No manual copy for each and every change required



Git Versioning

- Keep track of changes to files, managed by Git
- No manual copy for each and every change required


So you avoid this:



Git Versioning

- Keep track of changes to files, managed by Git
- No manual copy for each and every change required

So you avoid this:



How does it work

- behaves like a miniature filesystem, saving a “snapshot” of it with each commit

*except deleting the entire repo before saving it somewhere else or trying to manipulate git history



How does it work

- behaves like a miniature filesystem, saving a “snapshot” of it with each commit
- but if a file has not changed, it is not stored again

*except deleting the entire repo before saving it somewhere else or trying to manipulate git history



How does it work

- behaves like a miniature filesystem, saving a “snapshot” of it with each commit
- but if a file has not changed, it is not stored again
- if a snapshot has been committed to git it is nearly impossible to lose this change*

*except deleting the entire repo before saving it somewhere else or trying to manipulate git history



How does it work

- behaves like a miniature filesystem, saving a “snapshot” of it with each commit
- but if a file has not changed, it is not stored again
- if a snapshot has been committed to git it is nearly impossible to lose this change*
- nearly all operations are local

*except deleting the entire repo before saving it somewhere else or trying to manipulate git history




How does it work

- behaves like a miniature filesystem, saving a “snapshot” of it with each commit
- but if a file has not changed, it is not stored again
- if a snapshot has been committed to git it is nearly impossible to lose this change*
- nearly all operations are local
- files referenced by hashes for integrity

*except deleting the entire repo before saving it somewhere else or trying to manipulate git history



How does it work ii




3 Areas in Git


3 Areas in Git

Working Directory


3 Areas in Git




3 Areas in Git




3 Areas in Git



3 Areas in Git



3 Areas in Git



Setup your git

- tell git your identity

```
git config --global user.name "John Doe"
```

```
git config --global user.email johndoe@example.com
```

- choose your editor

```
git config --global core.editor vim
```

`$EDITOR` and `/etc/alternatives` should be honored too



Create a Repo (locally)

```
mkdir myrepo  
cd myrepo/  
git init  
git add *.c  
git add LICENSE  
git commit -m 'initial project version'
```



Or Clone a Repo i

The screenshot displays the GitHub web interface. At the top, the navigation bar includes links for Projects, Groups, Activity, Milestones, and Snippets. The main content area shows the repository 'cpp-kurs' by 'Bennet Becker'. It features a 'Clone with SSH' button, a 'Clone with HTTPS' button, and a 'Clone' button. Below these, the commit history is visible, showing a commit by 'someting something' (Bennet Becker) 3 months ago. A dropdown menu is open, showing the commit hash '7648dfe5' and a 'Verified' status. The bottom section of the image shows the repository 'isocpp / CppCoreGuidelines' with a 'Clone or download' button and a 'Download ZIP' button. A dropdown menu is also open for this repository, showing the commit hash '7648dfe5' and a 'Verified' status.

Clone with SSH
git@github.com:bb/bb/cpp-kurs.git

Clone with HTTPS
https://github.com/bb/bb/cpp-kurs.git

Verified 7648dfe5

isocpp / CppCoreGuidelines

Clone or download

Download ZIP

Or Clone a Repo ii

```
git clone --recursive git@gitlab.pks.mpg.de:user/repo.git
```



Protocols in Git

- HTTPS (`https://gitserver/user/repo.git`)
 - is often easier
 - username/password authentication
 - HTTPS is a very common protocol, so it works in most network setups
- SSH (`git@gitserver:/user/repo.git`)
 - easy server setup
 - authentication via public-keys
 - no anonymous access to repository
- git (`git://gitserver/user/repo.git`)
 - special daemon with special port
 - no authentication




Recording Changes to the Repo


Recording Changes to the Repo

Untracked


Recording Changes to the Repo




Recording Changes to the Repo




Recording Changes to the Repo




Recording Changes to the Repo




Recording Changes to the Repo




Recording Changes to the Repo



Recording Changes to the Repo



Recording Changes to the Repo




Ignoring Files i

- hide files you don't want to track at all
- Binaries / Large stuff
- Local configs
- confidential stuff
- automatically generated files

```
> cat .gitignore  
*.[oa]  
*~
```



Ignoring Files ii



`https://www.gitignore.io/`



Committing your changes


```
$ git commit
```

[illegible]

```
$ git commit -m "Your commit message"
```

Viewing the history i

```
$ git log
```

A terminal window with a dark background and light text. The title bar shows the user 'bennet@YOOOO-GA' and the path '~/Projects/cpp-kurs/skript/image'. The output of 'git log' shows four commits. The first is a merge commit from HEAD to master. The second is a commit from Bennet Becker with the message 'changes on mac'. The third is a commit from Bennet Becker with the message 'add libest and done documenting audiolib [ci skip]'. The fourth is a commit from Bennet Becker.

```
bennet@YOOOO-GA: ~/Projects/cpp-kurs/skript/image
commit 8c1ae407b6e066d7a90add045757f697355c2a77 (HEAD -> master, origin/master)
Merge: f9a1c17 51b96f9
Author: Bennet Becker <bbecker+macos@pks.mpg.de>
Date: Mon Dec 3 09:38:48 2018 +0100

    Merge branch 'master' of https://gitlab.pks.mpg.de/bbecker/cpp-kurs

commit f9a1c1703c7ae31417e16c086d7cd3d7c7191116
Author: Bennet Becker <bbecker+macos@pks.mpg.de>
Date: Mon Dec 3 09:33:46 2018 +0100

    changes on mac

commit 51b96f967d4eabaa8a54eb51e179c04fb3136a24
Author: Bennet Becker <bennet@becker-dd.de>
Date: Mon Dec 3 09:18:07 2018 +0100

    add libest and done documenting audiolib [ci skip]

commit 7b1dddef502f53e890bd1641f25ea9a8c59b284e
Author: Bennet Becker <bennet@becker-dd.de>
Date: Mon Dec 3 09:17:10 2018 +0100
```

Viewing the history ii

```
$ git log --all --decorate --oneline --graph
```

```
bennet@YO000-GA: ~/Projects/cpp-kurs/skript/image
* 8c1ae40 (HEAD -> master, origin/master) Merge branch 'master' of https://gitlab.pks.mpg.de/bbecker/cpp-kurs
/*
* 51b96f9 add libest and done documenting audiolib [ci skip]
* 7b1ddde update skript
* 71a8f60 remove fftw git repo [ci skip]
* 83b005e add fftw3 submodule and build definition for WIN32 [ci skip]
* a030d98 include algorithm for std::minmax under windows [ci skip]
* | f9a1c17 changes on mac
/*
* 3278724 add portaudio to audiolib for windows [ci skip]
* df47f3e animation for scopes
* 044b31c Merge branch 'master' of gitlab.pks.mpg.de:bbecker/cpp-kurs
/*
* 4cec98c Merge branch 'master' of gitlab.pks.mpg.de:bbecker/cpp-kurs
/*
* | 3b5139d update slides
* | 5aa2e4f finish functions cbr cbv. closes #9
/*
* | f1313c6 update slides
/*
* 4a235be Merge branch 'master' of gitlab.pks.mpg.de:bbecker/cpp-kurs
/*
```

Viewing the history iii



Undoing Things

- Undo Commit (not pushed) `git commit --amend`
- Unstage a file `git reset HEAD filename`
- Unmodify a file `git checkout -- filename`



Remotes

- when used `git clone`, a remote called `origin` is already set
- add remote `git remote add origin https://gitsrv/user/repo.git`
- modify url `git remote set-url origin https://gitsrv/user/repo.git`
- push to remote `git push origin branch`
- repository can have multiple remotes, you decide on push where to push to.
 - `git push -u origin branch` sets the remote as default for this branch, so you can just use `git push` later



Branching

- (recap) git stores series of snapshots
- commit contains a pointer to the snapshot of the staged content
- commit also contains author information (name, email), the commit-message, a pointers to it's parents (zero for initial, one for "normal" commit, multiple for merge commits)




Branching

commit




Create a new Branch i

git branch testing




Create a new Branch ii




Switching branches i

`git checkout branch`





Switching branches ii



Merge Branches

```
git merge
```





Pro Git, Scott Chacon and Ben Straub

Print ISBN 978-1-4842-0077-3

Online ISBN 978-1-4842-0076-6

Free E-book

[https://doi.org/10.1007/](https://doi.org/10.1007/978-1-4842-0076-6)

978-1-4842-0076-6