



CPT-182 - Programming in C++

Module 7

Overloading Operators in User-Defined Classes

Dayu Wang

• Operators

Operator Type	Operands Taken	Example
Unary Operator	1 Operand	! (Prefix) ++ (Prefix, Postfix) -- (Prefix, Postfix)
Binary Operator	2 Operands	+ (Arithmetic Addition) - (Arithmetic Subtraction) <= (Comparison)
Ternary Operator	3 Operands	? : (Conditional)

→ Operators behave differently for different data types of operands.

[Example 1] **A / B**

1) If both **A** and **B** are integers, what is the behavior of operator '/'?

Integer Division

2) If **A** is an integer and **B** is a double, what is the behavior of '/'?

Floating-Point Division

[Example 2] **A + B**

1) If both **A** and **B** are integers, what is the behavior of operator '+'?

Arithmetic Addition

2) If both **A** and **B** are strings, what is the behavior of operator '+'?

String Concatenation

- Let's take the Fraction class as an example.

→ Data fields

In "Fraction.h"

```
1 private:
2     // Data fields
3     int numerator;
4     unsigned int denominator;
```

Mathematically, to **negate** a fraction, we can either negate the denominator or the numerator.

[Example] Negation of $\frac{3}{5}$

$$\frac{-3}{5} = \frac{3}{-5} = -\frac{3}{5}$$

In the Fraction class, let's set denominator to be always positive. Then,

- 1) If numerator is positive, then the entire fraction is positive.
- 2) If numerator is negative, then the entire fraction is negative.
- 3) If numerator is 0, then the entire fraction is 0.

→ Constructor

In "Fraction.h"

```
1 public:
2     // Constructor
3     Fraction(int = 0, unsigned int = 1);
```

In "Fraction.cpp"

```
1 Fraction::Fraction(int numerator, unsigned int denominator) :
2     numerator(numerator), denominator(denominator) {}
```

Since mathematically the denominator of a fraction **cannot** be 0, we set it to 1 by default.

This constructor is **not** completed yet.

Later, we will add code in it.

→ The .print() function

In "Fraction.h"

```
1 // Prints the fraction to an output stream.
2 void print(ostream&) const;
```

In "Fraction.cpp"

```
1 void Fraction::print(ostream& out) const {
2     out << numerator << " / " << denominator << endl;
3 }
```

Temporary

→ Mathematically, two fractions can be added together.

$$\frac{1}{2} + \frac{3}{10} = \frac{5}{10} + \frac{3}{10} = \frac{8}{10} = \frac{4}{5}$$

Can we use the '+' operator in C++ to add two Fraction objects?

In "Main.cpp"

```
1 int main() {
2     Fraction f_1(1, 2), f_2(3, 10);
3     Fraction f_3 = f_1 + f_2; Code does not compile.
4     f_3.print(cout);
5     system("pause");
6     return 0;
7 }
```

Console

binary '+': 'Fraction' does not define this operator or a conversion to a type acceptable to the predefined operator

Compiler knows how to use '+' to add two integers; the compiler knows how to use '+' to add two doubles.

However, the compiler does **not** know how to use '+' to add two Fraction objects, because Fraction is a user-defined class.

If you want '+' to be used to add two Fraction objects, you need to "tell" the compiler how to add two Fraction objects.

→ How (and where) to tell the compiler the behavior of operator '+' for two Fraction objects?

We need to define the **operator function** for operator '+' in class Fraction.

We call this **overloading** operator '+' in the Fraction class.

Syntax of overloading an operator

```
1 [return_type] · operator · [operator_symbol]([arguments]);
```

→ Overloading operator '+' for "Fraction + Fraction" in class Fraction

1) What should be the return type?

Since the addition result of two fractions is another fraction, the return type should be Fraction.

2) How many arguments? What is the data type of each argument?

There should be only one argument, which is a Fraction type.

→ Here, the operator function is a class-member function.

"f1 + f2" should be understood as "f1.+(f2)".

f1 (**calling object**) is already a Fraction, so we only need to pass another Fraction (**only one**) to the function.

In "Fraction.h"

```
1 Fraction operator + (const Fraction&) const;
```

- 1) Here, the argument should be passed by const reference, since it will **not** be changed in the function.
- 2) The function should be a const function, since the function does **not** change the current object.
- 3) In other words, in calculation of "A + B", **neither** A **nor** B will change.

→ Before we implement the operator function, we need to define the `simplify()` function to simply a fraction to lowest terms.

How to simplify a fraction (mathematically)?

$$\frac{12}{28} = \frac{3}{7}$$

- 1) Find the **greatest common divisor (GCD)** for the numerator and denominator.
- 2) Divide the numerator and denominator by the GCD.

→ The algorithm of finding the GCD of two positive integers is **not** required in this chapter.

This algorithm will be discussed in future lectures

In "Fraction.h"

```
1 private:
2     // Finds the GCD of two positive integers.
3     static unsigned int GCD(unsigned int, unsigned int);
```

This function is in the **private** section since it is **not** expected to be used outside the Fraction class.

This function is **static** since it is **not** for any specific Fraction object.

In "Fraction.cpp"

```
1 /** Finds the GCD of two positive integers.
2     @return: GCD of the two positive integers
3 */
4 unsigned int Fraction::gcd(unsigned int x, unsigned int y) {
5     if (x < y) { return gcd(y, x); }
6     if (x % y == 0) { return y; }
7     else { return gcd(y, x % y); }
8 }
```

→ The simplify() function

In "Fraction.h"

```
1 private:
2     void simplify(); // Reduces the fraction to lowest terms.
```

In "Fraction.cpp"

```
1 /** Reduces the fraction to lowest terms. */
2 void Fraction::simplify() {
3     if (!numerator) {
4         denominator = 1;
5         return;
6     }
7     unsigned int GCD = gcd((unsigned int)abs(numerator), denominator);
8     numerator /= GCD;
9     denominator /= GCD;
10 }
```

→ Improving the implementation of the constructor

In "Fraction.cpp"

```
1 Fraction::Fraction(int numerator, unsigned int denominator) :
2     numerator(numerator), denominator(denominator) { simplify(); }
```

A Fraction object will be automatically simplified when it is created.

→ Implementing the operator function for operator '+'

Mathematically, how to add two fractions together?

$$\frac{a}{b} + \frac{c}{d} = \frac{ad}{bd} + \frac{bc}{bd} = \frac{ad + bc}{bd}$$

Finally, simplify the result.

In "Fraction.h"

```
1 Fraction operator + (const Fraction&) const;
```

In "Fraction.cpp"

```
1 /** Overloads operator '+' for "Fraction + Fraction".
2     @param other: the other fraction to add to this fraction
3     @return: addition result
4 */
5 Fraction Fraction::operator + (const Fraction& other) const {
6     Fraction result;
7     result.denominator = denominator * other.denominator;
8     result.numerator = numerator * other.denominator
9                     + denominator * other.numerator;
10    result.simplify();
11    return result;
12 }
```

→ Test in the main() function

In "Main.cpp"

```

1 int main() {
2     Fraction f_1(1, 2), f_2(3, 10);
3     Fraction f_3 = f_1 + f_2;
4     f_3.print(cout);
5     system("pause");
6     return 0;
7 }

```

Console 4 / 5

→ Mathematically, we can add a fraction and an integer together.

$$\frac{1}{2} + 3 = \frac{1}{2} + \frac{6}{2} = \frac{7}{2}$$

In "Main.cpp"

```

1 int main() {
2     Fraction f_1(1, 2)
3     Fraction f_2 = f_1 + 3;
4     f_2.print(cout);
5     system("pause");
6     return 0;
7 }

```

Compiler only knows how
to do "Fraction + Fraction".

It does **not** know how to
do "Fraction + int".

→ Overloading "Fraction + int".

In "Fraction.h"

```

1 Fraction operator + (const Fraction&) const; // "Fraction + Fraction".
2 Fraction operator + (int) const; // Overloads "Fraction + int".

```

In "Fraction.cpp"

```

1 /** Overloads operator '+' for "Fraction + int".
2     @param other: the integer to add to this fraction
3     @return: addition result
4 */
5 Fraction Fraction::operator +(int other) const {
6     return *this + Fraction(other, 1);
7 }

```

"*this" is a reference to the current object (Fraction).

"Fraction(other, 1)" converts an integer to a Fraction.

Now, the addition becomes "Fraction + Fraction" which has already been overloaded.

→ How about "int + Fraction"?

This is totally a different story.

"f1 + f2" should be understood as "f1.+(f2)".

Since the operator function is a class-member function in the Fraction class, only a Fraction object can call this function.

In other words, "f1" **must** be a Fraction object.

→ Therefore, if we want to overload "int + Fraction", we **cannot** write the function in the Fraction class anymore.

We have to write the function outside the Fraction class.

In "Fraction.h"

```
1 class Fraction { ... };
2
3 // Non-class-member functions
4
5 // Overloads "int + Fraction".
6 Fraction operator + (int, const Fraction&);
```

In "Fraction.cpp"

```
1 /** Overloads operator '+' for "int + Fraction". */
2 Fraction operator + (int left, const Fraction& right) {
3     return right + left;
4 }
```

In "Fraction.cpp"

```
1 /** Overloads operator '+' for "int + Fraction".
2     @param left: left operand (integer)
3     @param right: right operand (fraction)
4     @return: addition result
5 */
6 Fraction operator + (int left, const Fraction& right) {
7     return right + left;
8 }
```

Why this time, there are 2 arguments?

Because the function is **no longer** a ~~class-member function~~, which means that we do **not** have a Fraction object to call this function.

Therefore, we need 2 arguments.

→ The '+' operator does **not** always mean "arithmetic addition".

e.g., +3, +12

In "Fraction.h"

```
1 Fraction operator + () const; // Overloads unary '+' operator.
```

In "Fraction.cpp"

```
1 /** Overloads the unary '+' operator. @return: this fraction */
2 Fraction Fraction::operator + () const { return *this; }
```

• Overloading Operator '-'

→ Unary operator '-'

e.g., -3, -12

In "Fraction.h"

```
1 Fraction operator - () const; // Overloads the unary '-' operator.
```

In "Fraction.cpp"

```
1 /** Overloads the unary '-' operator.
2     @return: opposite fraction
3 */
4 Fraction Fraction::operator - () const {
5     return Fraction(-numerator, denominator);
6 }
```

→ Arithmetic subtraction operator '-'

$3 - 5 = 3 + (-5)$

$10 - (-15) = 10 + 15$

"Subtracting" is equivalent to "adding the opposite".

We can use operator '+' (already overloaded) to implement operator '-'.

→ Overloading "Fraction - Fraction".

In "Fraction.h"

```
1 Fraction operator - (const Fraction&) const; // "Fraction - Fraction"
```

In "Fraction.cpp"

```
1 /** Overloads "Fraction - Fraction".
2     @param other: the other fraction to subtract from this fraction
3     @return: subtraction result
4 */
5 Fraction Fraction::operator - (const Fraction& other) const {
6     return *this + (-other);
7 }
```

→ Overloading "Fraction - int".

In "Fraction.h"

```
1 Fraction operator - (int) const; // Overloads "Fraction - int".
```

In "Fraction.cpp"

```
1 /** Overloads "Fraction - int".
2     @param other: the integer to subtract from this fraction
3     @return: subtraction result
4 */
5 Fraction Fraction::operator - (int other) const {
6     return *this + (-other);
7 }
```


→ Overloading "int - Fraction"

In "Fraction.h"

```

1 class Fraction {
2     ...
3 };
4
5 // Non-class-member functions
6
7 // Overloads "int - Fraction".
8 Fraction operator - (int, const Fraction&);

```

In "Fraction.cpp"

```

1 /** Overloads "int - Fraction".
2     @param left: left operand (integer)
3     @param right: right operand (fraction)
4     @return: subtraction result
5 */
6 Fraction operator - (int left, const Fraction& right) {
7     return Fraction(left, 1) - right;
8 }

```

• Overloading Arithmetic Multiplication Operator '*'

In "Fraction.h"

```

1 class Fraction {
2     ...
3     Fraction operator * (const Fraction&) const; // Fraction * Fraction
4     Fraction operator * (int) const; // "Fraction * int"
5     ...
6 };
7 // Non-class-member functions
8 Fraction operator * (int, const Fraction&); // "int * Fraction".

```

In "Fraction.cpp"

```

1 Fraction Fraction::operator * (const Fraction& other) const {
2     Fraction result;
3     result.numerator = numerator * other.numerator;
4     result.denominator = denominator * other.denominator;
5     result.simplify();
6     return result;
7 }
8 Fraction Fraction::operator * (int other) const {
9     return *this * Fraction(other, 1);
10 }
11 Fraction operator * (int left, const Fraction& right) {
12     return right * left;
13 }

```

• Overloading Arithmetic Division Operator '/'

→ The `reciprocal()` function

In "Fraction.h"

```
1 private:
2     // Returns the reciprocal of the fraction.
3     Fraction reciprocal() const;
```

In "Fraction.cpp"

```
1 /** Returns the reciprocal of the fraction.
2     @return: reciprocal of the fraction
3 */
4 Fraction Fraction::reciprocal() const {
5     int sign = numerator > 0 ? 1 : -1;
6     unsigned int new_denominator = (unsigned int)std::abs(numerator);
7     int new_numerator = (int)denominator * sign;
8     return Fraction(new_numerator, new_denominator);
9 }
```

Here, for simplicity, we just **ignore** the ~~divide-by-zero~~ issues. We just assume that this will **not** happen.

→ Overloading the '/' operator

"Divide by" is equivalent to "times the reciprocal".

In "Fraction.h"

```
1 class Fraction {
2     ...
3     Fraction operator / (const Fraction&) const; // Fraction / Fraction
4     Fraction operator / (int) const; // "Fraction / int"
5     ...
6 };
7 // Non-class-member functions
8 Fraction operator / (int, const Fraction&); // "int / Fraction"
```

In "Fraction.cpp"

```
1 Fraction Fraction::operator / (const Fraction& other) const {
2     return *this * other.reciprocal();
3 }
4
5 Fraction Fraction::operator / (int other) const {
6     return *this / Fraction(other, 1);
7 }
8
9 Fraction operator / (int left, const Fraction& right) {
10    return Fraction(left, 1) / right;
11 }
```

- Compound Assignment Operators

In "Fraction.h"

```
1 Fraction operator += (const Fraction&); // "Fraction += Fraction"
2 Fraction operator += (int); // "Fraction += int"
3 Fraction operator -= (const Fraction&); // "Fraction -= Fraction"
4 Fraction operator -= (int); // "Fraction -= int"
5 Fraction operator *= (const Fraction&); // "Fraction *= Fraction"
6 Fraction operator *= (int); // "Fraction *= int"
7 Fraction operator /= (const Fraction&); // "Fraction /= Fraction"
8 Fraction operator /= (int); // "Fraction /= int"
```

Why they are **not** **const** functions?

"a += b", b is **not** changed; a is changed.

Why there are **no** "int += Fraction" (and so on) versions?

"a += b", a is an integer. "a += b" is equivalent to "a = a + b", so after the assignment, a becomes a Fraction.

In C++, this is **impossible** (static typing).

In "Fraction.cpp"

```
1 Fraction Fraction::operator += (const Fraction& other) {
2     return *this = *this + other;
3 }
4 Fraction Fraction::operator += (int other) {
5     return *this = *this + other;
6 }
7 Fraction Fraction::operator -= (const Fraction& other) {
8     return *this = *this - other;
9 }
10 Fraction Fraction::operator -= (int other) {
11     return *this = *this - other;
12 }
13 Fraction Fraction::operator *= (const Fraction& other) {
14     return *this = *this * other;
15 }
16 Fraction Fraction::operator *= (int other) {
17     return *this = *this * other;
18 }
19 Fraction Fraction::operator /= (const Fraction& other) {
20     return *this = *this / other;
21 }
22 Fraction Fraction::operator /= (int other) {
23     return *this = *this / other;
24 }
```

- **Increment Operator "++" and Decrement Operator "--"**

→ Since **prefix** increment/decrement and **postfix** increment/decrement have different behaviors, we need to overload respectively for prefix increment/decrement and postfix increment/decrement.

In "Fraction.h"

```
1 Fraction& operator ++ (); // Prefix increment
2 Fraction operator ++ (int); // Postfix increment
3 Fraction& operator -- (); // Prefix decrement
4 Fraction operator -- (int); // Postfix decrement
```

- 1) Prefix increment/decrement operator returns a reference of the Fraction **after** increment/decrement.
- 2) Postfix increment/decrement operator returns a copy of the Fraction **before** increment/decrement.
- 3) For prefix increment/decrement operator, there is **nothing** in the "()".
- 4) For postfix increment/decrement operator, the "(int)" means **nothing** but tells the compiler that this is postfix operator.

In "Fraction.cpp"

```
1 /** Overloads "++Fraction". */
2 Fraction& Fraction::operator ++ () {
3     *this += 1;
4     return *this;
5 }
6 /** Overloads "Fraction++". */
7 Fraction Fraction::operator ++ (int) {
8     Fraction result = *this;
9     ++*this;
10    return result;
11 }
12 /** Overloads "--Fraction". */
13 Fraction& Fraction::operator -- () {
14     *this -= 1;
15     return *this;
16 }
17 /** Overloads "Fraction--". */
18 Fraction Fraction::operator -- (int) {
19     Fraction result = *this;
20     --*this;
21     return result;
22 }
```

• Comparison Operators

1 operator < (**2** other) **3** ;

1) What should be the return type?

2) "Fraction&" or "const Fraction&"?

3) const function or not?

In "Fraction.h"

```
1 bool operator < (const Fraction&) const; // "Fraction < Fraction"
2 bool operator < (int) const; // "Fraction < int"
3 bool operator <= (const Fraction&) const; // "Fraction <= Fraction"
4 bool operator <= (int) const; // "Fraction <= int"
5 bool operator > (const Fraction&) const; // "Fraction > Fraction"
6 bool operator > (int) const; // "Fraction > int"
7 bool operator >= (const Fraction&) const; // "Fraction >= Fraction"
8 bool operator >= (int) const; // "Fraction >= int"
9 bool operator == (const Fraction&) const; // "Fraction == Fraction"
10 bool operator == (int) const; // "Fraction == int"
11 bool operator != (const Fraction&) const; // "Fraction != Fraction"
12 bool operator != (int) const; // "Fraction != int"
```

• Can we use the stream insertion operator ("<<") to write a Fraction object to the console?

In "Main.cpp"

```
1 cout << Fraction(1, 2) << endl; // Code does not compile.
```

Compiler does **not** know how to output a Fraction object, since it is a user-defined class.

You need to overload the "<<" operator in the Fraction class to tell the compiler how to output a Fraction object.

→ What is the left operand of the "<<" operator?

It is an output stream.

"cout" and "fout" are both output streams.

Therefore, "<<" is a non-class-member function.

→ What is the return type of the "<<" operator?

```
1 cout << b << c
```

Must return an output stream for the next evaluation.

In "Fraction.h"

```
1 friend ostream& operator << (ostream&, const Fraction&);
```

• Overloading the "<<" operator

→ Suppose the output format of Fraction(2, 3) is "2 / 3".

In "Fraction.cpp"

```
1 ostream& operator << (ostream& out, const Fraction& f) {
2     out << f.numerator << " / " << f.denominator;
3     return out;
4 }
```

1) Return type should be ostream, **not** ostream.

2) Do **not** forget that you need to return the ostream at the end.

• Overloading the ">>" operator

→ Suppose the input format is "[numerator] [denominator]".

In "Fraction.h"

```
1 friend istream& operator << (istream&, Fraction&);
```

In "Fraction.cpp"

```
1 istream& operator >> (istream& in, Fraction& f) {
2     in >> f.numerator >> f.denominator;
3     f.simplify();
4     return in;
5 }
```

• Overloading the subscript operator "[]"

→ You must overload the operator "[]" twice.

lvalue: arr[3] = 3

rvalue: my_var = arr[3]

- The lvalue returns a reference.
- The rvalue returns a const reference.

In "Simple_String.h"

```
1 class Simple_String {
2 public:
3     Simple_String(); // Default constructor
4     void push_back(char); // Appends a character to the end.
5     char& operator [] (size_t); // lvalue
6     const char& operator [] (size_t) const; // rvalue
7 private:
8     char c[100]; // Stores the characters in the string.
9     size_t size; // Stores the number of characters in the string.
10 };
```

In "Simple_String.cpp"

```
1 // lvalue
2 char& Simple_String::operator [] (unsigned int index) {
3     return c[index];
4 }
5 // rvalue
6 const char& Simple_String::operator [] (unsigned int index) const {
7     return c[index];
8 }
```

→ How can compiler know which one (reference or const reference) to return?

Assignment statement: A = B

1) Left side of the assignment operator is a reference.

2) Right side of the assignment operator is a const reference.

• In this lecture, we overloaded 48 operators.

→ The following two operators will be discussed in future lectures:

- Assignment operator '='
- Dereferencing operators, '*' (unary) and '->'.

• Restrictions of Overloading Operators

→ You **cannot** ~~change the precedence~~ of an operator.

→ The associativity **cannot** be changed.

For example, the associativity of the arithmetic addition operator ('+') is from left to right, and it **cannot** be changed.

→ Default parameter values **cannot** be used in operator functions.

→ You **cannot** change the ~~number of parameters~~ an operator takes.

→ You **cannot** ~~create new operators~~.

Only existing operators can be overloaded.

→ Some operators **cannot** be overloaded.

For example: '.', '::', '? :'

→ The meaning of how an operator works with built-in types, such as int, remains the same.

You **cannot** redefine how operators work with built-in data types.