

Conference Ops

Implementation record, persona workflows, Sessionboard comparison, Airtable operating boundary, release controls, and prospective-client handoff.

DOCUMENT	PRODUCT	USE
Final handoff	Conference Ops 0.2.0	Named, monitored evaluation



OPEN THE PROSPECTIVE-CLIENT PILOT

<https://conference-ops-pilot-app.techfren.workers.dev>

Create and verify your own account. Do not use or share an operator credential.

01 / ORIENTATION

What is being handed off

Conference Ops is a Cloudflare-native conference program workspace. It covers the lifecycle from a versioned call for proposals through track-based review, controlled decisions, speaker onboarding, conflict-aware scheduling, publication, communications, and Airtable-backed business records. This release is shaped by the customer's clarified MVP and rechecked against Sessionboard's participant and organizer learning material. It is not a pixel-for-pixel clone.

Evaluation status

Appropriate for a small, named, monitored prospective-client trial. Before broad anonymous promotion, add abuse controls, formal file scanning, and production retention/alerting. The organizer UI, not this PDF, is the authority for current Airtable connection health.

Audience	Use
Prospective organizer	Read persona workflows and the separate organizer guide; create an isolated event and use representative data.
Participant/reviewer/speaker	Use a separate verified account for each persona; follow only the event links sent by the organizer.
Airtable operator	Follow the fail-closed provisioning and cutover sequence. Never treat provisioning alone as source-of-truth activation.
Engineer/release owner	Use the release gates, architecture boundary, known limits, and version-control handoff.

Document map

- Pages 3-8: requirements, complete feature ledger, and persona workflows.
- Pages 9-12: Airtable data boundary, commissioning, cutover, recovery, and safe editing.
- Pages 13-17: architecture, privacy, audit method, agents, release controls, and known boundaries.
- Pages 18-19: client acceptance script and handoff index.

02 / ACCEPTANCE AUTHORITY

What Sessionboard parity means here

The product was audited against the updated customer requirements and the current Sessionboard overview, participant, and organizer learning pages. Every available visual on those pages was inspected as audit input: 140 of 140 reference images were processed without image-analysis failure. The customer's explicit clarifications control where Sessionboard is broader than the requested MVP.

Clarified requirement	Conference Ops contract	Status
Forms	Basic one-level equals/contains conditional logic is sufficient; multiple independently versioned CFPs are supported.	Implemented
Routing	Talks select one or more tracks; organizers explicitly map reviewers to one or more tracks.	Implemented
Review	Unreviewed to Approve, Maybe, or Deny, with evidence, weighted scoring, draft save, and final lock.	Implemented
Acceptance	Create the linked session, speaker access, configured onboarding work, audit record, and decision message.	Implemented
Onboarding	Hotel stay and flight reimbursement plus profile, talk details, media, files, announcements, colleague invites, and external actions.	Implemented
Email/calendar	Real MVP delivery through durable Cloudflare Email workflows and RFC 5545 calendar REQUEST attachments.	Configured runtime required
Schedule	Day/room plus drag/drop and conflict detection is sufficient; list, week, and conflict views are also present.	Implemented
Agent	Small useful read-only readiness assistant; admin UI remains the priority.	Implemented
Airtable	Canonical business records, guarded descriptive edits, webhook reconcile, conflicts, and Workflow Commands.	Implemented; cutover explicit
Accelevents	Explicitly skipped; controlled exports remain available.	Intentional scope

Human-readable references

- Product video overview: <https://learn.sessionboard.com/videos/overview>
- Participant overview: <https://learn.sessionboard.com/participants/overview>
- Organizer overview: <https://learn.sessionboard.com/get-started/overview>

03 / FEATURE LEDGER

Identity, events, forms, and submissions

Area	Implemented behavior	Use/guard
Identity	Email/password signup, verification, sign-in/out, token-aware password reset, invitations, speaker claims, and safe return routing.	Roles are event-scoped; one user may hold multiple roles without impersonating other people.
Event setup	Organization, event name/slug/purpose, dates, timezone, venue, website, accent, isolated workspace, and editable details.	CFP close must precede event start; invalid relationships are blocked in browser and API.
Fresh defaults	Draft CFP, review round/group, room, track, hotel and flight forms, profile/slides/calendar tasks, five message templates, and two reminder rules.	Defaults are organizer-editable, not hardcoded runtime decisions.
CFP portfolio	Create, switch, clone, independently version, publish, close, and copy a form-specific public link.	Published versions are immutable; applicant drafts stay pinned to their starting version.
Form builder	Text, long text, email, URL, select, multiselect, checkbox, information blocks, required rules, options, limits, and one-level conditions.	Visible-only validation, server allowlists, long-text budget, concurrency checks, and no public CFP file questions.
Applicant draft	Browser and account drafts, resume, multiple submissions, one or more tracks, participant minimum/maximum, distinct-email co-speakers, confirmation, and withdrawal.	Owner-scoped; submission caps and final consent are server-enforced.
Applicant revision	Reopen a non-final submission before the pinned form closes, or respond to an organizer change request and resubmit.	Accepted, rejected, or session-backed submissions stay locked. Submitted review evidence remains historical.

Routing rule

A reviewer invitation does not silently grant all tracks. Organizers explicitly map each track or reviewer group. A multi-track proposal receives the union of eligible reviewers, while owners and claimed co-speakers are excluded. Routing lane identifiers are comma-free so serialized multi-lane membership cannot split or merge ambiguously.

Review, decisions, and automatic activation

Area	Implemented behavior	Durable result
Review setup	Organizer-configurable active scoring plan, criteria, weights, evidence expectations, track groups, and reviewer membership.	Assignments are explicit and event-scoped.
Reviewer desk	Assignment queue, criterion scoring, note/evidence, recommendation, server-computed weighted preview, draft save/reload, and final submit.	Submitted review is immutable; applicant projections never expose scores or committee details.
Decision states	Submitted/under review to Accept queue, Decline queue, or Waitlist; final Accept or Reject; optional organizer note and request-changes path.	Audit trail records material state changes; final decisions are guarded and immutable.
Request changes	Organizer sends a revision note and applicant edit path; eligible applicant can revise before close.	Open review work is revoked; the new revision gets fresh revision-aware assignments; prior submitted review evidence remains organizer-visible history.
Final acceptance	One guarded workflow creates a linked unscheduled session, activates eligible speaker access, instantiates configured tasks, records audit evidence, and persists the decision email intent.	No partial acceptance state if the guarded workflow fails.
Final rejection	Records the final decision and configured communication intent without creating session or onboarding work.	Applicant sees final status; active review work is closed.

Minimum workflow

The customer asked for Unreviewed to Approve, Maybe, or Deny. Conference Ops adds staged decision queues and a controlled request-changes cycle without requiring a complex multi-round orchestration product.

05 / FEATURE LEDGER

Speaker onboarding, files, collaboration, and resources

Area	Implemented behavior	Privacy/visibility
Speaker access	Verified-email claim, explicit speaker portal, proposal/session-targeted work, and multi-role account routing.	Only the eligible account and event organizers can access private work.
Profile	Bio, title, company, city, pronouns, publication consent, headshot upload/replace, completeness, and public eligibility.	Public only after consent and published-session eligibility; private email/storage keys excluded.
Task plans	Organizer-authored manual, profile, questionnaire, file request, calendar acknowledgement, and external HTTPS action tasks.	Acceptance instantiates the event's configured task plan for the relevant speaker/session.
Default examples	Hotel stay, flight reimbursement, finalize talk description, bio/photo, slides, calendar, announce participation, and invite colleagues with a discount.	Organizers may edit, remove, or add templates before acceptance.
Files	Private task-scoped upload, replace, chronological version history, current/prior download, metadata, and organizer/speaker evidence.	Raw bytes remain in private R2; Airtable receives safe metadata, never file bytes.
Comments	Organizer and speaker task discussion with durable chronological history.	Event/task authorization on read and write.
Speaker Ops	Roster search, exact profile/task exceptions, deep links, reminders, reopen/complete, comments, and file evidence.	Organizer only; rejected/waitlisted work does not pollute outstanding views.
Resources	Organizer creates plain-text guides with optional HTTPS references, drafts/publishes them, and exposes them in portal/public index.	Safe text rendering; no arbitrary rich HTML.

06 / FEATURE LEDGER

Scheduling, publication, communications, and exports

Area	Implemented behavior	Guard
Venue model	Organizer CRUD for rooms and tracks, duplicate checks, capacity/color, and in-use delete guards.	All entities are event-scoped.
Sessions	Accepted-proposal conversion plus direct guaranteed/sponsor/program sessions; break/networking formats can omit a speaker.	Proposal conversion is one-to-one and guarded.
Schedule	List, day/room, week, and conflicts views; day/track filters; URL-persisted view state; explicit placement and drag/drop.	Event-window, room, track, and speaker collisions checked in client and server.
Overrides	Alternate placement or audited override with a durable reason; reschedule and calendar sequence bump.	Adjacency is allowed; unreasoned collisions are blocked.
Publish	Atomic readiness/preflight and agenda publication; later published schedule changes update the live program.	Only published, eligible records reach public projections.
Public	Agenda, day/track navigation, favorites, speaker gallery, resources, submit/portal links, and exact event-scoped iframe embed.	Public allowlists exclude accounts, email, reviews, private files, and raw storage keys.
Messages	Editable submission, acceptance, rejection, task-reminder, and calendar templates; scheduled draft/task reminders; recipient previews.	Durable D1 outbox before Queue delivery, idempotency, bounded retry, dead convergence.
History/calendar	Organizer-safe delivery history; RFC 5545 METHOD:REQUEST with stable UID and incremented SEQUENCE.	A queued/sent status is not an inbox-read guarantee; target delivery needs runtime configuration.
Exports	Protected speakers.csv, sessions.csv, and program.json for portable handoff.	CSV formula prefixes are neutralized; accepted/public and PII rules apply.
Assistant	Read-only, event-grounded readiness recommendations with workflow deep links.	Cannot mutate, send, decide, or bypass permissions.

07 / PERSONA WORKFLOWS

What each user actually does

Persona	Start	Core flow	Finish
Organizer	Create/verify account; create event.	Configure CFPs, routing, rubric, onboarding, resources, messages, venue, then invite staff.	Decide, schedule, publish, monitor, export, and inspect Airtable health.
Applicant	Open form-specific CFP link; verify account.	Save draft, answer visible questions, select tracks, add speakers, consent, submit, revise if eligible.	See status, respond to changes, withdraw when allowed, or move into speaker work after acceptance.
Reviewer	Accept invitation with a distinct account.	Open assigned tracks only; score rubric, add evidence, save draft, choose Approve/Maybe/Deny, submit.	Final evidence becomes read-only; organizer owns the final decision.
Speaker	Claim with the invited/accepted email.	Complete profile, hotel/flight and other forms, external actions, files, versions, comments, and tasks.	Confirm readiness and use participant resources; organizer publishes eligible profile/session.
Participant/public	Open event agenda, speaker, or resource URL.	Browse day/track, favorite sessions locally, view published speakers/resources, use embed.	No account/private workflow data is exposed.
Airtable operator	Provision one environment base with least privilege.	Reconcile, drain, review health/conflicts, switch authority through Workflow Command only.	Run a reversible descriptive-field round trip and retain D1 mirror/operational controls.

Account rule

Use separate verified people for organizer, reviewer, applicant, and speaker tests. Self-review exclusion is intentional. Never share an organizer password, reset link, invitation token, Airtable PAT, webhook secret, or raw provisioning artifact.

08 / ORGANIZER RUNWAY

The shortest complete evaluation

Step	Organizer action	Expected evidence
1	Create the event and verify details after reload.	Private event plus seeded operational defaults.
2	Create or choose a CFP; configure fields/track question; publish and copy that form's link.	Published immutable version and form-specific URL.
3	Map each track to explicit reviewer coverage; configure rubric and onboarding plan.	No uncovered track; no reviewer granted all tracks by invitation alone.
4	Invite a distinct reviewer; use another account to submit a multi-track proposal.	Eligible assignments only; owner excluded.
5	Reviewer saves and submits Approve/Maybe/Deny evidence.	Weighted final review is read-only.
6	Request changes or stage/finalize the decision.	Revision loop or automatic accepted session/tasks/message intent.
7	Speaker claims access, completes profile/forms, comments, and uploads/replaces a representative file.	Private current/prior file evidence and task readiness.
8	Place session in day/room; intentionally test a conflict; reschedule or override with reason.	Conflict-safe or audited placement visible in all views.
9	Publish agenda; check public agenda/speakers/resources/embed; queue a controlled message/calendar; export.	Published-only public output, durable delivery history, safe export.
10	Inspect Airtable status. Only if commissioned: verify canonical record and one allowed descriptive edit round trip.	Healthy authority, zero pending/dead/conflicts, no protected-state bypass.

Test data

Use synthetic or representative content. Do not upload customer-confidential, regulated, executable, or irreplaceable files during the monitored evaluation.

09 / AIRTABLE BOUNDARY

What is canonical and what stays operational

Airtable can be the canonical business-data source of truth. D1 remains the transactional workflow mirror that enforces relational and domain rules. The design deliberately separates editable conference records from authentication, authorization, binary storage, and delivery mechanics.

Airtable canonical business records	Cloudflare operational state
Organizations, events, memberships, and invitations	Better Auth passwords, accounts, sessions, and verification/reset values
CFP forms, versions, fields/configuration, proposals, participants, and rosters	Authorization policy, Worker secrets, connector credentials, and webhook MAC material
Reviewer groups/membership, rounds, rubrics, assignments, and review evidence	Raw R2 headshot, slide, and supporting-file bytes
Speaker profiles; task templates/instances/forms/responses; safe upload metadata; task comments	Outbox/Queue/DLQ leases, attempts, retry timing, and transport bookkeeping
Rooms, tracks, sessions, resources, embeds, message templates, reminder rules, and audit history	Airtable connection cursors, hashes, conflict bookkeeping, and runtime health details

Canonical format

Conference business rows are projected into a Records table as canonical JSON with stable external keys, entity identity, content hashes, timestamps, and tombstones. Do not change keys, entity types, hashes, or Deleted state by hand.

Direct edit policy

- Allowed: only registry-approved descriptive fields, validated against the same application domain rules.
- Blocked into conflict: invalid JSON, unknown entity, referential change, protected state, direct deletion, or unsupported mutation.
- Protected lifecycle work belongs in the app or in an implemented, validated, idempotent Workflow Command adapter.

Provision safely with least privilege

Phase	Required operator action	Fail-closed evidence
1. Isolate	Use one dedicated base for the deployed environment. Current release supports one enabled environment-global base; leave connection event_id null.	No base reuse across demo, pilot, or production.
2. Token	Create a base-restricted PAT with record read/write, schema read, and webhook manage. Add schema write only while tables must be created, then remove it.	Down-scoped PAT can still read/write intended base and cannot reach unrelated bases.
3. Callback	Provision using the exact deployed App origin, not localhost and not the demo origin. Rerun provisioning when the target origin changes.	Webhook callback resolves to the intended environment.
4. Artifact	Let the script write the mode-0600 gitignored provisioning artifact. Read IDs/secrets from it only into protected runtime setup.	Artifact, PAT, and secret values are absent from Git and logs.
5. Connection	Apply migrations, create one enabled connection in D1 with authority d1 and status syncing, then install secrets on the correct Workers.	Jobs receives PAT only; App receives webhook MAC only.
6. Config	Enable Airtable and configure the expected base, d1 default authority, and request limit on App/Jobs.	Configuration/readiness reports expected non-secret state.

Secret rule

Never paste the PAT, webhook MAC secret, or provisioning artifact into tickets, PDFs, screenshots, chat, source control, CI output, or organizer feedback. Rotate immediately if exposed.

Required PAT scopes

- data.records:read
- data.records:write
- schema.bases:read
- webhook:manage

11 / AIRTABLE CUTOVER

Make source-of-truth activation prove itself

Provisioning creates or validates tables and webhook metadata; it does not make Airtable authoritative. Start in D1 authority. Use Workflow Commands to request a full reconcile and later the guarded authority change. The authority switch must refuse to proceed unless the environment is demonstrably caught up and healthy.

Gate	Must be true before <code>set_authority</code> to airtable
Deployment	Callback points to the exact deployed App origin; App and Jobs contain the right non-secret configuration and separate secrets.
Reconcile	A fresh <code>full_reconcile</code> completed and enumerated all registered business records.
Drain	No pending sync work, no claimed/in-flight work, no dead changes, and no stalled retry window.
Conflicts	Zero unresolved Airtable conflicts.
Connection	Webhook and token checks are healthy; cursor advances safely; connection is not degraded or blocked.
Integrity	Counts, stable keys, entity types, hashes, and tombstones match the D1 workflow mirror.
Command	A unique idempotent Pending Workflow Command requests <code>set_authority</code> with authority <code>airtable</code> .
Round trip	One approved descriptive field changes in Airtable, webhook reconciliation updates D1/app, and the original can be restored.

No green status, no cutover

If pending, dead, conflict, webhook, token, schema, cursor, or reconciliation evidence is not clean, leave authority at D1. Do not force a database flag or edit the connection row to bypass the command guard.

12 / AIRTABLE OPERATIONS

Safe edits, commands, conflicts, and recovery

Situation	Correct action	Never do
Edit event copy	Change only an explicitly allowlisted descriptive field; wait for healthy reconciliation; verify in app.	Do not change External Key, Entity Type, Canonical JSON structure, or hash columns casually.
Decision/publication/task state	Use Conference Ops. Use Workflow Commands only where a matching adapter is documented.	Do not raw-edit acceptance, permissions, review finality, publication, completion, or deletion state.
Delete business row	Use the application's guarded delete/archive behavior; expect a Deleted tombstone.	Do not delete the canonical Airtable row.
Conflict	Stop related edits, inspect entity/key/reason and app history, correct the source or reconcile through a supported path.	Do not clear conflict rows while leaving invalid remote content.
Rate limit/transient failure	Leave the durable D1 change pending for its recorded retry time; monitor drain.	Do not sleep a Worker, duplicate commands, or rotate a healthy PAT unnecessarily.
Webhook expiry	Let Jobs refresh before the seven-day expiry; reprovision against the same origin if the webhook is missing.	Do not create duplicate callbacks across environments.
Authority rollback	Use a guarded set_authority back to d1, reconcile, diagnose, and preserve evidence.	Do not disable the integration mid-flight and assume nothing was lost.

Current command surface

- Implemented operator adapters: full_reconcile and guarded set_authority.
- Other protected command types are retained and visibly rejected until a domain adapter exists; they are not raw-SQL escape hatches.
- Every command uses a unique idempotency key and a visible Pending/processing/result lifecycle.
- The organizer Airtable panel is a read-only health and escalation surface. It does not expose conflict details; the platform operator owns dead/conflict resolution through the protected runbook and backend evidence.

13 / ARCHITECTURE

Cloudflare workflow mirror plus Airtable records

Layer	Ownership	Purpose
App Worker + Assets	Wrangler	React client, Hono API, Better Auth, public pages, embed, Airtable webhook and organizer status.
D1	Terraform + additive migrations	Transactional workflow mirror, relational constraints, auth metadata, outbox, sync queue, conflict and cursor bookkeeping.
Airtable	Base schema + least-privilege PAT	Canonical conference business records and guarded Workflow Commands.
Private R2	Terraform	Raw headshots, slides, and supporting-document bytes.
Queue + DLQ	Terraform; Jobs consumer	Immediate email/calendar/Airtable transport; durable D1 records remain recoverable.
Jobs Worker + Cron	Wrangler	Outbox delivery, reminders, Airtable batching/retry/reconcile, webhook refresh, and lease recovery.
Realtime Worker/DO	Wrangler	Readiness and event-scoped transport; current business UI uses focus plus bounded polling.
Terraform state	Private R2 backend	Stateful D1/R2/Queue desired state with destruction guards.

Write path

Application workflows validate permissions and state transitions, commit atomically to D1, and enqueue canonical projection. Under Airtable authority, only validated allowlisted descriptive edits flow back into the D1 mirror; protected workflows still use the application/command boundary.

14 / SECURITY AND PRIVACY

Client-safe operating rules

Control	Implemented contract	Client/operator responsibility
Tenant and role scope	Event membership on protected reads/writes; organizer/reviewer/applicant/speaker projections are separate.	Use a separate tester account per persona; report event slug, role, URL, and approximate time.
Public projection	Agenda/speakers/resources/embed use allowlists and published eligibility; ordinary pages deny framing.	Review public preview before publication.
Files	Private R2, MIME/size rules, authorized download, public headshot rechecks, no raw bytes in Airtable.	Use representative non-sensitive files; malware scanning is not yet a broad-launch control.
Messaging	Durable outbox, idempotency, retries, delivery history, and recipient previews.	Send only to approved test recipients; do not infer inbox receipt from queued state.
Secrets	External runtime secrets and gitignored mode-0600 Airtable artifact.	Never screenshot, paste, email, or commit credentials/tokens/links.
Exports	Protected access, accepted/public filters, PII limits, and CSV formula neutralization.	Store exports according to the client's data policy and delete trial copies when finished.

Launch gate

Add route-level rate limiting and Turnstile/CAPTCHA for auth and high-cost writes, plus malware scanning/quarantine and formal retention, before broad anonymous distribution.

How feature and control claims were checked

Evidence lane	Scope	Acceptance rule
Requirements trace	Updated private requirements, original walkthrough, clarified MVP answers, and current Sessionboard learning center.	Firm requirements override screenshot decoration and optional/de-scoped features.
Image analysis	140 of 140 tutorial visuals across participant/organizer reference pages.	Every extracted image processed; visible workflows mapped to product behavior, not copied styling.
Source/control inventory	Routes, API methods, buttons, links, dialogs, disabled states, destructive guards, focus, cancel/Escape, persistence, and projections.	Each named control has an expected outcome or an explicit boundary.
Automated	Unit, API, component, migration replay, schema drift, build, dependency audit, production-local Better Auth/D1 lifecycle, and E2E.	Final integrated revision and CI must be green; candidate counts are not frozen into this PDF.
Persona browser	Organizer, applicant, reviewer, speaker, public, desktop, 375 px, keyboard/focus, overflow, console/network, reload and URL state.	No unreviewed P0/P1 lifecycle blocker on the release revision.
Airtable	Registry, triggers, client batching, webhook cursor, queue/race behavior, validation, conflict policy, provisioning, operator UI, and live round trip.	Authority remains D1 until full reconcile/drain/health/conflict gates pass.
Security/release	Tenant boundaries, formula injection, secrets, migrations, Worker config, version control, CI, and deployment identity.	No secrets staged; exact released source is reproducible and mapped in release evidence.

Control log

The durable audit records the route/control expectation and result, including confirm/cancel paths, disabled states, persistence after reload, role authorization, desktop/mobile layout, and error behavior. Dynamic repeated controls are sampled by workflow class; the audit does not claim to enumerate every possible future data combination.

Independent lanes used to challenge the release

Lane	Responsibility	Contribution
Requirements and visual trace	Google Doc, original YouTube walkthrough, Sessionboard overview/participant/organizer pages, 140-image analysis.	Established controlling acceptance matrix and non-pixel parity boundary.
CFP and revisions	Multi-form portfolio, version pinning, conditional fields, applicant edit states, organizer request-changes, review history.	Closed form/submission parity gaps and locked final states.
Routing and review	Explicit multi-track membership, rubric plan, immutable submitted reviews, queue/final decisions, self-review exclusion.	Prevented invitations from broadening all track access.
Participant collaboration	Task files, versions, scoped downloads, comments, external actions, resources, portal/public views.	Added durable speaker/organizer evidence and safe publishing.
Schedule and communications	Four schedule views, URL state, conflicts, messages, reminders, ICS, sanitized delivery history, CSV export.	Closed organizer-operability and injection gaps.
Airtable core	Canonical schema, change capture, Jobs client, webhook, reconciliation, conflict policy, provisioning and operator status.	Added source-of-truth capability with a fail-closed boundary.
Airtable integrity audit	In-flight queue race, authority readiness, domain validation, connection health, one-base tenancy.	Required CAS-safe draining and blocked unsafe authority transitions.
Security/tenant audit	Authentication, role projection, task/file/resource authorization, CSV formula injection, secrets and migrations.	Found and drove closure of release blockers.
Desktop/mobile audit	Persona journeys, every named control class, focus, Escape, dialogs, overflow, console/network and 375 px.	Drove form portfolio and accessibility corrections.
Root integration	Reconcile shared tree, rerun full gates, source control, release manifest, Worker/Airtable cutover, final PDF.	Single accountable release decision and evidence handoff.

Agent names and internal task identifiers are implementation evidence, not product permissions. No agent is allowed to bypass authentication, disclose secrets, force Airtable authority, or claim a release gate it did not verify.

17 / RELEASE CONTROLS

Version control, deployment identity, and rollback

Artifact	Handoff rule
Version	Product version is 0.2.0. The final source revision, branch/PR, annotated tag, Worker version IDs, migration set, and CI result are recorded in GitHub and the release manifest after the final integrated cutover.
Source	Only intentional source, tests, migrations, docs, and the two public PDFs are staged. Local videos, rendered screenshots, Airtable PAT/artifact, Worker secret files, and generated audit media remain ignored.
Migrations	Additive migrations 0007 through 0010 add Airtable, revision provenance, task comments/external actions, and file/task collaboration. Replay from 0000, double-seed, schema-drift, and FK checks are release gates.
Deployment	Apply migrations before dependent code. Deploy Jobs before App when both change. Install Jobs PAT and App webhook MAC separately. Verify health/readiness before Airtable cutover.
Identity	This PDF intentionally does not guess an unfrozen commit SHA or Worker UUID. Use the pushed Git tag/PR and release manifest as exact machine identity.
Rollback	Roll Worker code to a known-good version; use guarded Airtable authority back to D1 and reconcile; use D1 Time Travel/export only for diagnosed data recovery. Never destroy D1 through Terraform to roll back code.

Release acceptance

Do not describe Airtable as live source of truth merely because the base exists. The released environment must show a healthy connection, completed reconcile, empty work/dead/conflict queues, successful authority command, and reversible round trip.

18 / KNOWN BOUNDARIES

What is intentionally limited or still required

Boundary	Current contract	Before broader production
Abuse	Named, monitored client evaluation.	Rate limits, Turnstile/CAPTCHA, quota alerts, and lockout/abuse telemetry.
Files/data	Representative test uploads; type/size/private-access gates.	Malware scanning/quarantine, formal retention/purge, and backup policy.
Collaboration	Visible workspaces refresh on focus and about every 25 seconds.	Add mutation fanout/client subscriptions only if sub-second collaboration is required.
Calendar	Email with RFC 5545 REQUEST attachment and sequence updates.	Add explicit cancellation/resend if client operations require managed cancel flows.
Airtable topology	One enabled environment-global base; event_id stays null.	Per-event bases/routing require a future isolation design and tests.
Airtable commands	full_reconcile and set_authority adapters; other command types reject visibly.	Implement and test each protected domain adapter before use.
Content	Plain-text resources with optional HTTPS links.	Rich CMS, arbitrary HTML, localization, or approval workflow if later required.
Integrations	Protected CSV/JSON exports; Accelevents skipped.	Implement only with explicit API access and a supported data contract.
Product scope	Conference program administration.	Payments, ticketing, CRM/marketing, multilingual portals, and AI decisions are not claimed.

Email wording

The UI may report a durable queue and delivery ledger. Actual target delivery requires a configured sender/binding and controlled mailbox proof; a queued status alone is not a delivery guarantee.

A clean handoff checklist

Prospective organizer

- Create and verify your own account; do not use the Apricot operator account.
- Create an isolated event with representative dates and content; reload to prove persistence.
- Complete the 10-step runway with distinct reviewer/applicant/speaker accounts.
- Check public agenda, speakers, resources, and embed from a signed-out window.
- Send email/calendar only to approved test recipients and retain no token-bearing screenshots.

Airtable operator

- Confirm dedicated base, least-privilege PAT, exact callback origin, separate Worker secrets, and ignored artifact.
- Start D1 authority; full reconcile; wait for zero pending/dead/conflicts; verify webhook/connection health.
- Use guarded set_authority; complete one allowed descriptive edit round trip; preserve audit evidence.

Release owner

- Integrated lint/type/unit/build/migrations/schema/smoke/dependency/E2E gates and staged secret scan are green.
- Intentional staged diff reviewed; commit/tag/PR pushed; CI green; Worker IDs and migration set recorded.
- Pilot readiness, D1 integrity, email/runtime status, and Airtable cutover checked after deploy.

Stop condition

Any failed authority, tenant, migration, secret, conflict, queue-drain, or final lifecycle gate is a no-cutover result. Keep the prior safe authority/version and report the evidence.

Routes, documents, and useful feedback

Item	Location/use
Prospective-client pilot	https://conference-ops-pilot-app.techfren.workers.dev
Seeded persona demo	https://conference-ops-staging-app.techfren.workers.dev - walkthrough only; not proof of persistent Airtable authority.
Organizer guide	https://conference-ops-pilot-app.techfren.workers.dev/conference-ops-organizer-trial-guide.pdf
Product parity record	docs/SESSIONBOARD-PARITY.md
Release audit	docs/RELEASE-AUDIT-0.2.0.md
Airtable runbook	infra/AIRTABLE.md
Architecture/security	ARCHITECTURE.md and SECURITY.md
Audit evidence	output/audit/ - visual analysis, control matrix, persona evidence, security/release findings, and agent ledger.

Send useful feedback

- What were you trying to accomplish?
- Which event slug, persona/role, page URL, browser, and approximate time were involved?
- What happened, what did you expect, and did a reload change it?
- Attach a screenshot only after removing names, emails, private files, reset/invitation links, and Airtable details.

Start here

Open <https://conference-ops-pilot-app.techfren.workers.dev>, create your own account, and follow the in-product Control Room runway or the separate organizer guide.