

# Conference Ops

Implementation record, persona workflows, Sessionboard comparison, Airtable operating boundary, release controls, and prospective-client handoff.

| DOCUMENT      | PRODUCT              | USE                         |
|---------------|----------------------|-----------------------------|
| Final handoff | Conference Ops 0.2.0 | Live Airtable / named trial |



OPEN THE PROSPECTIVE-CLIENT PILOT

<https://conference-ops-pilot-app.techfren.workers.dev>

Create and verify your own account. Do not use or share an operator credential.

01 / ORIENTATION

# What is being handed off

Conference Ops is a Cloudflare-native conference program workspace. It covers the lifecycle from a versioned call for proposals through track-based review, controlled decisions, speaker onboarding, conflict-aware scheduling, publication, communications, and Airtable-backed business records. This release is shaped by the customer's clarified MVP and rechecked against Sessionboard's participant and organizer learning material. It is not a pixel-for-pixel clone.

**Live pilot status**

The monitored pilot is live with healthy Airtable authority. Program setup visibly reports Healthy and 'Airtable is the current source of truth,' including both sync directions. This remains a small, named evaluation; add abuse controls, formal file scanning, and production retention/alerting before broad anonymous promotion.

| Audience                     | Use                                                                                                                     |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Prospective organizer        | Read persona workflows and the separate organizer guide; create an isolated event and use representative data.          |
| Participant/reviewer/speaker | Use a separate verified account for each persona; follow only the event links sent by the organizer.                    |
| Airtable operator            | Follow the fail-closed provisioning and cutover sequence. Never treat provisioning alone as source-of-truth activation. |
| Engineer/release owner       | Use the release gates, architecture boundary, known limits, and version-control handoff.                                |

## Document map

- Pages 3-9: requirements, complete feature ledger, persona workflows, and organizer runway.
- Pages 10-13: Airtable data boundary, commissioning, cutover, recovery, and safe editing.
- Pages 14-19: architecture, privacy, audit method, agents, release controls, and known boundaries.
- Pages 20-21: client acceptance script and handoff index.

02 / ACCEPTANCE AUTHORITY

# What Sessionboard parity means here

The product was audited against the updated customer requirements and the current Sessionboard overview, participant, and organizer learning pages. Every available visual on those pages was inspected as audit input: 140 of 140 reference images were processed without image-analysis failure. The customer's explicit clarifications control where Sessionboard is broader than the requested MVP.

| Clarified requirement | Conference Ops contract                                                                                                               | Status                                    |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| Forms                 | Basic one-level equals/contains conditional logic is sufficient; multiple independently versioned CFPs are supported.                 | Implemented                               |
| Routing               | Talks select one or more tracks; organizers explicitly map reviewers to one or more tracks.                                           | Implemented                               |
| Review                | Unreviewed to Approve, Maybe, or Deny, with evidence, weighted scoring, draft save, and final lock.                                   | Implemented                               |
| Acceptance            | Create the linked session, speaker access, configured onboarding work, audit record, and decision message.                            | Implemented                               |
| Onboarding            | Hotel stay and flight reimbursement plus profile, talk details, media, files, announcements, colleague invites, and external actions. | Implemented                               |
| Email/calendar        | Real MVP delivery through durable Cloudflare Email workflows and RFC 5545 calendar REQUEST attachments.                               | Operational pilot; receipt check required |
| Schedule              | Day/room plus drag/drop and conflict detection is sufficient; list, week, and conflict views are also present.                        | Implemented                               |
| Agent                 | Small useful read-only readiness assistant; admin UI remains the priority.                                                            | Implemented                               |
| Airtable              | Canonical business records, guarded descriptive edits, webhook reconcile, conflicts, and Workflow Commands.                           | LIVE; healthy Airtable authority          |
| Accelevents           | Explicitly skipped; controlled exports remain available.                                                                              | Intentional scope                         |

## Human-readable references

- Product video overview: <https://learn.sessionboard.com/videos/overview>
- Participant overview: <https://learn.sessionboard.com/participants/overview>
- Organizer overview: <https://learn.sessionboard.com/get-started/overview>

03 / FEATURE LEDGER

# Identity, events, forms, and submissions

| Area               | Implemented behavior                                                                                                                                                 | Use/guard                                                                                                           |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Identity           | Email/password signup, verification, sign-in/out, token-aware password reset, invitations, speaker claims, and safe return routing.                                  | Roles are event-scoped; one user may hold multiple roles without impersonating other people.                        |
| Event setup        | Organization, event name/slug/purpose, dates, timezone, venue, website, accent, isolated workspace, and editable details.                                            | CFP close must precede event start; invalid relationships are blocked in browser and API.                           |
| Fresh defaults     | Draft CFP, review round/group, room, track, hotel and flight forms, profile/slides/calendar tasks, five message templates, and two reminder rules.                   | Defaults are organizer-editable, not hardcoded runtime decisions.                                                   |
| CFP portfolio      | Create, switch, clone, independently version, publish, close, and copy a form-specific public link.                                                                  | Published versions are immutable; applicant drafts stay pinned to their starting version.                           |
| Form builder       | Text, long text, email, URL, select, multiselect, checkbox, information blocks, required rules, options, limits, and one-level conditions.                           | Visible-only validation, server allowlists, long-text budget, concurrency checks, and no public CFP file questions. |
| Applicant draft    | Browser and account drafts, resume, multiple submissions, one or more tracks, participant minimum/maximum, distinct-email co-speakers, confirmation, and withdrawal. | Owner-scoped; submission caps and final consent are server-enforced.                                                |
| Applicant revision | Reopen a non-final submission before the pinned form closes, or respond to an organizer change request and resubmit.                                                 | Accepted, rejected, or session-backed submissions stay locked. Submitted review evidence remains historical.        |

Routing rule

A reviewer invitation does not silently grant all tracks. Organizers explicitly map each track or reviewer group. A multi-track proposal receives the union of eligible reviewers, while owners and claimed co-speakers are excluded. Routing lane identifiers are comma-free so serialized multi-lane membership cannot split or merge ambiguously.

# Review, decisions, and automatic activation

| Area             | Implemented behavior                                                                                                                                                                         | Durable result                                                                                                                                          |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Review setup     | Organizer-configurable active scoring plan, criteria, weights, evidence expectations, track groups, and reviewer membership.                                                                 | Assignments are explicit and event-scoped.                                                                                                              |
| Reviewer desk    | Assignment queue, criterion scoring, note/evidence, recommendation, server-computed weighted preview, draft save/reload, and final submit.                                                   | Submitted review is immutable; applicant projections never expose scores or committee details.                                                          |
| Decision states  | Submitted/under review to Accept queue, Decline queue, or Waitlist; final Accept or Reject; optional organizer note and request-changes path.                                                | Audit trail records material state changes; final decisions are guarded and immutable.                                                                  |
| Request changes  | Organizer sends a revision note and applicant edit path; eligible applicant can revise before close.                                                                                         | Open review work is revoked; the new revision gets fresh revision-aware assignments; prior submitted review evidence remains organizer-visible history. |
| Final acceptance | One guarded workflow creates a linked unscheduled session, activates eligible speaker access, instantiates configured tasks, records audit evidence, and persists the decision email intent. | No partial acceptance state if the guarded workflow fails.                                                                                              |
| Final rejection  | Records the final decision and configured communication intent without creating session or onboarding work.                                                                                  | Applicant sees final status; active review work is closed.                                                                                              |

**Minimum workflow**

The customer asked for Unreviewed to Approve, Maybe, or Deny. Conference Ops adds staged decision queues and a controlled request-changes cycle without requiring a complex multi-round orchestration product.

05 / FEATURE LEDGER

# Speaker onboarding, files, collaboration, and resources

| Area             | Implemented behavior                                                                                                                                     | Privacy/visibility                                                                                |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Speaker access   | Verified-email claim, explicit speaker portal, proposal/session-targeted work, and multi-role account routing.                                           | Only the eligible account and event organizers can access private work.                           |
| Profile          | Bio, title, company, city, pronouns, publication consent, headshot upload/replace, completeness, and public eligibility.                                 | Public only after consent and published-session eligibility; private email/storage keys excluded. |
| Task plans       | Organizer-authored manual, profile, questionnaire, file request, calendar acknowledgement, and external HTTPS action tasks.                              | Acceptance instantiates the event's configured task plan for the relevant speaker/session.        |
| Default examples | Hotel stay, flight reimbursement, finalize talk description, bio/photo, slides, calendar, announce participation, and invite colleagues with a discount. | Organizers may edit, remove, or add templates before acceptance.                                  |
| Files            | Private task-scoped upload, replace, chronological version history, current/prior download, metadata, and organizer/speaker evidence.                    | Raw bytes remain in private R2; Airtable receives safe metadata, never file bytes.                |
| Comments         | Organizer and speaker task discussion with durable chronological history.                                                                                | Event/task authorization on read and write.                                                       |
| Speaker Ops      | Roster search, exact profile/task exceptions, deep links, reminders, reopen/complete, comments, and file evidence.                                       | Organizer only; rejected/waitlisted work does not pollute outstanding views.                      |
| Resources        | Organizer creates plain-text guides with optional HTTPS references, drafts/publishes them, and exposes them in portal/public index.                      | Safe text rendering; no arbitrary rich HTML.                                                      |

06 / FEATURE LEDGER

# Scheduling, publication, communications, and exports

| Area             | Implemented behavior                                                                                                                   | Guard                                                                                             |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Venue model      | Organizer CRUD for rooms and tracks, duplicate checks, capacity/color, and in-use delete guards.                                       | All entities are event-scoped.                                                                    |
| Sessions         | Accepted-proposal conversion plus direct guaranteed/sponsor/program sessions; break/networking formats can omit a speaker.             | Proposal conversion is one-to-one and guarded.                                                    |
| Schedule         | List, day/room, week, and conflicts views; day/track filters; URL-persisted view state; explicit placement and drag/drop.              | Event-window, room, track, and speaker collisions checked in client and server.                   |
| Overrides        | Alternate placement or audited override with a durable reason; reschedule and calendar sequence bump.                                  | Adjacency is allowed; unreasoned collisions are blocked.                                          |
| Publish          | Atomic readiness/preflight and agenda publication; later published schedule changes update the live program.                           | Only published, eligible records reach public projections.                                        |
| Public           | Agenda, day/track navigation, favorites, speaker gallery, resources, submit/portal links, and exact event-scoped iframe embed.         | Public allowlists exclude accounts, email, reviews, private files, and raw storage keys.          |
| Messages         | Editable submission, acceptance, rejection, task-reminder, and calendar templates; scheduled draft/task reminders; recipient previews. | Durable D1 outbox before Queue delivery, idempotency, bounded retry, dead convergence.            |
| History/calendar | Organizer-safe delivery history; RFC 5545 METHOD:REQUEST with stable UID and incremented SEQUENCE.                                     | A queued/sent status is not an inbox-read guarantee; target delivery needs runtime configuration. |
| Exports          | Protected speakers.csv, sessions.csv, and program.json for portable handoff.                                                           | CSV formula prefixes are neutralized; accepted/public and PII rules apply.                        |
| Assistant        | Read-only, event-grounded readiness recommendations with workflow deep links.                                                          | Cannot mutate, send, decide, or bypass permissions.                                               |

07 / PERSONA WORKFLOWS

# What each user actually does

| Persona            | Start                                                | Core flow                                                                                               | Finish                                                                                             |
|--------------------|------------------------------------------------------|---------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Organizer          | Create/verify account; create event.                 | Configure CFPs, routing, rubric, onboarding, resources, messages, venue, then invite staff.             | Decide, schedule, publish, monitor, export, and inspect Airtable health.                           |
| Applicant          | Open form-specific CFP link; verify account.         | Save draft, answer visible questions, select tracks, add speakers, consent, submit, revise if eligible. | See status, respond to changes, withdraw when allowed, or move into speaker work after acceptance. |
| Reviewer           | Accept invitation with a distinct account.           | Open assigned tracks only; score rubric, add evidence, save draft, choose Approve/Maybe/Deny, submit.   | Final evidence becomes read-only; organizer owns the final decision.                               |
| Speaker            | Claim with the invited/accepted email.               | Complete profile, hotel/flight and other forms, external actions, files, versions, comments, and tasks. | Confirm readiness and use participant resources; organizer publishes eligible profile/session.     |
| Participant/public | Open event agenda, speaker, or resource URL.         | Browse day/track, favorite sessions locally, view published speakers/resources, use embed.              | No account/private workflow data is exposed.                                                       |
| Airtable operator  | Provision one environment base with least privilege. | Reconcile, drain, review health/conflicts, switch authority through Workflow Command only.              | Run a reversible descriptive-field round trip and retain D1 mirror/operational controls.           |

**Account rule**

Use separate verified people for organizer, reviewer, applicant, and speaker tests. Self-review exclusion is intentional. Never share an organizer password, reset link, invitation token, Airtable PAT, webhook secret, or raw provisioning artifact.

08 / ORGANIZER RUNWAY

# The shortest complete evaluation

| Step | Organizer action                                                                                           | Expected evidence                                                                         |
|------|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| 1    | Create the event and verify details after reload.                                                          | Private event plus seeded operational defaults.                                           |
| 2    | Create or choose a CFP; configure fields/track question; publish and copy that form's link.                | Published immutable version and form-specific URL.                                        |
| 3    | Map each track to explicit reviewer coverage; configure rubric and onboarding plan.                        | No uncovered track; no reviewer granted all tracks by invitation alone.                   |
| 4    | Invite a distinct reviewer; use another account to submit a multi-track proposal.                          | Eligible assignments only; owner excluded.                                                |
| 5    | Reviewer saves and submits Approve/Maybe/Deny evidence.                                                    | Weighted final review is read-only.                                                       |
| 6    | Request changes or stage/finalize the decision.                                                            | Revision loop or automatic accepted session/tasks/message intent.                         |
| 7    | Speaker claims access, completes profile/forms, comments, and uploads/replaces a representative file.      | Private current/prior file evidence and task readiness.                                   |
| 8    | Place session in day/room; intentionally test a conflict; reschedule or override with reason.              | Conflict-safe or audited placement visible in all views.                                  |
| 9    | Publish agenda; check public agenda/speakers/resources/embed; queue a controlled message/calendar; export. | Published-only public output, durable delivery history, safe export.                      |
| 10   | Inspect the commissioned Airtable status, then verify one allowed descriptive edit round trip.             | Healthy Airtable authority, zero queued/failed/dead/conflicts, no protected-state bypass. |

**Test data**

Use synthetic or representative content. Do not upload customer-confidential, regulated, executable, or irreplaceable files during the monitored evaluation.

09 / AIRTABLE BOUNDARY

# What is canonical and what stays operational

Airtable is the live canonical business-data source of truth for the pilot. D1 remains the transactional workflow mirror that enforces relational and domain rules. The design deliberately separates editable conference records from authentication, authorization, binary storage, delivery mechanics, and connector bookkeeping.

| Airtable canonical business records                                                              | Cloudflare operational state                                                          |
|--------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Organizations, events, memberships, and invitations                                              | Better Auth passwords, accounts, sessions, and verification/reset values              |
| CFP forms, versions, fields/configuration, proposals, participants, and rosters                  | Authorization policy, Worker secrets, connector credentials, and webhook MAC material |
| Reviewer groups/membership, rounds, rubrics, assignments, and review evidence                    | Raw R2 headshot, slide, and supporting-file bytes                                     |
| Speaker profiles; task templates/instances/forms/responses; safe upload metadata; task comments  | Outbox/Queue/DLQ leases, attempts, retry timing, and transport bookkeeping            |
| Rooms, tracks, sessions, resources, embeds, message templates, reminder rules, and audit history | Airtable connection cursors, hashes, conflict bookkeeping, and runtime health details |

Canonical format

Conference business rows are projected into a Records table as canonical JSON with stable external keys, entity identity, content hashes, timestamps, and tombstones. Do not change keys, entity types, hashes, or Deleted state by hand.

## Direct edit policy

- Allowed: only registry-approved descriptive fields, validated against the same application domain rules.
- Blocked into conflict: invalid JSON, unknown entity, referential change, protected state, direct deletion, or unsupported mutation.
- Protected lifecycle work belongs in the app or in an implemented, validated, idempotent Workflow Command adapter.

10 / AIRTABLE COMMISSIONING

# Reusable provisioning procedure

Pilot status: commissioning is complete and Airtable authority is live. Do not reprovision, replace the connection, or change authority during evaluation unless the protected operator runbook requires recovery.

| Phase         | Required operator action                                                                                                                                  | Fail-closed evidence                                                                 |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| 1. Isolate    | Use one dedicated base for the deployed environment. Current release supports one enabled environment-global base; leave connection event_id null.        | No base reuse across demo, pilot, or production.                                     |
| 2. Token      | Create a base-restricted PAT with record read/write, schema read, and webhook manage. Add schema write only while tables must be created, then remove it. | Down-scoped PAT can still read/write intended base and cannot reach unrelated bases. |
| 3. Callback   | Provision using the exact deployed App origin, not localhost and not the demo origin. Rerun provisioning when the target origin changes.                  | Webhook callback resolves to the intended environment.                               |
| 4. Artifact   | Let the script write the mode-0600 gitignored provisioning artifact. Read IDs/secrets from it only into protected runtime setup.                          | Artifact, PAT, and secret values are absent from Git and logs.                       |
| 5. Connection | Apply migrations, create one enabled connection in D1 with authority d1 and status syncing, then install secrets on the correct Workers.                  | Jobs receives PAT only; App receives webhook MAC only.                               |
| 6. Config     | Enable Airtable and configure the expected base, d1 default authority, and request limit on App/Jobs.                                                     | Configuration/readiness reports expected non-secret state.                           |

Secret rule

Never paste the PAT, webhook MAC secret, or provisioning artifact into tickets, PDFs, screenshots, chat, source control, CI output, or organizer feedback. Rotate immediately if exposed.

## Required PAT scopes

- data.records:read
- data.records:write
- schema.bases:read
- webhook:manage

11 / AIRTABLE CUTOVER

# Reusable authority-change gates

Pilot status: cutover is complete and the Program setup card reports Healthy with Airtable as the current source of truth. For a future environment or recovery, provisioning alone is never authority. Start in D1, request full\_reconcile, and use the guarded authority command only after every gate below passes.

| Gate       | Must be true before set_authority to airtable                                                                                   |
|------------|---------------------------------------------------------------------------------------------------------------------------------|
| Deployment | Callback points to the exact deployed App origin; App and Jobs contain the right non-secret configuration and separate secrets. |
| Reconcile  | A fresh full_reconcile completed and enumerated all registered business records.                                                |
| Drain      | No pending sync work, no claimed/in-flight work, no dead changes, and no stalled retry window.                                  |
| Conflicts  | Zero unresolved Airtable conflicts.                                                                                             |
| Connection | Webhook and token checks are healthy; cursor advances safely; connection is not degraded or blocked.                            |
| Integrity  | Counts, stable keys, entity types, hashes, and tombstones match the D1 workflow mirror.                                         |
| Command    | A unique idempotent Pending Workflow Command requests set_authority with authority airtable.                                    |
| Round trip | One approved descriptive field changes in Airtable, webhook reconciliation updates D1/app, and the original can be restored.    |

Verified live proof

The pilot has 140/140 records and maps with unique external keys and matching hashes, a natural webhook, zero queued, failed, or dead changes, and zero open conflicts. Synthetic Evaluation Sandbox tests proved Airtable description to D1/app and organizer Event details UI to Airtable; the original value was restored. If any gate later degrades, pause edits and use the protected recovery path.

12 / AIRTABLE OPERATIONS

# Safe edits, commands, conflicts, and recovery

| Situation                       | Correct action                                                                                                           | Never do                                                                                              |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Edit event copy                 | Change only an explicitly allowlisted descriptive field; wait for healthy reconciliation; verify in app.                 | Do not change External Key, Entity Type, Canonical JSON structure, or hash columns casually.          |
| Decision/publication/task state | Use Conference Ops. Use Workflow Commands only where a matching adapter is documented.                                   | Do not raw-edit acceptance, permissions, review finality, publication, completion, or deletion state. |
| Delete business row             | Use the application's guarded delete/archive behavior; expect a Deleted tombstone.                                       | Do not delete the canonical Airtable row.                                                             |
| Conflict                        | Stop related edits, inspect entity/key/reason and app history, correct the source or reconcile through a supported path. | Do not clear conflict rows while leaving invalid remote content.                                      |
| Rate limit/transient failure    | Leave the durable D1 change pending for its recorded retry time; monitor drain.                                          | Do not sleep a Worker, duplicate commands, or rotate a healthy PAT unnecessarily.                     |
| Webhook expiry                  | Let Jobs refresh before the seven-day expiry; reprovision against the same origin if the webhook is missing.             | Do not create duplicate callbacks across environments.                                                |
| Authority rollback              | Use a guarded set_authority back to d1, reconcile, diagnose, and preserve evidence.                                      | Do not disable the integration mid-flight and assume nothing was lost.                                |

## Current command surface

- Implemented operator adapters: full\_reconcile and guarded set\_authority.
- Other protected command types are retained and visibly rejected until a domain adapter exists; they are not raw-SQL escape hatches.
- Every command uses a unique idempotency key and a visible Pending/processing/result lifecycle.
- The organizer Airtable panel is a read-only health and escalation surface. It does not expose conflict details; the platform operator owns dead/conflict resolution through the protected runbook and backend evidence.

13 / ARCHITECTURE

# Cloudflare workflow mirror plus Airtable records

| Layer               | Ownership                         | Purpose                                                                                                                    |
|---------------------|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| App Worker + Assets | Wrangler                          | React client, Hono API, Better Auth, public pages, embed, Airtable webhook and organizer status.                           |
| D1                  | Terraform + additive migrations   | Transactional workflow mirror, relational constraints, auth metadata, outbox, sync queue, conflict and cursor bookkeeping. |
| Airtable            | Base schema + least-privilege PAT | Canonical conference business records and guarded Workflow Commands.                                                       |
| Private R2          | Terraform                         | Raw headshots, slides, and supporting-document bytes.                                                                      |
| Queue + DLQ         | Terraform; Jobs consumer          | Immediate email/calendar/Airtable transport; durable D1 records remain recoverable.                                        |
| Jobs Worker + Cron  | Wrangler                          | Outbox delivery, reminders, Airtable batching/retry/reconcile, webhook refresh, and lease recovery.                        |
| Realtime Worker/DO  | Wrangler                          | Readiness and event-scoped transport; current business UI uses focus plus bounded polling.                                 |
| Terraform state     | Private R2 backend                | Stateful D1/R2/Queue desired state with destruction guards.                                                                |

Write path

Application workflows validate permissions and state transitions, commit atomically to D1, and enqueue canonical projection. Under Airtable authority, only validated allowlisted descriptive edits flow back into the D1 mirror; protected workflows still use the application/command boundary.

14 / SECURITY AND PRIVACY

# Client-safe operating rules

| Control               | Implemented contract                                                                                       | Client/operator responsibility                                                                 |
|-----------------------|------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| Tenant and role scope | Event membership on protected reads/writes; organizer/reviewer/applicant/speaker projections are separate. | Use a separate tester account per persona; report event slug, role, URL, and approximate time. |
| Public projection     | Agenda/speakers/resources/embed use allowlists and published eligibility; ordinary pages deny framing.     | Review public preview before publication.                                                      |
| Files                 | Private R2, MIME/size rules, authorized download, public headshot rechecks, no raw bytes in Airtable.      | Use representative non-sensitive files; malware scanning is not yet a broad-launch control.    |
| Messaging             | Durable outbox, idempotency, retries, delivery history, and recipient previews.                            | Send only to approved test recipients; do not infer inbox receipt from queued state.           |
| Secrets               | External runtime secrets and gitignored mode-0600 Airtable artifact.                                       | Never screenshot, paste, email, or commit credentials/tokens/links.                            |
| Exports               | Protected access, accepted/public filters, PII limits, and CSV formula neutralization.                     | Store exports according to the client's data policy and delete trial copies when finished.     |

**Launch gate**

Add route-level rate limiting and Turnstile/CAPTCHA for auth and high-cost writes, plus malware scanning/quarantine and formal retention, before broad anonymous distribution.

# How feature and control claims were checked

| Evidence lane            | Scope                                                                                                                                                  | Acceptance rule                                                                                                       |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Requirements trace       | Updated private requirements, original walkthrough, clarified MVP answers, and current Sessionboard learning center.                                   | Firm requirements override screenshot decoration and optional/de-scoped features.                                     |
| Image analysis           | 140 of 140 tutorial visuals across participant/organizer reference pages.                                                                              | Every extracted image processed; visible workflows mapped to product behavior, not copied styling.                    |
| Source/control inventory | Routes, API methods, buttons, links, dialogs, disabled states, destructive guards, focus, cancel/Escape, persistence, and projections.                 | Each named control has an expected outcome or an explicit boundary.                                                   |
| Automated                | Unit, API, component, migration replay, schema drift, build, dependency audit, production-local Better Auth/D1 lifecycle, and E2E.                     | pnpm verify passed 94 files / 474 tests; prior full E2E passed 40 with 6 intentional skips.                           |
| Persona browser          | Organizer, applicant, reviewer, speaker, public, desktop, 375 px, keyboard/focus, overflow, console/network, reload and URL state.                     | No unreviewed P0/P1 lifecycle blocker on the release revision.                                                        |
| Airtable                 | Registry, triggers, client batching, webhook cursor, queue/race behavior, validation, conflict policy, provisioning, operator UI, and live round trip. | D1 was retained until every cutover gate passed; the pilot is now healthy and Airtable-authoritative.                 |
| Security/release         | Tenant boundaries, formula injection, secrets, migrations, Worker config, version control, CI, and deployment identity.                                | PR #1 required checks were green at handoff; public artifacts exclude secrets and private infrastructure identifiers. |

Control log

The durable audit records the route/control expectation and result, including confirm/cancel paths, disabled states, persistence after reload, role authorization, desktop/mobile layout, and error behavior. Dynamic repeated controls are sampled by workflow class; the audit does not claim to enumerate every possible future data combination.

# Independent lanes used to challenge the release

| Lane                          | Responsibility                                                                                                                                  | Contribution                                                                                                                    |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Requirements and visual trace | Google Doc, original YouTube walkthrough, Sessionboard overview/participant/organizer pages, 140-image analysis.                                | Established controlling acceptance matrix and non-pixel parity boundary.                                                        |
| CFP and revisions             | Multi-form portfolio, version pinning, conditional fields, applicant edit states, organizer request-changes, review history.                    | Closed form/submission parity gaps and locked final states.                                                                     |
| Routing and review            | Explicit multi-track membership, rubric plan, immutable submitted reviews, queue/final decisions, self-review exclusion.                        | Prevented invitations from broadening all track access.                                                                         |
| Participant collaboration     | Task files, versions, scoped downloads, comments, external actions, resources, portal/public views.                                             | Added durable speaker/organizer evidence and safe publishing.                                                                   |
| Schedule and communications   | Four schedule views, URL state, conflicts, messages, reminders, ICS, sanitized delivery history, CSV export.                                    | Closed organizer-operability and injection gaps.                                                                                |
| Airtable core                 | Canonical schema, change capture, Jobs client, webhook, reconciliation, conflict policy, provisioning and operator status.                      | Added source-of-truth capability with a fail-closed boundary.                                                                   |
| Airtable integrity audit      | In-flight queue race, authority readiness, domain validation, connection health, one-base tenancy, scheduled isolation, and self-echo handling. | Closed queue races and unsafe authority transitions; self/no-op echoes now preserve map.last_synced_at alignment with Airtable. |
| Security/tenant audit         | Authentication, role projection, task/file/resource authorization, CSV formula injection, secrets and migrations.                               | Found and drove closure of release blockers.                                                                                    |
| Desktop/mobile audit          | Persona journeys, every named control class, focus, Escape, dialogs, overflow, console/network and 375 px.                                      | Drove form portfolio and accessibility corrections.                                                                             |
| Root integration              | Reconcile shared tree, rerun full gates, source control, release manifest, Worker/Airtable cutover, final PDF.                                  | Single accountable release decision and evidence handoff.                                                                       |

Agent names and internal task identifiers are implementation evidence, not product permissions. No agent is allowed to bypass authentication, disclose secrets, force Airtable authority, or claim a release gate it did not verify.

17 / RELEASE CONTROLS

# Version control, deployment identity, and rollback

| Artifact     | Handoff rule                                                                                                                                                                                                                                   |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version      | Product version is 0.2.0. PR #1 required checks were green at handoff; the approval-gated remote infrastructure plan is intentionally skipped.                                                                                                 |
| Source       | Intentional source, tests, migrations, docs, and the two public PDFs form the handoff. Local videos, rendered audit media, Airtable artifacts, and Worker secret files remain outside the public packet.                                       |
| Migrations   | Additive migrations 0000 through 0011 replay cleanly, including Airtable, revision-aware reviews, task collaboration, and lifecycle hardening.                                                                                                 |
| Deployment   | Jobs Worker version 49e1d03d-313e-4179-8265-40bbe9e194ad is deployed. App redeploy follows PDF generation, so its final version is intentionally not hardcoded here. Apply migrations before dependent code and keep Worker secrets separated. |
| Remediations | Scheduled reminder preparation no longer blocks later Airtable/outbox work. Self/no-op echoes preserve map.last_synced_at so it stays aligned with Airtable; the later valid-edit sequence is regression-tested.                               |
| Rollback     | Roll Worker code to a known-good version; use guarded Airtable authority back to D1 and reconcile; use D1 Time Travel/export only for diagnosed data recovery. Never destroy D1 through Terraform to roll back code.                           |

Release acceptance

Verified live: Airtable authority is active and healthy, 140/140 records/maps reconcile with unique keys and matching hashes, queue/dead/conflict counts are zero, the natural webhook is active, and both directions passed a restored Evaluation Sandbox test. The UI remains the authority for current health.

18 / KNOWN BOUNDARIES

# What is intentionally limited or still required

| Boundary          | Current contract                                                               | Before broader production                                                                   |
|-------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| Abuse             | Named, monitored client evaluation.                                            | Rate limits, Turnstile/CAPTCHA, quota alerts, and lockout/abuse telemetry.                  |
| Files/data        | Representative test uploads; type/size/private-access gates.                   | Malware scanning/quarantine, formal retention/purge, and backup policy.                     |
| Collaboration     | Visible workspaces refresh on focus and about every 25 seconds.                | Add mutation fanout/client subscriptions only if sub-second collaboration is required.      |
| Calendar          | Email with RFC 5545 REQUEST attachment and sequence updates.                   | Add explicit cancellation/resend if client operations require managed cancel flows.         |
| Airtable topology | One enabled environment-global base; event_id stays null.                      | Per-event bases/routing require a future isolation design and tests.                        |
| Airtable commands | full_reconcile and set_authority adapters; other command types reject visibly. | Implement and test each protected domain adapter before use.                                |
| Content           | Plain-text resources with optional HTTPS links.                                | Rich CMS, arbitrary HTML, localization, or approval workflow if later required.             |
| Integrations      | Protected CSV/JSON exports; Accelevents skipped.                               | Implement only with explicit API access and a supported data contract.                      |
| Product scope     | Conference program administration.                                             | Payments, ticketing, CRM/marketing, multilingual portals, and AI decisions are not claimed. |

Email wording

The UI may report a durable queue and delivery ledger. Actual target delivery requires a configured sender/binding and controlled mailbox proof; a queued status alone is not a delivery guarantee.

# A clean handoff checklist

## Prospective organizer

- Create and verify your own account; do not use the Apricot operator account.
- Create an isolated event with representative dates and content; reload to prove persistence.
- Complete the 10-step runway with distinct reviewer/applicant/speaker accounts.
- Check public agenda, speakers, resources, and embed from a signed-out window.
- Send email/calendar only to approved test recipients and retain no token-bearing screenshots.

## Airtable operator

- Confirm dedicated base, least-privilege PAT, exact callback origin, separate Worker secrets, and ignored artifact.
- Confirm the live Program setup card still reports Healthy and Airtable as the current source of truth before any spreadsheet edit.
- Preserve 140/140 reconcile, empty queue/dead/conflict, natural-webhook, and restored two-way round-trip evidence; use guarded recovery if any signal degrades.

## Release owner

- pnpm verify is green at 94 files / 474 tests; migrations 0000-0011 and the prior 40-pass / 6-skip E2E run are recorded.
- PR #1 required checks were green at handoff; Jobs version is recorded; final App identity is recorded after its post-PDF redeploy.
- Pilot readiness, D1 integrity, email/runtime status, and Airtable cutover checked after deploy.

**Stop condition**

Any failed authority, tenant, migration, secret, conflict, queue-drain, or final lifecycle gate is a no-cutover result. Keep the prior safe authority/version and report the evidence.

# Routes, documents, and useful feedback

| Item                     | Location/use                                                                                                                                                                                                |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Prospective-client pilot | <a href="https://conference-ops-pilot-app.techfren.workers.dev">https://conference-ops-pilot-app.techfren.workers.dev</a>                                                                                   |
| Seeded persona demo      | <a href="https://conference-ops-staging-app.techfren.workers.dev">https://conference-ops-staging-app.techfren.workers.dev</a> - walkthrough only; not proof of persistent Airtable authority.               |
| Organizer guide          | <a href="https://conference-ops-pilot-app.techfren.workers.dev/conference-ops-organizer-trial-guide.pdf">https://conference-ops-pilot-app.techfren.workers.dev/conference-ops-organizer-trial-guide.pdf</a> |
| Product parity record    | docs/SESSIONBOARD-PARITY.md                                                                                                                                                                                 |
| Release audit            | docs/RELEASE-AUDIT-0.2.0.md                                                                                                                                                                                 |
| Airtable runbook         | infra/AIRTABLE.md                                                                                                                                                                                           |
| Architecture/security    | ARCHITECTURE.md and SECURITY.md                                                                                                                                                                             |
| Audit evidence           | output/audit/ - visual analysis, control matrix, persona evidence, security/release findings, and agent ledger.                                                                                             |

## Send useful feedback

- What were you trying to accomplish?
- Which event slug, persona/role, page URL, browser, and approximate time were involved?
- What happened, what did you expect, and did a reload change it?
- Attach a screenshot only after removing names, emails, private files, reset/invitation links, and Airtable details.

Start here

Open <https://conference-ops-pilot-app.techfren.workers.dev>, create your own account, and follow the in-product Control Room runway or the separate organizer guide.