

Conference Ops

Implementation record, persona workflows, Sessionboard comparison, Airtable operating boundary, release controls, and prospective-client handoff.

DOCUMENT	PRODUCT	USE
Final handoff	Conference Ops 0.3.0	Release candidate / deploy separately



OPEN THE CURRENT DEPLOYED PILOT

<https://conference-ops-pilot-app.techfren.workers.dev>

Create and verify your own account. Deployment is a separate release step; confirm the visible version before testing 0.3.0.

01 / ORIENTATION

What is being handed off

Conference Ops is a Cloudflare-native conference program workspace. Version 0.3.0 covers the lifecycle from versioned calls for proposals through multi-round review, controlled decisions, speaker and content operations, conflict-aware scheduling, five public widgets, communications, and Airtable-backed business records. It is shaped by the customer's clarified MVP and rechecked against Sessionboard's participant and organizer learning material, not copied pixel for pixel.

Candidate
versus
deployment

The 0.3.0 source candidate is locally verified but is not declared deployed by this document. The current pilot may still run the tagged 0.2.0 release. After an authorized deploy, apply migrations 0012-0013, fully reconcile the expanded Airtable registry, confirm health, and collect the pending scheduled-reminder inbox receipt before calling the new release operational.

Audience	Use
Prospective organizer	Read persona workflows and the separate organizer guide; create an isolated event and use representative data.
Participant/reviewer/speaker	Use a separate verified account for each persona; follow only the event links sent by the organizer.
Airtable operator	Follow the fail-closed provisioning and cutover sequence. Never treat provisioning alone as source-of-truth activation.
Engineer/release owner	Use the release gates, architecture boundary, known limits, and version-control handoff.

Document map

- Pages 3-9: requirements, feature ledger, KillMySaaS boundary, persona workflows, and organizer runway.
- Pages 10-13: Airtable data boundary, commissioning, cutover, recovery, and safe editing.
- Pages 14-19: architecture, privacy, audit method, agents, release controls, and known boundaries.
- Pages 20-21: client acceptance script and handoff index.

02 / ACCEPTANCE AUTHORITY

What Sessionboard parity means here

The product was audited against the updated customer requirements and the current Sessionboard overview, participant, and organizer learning pages. Every available visual on those pages was inspected as audit input: 140 of 140 reference images were processed without image-analysis failure. The customer's explicit clarifications control where Sessionboard is broader than the requested MVP.

Clarified requirement	Conference Ops contract	Status
Forms	Basic one-level equals/contains conditional logic is sufficient; multiple independently versioned CFPs are supported.	Implemented
Routing	Talks select one or more tracks; organizers explicitly map reviewers to one or more tracks.	Implemented
Review	Unreviewed to Approve, Maybe, or Deny, with independent rounds, typed weighted rubrics, explicit pools/caps, blind mode, recusal, evidence, and final lock.	Implemented
Acceptance	Create the linked session, speaker access, configured onboarding work, audit record, and decision message.	Implemented
Onboarding	Hotel stay and flight reimbursement plus profile, talk details, media, files, announcements, colleague invites, and external actions.	Implemented
Email/calendar	Real MVP delivery through durable Cloudflare Email workflows and RFC 5545 calendar REQUEST attachments.	Operational pilot; receipt check required
Schedule	Day/room plus drag/drop and conflict detection is sufficient; list, week, conflict, and deterministic safe auto-place are also present.	Implemented
Agent	Small useful read-only readiness assistant; admin UI remains the priority.	Implemented
Widgets	Five anonymous program surfaces plus search, facets, itinerary/favorites, ICS, iframe/share links, and JSON/XML/iCal feeds.	Implemented
Airtable	38 canonical business entities, guarded descriptive edits, webhook reconcile, conflicts, and Workflow Commands.	Implemented; post-deploy reconcile
Accelevents	Explicitly skipped; controlled exports remain available.	Intentional scope

Human-readable references

- Product video overview: <https://learn.sessionboard.com/videos/overview>
- Participant overview: <https://learn.sessionboard.com/participants/overview>
- Organizer overview: <https://learn.sessionboard.com/get-started/overview>

**KillMySaaS
score
boundary**

The pinned evaluator maps all 84 required items to implemented source and deterministic evidence for a 100% implementation projection. This is not an official judge score. The paid browser judge was not run, CFP confirmation has a redacted delivery receipt, and the fresh scheduled speaker-reminder inbox receipt remains pending after deployment. Evaluator:

<https://forge.smol.ai/swyx/killmysaas-evals/blob/main/README.md>

03 / FEATURE LEDGER

Identity, events, forms, and submissions

Area	Implemented behavior	Use/guard
Identity	Email/password signup, verification, sign-in/out, token-aware password reset, invitations, speaker claims, and safe return routing.	Roles are event-scoped; one user may hold multiple roles without impersonating other people.
Event setup	Organization, event name/slug/purpose, dates, timezone, venue, website, accent, isolated workspace, and editable details.	CFP close must precede event start; invalid relationships are blocked in browser and API.
Fresh defaults	Draft CFP, review round/group, room, track, hotel and flight forms, profile/slides/calendar tasks, five message templates, and two reminder rules.	Defaults are organizer-editable, not hardcoded runtime decisions.
CFP portfolio	Create, switch, clone, independently version, publish, close, and copy a form-specific public link.	Published versions are immutable; applicant drafts stay pinned to their starting version.
Form builder	Text, long text, email, URL, select, multiselect, checkbox, information blocks, required rules, options, limits, and one-level conditions.	Visible-only validation, server allowlists, long-text budget, concurrency checks, and no public CFP file questions.
Applicant draft	Browser and account drafts, resume, multiple submissions, one or more tracks, participant minimum/maximum, distinct-email co-speakers, confirmation, and withdrawal.	Owner-scoped; submission caps and final consent are server-enforced.
Applicant revision	Reopen a non-final submission before the pinned form closes, or respond to an organizer change request and resubmit.	Accepted, rejected, or session-backed submissions stay locked. Submitted review evidence remains historical.

Routing rule

A reviewer invitation does not silently grant all tracks. Organizers explicitly map each track or reviewer group. A multi-track proposal receives the union of eligible reviewers, while owners and claimed co-speakers are excluded. Routing lane identifiers are comma-free so serialized multi-lane membership cannot split or merge ambiguously.

04 / FEATURE LEDGER

Review, decisions, and automatic activation

Area	Implemented behavior	Durable result
Review plans	Independent dated rounds with draft/active/closed state, numeric/dropdown/text criteria, weights, required evidence, blind mode, explicit reviewer pools, and per-reviewer caps.	Plans and assignments are round- and event-scoped.
Reviewer desk	Exact assignment queue, anonymized proposal where configured, criterion answers, note/evidence, recommendation, weighted preview, draft save/reload, recusal, and final submit.	Submitted review is immutable; applicant projections never expose scores or committee details.
Review control	Organizer progress by round/reviewer, capped distribution, reminders, aggregate sorting, and formula-safe CSV.	Submitted round evidence is retained independently.
AI triage	Bounded proposal evaluation returns a numeric signal and written reasons; organizer may record a clearly distinct human override with rationale.	Advisory only; no automatic program decision.
Decision states	Submitted/under review to Accept queue, Decline queue, or Waitlist; final Accept or Reject; optional organizer note and request-changes path.	Audit trail records material state changes; final decisions are guarded and immutable.
Request changes	Organizer sends a revision note and applicant edit path; eligible applicant can revise before close.	Open review work is revoked; the new revision gets fresh revision-aware assignments; prior submitted review evidence remains organizer-visible history.
Final acceptance	One guarded workflow creates a linked unscheduled session, activates eligible speaker access, instantiates configured tasks, records audit evidence, and persists the decision email intent.	No partial acceptance state if the guarded workflow fails.
Final rejection	Records the final decision and configured communication intent without creating session or onboarding work.	Applicant sees final status; active review work is closed.

Minimum workflow

The customer asked for Unreviewed to Approve, Maybe, or Deny. Conference Ops preserves that minimum while adding configurable independent rounds, explicit capacity, blind review, recusal, progress, and advisory triage. Organizers still own every final decision.

05 / FEATURE LEDGER

Speaker onboarding, files, collaboration, and resources

Area	Implemented behavior	Privacy/visibility
Speaker access	Verified-email claim, explicit speaker portal, proposal/session-targeted work, and multi-role account routing.	Only the eligible account and event organizers can access private work.
Roster	Organizer search/filter, manual create/edit/delete, CSV import/merge, workflow status, headshot, social links, assigned sessions, and task progress.	Organizer-private logistics stay out of speaker projections and cannot be overwritten by speaker edits.
Profile	Speaker-scoped bio, title, company, city, pronouns, social links, headshot upload/replace, completeness, and assigned sessions.	Only organizers can publish/unpublish. Public eligibility also requires an approved published session; private email/storage keys are excluded.
Task plans	Organizer-authored manual, profile, questionnaire, file request, calendar acknowledgement, and external HTTPS action tasks.	Acceptance instantiates the event's configured task plan for the relevant speaker/session.
Default examples	Hotel stay, flight reimbursement, finalize talk description, bio/photo, slides, calendar, announce participation, and invite colleagues with a discount.	Organizers may edit, remove, or add templates before acceptance.
Files	Private task-scoped upload, replace, chronological version history, current/prior download, metadata, organizer/speaker evidence, central library, and latest-version ZIP grouped by session.	Raw bytes remain in private R2; Airtable receives safe metadata, never file bytes.
Comments	Organizer and speaker task discussion with durable chronological history.	Event/task authorization on read and write.
Content	Organizer edits session speakers/title/description, moves draft to in-review/approved, reviews attributed immutable history, and restores an earlier snapshot as a new revision.	Every public program, speaker, headshot, widget, and feed fails closed without explicit approved content.
Resources	Organizer creates plain-text guides with optional HTTPS references, drafts/publishes them, and exposes them in portal/public index.	Safe text rendering; no arbitrary rich HTML.

06 / FEATURE LEDGER

Scheduling, publication, communications, and exports

Area	Implemented behavior	Guard
Venue model	Organizer CRUD for rooms and tracks, duplicate checks, capacity/color, and in-use delete guards.	All entities are event-scoped.
Sessions	Accepted-proposal conversion plus direct guaranteed/sponsor/program sessions; break/networking formats can omit a speaker.	Proposal conversion is one-to-one and guarded.
Schedule	List, day/room, week, and conflicts views; day/track filters; URL-persisted view state; explicit placement and drag/drop.	Event-window, room, track, and speaker collisions checked in client and server.
Safe auto-place	One action previews deterministic placements for unscheduled sessions, explains unplaced work, and applies only confirmed safe slots.	Never overrides existing sessions or conflicts.
Overrides	Alternate placement or audited override with a durable reason; reschedule and calendar sequence bump.	Adjacency is allowed; unreasoned collisions are blocked.
Publish	Atomic readiness/preflight and agenda publication; later published schedule changes update the live program.	Only published, eligible records reach public projections.
Public widgets	Sessions List, Speakers List, Agenda, Schedule Itinerary, and Speaker Gallery with search/facets/details, local favorites, reload persistence, and ICS.	Public allowlists exclude accounts, email, reviews, private files, travel notes, and raw storage keys.
Embed Studio	All five widgets support iframe/share output, live preview, accent/theme, filters, field selection, and JSON/XML/iCal feeds.	Every output reads the same published and explicitly approved canonical program.
Messages	Editable submission, acceptance, rejection, task-reminder, and calendar templates; scheduled draft/task reminders; recipient previews.	Durable D1 outbox before Queue delivery, idempotency, bounded retry, dead convergence.
History/calendar	Organizer-safe delivery history; RFC 5545 METHOD:REQUEST with stable UID and incremented SEQUENCE.	A queued/sent status is not an inbox-read guarantee; target delivery needs runtime configuration.
Exports	Protected speakers.csv, sessions.csv, and program.json for portable handoff.	CSV formula prefixes are neutralized; accepted/public and PII rules apply.
Assistant	Read-only, event-grounded readiness recommendations with workflow deep links.	Cannot mutate, send, decide, or bypass permissions.

07 / PERSONA WORKFLOWS

What each user actually does

Persona	Start	Core flow	Finish
Organizer	Create/verify account; create event.	Configure CFPs, review rounds/pools/caps, onboarding, speaker/content operations, resources, messages, venue, and widgets; then invite staff.	Decide, safely schedule, approve content, publish, monitor, export, and inspect Airtable health.
Applicant	Open form-specific CFP link; verify account.	Save draft, answer visible questions, select tracks, add speakers, consent, submit, revise if eligible.	See status, respond to changes, withdraw when allowed, or move into speaker work after acceptance.
Reviewer	Accept invitation with a distinct account.	Open exact round assignments; review blinded content where configured; score typed rubric, save draft, recuse or choose Approve/Maybe/Deny, submit.	Final evidence becomes read-only; organizer owns the final decision.
Speaker	Claim with the invited/accepted email.	Complete public profile/social/headshot, hotel/flight and other forms, external actions, files, versions, comments, and tasks.	Private organizer travel notes remain hidden; organizer approves/publishes eligible content.
Participant/public	Open event program or widget URL.	Search/facet sessions and speakers, inspect details, change agenda day, save itinerary/favorites, download ICS, and use embed/share/feed outputs.	No account/private workflow data is exposed.
Airtable operator	Provision one environment base with least privilege.	Reconcile, drain, review health/conflicts, switch authority through Workflow Command only.	Run a reversible descriptive-field round trip and retain D1 mirror/operational controls.

Account rule

Use separate verified people for organizer, reviewer, applicant, and speaker tests. Self-review exclusion is intentional. Never share an organizer password, reset link, invitation token, Airtable PAT, webhook secret, or raw provisioning artifact.

08 / ORGANIZER RUNWAY

The shortest complete evaluation

Step	Organizer action	Expected evidence
1	Create the event and verify details after reload.	Private event plus seeded operational defaults.
2	Create or choose a CFP; configure fields/track question; publish and copy that form's link.	Published immutable version and form-specific URL.
3	Create review rounds, typed rubric, dates, blind setting, explicit pool/caps, track coverage, and onboarding plan.	Independent rounds; no uncovered track or invitation-wide access.
4	Invite a distinct reviewer; use another account to submit a multi-track proposal.	Eligible assignments only; owner excluded.
5	Reviewer saves and submits Approve/Maybe/Deny evidence.	Weighted final review is read-only.
6	Request changes or stage/finalize the decision.	Revision loop or automatic accepted session/tasks/message intent.
7	Speaker claims access, completes public profile/forms/comments, and uploads/replaces a representative file; organizer verifies private logistics and content history.	Scoped current/prior evidence; no private travel-note leak.
8	Approve content; preview/apply safe auto-place or place manually; intentionally test a conflict; reschedule or override with reason.	Only safe automatic placements; conflict-safe or audited manual placement.
9	Publish; test all five widgets, details, filters, itinerary persistence, ICS, iframe/share/feed output; queue controlled message/calendar; export.	Approved published-only output, durable delivery history, safe export.
10	After authorized deploy, migrate/reconcile Airtable, drain work, confirm zero dead/conflicts, then reverse one allowed descriptive edit round trip.	Expanded v0.3 entity set healthy before authority is relied upon.

Test data

Use synthetic or representative content. Do not upload customer-confidential, regulated, executable, or irreplaceable files during the monitored evaluation.

09 / AIRTABLE BOUNDARY

What is canonical and what stays operational

Conference Ops 0.3.0 implements Airtable source-of-truth support for 38 registered business entity types. D1 remains the transactional workflow mirror that enforces relational and domain rules. The existing pilot's v0.2 Airtable proof is historical; the expanded v0.3 entity set becomes operational only after an authorized deploy, migrations, full reconcile, and health checks.

Airtable canonical business records	Cloudflare operational state
Organizations, events, memberships, and invitations	Better Auth passwords, accounts, sessions, and verification/reset values
CFP forms, versions, fields/configuration, proposals, participants, and rosters	Authorization policy, Worker secrets, connector credentials, and webhook MAC material
Reviewer groups/membership, dated rounds, reviewer pools/caps, rubrics, assignments, review evidence, and bounded AI evaluations	Raw R2 headshot, slide, and supporting-file bytes
Speaker profiles and operations; communication logs; task templates/instances/forms/responses; safe upload metadata; task comments	Outbox/Queue/DLQ leases, attempts, retry timing, and transport bookkeeping
Rooms, tracks, sessions, content status/revisions, resources, embeds, message templates, reminder rules, and audit history	Airtable connection cursors, hashes, conflict bookkeeping, and runtime health details

Canonical format

Conference business rows are projected into a Records table as canonical JSON with stable external keys, entity identity, content hashes, timestamps, and tombstones. Do not change keys, entity types, hashes, or Deleted state by hand.

Direct edit policy

- Allowed: only registry-approved descriptive fields, validated against the same application domain rules.
- Blocked into conflict: invalid JSON, unknown entity, referential change, protected state, direct deletion, or unsupported mutation.
- Protected lifecycle work belongs in the app or in an implemented, validated, idempotent Workflow Command adapter.

10 / AIRTABLE COMMISSIONING

Reusable provisioning procedure

Version 0.3 commissioning is a post-deploy operator action. Do not assume the prior pilot connection covers the expanded registry, and do not reprovision, replace the connection, or change authority outside the protected operator runbook.

Phase	Required operator action	Fail-closed evidence
1. Isolate	Use one dedicated base for the deployed environment. Current release supports one enabled environment-global base; leave connection event_id null.	No base reuse across demo, pilot, or production.
2. Token	Create a base-restricted PAT with record read/write, schema read, and webhook manage. Add schema write only while tables must be created, then remove it.	Down-scoped PAT can still read/write intended base and cannot reach unrelated bases.
3. Callback	Provision using the exact deployed App origin, not localhost and not the demo origin. Rerun provisioning when the target origin changes.	Webhook callback resolves to the intended environment.
4. Artifact	Let the script write the mode-0600 gitignored provisioning artifact. Read IDs/secrets from it only into protected runtime setup.	Artifact, PAT, and secret values are absent from Git and logs.
5. Connection	Apply migrations, create one enabled connection in D1 with authority d1 and status syncing, then install secrets on the correct Workers.	Jobs receives PAT only; App receives webhook MAC only.
6. Config	Enable Airtable and configure the expected base, d1 default authority, and request limit on App/Jobs.	Configuration/readiness reports expected non-secret state.

Secret rule

Never paste the PAT, webhook MAC secret, or provisioning artifact into tickets, PDFs, screenshots, chat, source control, CI output, or organizer feedback. Rotate immediately if exposed.

Required PAT scopes

- data.records:read
- data.records:write
- schema.bases:read
- webhook:manage

Reusable authority-change gates

For the 0.3 candidate, cutover is not claimed by this document. Provisioning alone is never authority. Start in D1, request full_reconcile, and use the guarded authority command only after every gate below passes in the exact target environment.

Gate	Must be true before set_authority to airtable
Deployment	Callback points to the exact deployed App origin; App and Jobs contain the right non-secret configuration and separate secrets.
Reconcile	A fresh full_reconcile completed and enumerated all registered business records.
Drain	No pending sync work, no claimed/in-flight work, no dead changes, and no stalled retry window.
Conflicts	Zero unresolved Airtable conflicts.
Connection	Webhook and token checks are healthy; cursor advances safely; connection is not degraded or blocked.
Integrity	Counts, stable keys, entity types, hashes, and tombstones match the D1 workflow mirror.
Command	A unique idempotent Pending Workflow Command requests set_authority with authority airtable.
Round trip	One approved descriptive field changes in Airtable, webhook reconciliation updates D1/app, and the original can be restored.

Required
v0.3 proof

After deployment, reconcile all 38 registered entity types; confirm unique external keys and matching hashes, a natural webhook, zero queued/dead changes, and zero open conflicts; then reverse one allowlisted descriptive-field round trip. Prior v0.2 record-count proof is historical and cannot substitute for this check.

12 / AIRTABLE OPERATIONS

Safe edits, commands, conflicts, and recovery

Situation	Correct action	Never do
Edit event copy	Change only an explicitly allowlisted descriptive field; wait for healthy reconciliation; verify in app.	Do not change External Key, Entity Type, Canonical JSON structure, or hash columns casually.
Decision/publication/task state	Use Conference Ops. Use Workflow Commands only where a matching adapter is documented.	Do not raw-edit acceptance, permissions, review finality, publication, completion, or deletion state.
Delete business row	Use the application's guarded delete/archive behavior; expect a Deleted tombstone.	Do not delete the canonical Airtable row.
Conflict	Stop related edits, inspect entity/key/reason and app history, correct the source or reconcile through a supported path.	Do not clear conflict rows while leaving invalid remote content.
Rate limit/transient failure	Leave the durable D1 change pending for its recorded retry time; monitor drain.	Do not sleep a Worker, duplicate commands, or rotate a healthy PAT unnecessarily.
Webhook expiry	Let Jobs refresh before the seven-day expiry; reprovision against the same origin if the webhook is missing.	Do not create duplicate callbacks across environments.
Authority rollback	Use a guarded set_authority back to d1, reconcile, diagnose, and preserve evidence.	Do not disable the integration mid-flight and assume nothing was lost.

Current command surface

- Implemented operator adapters: full_reconcile and guarded set_authority.
- Other protected command types are retained and visibly rejected until a domain adapter exists; they are not raw-SQL escape hatches.
- Every command uses a unique idempotency key and a visible Pending/processing/result lifecycle.
- The organizer Airtable panel is a read-only health and escalation surface. It does not expose conflict details; the platform operator owns dead/conflict resolution through the protected runbook and backend evidence.

Cloudflare workflow mirror plus Airtable records

Layer	Ownership	Purpose
App Worker + Assets	Wrangler	React client, Hono API, Better Auth, public pages, embed, Airtable webhook and organizer status.
D1	Terraform + additive migrations	Transactional workflow mirror, relational constraints, auth metadata, outbox, sync queue, conflict and cursor bookkeeping.
Airtable	Base schema + least-privilege PAT	Canonical conference business records and guarded Workflow Commands.
Private R2	Terraform	Raw headshots, slides, and supporting-document bytes.
Queue + DLQ	Terraform; Jobs consumer	Immediate email/calendar/Airtable transport; durable D1 records remain recoverable.
Jobs Worker + Cron	Wrangler	Outbox delivery, reminders, Airtable batching/retry/reconcile, webhook refresh, and lease recovery.
Realtime Worker/DO	Wrangler	Readiness and event-scoped transport; current business UI uses focus plus bounded polling.
Terraform state	Private R2 backend	Stateful D1/R2/Queue desired state with destruction guards.

Write path

Application workflows validate permissions and state transitions, commit atomically to D1, and enqueue canonical projection. Under Airtable authority, only validated allowlisted descriptive edits flow back into the D1 mirror; protected workflows still use the application/command boundary.

14 / SECURITY AND PRIVACY

Client-safe operating rules

Control	Implemented contract	Client/operator responsibility
Tenant and role scope	Event membership on protected reads/writes; organizer/reviewer/applicant/speaker projections are separate.	Use a separate tester account per persona; report event slug, role, URL, and approximate time.
Public projection	Agenda/speakers/resources/embed use allowlists and published eligibility; ordinary pages deny framing.	Review public preview before publication.
Files	Private R2, MIME/size rules, authorized download, public headshot rechecks, no raw bytes in Airtable.	Use representative non-sensitive files; malware scanning is not yet a broad-launch control.
Messaging	Durable outbox, idempotency, retries, delivery history, and recipient previews.	Send only to approved test recipients; do not infer inbox receipt from queued state.
Secrets	External runtime secrets and gitignored mode-0600 Airtable artifact.	Never screenshot, paste, email, or commit credentials/tokens/links.
Exports	Protected access, accepted/public filters, PII limits, and CSV formula neutralization.	Store exports according to the client's data policy and delete trial copies when finished.

Launch gate

Add route-level rate limiting and Turnstile/CAPTCHA for auth and high-cost writes, plus malware scanning/quarantine and formal retention, before broad anonymous distribution.

How feature and control claims were checked

Evidence lane	Scope	Acceptance rule
Requirements trace	Updated private requirements, original walkthrough, clarified MVP answers, and current Sessionboard learning center.	Firm requirements override screenshot decoration and optional/de-scoped features.
Image analysis	140 of 140 tutorial visuals across participant/organizer reference pages.	Every extracted image processed; visible workflows mapped to product behavior, not copied styling.
Source/control inventory	Routes, API methods, buttons, links, dialogs, disabled states, destructive guards, focus, cancel/Escape, persistence, and projections.	Each named control has an expected outcome or an explicit boundary.
Automated	Unit, API, component, migration replay, schema drift, build, dependency audit, production-local Better Auth/D1 lifecycle, and E2E.	pnpm verify passed 105 files / 541 tests; full E2E passed 52 with 6 intentional viewport skips.
Persona browser	Organizer, applicant, reviewer, speaker, public, desktop, 375 px, keyboard/focus, overflow, console/network, reload and URL state.	No unreviewed P0/P1 lifecycle blocker on the release revision.
Airtable	38-entity registry, triggers, client batching, webhook cursor, queue/race behavior, validation, conflict policy, provisioning, and operator UI.	Candidate implementation is verified locally; target-environment cutover requires the post-deploy gates.
KillMySaaS	Pinned 84 required items with weights, implementation evidence, and manual/official state.	100% implementation projection; official judge not run; one post-deploy reminder receipt remains pending.
Security/release	Tenant boundaries, formula injection, secrets, migrations, Worker config, version control, CI, and deployment identity.	Local release gates are green; commit, CI, deployment, and runtime identity remain separate release-owner actions.

Control log

The durable audit records the route/control expectation and result, including confirm/cancel paths, disabled states, persistence after reload, role authorization, desktop/mobile layout, and error behavior. Dynamic repeated controls are sampled by workflow class; the audit does not claim to enumerate every possible future data combination.

Independent lanes used to challenge the release

Lane	Responsibility	Contribution
Requirements and visual trace	Google Doc, original YouTube walkthrough, Sessionboard overview/participant/organizer pages, 140-image analysis.	Established controlling acceptance matrix and non-pixel parity boundary.
CFP and revisions	Multi-form portfolio, version pinning, conditional fields, applicant edit states, organizer request-changes, review history.	Closed form/submission parity gaps and locked final states.
Routing and abstract review	Explicit multi-track membership, dated rounds, pools/caps, typed criteria, blind review, recusal, AI triage, immutable reviews, and final decisions.	Prevented invitations from broadening track access and kept automated triage subordinate to human decisions.
Speaker, content, and widgets	Roster/import, private logistics, task/file versions, content approval/history, five public widgets, feeds, and Embed Studio.	Added durable speaker/organizer evidence and fail-closed public projection.
Schedule and communications	Four schedule views, safe auto-place, conflicts, messages, reminders, ICS, sanitized delivery history, and CSV export.	Closed organizer-operability and injection gaps.
Airtable core	Canonical schema, change capture, Jobs client, webhook, reconciliation, conflict policy, provisioning and operator status.	Added source-of-truth capability with a fail-closed boundary.
Airtable integrity audit	In-flight queue race, authority readiness, domain validation, connection health, one-base tenancy, scheduled isolation, and self-echo handling.	Closed queue races and unsafe authority transitions; self/no-op echoes now preserve map.last_synced_at alignment with Airtable.
Security/tenant audit	Authentication, role projection, task/file/resource authorization, CSV formula injection, secrets and migrations.	Found and drove closure of release blockers.
Desktop/mobile audit	Persona journeys, every named control class, focus, Escape, dialogs, overflow, console/network and 375 px.	Drove form portfolio and accessibility corrections.
Root integration	Reconcile shared tree, rerun full gates, source-control audit, release manifest, and public artifacts.	Single accountable release-candidate decision and evidence handoff without implying deployment.

Agent names and internal task identifiers are implementation evidence, not product permissions. No agent is allowed to bypass authentication, disclose secrets, force Airtable authority, or claim a release gate it did not verify.

17 / RELEASE CONTROLS

Version control, deployment identity, and rollback

Artifact	Handoff rule
Version	Product version is 0.3.0 at source commit 1a077fa6d0a1ef66bbc5546dad67aeb547bc2f6. The release tag, required CI, and deployment identity are recorded only after those actions complete.
Source	Intentional source, tests, migrations, docs, and the two public PDFs form the handoff. Local videos, rendered audit media, Airtable artifacts, and Worker secret files remain outside the public packet.
Migrations	Additive migrations 0000 through 0013 replay cleanly, including expanded reviews, speaker/content operations, public widgets, Airtable projection, and lifecycle hardening.
Deployment	Not performed by this artifact task. Apply migrations before dependent code, then record App/Jobs deployment identities and runtime checks after an authorized release.
Remediations	Acceptance SQL is D1-compatible; public content fails closed; speaker publication is organizer-only; private travel data is not disclosed or overwritten; scheduled reminders and Airtable self-echoes have focused regressions.
Rollback	Roll Worker code to a known-good version; use guarded Airtable authority back to D1 and reconcile; use D1 Time Travel/export only for diagnosed data recovery. Never destroy D1 through Terraform to roll back code.

Candidate acceptance

Local lint, typecheck, 105-file / 541-test suite, production build, 52-pass browser suite, schema no-drift check, migration replay, and production-local lifecycle are green. Deployment, Airtable reconcile/cutover, and a fresh scheduled-reminder inbox receipt remain post-deploy actions.

18 / KNOWN BOUNDARIES

What is intentionally limited or still required

Boundary	Current contract	Before broader production
Abuse	Named, monitored client evaluation.	Rate limits, Turnstile/CAPTCHA, quota alerts, and lockout/abuse telemetry.
Files/data	Representative test uploads; type/size/private-access gates.	Malware scanning/quarantine, formal retention/purge, and backup policy.
Collaboration	Visible workspaces refresh on focus and about every 25 seconds.	Add mutation fanout/client subscriptions only if sub-second collaboration is required.
Calendar	Email with RFC 5545 REQUEST attachment and sequence updates.	Add explicit cancellation/resend if client operations require managed cancel flows.
Airtable topology	One enabled environment-global base; event_id stays null.	Per-event bases/routing require a future isolation design and tests.
Airtable commands	full_reconcile and set_authority adapters; other command types reject visibly.	Implement and test each protected domain adapter before use.
Content	Plain-text resources with optional HTTPS links plus explicit session-content approval/history.	Rich CMS, arbitrary HTML, localization, or multi-stage editorial workflow if later required.
Integrations	Protected CSV/JSON exports; Accelevents skipped.	Implement only with explicit API access and a supported data contract.
Evaluation	100% implementation projection; official judge not run; CFP receipt verified; scheduled reminder receipt pending.	Run the judge on a disposable authorized deployment and collect the SPK-16 receipt.
Product scope	Conference program administration with bounded read-only/triage assistance.	Payments, ticketing, CRM/marketing, multilingual portals, and autonomous AI decisions are not claimed.

Email wording

The UI may report a durable queue and delivery ledger. Actual target delivery requires a configured sender/binding and controlled mailbox proof; a queued status alone is not a delivery guarantee.

A clean handoff checklist

Prospective organizer

- Create and verify your own account; do not use the Apricot operator account.
- Create an isolated event with representative dates and content; reload to prove persistence.
- Complete the 10-step runway with distinct reviewer/applicant/speaker accounts.
- Check Sessions, Speakers, Agenda, Itinerary, and Gallery widgets plus feeds/embed from a signed-out window.
- Send email/calendar only to approved test recipients and retain no token-bearing screenshots.

Airtable operator

- Confirm dedicated base, least-privilege PAT, exact callback origin, separate Worker secrets, and ignored artifact.
- After deployment, confirm Program setup reports Healthy and the intended Airtable authority before any spreadsheet edit.
- Reconcile all 38 registered entity types; require empty queue/dead/conflict state, a natural webhook, and a reversed allowlisted round trip.

Release owner

- pnpm verify is green at 105 files / 541 tests; migrations 0000-0013 and the 52-pass / 6-skip E2E run are recorded.
- Record the release commit/tag, required CI, and App/Jobs deployment identities after those actions complete.
- After deploy, check D1 integrity, email/runtime status, expanded Airtable reconcile/cutover, and the pending SPK-16 inbox receipt.

Stop condition

Any failed authority, tenant, migration, secret, conflict, queue-drain, or final lifecycle gate is a no-cutover result. Keep the prior safe authority/version and report the evidence.

Routes, documents, and useful feedback

Item	Location/use
Prospective-client pilot	https://conference-ops-pilot-app.techfren.workers.dev
Seeded persona demo	https://conference-ops-staging-app.techfren.workers.dev - walkthrough only; not proof of persistent Airtable authority.
Organizer guide	https://conference-ops-pilot-app.techfren.workers.dev/conference-ops-organizer-trial-guide.pdf
Product parity record	docs/SESSIONBOARD-PARITY.md
Release audit	docs/RELEASE-AUDIT-0.3.0.md
KillMySaaS method	https://forge.smol.ai/swyx/killmysaas-evals/blob/main/README.md and docs/KILLMYSAAS-EVALUATION.md
Airtable runbook	infra/AIRTABLE.md
Architecture/security	ARCHITECTURE.md and SECURITY.md
Audit evidence	docs/evidence/ - durable redacted evidence; generated/private media and credentials stay outside the public packet.

Send useful feedback

- What were you trying to accomplish?
- Which event slug, persona/role, page URL, browser, and approximate time were involved?
- What happened, what did you expect, and did a reload change it?
- Attach a screenshot only after removing names, emails, private files, reset/invitation links, and Airtable details.

Start here

Open <https://conference-ops-pilot-app.techfren.workers.dev>, create your own account, and follow the in-product Control Room runway or the separate organizer guide.