Milestone 5: Performance Testing & Evaluate the results

Activity 1: Testing model with multiple evaluation metrics

Multiple evaluation metrics means evaluating the model's performance on a test set using different performance measures. This can provide a more comprehensive understanding of the model's strengths and weaknesses. We are using evaluation metrics for classification tasks including accuracy, precision, recall, support and F1-score.

Compare the model

```
from sklearn import model_selection

dfs = []
models = [
          ('LogReg', LogisticRegression()),
          ('RF', RandomForestClassifier()),
          ('DecisionTree',DecisionTreeClassifier()),

        ]
results = []
names = []
scoring = ['accuracy', 'precision_weighted', 'recall_weighted', 'f1_weighted', 'roc_auc']
target_names = ['NO CKD', 'CKD']
for name, model in models:
    kfold = model_selection.KFold(n_splits=5, shuffle=True, random_state=90210)
    cv_results = model_selection.cross_validate(model, x_train, y_train, cv=kfold, scoring=scoring)
    clf = model.fit(x_train, y_train)
    y_pred = clf.predict(x_test)
    print(name)
    print(classification_report(y_test, y_pred, target_names=target_names))
    results.append(cv_results)
    names.append(name)
    this_df = pd.DataFrame(cv_results)
    this_df['model'] = name
    dfs.append(this_df)
final = pd.concat(dfs, ignore_index=True)
return final
```

```
LogReg
              precision    recall  f1-score   support

       NO CKD       1.00      0.87      0.93        54
          CKD       0.79      1.00      0.88        26

     accuracy                           0.91        80
    macro avg       0.89      0.94      0.91        80
 weighted avg       0.93      0.91      0.91        80
```

```python
# Making the Confusion Matrix
from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_predict)
cm
```

```
array([[47,  7],
       [ 0, 26]], dtype=int64)
```

```python
# Plotting confusion matrix
plt.figure(figsize=(8,6))
sns.heatmap(cm, cmap='Blues', annot=True, xticklabels=['no ckd', 'ckd'], yticklabels=['no ckd', 'ckd'])
plt.xlabel('Predicted values')
plt.ylabel('Actual values')
plt.title('Confusion Matrix for Logistic Regression model')
plt.show()
```



RF

	precision	recall	f1-score	support
NO CKD	0.96	0.96	0.96	54
CKD	0.92	0.92	0.92	26
accuracy			0.95	80
macro avg	0.94	0.94	0.94	80
weighted avg	0.95	0.95	0.95	80

```python
# Making the Confusion Matrix
from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_predict)
cm
```

```
array([[52,  2],
       [ 3, 23]], dtype=int64)
```

```python
# Plotting confusion matrix
plt.figure(figsize=(8,6))
sns.heatmap(cm, cmap='Blues', annot=True, xticklabels=['no ckd', 'ckd'], yticklabels=['no ckd', 'ckd'])
plt.xlabel('Predicted values')
plt.ylabel('Actual values')
plt.title('Confusion Matrix for RandomForestClassifier')
plt.show()
```



DecisionTree

	precision	recall	f1-score	support
NO CKD	0.93	0.94	0.94	54
CKD	0.88	0.85	0.86	26
accuracy			0.91	80
macro avg	0.90	0.90	0.90	80
weighted avg	0.91	0.91	0.91	80

```python
# Making the Confusion Matrix
from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_predict)
cm
```

```
array([[52,  2],
       [ 1, 25]], dtype=int64)
```

```python
# Plotting confusion matrix
plt.figure(figsize=(8,6))
sns.heatmap(cm, cmap='Blues', annot=True, xticklabels=['no ckd', 'ckd'], yticklabels=['no ckd', 'ckd'])
plt.xlabel('Predicted values')
plt.ylabel('Actual values')
plt.title('Confusion Matrix for DecisionTreeClassifier')
plt.show()
```



For ANN

```
[201] print (classification_report(y_test, y_pred))
```

```
...                  precision    recall  f1-score   support

           0       0.96      0.96      0.96        54
           1       0.92      0.92      0.92        26

    accuracy                           0.95        80
   macro avg       0.94      0.94      0.94        80
weighted avg       0.95      0.95      0.95        80
```

```
# Making the Confusion Matrix
from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_pred)
cm
```

```
array([[52,  2],
       [ 2, 24]], dtype=int64)
```

```
# Plotting confusion matrix
plt.figure(figsize=(8,6))
sns.heatmap(cm, cmap='Blues', annot=True, xticklabels=['no ckd', 'ckd'], yticklabels=['no ckd', 'ckd'])
plt.xlabel('Predicted values')
plt.ylabel('Actual values')
plt.title('Confusion Matrix for ANN model')
plt.show()
```



All above models are performing well for this dataset.

Activity 2: Evaluate the results

```
bootstraps = []
for model in list(set(final.model.values)):
    model_df = final.loc[final.model == model]
    bootstrap = model_df.sample(n=30, replace=True)
    bootstraps.append(bootstrap)

bootstrap_df = pd.concat(bootstraps, ignore_index=True)
results_long = pd.melt(bootstrap_df,id_vars=['model'],var_name='metrics', value_name='values')
time_metrics = ['fit_time','score_time'] # fit time metrics
## PERFORMANCE METRICS
results_long_nofit = results_long.loc[~results_long['metrics'].isin(time_metrics)] # get df without fit data
results_long_nofit = results_long_nofit.sort_values(by='values')
## TIME METRICS
results_long_fit = results_long.loc[results_long['metrics'].isin(time_metrics)] # df with fit data
results_long_fit = results_long_fit.sort_values(by='values')
```



Among all these 4 models logistic regression has recall 1. So, we are going for logreg model.