Verdikt.

AI reads the case. Deterministic code writes the reply. Humans decide.

The *problem*

A patient-assistance application is a stack of four documents: enrollment form, income proof, insurance card and prescription. The eligibility decision is small, but intake, eligibility, fulfillment and compliance each re-read the same stack. That re-reading is where the days go. Verdikt reads the stack once, decides against the program's own rules, and sends a reply that no language model touched.

How it *works* — five stages

INGEST
MiniCPM-V 4.5
Reads attachments into the program's field schema.

TRIAGE
Nemotron Nano
Classifies the case and routes it. Rule-based fallback.

DECIDE
Qwen3-Embedding + Nemotron Super
Retrieves rules, then a cited verdict.

DELIVER
No model
Merges the verdict into a frozen, human-approved template.

REMEMBER
No model
Audit entry per stage; template hash; render fingerprint.

Architecture — *one line* that matters

IN
Email (IMAP), JSON API, MCP tools. Fax and scans arrive as email attachments.

→

AI-IN · REVIEWABLE
Read, classify, retrieve, reason to a structured verdict with citations.

→

DETERMINISTIC-OUT
Frozen template merge. No model on this path. Reply letter plus JSON verdict.

FastAPI web, background worker, Postgres, Redis and S3-compatible storage. All model calls go through one Nebius Token Factory endpoint; the model for each stage is configurable per program. A boundary test fails the build if the render core imports the AI layer.

Proof

934	928	0	6
tests	passing	failing	skipped

- Labeler: 24 → 98 of 104 fields correct on one dense form after switching to vision with chunk and crop (one benchmark, not a guarantee).
- One audit entry per pipeline stage, recording the model and the time taken.

Business *value*

DEMONSTRATED

- Every verdict cites the rule that fired.
- Refills skip the verdict entirely.
- The reply letter is merged, never generated.

BY DESIGN

- A new program is configuration, not a build.
- A new channel is one adapter.
- Models swap per program with no code change.

TO MEASURE

- [__]% of cases a reviewer re-opens the source PDF.
- [__] median time from receipt to verdict.
- [__] cost per case.

What ships *next*

Deploy on Nebius AI Cloud (runbook ready) · byte-level reproducibility assertions in CI · a measured pilot to fill the numbers above. A second program (different rules pack, opposite verdict, same code) already runs as a cameo.