

# A Comparison of Antenna Placement Algorithms

Abhinav Jauhri  
Carnegie Mellon University  
ajauhri@cmu.edu

## ABSTRACT

Co-location of multiple antenna systems on a single fixed or mobile platform can be challenging due to a variety of factors, such as mutual coupling, individual antenna constraints, multipath, obstructions, and parasitic effects due to the platform. The situation frequently arises where a new communication capability, and hence antenna system, is needed on an existing platform. The problem of placing new antennas requires a long, manual effort in order to complete an antenna placement study. An automated procedure for determining such placements would not only save time, but would be able to optimize the performance of all co-located antenna systems. In this paper we examine a set of stochastic algorithms to determine their effectiveness at finding optimal placements for multiple antennas on a platform. To our knowledge, this is the first study to investigate optimizing multiple antenna placement on a single platform using multiple stochastic algorithms. Of the four algorithms compared on the basis of convergence rates, simulated annealing and evolutionary strategy were found to be most effective in finding optimal placements.

## 1. INTRODUCTION

Antenna placement on a multi-antenna platform currently involves a manual process that is challenging, time-consuming, and may result in sub-optimal placements leading to lowered communication systems' performance. Moreover, the search space becomes exponentially large with regard to the number of antennas to be placed ( $|\text{search space}| = m^n$ , where  $m$  is the number of allowable placements for each antenna and  $n$  is number of antennas).

Applying an evolutionary algorithm (EA) to this problem could greatly improve this process by automatically determining acceptable antenna placements. Evolutionary algorithms encompass a variety of computer search technologies, with the Genetic Algorithm (GA) being the most well-known [10]. EAs have proven very capable in discovering high performance antenna designs and previous work has been responsible for a number of advances [9], including the seminal patent for this process and genetically-evolved antennas deployed in space [13, 15]. Additionally, our work is *highly generic* such that any type of a platform may be used to find optimal placement of antennas.

Our main contributions are:

- Applying existing stochastic algorithms to help determining optimal or near-optimal antenna placements on a platform
- Our approach is agnostic of the type of platform used
- We apply experiments on different types of platforms

and antennas to demonstrate the effectiveness of different stochastic algorithms

In Section 2, we provide some related work done with finding optimal antenna placements. Section 3 formally describes the problem statement, fitness calculation, and the representation of an individual which we shall refer to as *hypothesis*. Different algorithms used in our study to find optimal antenna placements are formally described in Section 4. Experimental setup is described in Section 5. Section 6 has simulation results and comparison of algorithms. Selection of parameters for certain algorithms is also described in Section 6. In the last section, we conclude, and provide future directions for further investigation.

## 2. RELATED WORKS

The problem of optimizing the placement of multiple antennas on a single platform has rarely been studied, if at all. The closest research we have found concerns algorithms for locating and configuring infrastructure for cellular wireless networks with the assumption of isotropic radiation pattern, for example [24]. Another related is work used characteristic mode analysis to compute optimal antenna locations for an antenna placed within a mobile device [23, 7]. In our work, none of the algorithms discussed have prior information of good antenna placements or type of antennas to be placed on the platform.

In addition, the related problem of co-designing antennas for a given platform (*in-situ* design) using EAs has been investigated in [14] with encouraging results. Because antenna placement bears many similarities to antenna design, we believe that such algorithms will prove effective.

## 3. PROBLEM FORMULATION


A platform for our problem formulation could vary from a simple rectangular box to an aircraft.

### 3.1 Inputs

Our inputs to an algorithm shall comprise of a platform and set of antennas each with allowable placements on the platform. Formally, a platform,  $P$ , in 3-dimensional space with its surface discretized into a regular grid with some spacing consisting of potential antenna placement points (see Figure 1). Let  $m$  denote the number of antennas to be placed on  $P$  such that  $m > 1$ , and let  $A$  represent the set of antennas:  $A = \{A_1, \dots, A_m\}$ . For each antenna  $A_i$ , let  $L_i$  denote the set allowable placement coordinates  $\in \mathbb{R}^3$  on  $P$  such that  $|L_i| = n_i$ , and  $\forall i, n_i > 1$ :

$$L_i = \{(x_1, y_1, z_1), \dots, (x_{n_i}, y_{n_i}, z_{n_i})\}$$

Using the inputs, a *hypothesis* (an individual is re-



**Figure 1: Platform used for test case 1 (tc1) & 4 (tc4)**

ferred to as hypothesis in this paper<sup>1</sup>),  $H$ , is formed by a set of  $m$  antenna locations. In other words, a hypothesis is a placement configuration i.e. a set having  $m$  placements, one for each of the  $m$  antennas, in 3-dimensional space:

$$H = \{(x_1, y_1, z_1), \dots, (x_m, y_m, z_m)\}$$

The reader should note that the number of allowable placements for any antenna are finite. We shall elaborate how that is ensured later in Section 5.

### 3.2 Fitness Evaluation

The placement optimization aims to find the best *hypothesis*,  $H^*$ , such that the radiation pattern and mutual coupling are optimal. For optimal radiation pattern, we shall minimize the difference between the free-space gain pattern (FSG) of antenna  $A_i$ , and its pattern when placed on  $P$  and in the presence of all remaining antennas (in-situ gain, or ISG). Thus, for each gain point for  $A_i$  we compute:

$$F_{RP}(A_i) = \sum_{\theta} \sum_{\phi} \|ISG_i(\theta, \phi) - FSG_i(\theta, \phi)\|^2, \quad (1)$$

where  $\theta$  &  $\phi$  define the spherical and cylindrical coordinates of a field point respectively (see Section 5 for more information).

For the second objective, it is desired to minimize the mutual coupling between the antennas for a given placement configuration because strong mutual coupling reduces antenna efficiency [12]. This is computed in a pairwise manner where the CP function computes the coupling between two antennas:

$$F_{MC} = \sum_{i=1}^{m-1} \sum_{j=i+1}^m CP(A_i, A_j) \quad (2)$$

The overall optimization for a given placement configuration is to minimize fitness,  $F$ , as follows optimal antenna

<sup>1</sup>Hypotheses are described as bit strings with interpretation based on the application [19]

**Table 1: Equivalence of fitness to efficiency**

ID	$\mathbb{E}_g$	$\Delta_c$ (dB)
tc1	872.277	0.5474
tc2	862.082	1.3034
tc3	861.845	1.5180
tc4	871.049	0.5693

For a particular test case, fitness change of 0.01 is equivalent to either the corresponding value under  $\mathbb{E}_g$  column, or difference in coupling ( $\Delta_c$ ).

placement for mobile terminals using characteristic analysis:

$$F = \alpha F_{MC} + \beta \sum_i F_{RP}(A_i), \quad (3)$$

where  $\alpha$  and  $\beta$  are constants which satisfy:  $\alpha + \beta = 1$ . Values for  $F_{MC}$  and  $F_{RP}$  are positively correlated [29], and therefore we can set  $\alpha$  and  $\beta$  to some value  $\in [0, 1]$  without loss of generality.  $F$  will be provided by an antenna simulation software which will be introduced in Section 5.

Radiation pattern and antenna coupling are measured in decibels (dB) which is a logarithmic unit used to express the ratio between two quantities i.e.  $10 \cdot \log x_1/x_2$ . For radiation pattern fitness parameter, the *antenna strength* or gain shown in Eq.(1), at any given point on a sphere is the ratio of the signal strength of the antenna being tested to a perfectly isotropic antenna, expressed in dB. For coupling, the ratio compares the energy absorbed by one antenna when the another antenna is operating nearby. For our antenna placement problem, this absorption is undesirable because we want the energy to be radiated away in order to establish a communication link, and not be absorbed by a nearby antenna. This coupling thus reduces the antenna's efficiency. For example, if the coupling ( $F_{MC}$ ) was  $-10$  dB for an hypothesis instead of the best, let's say  $-13$  dB, then this reflects a difference  $\Delta_c$  of 3 dB which translates to a doubling of energy absorbed in the  $-10$  dB case compared to the  $-13$  dB case. Shown in Table 1 is the equivalence of overall fitness ( $F$ ) to  $\Delta_c$ . Also shown is the equivalence to expected gain defined as:

$$\mathbb{E}_g = \frac{1}{N \cdot m} \sum_i^m F_{RP}(A_i), \quad (4)$$

where  $N = |\theta| \cdot |\phi|$ .

Each test case has its specific bounds on the different fitness parameters, and therefore the equivalence values are dependent on the test case as shown Table 1.

## 4. STOCHASTIC SEARCH ALGORITHMS

Here, we formally describe all stochastic algorithms used for experiments and comparative analysis. Following details are similar between algorithms and should be highlighted for easy reproduction of this work:

- A hypothesis used by any algorithm is similar to as defined in the previous Section 3.1.
- For any hypothesis, no two antenna placements overlap. It may be the case that two different antennas have overlapping set of allowable placements, but the formation of any hypothesis avoids such a case as it may result in imprecise calculation of fitness.

- The  $fitness(H)$  function used in all four algorithms is the equivalent of Eq.(3), assuming we have its inputs i.e.  $F_{MC}$  and  $F_{RP}$ .

## 4.1 Genetic Algorithm

Genetic algorithms aims to model different DNA operations in nature like crossover and mutation. They have been used extensively as stochastic search procedures for numerous applications [22]. We have used elitism in our algorithm since results in [35, 25] have shown performance speed up of a GA significantly.

---

### Algorithm 1: AP-GA

---

**Data:** Set of placements  $L = \{L_1, \dots, L_m\}$ ;  $p$  - population size;  $p_m$  - percentage of population to be with mutation operator;  $p_c$  - crossover probability;  $e$  - ratio of elite population;  $gen_{max}$  - maximum number of generations

**Result:**  $H^*$  from  $P$

```

1 Initialize  $P \leftarrow$  generate  $p$  random hypothesis. Each hypothesis contains a placement for all  $m$  antennas. A placement is chosen uniformly from each  $L_i$ , for all antennas ;
2 Compute the  $fitness(h_i), i = 1, \dots, p$  ;
3 Order hypotheses in  $P$  such that  $fitness(h_i) < fitness(h_j)$ , where  $i < j$  ;
4  $gen_{id} = 0$  ;
5 while  $gen_{id} < gen_{max}$  do
6   Elitism - Select top  $e \cdot p$  hypotheses, elites, to add to  $P'$  ;
7   Crossover - Select  $((1 - e) \cdot p)/2$  pairs of hypotheses. Each pair is formed by choosing one hypothesis using tournament selection and other uniformly randomly from the population. For each pair  $M$  : ;
8   if  $rand(0, 1) < p_c$  then
9     Apply one-point crossover operator to get two offsprings  $O$  ;
9     Add  $O$  to  $P'$  ;
10  else
11    Add  $M$  to  $P'$  ;
12  end
13  Mutation - Uniformly select  $p_m \cdot p$  hypothesis from  $P$ . For each, modify one uniformly at random selected antenna location to a different allowable location also selected uniformly at random ;
14  Update  $P \leftarrow P'$  ;
15  Compute  $fitness(h_i), i = 1, \dots, p$ , and order new population based on fitness ;
16  Update  $gen_{id} \leftarrow gen_{id} + 1$  ;
17 end

```

---

Operators in Antenna Placement Genetic Algorithm(AP-GA, Algorithm 1) are *one-point crossover* and *mutation*. Each pair for one-point crossover operation comprises of one hypothesis uniformly selected from the population and the other hypothesis from a tournament selection [17]. The size of the hypothesis is not arbitrarily large, and therefore it was preferred to keep the mutation restricted to just manipulating one antenna placement of an hypothesis. For arbitrarily large number of antennas, one may need to consider changing the mutation operator to manipulate more than one antenna placement. The mutation operator described

in Algorithm 1 is common to all other algorithms compared in this work.

We shall discuss about intuition for selecting values of  $p_m$  and  $p_c$  in Section 6.

## 4.2 Evolutionary Strategy

The evolutionary strategy  $(\mu + \lambda)$  [26, 8] is different from a genetic algorithm in the following ways: mutation is the primary operator here for maintaining diversity in the population since there are no crossover operations. Survivor selection is done by selecting only fittest  $\mu$  hypotheses to the next generation. See Algorithm 2. A  $1/7$  ratio was maintained between  $\mu$  and  $\lambda$  as suggested in [6].

Since we have a discrete set of placements (end points of wires of a platform), *mutation's* step size involves a new placement from the set of allowable placements for an antenna only. Both the antenna and its new placement are selected uniformly at random. *Mutation* operator is surely applied once on an hypothesis to generate the offspring.

---

### Algorithm 2: AP-ES

---

**Data:** Set of placements  $L = \{L_1, \dots, L_m\}$ ;  $\mu$ ;  $\lambda$ ;  $gen_{max}$  - maximum number of generations

**Result:**  $H^*$  from  $P$

```

1 Initialize  $P \leftarrow$  generate  $\mu$  random hypothesis ;
2  $gen_{id} = 0$  ;
3 while  $gen_{id} < gen_{max}$  do
4   Create  $\lambda/\mu$  offsprings from each  $\mu$  hypotheses by applying mutation operator, and add all offsprings to  $P$  ;
5   Compute the  $fitness(h_i), i = 1, \dots, \lambda$  ;
6   Keep  $\mu$  best hypotheses in  $P$ , and discard remaining  $\lambda - \mu$  hypotheses ;
7   Update  $gen_{id} \leftarrow gen_{id} + 1$  ;
8 end

```

---

## 4.3 Simulated Annealing

Simulated annealing models thermodynamics by including a temperature cooling schedule. Numerous applications [27, 5] have compared simulated annealing with evolutionary techniques. *AP-SA* (Algorithm 3) is similar to [34]. However, we perform some extra computation to determine initial temperature using an approach stated in [2].

## 4.4 Hill-Climbing

Hill climbing is different from a simulated annealing since there is no cooling schedule. This makes a hill-climbing prone to getting stuck in locally optimal solutions [16, 3]. However, the ease of implementation and effectiveness in numerous optimization problems [28, 33] makes hill-climbing a popular approach for stochastic search spaces. Here is a simple hill-climbing algorithm, similar to [28], to provide a basis on how a naive random search algorithm would do on the antenna placement problem in comparison to other stochastic techniques.

## 5. EXPERIMENTAL SETUP

We used an open source antenna modeling software called Numerical Electromagnetic Code(NEC)[4] to calculate the fitness of an hypothesis. NEC has been widely used for elec-

---

**Algorithm 3: AP-SA**

---

**Data:** Set of placements  $L = \{L_1, \dots, L_m\}$ ;  $T$  - initial temperature;  $i_m$  - maximum iterations;  $f_{cooling}$  - cooling factor

**Result:**  $H^*$  from  $P$

```
1 Initialize  $H \leftarrow$  generate a random hypothesis ;
2 Compute  $fitness(H)$  ;
3  $i = 0$  ;
4 while  $i < i_m$  do
5   Mutation - Apply the operation on  $H$  as stated in
     Algorithm 1. Call the perturbed/mutated
     hypothesis  $C$  ;
6   Compute  $\delta f = fitness(C) - fitness(H)$  ;
7   if  $\delta f > 0$  then
8     Generate a random number  $\epsilon$  using a uniform
       distribution over  $[0, 1]$  ;
9     if  $\epsilon < e^{-\delta f/T}$  then
10       $H \leftarrow C$ 
11    end
12  else
13     $H \leftarrow C$  ;
14  end
15   $T \leftarrow T \cdot f_{cooling}$  ;
16   $i \leftarrow i + 1$  ;
17 end
```

---

---

**Algorithm 4: AP-HC**

---

**Data:** Set of placements  $L = \{L_1, \dots, L_m\}$ ;  $i_m$  - maximum iterations

**Result:**  $H$

```
1 Initialize  $H \leftarrow$  generate a random hypothesis ;
2 Compute  $fitness(H)$  ;
3  $i = 0$  ;
4 while  $i < i_m$  do
5   Mutation - Apply the operator on  $H$  & assign the
     slightly perturbed hypothesis to  $C$  ;
6   Compute  $\delta f = fitness(C) - fitness(H)$  ;
7   if  $\delta f < 0$  then
8      $H \leftarrow C$ 
9   end
10   $i \leftarrow i + 1$ 
11 end
```

---

tromagnetic analysis and simulation work [31, 21]. Moreover, NEC provides a convenient interface to input details about platform with antennas mounted, and to collect simulation results which are mutual coupling and radiation pattern. Our application, *Evolutionary Antenna Placement*<sup>2</sup> (*EAP*), interacts with NEC to provide the input, and subsequently uses the output generated by NEC to calculate fitness.

For our purposes, the hypothesis is written to an input file (to be referred as  $N_{in}$ ) which is used by NEC modeler to generate an output file (to be referred as  $N_{out}$ ). The platform and all antennas of an hypothesis are written to  $N_{in}$  as a set of wires with a start-point and an end-point in 3-dimensional space. For instance, consider a wire represented by 2-tuple,

<sup>2</sup>Link to code repository: <https://github.com/ajauhri/evol-ant-placement>




Figure 2: Platform used for test case 2 (tc2)




Figure 3: Platform used for test case 3 (tc3)

$w$ , of real-valued coordinates;  $\{(0, 0, 0.1), (0, 0.1, 0)\}$ .

Figure 2 shows the meshed platform depicting a squared plate with box and a sloped front used in test case 2 of our experiments. The platform and antenna are just a set of tuples similar to  $w$ . A square plate with box and sides fixed was the platform for test case 3 (Figure 3). Possible antenna locations, for all test cases, are defined by either start-points or end-points of platform wires. Experiments with multiple platforms highlight the technique to be *highly generic* for platforms with any shape and design.

NEC has pre-defined cards which are inserted in  $N_{in}$  to enable collection of fitness parameters. Radiation pattern, generated by the *RF* card, is calculated using a set of field points around a sphere. The number of field points in a radiation pattern is determined by the product of total number of spherical( $\theta$ ) and cylindrical( $\phi$ ) values which encompass points in a sphere. All experiments computed the radiation gain over 4140 points i.e.  $|\theta| \cdot |\phi|$ .

For our placement study,  $m$  input files would be generated by *EAP* for an hypothesis with  $m$  antennas and with only one of the  $m$  antennas excited in each input file. Subsequently, NEC would generate  $m$  output files with perfor-

**Table 2: Antenna Placement Test Cases**

ID	Antennas	Total allowable placements <sup>3</sup>
tc1	2	7,056 (83x83)
tc2	3	50,625 (45x45x25)
tc3	3	126,025 (71x71x25)
tc4	4	20,736 (12x12x12x12)

mance measures. By exciting one antenna in each input file, we are able to quantify the radiation pattern of an antenna in presence of the platform and other antennas. To determine the free-space gain pattern(FSG) for an antenna, an input file is formed with just the antenna and no platform.  $F_{RP}$  is then calculated by *EAP* parsing  $2m(m$  files with platform and antennas;  $m$  files for free space pattern) output files generated by NEC and performing a summation over squared difference in gain between free-space and in the presence of the platform and antennas (Eq.(1)).

The second fitness parameter - mutual coupling, is generated by inserting the *CP* card in the  $(m + 1)th$  file generated by *EAP*. A single file is needed for NEC to generate an output file with mutual coupling results between all possible pairs of antenna placements of an hypothesis.

All test cases were subjected to the same frequency of 100 MegaHertz using the *FR* card. For a detailed description of formatting of  $N_{in}$  and  $N_{out}$  files, refer to the NEC manual [4].

## 6. SIMULATION RESULTS

Comparative study of algorithms is based on multiple test cases listed in Table 2. Test cases were evaluated by NEC simulator which was run in parallel using *GNU Parallel* software package [30].

Each test case was first evaluated with an exhaustive search to determine fitness for all allowable placements and antennas. The results from exhaustive search were also used to normalize fitness function values between  $[0, 1]$ . For all experiments  $\alpha = \beta = 0.5$  in Eq.(3).


Prior to collection of results, a series of trial and error runs were conducted in the case of Algorithm 1 to determine an appropriate mutation rate. Intuitively, a high mutation rate, referred as  $p_m$  in Section 4.1, drives the algorithm into a random search and renders evolutionary aspect of the algorithm weak. This is ascertained in Figure 4 where the mean fitness for each generation is shown over 10 runs of *AP-GA*. However, it is preferred to have a high value for  $p_c$ [18]. For all test cases, *AP-GA* uses  $p_m = 0.1$  &  $p_c = 0.6$ .  $gen_{max}$  for *AP-GA* and *AP-ES* is 10.

For simulated annealing, the cooling factor was kept as  $1 - \tau$ , where  $\tau = 0.01 \cdot m_{iters}$ . Maximum iterations( $m_{iters}$ ) were about 70% of the total allowable placements of a test case. The initial temperature calculated using technique described in [2] ranged  $\in [0.23, 0.27]$ .

... summarizes the average best fitness over 10 runs found by all four algorithms. The best hypothesis  $H^*$ 's fitness is shown under the *Exhaustive* algorithm column.

The reader should observe in Table ... that effectiveness of a stochastic algorithm can be computed by the difference in the fitness found by the exhaustive search algorithm and

<sup>3</sup>Allowable placements for each antenna are provided within parenthesis



**Figure 4: Mutation rates for AP-GA. The mean fitness is calculated over a population size of 500 using test case 1**

stochastic algorithms. Formally:

$$M_{error} = | fitness(H^*) - \sum_{i=1}^{n=10} b_i/n |, \quad (5)$$

where  $b_i$  is the best fitness of the hypothesis found in a run by the stochastic search algorithm. For a test case, this is equivalent to the difference of the cell values of *Exhaustive* column and any one of the stochastic search algorithms in Table

The other important observation is of how many number of fitness function evaluations did each algorithm take to find a good hypothesis? Evolutionary strategy and simulated annealing outperformed the genetic algorithm in terms of mean number of fitness evaluations to find the best hypothesis as seen in Table 3. The number of evaluations recorded were until the algorithm found the best hypothesis or got stuck at some local optimal hypothesis. Number of function evaluations is more appropriate here rather than the CPU clock time as the time may vary for each machine based on the hardware configuration.

We also visualized the fitness terrain of the best hypothesis followed by each of the stochastic algorithms<sup>4</sup>. Such visualization is a good tool to observe the correctness of the algorithm. For instance, a simulated annealing is prone to have an event of accepting a bad hypothesis with a higher probability initially in the run and this event should happen with low probability as algorithm proceeds. For all simulated annealing graphs in Figures 5, 6, 7, & 8, we observe that the gap between any two consecutive events of such nature increases as the algorithm proceeds in the search space.

The genetic algorithm in Figure 6 accepted a worse hypothesis because of the fact that mutation could happen even in the group of elite hypothesis as stated in Algorithm 1. The elites were included in the mutation pool to maintain diversity. For evolutionary strategy and hill climbing,

<sup>4</sup>The best hypothesis's fitness curve was almost similar for all 10 runs




Figure 5: Test Case 1 Comparison




Figure 6: Test Case 2 Comparison

the fitness terrain does not have unorthodox patterns. The values in parenthesis for all population based algorithms viz. genetic algorithm and evolutionary strategy, represent the population size. They were kept at approximately the same ratio with the corresponding size of the search space in Table 2.

This is not the case, since the top ten hypotheses lie within a small fitness range of  $[0.49747, 0.498428]$ . As known in general, the hill-climbing algorithm made progress only in the initial phases of the run and got stuck in local optimums for 80% of the runs for test case 3. The purpose for inclusion of such a random search algorithm was to highlight that antenna placements may not be a trivial task to solve with high probability, if the search space is large as in the case of test case 3. For smaller test cases like test case 4, hill-climbing may be appropriate.

## 7. CONCLUSION




Figure 7: Test Case 3 Comparison




Figure 8: Test Case 4 Comparison

**Table 3: Mean evaluations**

test case \ method	AP-GA	AP-ES	AP-SA	AP-HC
tc1	2350	1728	667	164
tc2	31 680	11 165	1653	174
tc3	45 900	26 880	4809	227
tc4	6150	4466	423	90

A comparison of four stochastic search algorithms applied to antenna placement optimization was presented. The results showed that a trade-off space exists: faster, less successful simulated annealing (*AP-SA*) search versus slower, more successful search by evolutionary strategy (*AP-ES*). The other generation-based algorithm (*AP-GA*) did not prove as effective as evolutionary strategy, and also much slower to find the optimal placements. Also, a random search was studied to ascertain that the antenna placement problem may not be effectively solved by a naive algorithm for large search spaces.

Our work showed that a simple formulation of the antenna placement problem and the usage of open-source technologies (NEC) can be applied effectively for a hard problem. Moreover, our methodology can be applied to any type of a platform which otherwise may be time consuming and expensive in case of large objects like satellites and aircrafts.

## 7.1 Future Work

Most of the stochastic algorithms presented here were elementary and there were no variations to them. For instance, scheduling problems have been effectively solved using hybrid versions of genetic algorithms [32]. Similarly, variations of algorithms mentioned here should also be looked at for the antenna placement problem.

More experiments need to be conducted for population based algorithms with different population sizes, and to statistically compare how this may affect the performance of the algorithm. Also, bigger search spaces need to be considered with more number of antennas. Other evolutionary techniques like ALPS [11], differential evolution algorithm [20], and genetic programming [1] need to be compared in terms of how quickly they find the optimal solution.

## References

- [1] Wolfgang Banzhaf, Peter Nordin, Robert E Keller, and Frank D Francone. Genetic programming: An introduction: On the automatic evolution of computer programs and its applications (the morgan kaufmann series in artificial intelligence). 1997.
- [2] Walid Ben-Ameur. Computing the initial temperature of simulated annealing. *Computational Optimization and Applications*, 29(3):369–385, 2004.
- [3] Julia Borghoff, Lars R Knudsen, and Krystian Matysiewicz. Hill climbing algorithms and trivium. In *Selected Areas in Cryptography*, pages 57–73. Springer, 2011.
- [4] GJ Burke and AJ Poggio. Numerical electromagnetics code (nec)-method of moments, part iii: User’s guide. *Lawrence Livermore National Laboratory*, (1), 1981.
- [5] Lawrence Davis. Genetic algorithms and simulated annealing. 1987.
- [6] Agostin E Eiben and James E Smith. *Introduction to evolutionary computing*, volume 2. Springer Berlin, 2010.
- [7] Celestin Tamgue Famdie, Werner L Schroeder, and Klaus Solbach. Optimal antenna location on mobile phones chassis based on the numerical analysis of characteristic modes. In *Microwave Conference, 2007. European*, pages 987–990. IEEE, 2007.
- [8] David B Fogel. An introduction to simulated evolutionary optimization. *Neural Networks, IEEE Transactions on*, 5(1):3–14, 1994.
- [9] Randy L Haupt and Douglas H Werner. *Genetic algorithms in electromagnetics*. Wiley. com, 2007.
- [10] John H Holland. *Adaptation in natural and artificial systems: An introductory analysis with applications to biology, control, and artificial intelligence*. U Michigan Press, 1975.
- [11] Gregory S Hornby. Alps: the age-layered population structure for reducing the problem of premature convergence. In *Proceedings of the 8th annual conference on Genetic and evolutionary computation*, pages 815–822. ACM, 2006.
- [12] Janne Leivo and Tin Vukusic. Improving the performance of strongly coupled antennas using a compensating transmission line network. 2009.
- [13] Derek S Linden. Automated design and optimization of wire antennas using genetic algorithms. Technical report, DTIC Document, 1997.
- [14] Derek S Linden. Wire antennas optimized in the presence of satellite structures using genetic algorithms. In *Aerospace Conference Proceedings, 2000 IEEE*, volume 5, pages 91–99. IEEE, 2000.
- [15] Jason D Lohn, Derek S Linden, Gregory S Hornby, Adan Rodriguez-Arroyo, Stephen E Seufert, Bruce Blevins, and Thomas Greenling. Evolutionary design of a single-wire circularly-polarized x-band antenna for nasa’s space technology 5 mission. In *Antennas and Propagation Society International Symposium, 2005 IEEE*, volume 2, pages 267–270. IEEE, 2005.
- [16] Zbigniew Michalewicz and David B Fogel. *Escaping Local Optima*. Springer, 2000.
- [17] Brad L Miller and David E Goldberg. Genetic algorithms, tournament selection, and the effects of noise. *Urbana*, 51:61801, 1995.
- [18] Vladimiro Miranda, JV Ranito, and Luis Miguel Proenca. Genetic algorithms in optimal multistage distribution network planning. *Power Systems, IEEE Transactions on*, 9(4):1927–1933, 1994.
- [19] Thomas M. Mitchell. *Machine Learning*. McGraw-Hill, Inc., New York, NY, USA, 1 edition, 1997.
- [20] Quan-Ke Pan, Mehmet Fatih Tasgetiren, and Yun-Chia Liang. A discrete differential evolution algorithm for the permutation flowshop scheduling problem. *Computers & Industrial Engineering*, 55(4):795–816, 2008.



- [21] Ramesh K Pokharel, Masaru Ishii, and Yoshihiro Baba. Numerical electromagnetic analysis of lightning-induced voltage over ground of finite conductivity. *Electromagnetic Compatibility, IEEE Transactions on*, 45(4):651–656, 2003.
- [22] Yahya Rahmat-Samii and Eric Michielssen. *Electromagnetic optimization by genetic algorithms*. John Wiley & Sons, Inc., 1999.
- [23] Jussi Rahola and Jani Ollikainen. Optimal antenna placement for mobile terminals using characteristic mode analysis. In *Antennas and Propagation, 2006. EuCAP 2006. First European Conference on*, pages 1–6. IEEE, 2006.
- [24] Larry Raisanen and Roger M Whitaker. Comparison and evaluation of multiple objective genetic algorithms for the antenna placement problem. *Mobile Networks and Applications*, 10(1-2):79–88, 2005.
- [25] G Rudolph. Evolutionary search under partially ordered sets. *Dept. Comput. Sci./LS11, Univ. Dortmund, Dortmund, Germany, Tech. Rep. CI-67/99*, 1999.
- [26] Hans-Paul Schwefel. *Numerische Optimierung von Computer-Modellen mittels der Evolutionsstrategie: mit einer vergleichenden Einführung in die Hill-Climbing-und Zufallsstrategie*. Birkhäuser Basel, 1977.
- [27] Randall S Sexton, Robert E Dorsey, and John D Johnson. Optimization of neural networks: A comparative analysis of the genetic algorithm and simulated annealing. *European Journal of Operational Research*, 114(3):589–601, 1999.
- [28] David B Skalak. Prototype and feature selection by sampling and random mutation hill climbing algorithms. In *ICML*, pages 293–301. Citeseer, 1994.
- [29] Anders Stjernman. Antenna mutual coupling effects on correlation, efficiency and shannon capacity. In *Antennas and Propagation, 2006. EuCAP 2006. First European Conference on*, pages 1–6. IEEE, 2006.
- [30] Ole Tange. Gnu parallel-the command-line power tool. *login: The USENIX Magazine*, pages 42–47, 2011.
- [31] Tomasz Topa, Andrzej Karwowski, and Artur Noga. Using gpu with cuda to accelerate mom-based electromagnetic simulation of wire-grid models. *Antennas and Wireless Propagation Letters, IEEE*, 10:342–345, 2011.
- [32] Vicente Valls, Francisco Ballestin, and Sacramento Quintanilla. A hybrid genetic algorithm for the resource-constrained project scheduling problem. *European Journal of Operational Research*, 185(2):495–508, 2008.
- [33] Bowei Xi, Zhen Liu, Mukund Raghavachari, Cathy H Xia, and Li Zhang. A smart hill-climbing algorithm for application server configuration. In *Proceedings of the 13th international conference on World Wide Web*, pages 287–296. ACM, 2004.
- [34] Lei Xu and Erkki Oja. Improved simulated annealing, boltzmann machine, and attributed graph matching. In *Neural Networks*, pages 151–160. Springer, 1990.
- [35] Eckart Zitzler, Kalyanmoy Deb, and Lothar Thiele. Comparison of multiobjective evolutionary algorithms: Empirical results. *Evolutionary computation*, 8(2):173–195, 2000.