A Comparison of Antenna Placement Algorithms

Abhinav Jauhri

March 12, 2015

Motivation

- Antenna placement on a multi-platform is a manual, and time consuming process

Motivation

- Antenna placement on a multi-platform is a manual, and time consuming process
- Number of possible placements (search space) of antennas becomes exponentially large in the number of antennas to be placed

Motivation

- Antenna placement on a multi-platform is a manual, and time consuming process
- Number of possible placements (search space) of antennas becomes exponentially large in the number of antennas to be placed
- Stochastic algorithms have been used effectively to find antenna designs *(Reference: Hornby, Lohn, & Linden. "Computer-Automated Evolution of an X-Band Antenna for NASA's Space Technology 5 Mission." 2011)*

Motivation

- Antenna placement on a multi-platform is a manual, and time consuming process
- Number of possible placements (search space) of antennas becomes exponentially large in the number of antennas to be placed
- Stochastic algorithms have been used effectively to find antenna designs *(Reference: Hornby, Lohn, & Linden. "Computer-Automated Evolution of an X-Band Antenna for NASA's Space Technology 5 Mission." 2011)*

How can we automate the process by use of stochastic algorithms?

Antenna Placement Example



- A_1 has 24 possible antenna placements
- A_2 has 33 possible antenna placements
- A_3 has 136 possible antenna placements

Size of search space $= m^n$

Antenna Placement Problem

Given:

- platform P with its surface gridded such that end points represent possible antenna placement

Antenna Placement Problem

Given:

- platform P with its surface gridded such that end points represent possible antenna placement
- set of m $(m > 1)$ antennas $A = A_1, A_2, \ldots, A_m$

Antenna Placement Problem

Given:

- platform P with its surface gridded such that end points represent possible antenna placement
- set of m $(m > 1)$ antennas $A = A_1, A_2, \ldots, A_m$
- for each A_i, let L_i denote the set of allowable placements locations $\in \mathbb{R}^3$ such that $\mid L_i \mid = n_i$ and $\forall i, n_i > 1$; $L_i = \{(x_1, y_1, z_1) \ldots (x_{n_i}, y_{n_i}, z_{n_i})\}$

Antenna Placement Problem

Given:

- platform P with its surface gridded such that end points represent possible antenna placement
- set of m $(m > 1)$ antennas $A = A_1, A_2, \ldots, A_m$
- for each A_i, let L_i denote the set of allowable placements locations $\in \mathbb{R}^3$ such that $|L_i| = n_i$ and $\forall i, n_i > 1$; $L_i = \{(x_1, y_1, z_1) \ldots (x_{n_i}, y_{n_i}, z_{n_i})\}$

Goal: A set of m optimal antenna locations on P

Stochastic Algorithms

We will consider algorithms which rely on *randomization* principle.

- Simple Genetic Algorithm
- Evolutionary Strategy
- Simulated Annealing
- Hill Climbing

Representation



A hypothesis is represented by a set of antenna placements. For instance - $((x_1, y_1, z_1), (x_1, y_1, z_1), (x_1, y_1, z_1))$

Evolutionary Strategy

Algorithm 1: AP-ES

Data: Set of placements $L = \{L_1, \cdots, L_m\}$; μ; λ; gen_{max} - maximum number of generations

Result: H^* from P

Initialize $P \leftarrow$ generate μ random hypothesis ;

$gen_{id} = 0$;

while $gen_{id} < gen_{max}$ **do**

    Create λ/μ offsprings from each μ hypotheses by applying mutation operator, and add all offsprings to P ;

    Compute the $fitness(h_i), i = 1, \ldots, \lambda$;

    Keep μ best hypotheses in P, and discard remaining $\lambda - \mu$ hypotheses ;

    Update $gen_{id} \leftarrow gen_{id} + 1$

end

Simulated Annealing

Algorithm 2: AP-SA

Data: Set of placements $L = \{L_1, \cdots, L_m\}$; T - initial temperature; i_m - maximum iterations; $f_{cooling}$ - cooling factor

Result: H^* from P

Initialize $H \leftarrow$ generate a random hypothesis ;
Compute $fitness(H)$;
$i = 0$;
while $i < i_m$ **do**
    Mutation - Apply the operation on H as stated in Algorithm . Call the pertubrated/mutated hypothesis C ;
    Compute $\delta f = fitness(C) - fitness(H)$;
    if $\delta f > 0$ **then**
        Generate a random number ϵ using a uniform distribution over $[0, 1]$;
        if $\epsilon < e^{-\delta f / T}$ **then**
            $H \leftarrow C$
        end
    else
        $H \leftarrow C$;
    end
    $T \leftarrow T \cdot f_{cooling}$;
    $i \leftarrow i + 1$;
end

Antenna Placement Objectives

Antenna Placement Issues

- → Coupling among antennas
- → Parasitic effects and reflections from the host platform
- → Loss of efficiency
- → Difficulty conforming to aerodynamic, thermal, other enovironment factors

Desired Antenna Placement Objectives

- → Gain in radiation pattern
- → Minimize coupling

Minimize Difference in Radiation Pattern

Pattern defines the ratio of energy radiated and input energy in a particular direction. For each antenna A_i:

$$F_{RP}(A_i) = \sum_{\theta}\sum_{\phi} \| ISG_i(\theta,\phi) - FSG_i(\theta,\phi) \|^2, \qquad (1)$$

where

- θ,ϕ spherical and cylindrical coordinates
- $ISG(\cdot)$ returns in-situ gain pattern
- $FSG(\cdot)$ returns free-space gain pattern



Minimize Coupling

Coupling is the absorption of radiated energy by nearby antennas

$$F_{MC} = \sum_{i=1}^{m-1} \sum_{j=i+1}^{m} CP(A_i, A_j), \qquad (2)$$

where

- $CP(\cdot)$ computes the coupling between two antennas
- $i \neq j$

Overall Fitness Function

For an hypothesis, fitness is defined as:

$$F = \alpha F_{MC} + \beta \sum_i F_{RP}(A_i), \tag{3}$$

TODO: about weights

Experimental Setup

- Create (s) such that each individual is defined by a placement for each of the *m* antennas
- Run all individuals through *NEC* simulator [1] to get fitness parameters
- Apply EA operators
- Repeat...

[1] http://www.nec2.org

Experiments: Test Cases

Test Case	Antennas	Total allowable placements
1	2	7,056 (83x83)
2	3	50,625 (45x45x25)
3	3	126,025 (71x71x25)
4	4	20,736 (12x12x12x12)

*Allowable placements for each antenna are provided within parenthesis

Results - Success Probability





Results - Success Probability





Results: Mean Evaluations

Mean number of evaluations to reach the best solution (over 10 runs):

test case \ method	GA	ES	SA	HC
tc1(7056)[2]	2350	1728	667	164
tc2(50,625)	31 680	11 165	1653	174
tc3(126,025)	45 900	26 880	4809	227
tc4(20,736)	6150	4466	423	90

[2] Total number of possible evaluations within parenthesis

Equivalence of fitness to efficiency

For a particular test case, fitness change of 0.01 is equivalent to either the corresponding value under expected gain ($\mathbb{E}_g$) column, or difference in coupling (Δ_c).

ID	$\mathbb{E}_g$	Δ_c (dB)
tc1	872.277	0.5474
tc2	862.082	1.3034
tc3	861.845	1.5180
tc4	871.049	0.5693

$\mathbb{E}_g = \frac{1}{N \cdot m} \sum_i^m F_{RP}(A_i)$, where $N = |\theta| \cdot |\phi|$

Conclusion

- Formulation of the antenna placement problem
- Generic to accommodate multiple antennas and platforms
- Optimal placements found using stochastic algorithms