API Reference

All endpoints are JSON over HTTPS under `/api`, called by the panel's own UI with the session cookie. There is no public API key scheme. Third parties integrate only through webhooks.

> **Generated from the route files.** The tables below were produced from `src/routes/*.js`, and the *Permission* column from the rules in `src/lib/authGuard.js`. When a route is added, regenerate or update this file in the same change.

1. Conventions

Topic	Rule
Authentication	HttpOnly cookie `ad_session`, set by `/api/auth/login/verify`. Missing or expired → `401 { needsAuth: true }`
CSRF	Every non-GET `/api` request must be same-origin (`Sec-Fetch-Site` / `Origin` / `Referer` checked) → else `403`
Tenancy	Every organisation-scoped route acts on the requester's organisation only. Another organisation's id → `404`
Plan gate	Organisation routes (servers, apps, installs, runners, credentials, environments, connectors, git OAuth) need an active plan → else `402 { needsPlan: true, trialExpired? }`
Plan limits	Creating servers, apps, members, database connections or domains beyond the plan's limit → `403 { limitReached: true, limit }` (the UI shows the message instead of jumping to billing)
Errors	`{ error: "sentence" }` with 400 / 401 / 402 / 403 / 404 / 429 / 502
Long work	Deploys and installs return immediately; poll the resource's status

Permission column

The permission comes from the HTTP method, applied by `guardMutations` to every signed-in route:

Method	Needs
`GET`	`view`
`POST`	`create`, **except** read-only POSTs (testing, verifying, browsing) on an explicit allowlist, which need only `view`
`PUT` / `PATCH`	`edit`
`DELETE`	`delete`

Some routes check more inside the handler, for example:

- `/api/team/*` and choosing or paying for a plan need `members`.
- Environment and app variable *values* need `edit`.
- `/api/platform/*` is super admin only.

2. Endpoints outside the routers

Method	Path	Access	Purpose
`GET`	`/api/health`	public	Panel status (database reachable, counts for the signed-in organisation)
`GET`	`/api/public/plans`	public	Plans for the pricing section
`POST`	`/api/public/leads`	public, rate-limited	Landing page "Get started" form
`GET`	`/api/public/docs`	public	The guide list
`GET`	`/api/activity`	view	Last 50 activity log entries for the organisation
`POST`	`/api/hooks/apps/:token`	webhook token	Git push / merge webhook → auto deploy
`POST`	`/api/hooks/razorpay`	HMAC signature	Razorpay payment events
`GET` (WS)	`/api/connectors/ws`	connector token	Connector relay channel
`GET` (WS)	`/api/terminal/ws?server=:id`	session + same origin + `edit` + plan	Browser terminal
`GET`	`/vendor/xterm/*`, `/vendor/addon-fit/*`	public	Terminal UI library files

WebSocket message formats

Terminal (`/api/terminal/ws`)

Direction	Frame
browser → panel	`{"t":"in","d":"<keystrokes>"}`, `{"t":"resize","cols":120,"rows":32}`
panel → browser	binary frames = terminal output; `{"t":"ready"}`, `{"t":"error","message"}`, `{"t":"exit","code"}`
close codes	`4000 + HTTP status` when refused (e.g. `4401` not signed in, `4403` cross-site or no permission, `4402` no plan, `4429` too many terminals)

3. Endpoints by module

Sign-in, sign-up, OTP, profile — `/api/auth` (12)

Source: src/routes/auth.js

Method	Path	Permission	Notes
`GET`	`/api/auth/state`	public	What the browser needs before it can draw anything
`POST`	`/api/auth/setup`	public	First run only
`POST`	`/api/auth/signup`	public	Anyone can create their own organisation, in three steps
`POST`	`/api/auth/signup/verify`	public	Step 2

Method	Path	Permission	Notes
`POST`	`/api/auth/otp/resend`	public	A new code for a sign-up or sign-in that is waiting on one
`POST`	`/api/auth/login`	public	Sign in with an email or a mobile number and the password, then a one-time code
`POST`	`/api/auth/login/verify`	public	Step 2 of signing in
`POST`	`/api/auth/verify-email/resend`	public	Send the verification link again
`POST`	`/api/auth/logout`	signed in	
`PUT`	`/api/auth/profile`	signed in	Change your own name, mobile number or the email you sign in with
`POST`	`/api/auth/password`	signed in	Change your own password
`POST`	`/api/auth/organisation`	signed in	A super admin opens a client organisation to work inside it, or (org_id empty) goes back to the platform

The organisation's plan and payments — `/api/billing` (7)

Source: src/routes/billing.js

Method	Path	Permission	Notes
`GET`	`/api/billing`	view	
`POST`	`/api/billing/choose`	create	Pick a plan
`POST`	`/api/billing/checkout`	create	Open a Razorpay order for a paid plan; the browser opens Checkout on it
`POST`	`/api/billing/checkout/verify`	create	Checkout finished
`POST`	`/api/billing/checkout/recheck`	create	Checkout closed without a confirmed answer
`POST`	`/api/billing/checkout/failed`	create	Checkout reported a failed or abandoned payment
`DELETE`	`/api/billing/request`	delete	Withdraw a request that has not been switched on yet

Members and organisations — `/api/team` (8)

Source: src/routes/team.js

Method	Path	Permission	Notes
`GET`	`/api/team/members`	view	Everyone in the organisation you are working in
`POST`	`/api/team/members`	create	Add someone to this organisation with a role
`PUT`	`/api/team/members/:id`	edit	Change someone's name, role, status or password
`DELETE`	`/api/team/members/:id`	delete	

Method	Path	Permission	Notes
`GET`	`/api/team/organisations`	view	A super admin sees every organisation; everyone else sees only their own
`POST`	`/api/team/organisations`	create	
`PUT`	`/api/team/organisations/:id`	edit	
`DELETE`	`/api/team/organisations/:id`	delete	Deleting an organisation takes its servers, credentials and people with it, so it is refused while anything is still in there

Platform console — `/api/platform` (24)

Source: src/routes/platform.js

Method	Path	Permission	Notes
`GET`	`/api/platform/docs`	super admin	Every guide, including the ones only super admins see
`GET`	`/api/platform/plans`	super admin	
`POST`	`/api/platform/plans`	super admin	
`PUT`	`/api/platform/plans/:id`	super admin	
`DELETE`	`/api/platform/plans/:id`	super admin	A plan someone is on is archived (hidden, kept); one nobody ever used is deleted
`GET`	`/api/platform/organisations`	super admin	
`POST`	`/api/platform/organisations`	super admin	A new organisation, optionally with its first admin and a plan
`PUT`	`/api/platform/organisations/:id`	super admin	
`PUT`	`/api/platform/organisations/:id/subscription`	super admin	
`PUT`	`/api/platform/organisations/:id/subscription/expiry`	super admin	End any plan — free or paid — on a date, or now
`POST`	`/api/platform/organisations/:id/subscription/activate`	super admin	Switch on the plan an organisation asked for
`DELETE`	`/api/platform/organisations/:id/subscription/request`	super admin	Turn down a plan request; whatever the organisation is on stays as it is
`GET`	`/api/platform/organisations/:id`	super admin	One organisation in full
`POST`	`/api/platform/organisations/:id/users`	super admin	A new person in a client organisation

Method	Path	Permission	Notes
`GET`	`/api/platform/admins`	super admin	
`POST`	`/api/platform/admins`	super admin	
`PUT`	`/api/platform/admins/:id`	super admin	
`DELETE`	`/api/platform/admins/:id`	super admin	
`GET`	`/api/platform/payments`	super admin	
`POST`	`/api/platform/organisations/:id/payments`	super admin	
`DELETE`	`/api/platform/payments/:id`	super admin	
`GET`	`/api/platform/users`	super admin	
`PUT`	`/api/platform/users/:id/organisation`	super admin	Move someone to another organisation (roles, status and passwords go through /api/team)
`GET`	`/api/platform/dashboard`	super admin	

Leads CRM — `/api/platform/leads` (11)

Source: src/routes/leads.js

Method	Path	Permission	Notes
`GET`	`/api/platform/leads`	super admin	
`POST`	`/api/platform/leads`	super admin	A lead typed in by hand — a phone call, a referral
`GET`	`/api/platform/leads/analytics`	super admin	
`GET`	`/api/platform/leads/summary`	super admin	How many leads are waiting — for the badge in the side menu
`GET`	`/api/platform/leads/:id`	super admin	
`PUT`	`/api/platform/leads/:id`	super admin	Move a lead along, hand it to someone, or correct its details
`POST`	`/api/platform/leads/:id/locate`	super admin	Look the lead's IP address up again (or for the first time, for leads from before locations were kept)
`POST`	`/api/platform/leads/:id/notes`	super admin	

Method	Path	Permission	Notes
`DELETE`	`/api/platform/leads/:id/notes/:noteId`	super admin	
`POST`	`/api/platform/leads/:id/convert`	super admin	Turn a lead into a client
`DELETE`	`/api/platform/leads/:id`	super admin	

Servers and everything on them — `/api/servers` (76)

Source: src/routes/servers.js

Method	Path	Permission	Notes
`GET`	`/api/servers`	view	
`GET`	`/api/servers/status`	view	Just the statuses, for the list to poll
`POST`	`/api/servers/test`	create	
`GET`	`/api/servers/setup-script`	view	Downloads `aj-pilot-setup.sh` (`text/x-shellscript`, attachment). Query, all optional: `ssh_port` (1–65535, default 22), `timezone` (IANA name), `hostname`, `user` (account to give passwordless sudo; default the one running `sudo`), `ssh_key` (one OpenSSH public key line), `screen_minutes` (1–60, default 1), and on/off flags `sleep`, `lid`, `screen`, `wifi`, `wol`, `time`, `firewall`, `web_ports`, `fail2ban`, `updates`, `sudo`, `swap`, `docker`, `tools` (`1`/`0`; all default on except `docker`). `400` with `{ error }` for a bad value. Contains no secrets
`POST`	`/api/servers`	create	
`GET`	`/api/servers/:id`	view	
`GET`	`/api/servers/:id/history`	view	Every profile ever collected for this server, newest first
`GET`	`/api/servers/:id/metrics`	view	CPU, memory, disk and load over `?range=daily
`PUT`	`/api/servers/:id`	edit	
`DELETE`	`/api/servers/:id`	delete	
`GET`	`/api/servers/:id/secrets`	view	The stored password, passphrase and sudo password, for the Show button of the edit form

Method	Path	Permission	Notes
`POST`	`/api/servers/:id/host-key/reset`	create	Forget the remembered SSH host key, after the server was rebuilt or reinstalled
`POST`	`/api/servers/:id/test`	view	
`POST`	`/api/servers/:id/facts`	view	
`GET`	`/api/servers/:id/facts`	view	
`GET`	`/api/servers/:id/services`	view	Every systemd service on the host, live
`GET`	`/api/servers/:id/services/:unit`	view	One unit in full, with its recent journal
`POST`	`/api/servers/:id/services/:unit/action`	create	start / stop / restart / reload / enable / disable a unit
`POST`	`/api/servers/:id/services`	create	Create a new systemd service from the add-service form
`DELETE`	`/api/servers/:id/services/:unit`	delete	Remove a unit this panel wrote
`GET`	`/api/servers/:id/docker`	view	Is Docker there, its networks, and everything running on it
`POST`	`/api/servers/:id/docker/networks`	create	A user-defined network, so installed services can reach each other by name
`POST`	`/api/servers/:id/docker/login`	create	Sign this server in to a container registry, so it can pull private images

Method	Path	Permission	Notes
`POST`	`/api/servers/:id/docker/logout`	create	
`DELETE`	`/api/servers/:id/docker/volumes/:name`	delete	Remove a named volume — with the data in it
`DELETE`	`/api/servers/:id/docker/networks/:name`	delete	
`GET`	`/api/servers/:id/summary`	view	What is on this server, counted — one SSH pass for the Overview tab
`GET`	`/api/servers/:id/cron`	view	Everything scheduled on this server, wherever it is written down
`POST`	`/api/servers/:id/cron/install`	create	
`POST`	`/api/servers/:id/cron/jobs`	create	Add a job to a user's crontab
`PUT`	`/api/servers/:id/cron/jobs`	edit	Change one job
`POST`	`/api/servers/:id/reboot`	create	Restart the machine
`GET`	`/api/servers/:id/users`	view	
`POST`	`/api/servers/:id/users`	create	
`PUT`	`/api/servers/:id/users/:name`	edit	

Method	Path	Permission	Notes
`POST`	`/api/servers/:id/users/:name/keys`	create	Add public keys, or have the server make a new pair and hand back the private half once
`DELETE`	`/api/servers/:id/users/:name/keys`	delete	
`DELETE`	`/api/servers/:id/users/:name`	delete	
`DELETE`	`/api/servers/:id/cron/jobs`	delete	
`GET`	`/api/servers/:id/runners`	view	The CI runners on this server, as the machine itself reports them
`GET`	`/api/servers/:id/stats`	view	One sample, for anything that wants a number rather than a stream
`GET`	`/api/servers/:id/stats/stream`	view	SSE: `sample`, `problem`, `end` events every `?every=` ms (2000–60000, default 5000)
`POST`	`/api/servers/:id/containers/:name/action`	create	start / stop / restart a container, whoever put it there
`GET`	`/api/servers/:id/containers/:name`	view	Everything about one container
`DELETE`	`/api/servers/:id/containers/:name`	delete	Remove a container that is not one of the panel's own
`GET`	`/api/servers/:id/containers/:name/logs`	view	

Method	Path	Permission	Notes
`GET`	`/api/servers/:id/containers/:name/stream`	view	SSE for the container page: `sample` = `{ at, host, containers:[one], usage }` every `?every=` ms (2000–60000, default 3000); `log` = `{ lines[] }`, each `<RFC 3339 timestamp> <text>`, first the last `?tail=` lines (1–2000, default 200) then new ones as written, resumed after a stop or restart; `problem`, `end`. Shares the `STATS_MAX_STREAMS` / `STATS_MAX_STREAMS_PER_ORG` slots (else `429`)
`GET`	`/api/servers/:id/containers/:name/compose`	edit	Download `<name>.docker-compose.yml`, rebuilt from `docker inspect`, environment values included
`GET`	`/api/servers/:id/containers/:name/backup`	edit	Download `<name>-backup-<date>.tar.gz`: compose file, `inspect.json`, `README.txt`, `volumes/<volume>.tar.gz` per volume mounted (named or anonymous). `?pause=1` pauses a running container while its volumes are copied
`GET`	`/api/servers/:id/docker/volumes/:name/download`	edit	Download one named volume's contents as `<name>.tar.gz`
`GET`	`/api/servers/:id/nginx`	view	nginx, its sites and its certificates — everything the tab draws
`POST`	`/api/servers/:id/nginx/install`	create	
`POST`	`/api/servers/:id/nginx/action`	create	reload / restart / start / stop / test
`POST`	`/api/servers/:id/nginx/upstreams`	create	Add an upstream
`PUT`	`/api/servers/:id/nginx/upstreams/:name`	edit	Change an upstream — its servers, ports, weights and balancing — where it is
`DELETE`	`/api/servers/:id/nginx/upstreams/:name`	delete	

Method	Path	Permission	Notes
`POST`	`/api/servers/:id/nginx/sites`	create	Add a domain
`GET`	`/api/servers/:id/nginx/sites/:name`	view	The file as it stands, for the edit box
`PUT`	`/api/servers/:id/nginx/sites/:name`	edit	Edit a domain — the whole file, or the form's fields again
`DELETE`	`/api/servers/:id/nginx/sites/:name`	delete	Remove a domain
`POST`	`/api/servers/:id/nginx/ssl`	create	Ask Let's Encrypt for a certificate and let certbot put it into the vhost
`POST`	`/api/servers/:id/nginx/ssl/renew`	create	Renew everything due, or one certificate
`GET`	`/api/servers/:id/nginx/logs`	view	The access and error logs, analysed — with findings and fixes
`POST`	`/api/servers/:id/nginx/logs/analyzer`	create	Add the analyzer's log format (and an empty blocklist) to nginx
`DELETE`	`/api/servers/:id/nginx/logs/analyzer`	delete	
`POST`	`/api/servers/:id/nginx/logs/blocklist`	create	
`DELETE`	`/api/servers/:id/nginx/logs/blocklist`	delete	

Method	Path	Permission	Notes
`POST`	`/api/servers/:id/nginx/logs/fail2ban`	create	fail2ban with its nginx jails, so repeat offenders are banned without anyone watching
`POST`	`/api/servers/:id/exec`	create	
`GET`	`/api/servers/:id/files`	view	
`GET`	`/api/servers/:id/files/content`	view	
`GET`	`/api/servers/:id/files/download`	view	
`PUT`	`/api/servers/:id/files/content`	edit	
`POST`	`/api/servers/:id/files/folder`	create	
`POST`	`/api/servers/:id/files/file`	create	
`POST`	`/api/servers/:id/files/upload`	create	
`PUT`	`/api/servers/:id/files/move`	edit	
`POST`	`/api/servers/:id/files/copy`	create	
`PUT`	`/api/servers/:id/files/permissions`	edit	

Method	Path	Permission	Notes
`POST`	`/api/servers/:id/files/extract`	create	
`DELETE`	`/api/servers/:id/files`	delete	

Deployed apps, auto deploy, domains, usage — `/api/apps` (27)

Source: src/routes/apps.js

Method	Path	Permission	Notes
`POST`	`/api/apps/folders`	create	The folders in a branch that hold a project of their own, for a repository with several apps in it
`POST`	`/api/apps/inspect`	create	Is this repository (or this folder of it) something the panel can deploy, and with what settings?
`POST`	`/api/apps/ports`	create	Body `{ server_id, ports[], app_id? }` → `{ busy: [{ port, by }], checked }`. Host ports already published by another app on that server, or listening there (`ss -ltnH` over SSH). `app_id` leaves that app's own ports out. `checked: false` when the server could not be reached (only the panel's own apps were compared)
`GET`	`/api/apps`	view	Each app carries `health` — its latest recorded level (`ok` / `warning` / `critical`), or null
`GET`	`/api/apps/stats`	view	What every app uses right now — `{ apps: { [id]: usage
`GET`	`/api/apps/:id`	view	
`GET`	`/api/apps/:id/metrics`	view	CPU and memory (as a share of the server) over `?range=daily
`GET`	`/api/apps/:id/stats/stream`	view	SSE: one app's containers every `?every=` ms — `sample = { at, host, containers[], usage }`; at most `APP_STATS_STREAMS_PER_ORG` open per organisation (else `429`)
`POST`	`/api/apps`	create	`409` when a chosen host port is already used on the server (same check as `/api/apps/ports`)
`GET`	`/api/apps/:id/auto-deploy`	view	The settings, with the webhook address — secret, so only for people who can edit
`PUT`	`/api/apps/:id/auto-deploy`	edit	Turn auto deploy on or off, choose "every push" or "merged requests only", and (re)add the webhook

Method	Path	Permission	Notes
`POST`	`/api/apps/:id/auto-deploy/check`	create	"Check now"
`GET`	`/api/apps/:id/deployments`	view	
`GET`	`/api/apps/:id/deployments/:did`	view	One deploy with its full log — the running one reads the live log
`PUT`	`/api/apps/:id/settings`	edit	
`POST`	`/api/apps/:id/deploy`	create	Build and run the current branch again — the same path as the first deploy
`POST`	`/api/apps/:id/deploy/stop`	create	Stop a deploy that is running — a manual one or an auto deploy
`POST`	`/api/apps/:id/deploy/restart`	create	Stop the running deploy and start a fresh one from the branch as it is now
`POST`	`/api/apps/:id/domains`	create	Add another domain to an app. Body `{ domain, domain_mode: "dns" | "zerotrust" | "nginx", domain_port?, domain_email? }`; `dns` and `zerotrust` also need `domain_cred_id` (Cloudflare), `nginx` takes `domain_ssl: true|false` and needs no credential. `202` — set up in the background. The same `domain_*` fields (plus `domain_enabled: true`) add a domain in `POST /api/apps`
`POST`	`/api/apps/:id/domains/:domainId/retry`	create	Run one domain's setup again
`DELETE`	`/api/apps/:id/domains/:domainId`	delete	Take one domain off an app
`GET`	`/api/apps/:id/env`	view	The variables as they are, so they can be edited rather than retyped
`PUT`	`/api/apps/:id/env`	edit	Replace the environment of a service that is already running
`PUT`	`/api/apps/:id/containers`	edit	Add or remove containers, and give each one the port it publishes on. `409` when a new port is already used on the server

Method	Path	Permission	Notes
`POST`	`/api/apps/:id/action`	create	
`GET`	`/api/apps/:id/logs`	view	
`DELETE`	`/api/apps/:id`	delete	Removing takes a while — stopping containers, deleting the image, Cloudflare, nginx and the certificate for every domain — longer than a pro

Catalog installations — `/api/installs` (10)

Source: src/routes/installs.js

Method	Path	Permission	Notes
`GET`	`/api/installs/catalog`	view	What can be installed, and the form each one needs; each entry carries `requires` — the services that must be on the server first
`GET`	`/api/installs/requirements`	view	`?server_id=&kind=` → `{ missing: [{ key, label, problem }] }` — the services `kind` needs (catalog `requires`: `docker`, `nginx`) that the server lacks, checked over SSH. `POST /api/installs` refuses the same cases
`GET`	`/api/installs`	view	
`GET`	`/api/installs/:id`	view	
`POST`	`/api/installs`	create	
`POST`	`/api/installs/:id/refresh`	view	What Docker says about this container right now
`POST`	`/api/installs/:id/action`	create	
`GET`	`/api/installs/:id/logs`	view	
`PUT`	`/api/installs/:id/port`	edit	Change the published port
`DELETE`	`/api/installs/:id`	delete	Remove the container

CI runners — `/api/runners` (6)

Source: src/routes/runners.js

Method	Path	Permission	Notes
`GET`	`/api/runners`	view	Every runner, or only those for one git account (`credential_id`) or server (`server_id`)

Method	Path	Permission	Notes
`GET`	`/api/runners/:id`	view	
`POST`	`/api/runners`	create	
`POST`	`/api/runners/:id/refresh`	view	Ask the provider what it thinks of this runner right now
`POST`	`/api/runners/:id/action`	create	Start, stop or restart the runner's systemd service on its server
`DELETE`	`/api/runners/:id`	delete	Unregister the runner with the provider, take it off the server, and forget it here

Git, Docker Hub, Cloudflare, MySQL accounts — `/api/credentials` (45)

Source: src/routes/credentials.js

Method	Path	Permission	Notes
`GET`	`/api/credentials`	view	
`GET`	`/api/credentials/:id`	view	
`POST`	`/api/credentials`	create	
`PUT`	`/api/credentials/:id`	edit	
`DELETE`	`/api/credentials/:id`	delete	
`POST`	`/api/credentials/:id/verify`	view	
`POST`	`/api/credentials/test-mysql`	view	Test MySQL details before saving them
`POST`	`/api/credentials/test-git`	view	Authenticate a git token before saving it
`POST`	`/api/credentials/:id/git/account`	view	Re-authenticate and refresh the stored account details
`POST`	`/api/credentials/:id/git/repositories`	view	Repositories this account can reach
`POST`	`/api/credentials/:id/git/branches`	view	Branches of one repository — `full` is "owner/repo"
`POST`	`/api/credentials/:id/git/commits`	view	Recent commits on a branch
`POST`	`/api/credentials/:id/git/organizations`	view	Organisations (GitHub) or groups (GitLab) a runner can be registered in
`POST`	`/api/credentials/:id/git/runners`	view	Runners the provider itself knows about for one repository, organisation or group — including ones this panel never installed
`GET`	`/api/credentials/dockerhub/token-link`	view	Where the browser flow sends the person to create a token
`POST`	`/api/credentials/dockerhub/connect`	create	Finish the browser flow

Method	Path	Permission	Notes
`POST`	`/api/credentials/:id/dockerhub/repositories`	view	Repositories in the account's own namespace, or one of its organisations
`POST`	`/api/credentials/:id/dockerhub/repositories/:ns/:repo`	view	One repository with every tag
`DELETE`	`/api/credentials/:id/dockerhub/repositories/:ns/:repo/tags/:tag`	delete	
`GET`	`/api/credentials/cloudflare/token-link`	view	The dashboard link that opens a pre-filled "Create API token" form
`POST`	`/api/credentials/test-cloudflare`	view	Verify a token and show what it can see, without saving it
`POST`	`/api/credentials/cloudflare/connect`	create	Finish the browser flow
`POST`	`/api/credentials/:id/cloudflare/account`	view	Re-read the account, its accounts and zones
`POST`	`/api/credentials/:id/cloudflare/zones/:zoneId`	view	One zone in full
`DELETE`	`/api/credentials/:id/cloudflare/zones/:zoneId`	delete	Remove a domain from Cloudflare
`POST`	`/api/credentials/:id/cloudflare/zones/:zoneId/dns/records`	create	Add a DNS record
`PUT`	`/api/credentials/:id/cloudflare/zones/:zoneId/dns/records/:recordId`	edit	Change a DNS record
`DELETE`	`/api/credentials/:id/cloudflare/zones/:zoneId/dns/records/:recordId`	delete	Delete a DNS record
`POST`	`/api/credentials/:id/cloudflare/zones/:zoneId/dns`	view	DNS records of one zone this token can see
`POST`	`/api/credentials/:id/mysql/overview`	view	
`POST`	`/api/credentials/:id/mysql/databases/:database`	view	
`POST`	`/api/credentials/:id/mysql/databases/:database/tables/:table`	view	
`POST`	`/api/credentials/:id/mysql/query`	view	
`POST`	`/api/credentials/:id/mysql/charsets`	view	
`POST`	`/api/credentials/:id/mysql/schemas`	create	Creating goes to /schemas so it never matches the read-only /databases/:db pattern.

Method	Path	Permission	Notes
`PUT`	`/api/credentials/:id/mysql/databases/:database`	edit	
`DELETE`	`/api/credentials/:id/mysql/databases/:database`	delete	
`POST`	`/api/credentials/:id/mysql/users/list`	view	
`POST`	`/api/credentials/:id/mysql/users`	create	
`PUT`	`/api/credentials/:id/mysql/users`	edit	
`DELETE`	`/api/credentials/:id/mysql/users`	delete	
`POST`	`/api/credentials/:id/mysql/users/grants`	create	
`DELETE`	`/api/credentials/:id/mysql/users/grants`	delete	
`POST`	`/api/credentials/:id/mysql/variables`	view	
`PUT`	`/api/credentials/:id/mysql/variables`	edit	

PostgreSQL, MongoDB, Redis, Elasticsearch — `/api/credentials` (22)

Source: src/routes/dbEngines.js. The engine is picked from the credential's `provider`. For Elasticsearch, "database" in these paths means an **index**, `item` is a field of that index, `users` are security users, `grants` are roles, and `config` is persistent cluster settings. `POST …/db/query` takes Dev Tools syntax, for example `GET /_cat/indices` or `POST /orders/_search` followed by a JSON body. Only `GET` and search-type `POST` (`_search`, `_count`, `_msearch`, `_field_caps`, `_validate/query`, `_sql`) are allowed.

Method	Path	Permission	Notes
`POST`	`/api/credentials/test-db`	view	Try the details on the add-connection form before saving them
`POST`	`/api/credentials/:id/db/overview`	view	
`POST`	`/api/credentials/:id/db/databases`	view	
`POST`	`/api/credentials/:id/db/database`	view	
`POST`	`/api/credentials/:id/db/item`	view	
`POST`	`/api/credentials/:id/db/users/list`	view	
`POST`	`/api/credentials/:id/db/config`	view	
`POST`	`/api/credentials/:id/db/query`	view	
`POST`	`/api/credentials/:id/db/schemas`	create	

Method	Path	Permission	Notes
`DELETE`	`/api/credentials/:id/db/databases`	delete	
`POST`	`/api/credentials/:id/db/users`	create	
`PUT`	`/api/credentials/:id/db/users`	edit	
`DELETE`	`/api/credentials/:id/db/users`	delete	
`POST`	`/api/credentials/:id/db/users/grants`	create	
`DELETE`	`/api/credentials/:id/db/users/grants`	delete	
`PUT`	`/api/credentials/:id/db/config`	edit	
`POST`	`/api/credentials/:id/redis/scan`	view	
`POST`	`/api/credentials/:id/redis/key`	view	
`POST`	`/api/credentials/:id/redis/keys`	create	
`PUT`	`/api/credentials/:id/redis/key`	edit	
`DELETE`	`/api/credentials/:id/redis/keys`	delete	
`GET`	`/api/credentials/pulse`	view	

Named variable sets — `/api/environments` (6)

Source: src/routes/environments.js

Method	Path	Permission	Notes
`GET`	`/api/environments`	view	
`GET`	`/api/environments/:id`	view	
`POST`	`/api/environments`	create	
`POST`	`/api/environments/:id/duplicate`	create	A copy under a new name — a staging set made from production, say
`PUT`	`/api/environments/:id`	edit	Change the name, description or variables
`DELETE`	`/api/environments/:id`	delete	Apps and services made from it keep their own copy of the variables; only the link goes

PC relays — `/api/connectors` (5)

Source: src/routes/connectors.js

Method	Path	Permission	Notes
`GET`	`/api/connectors`	view	
`POST`	`/api/connectors`	create	A new connector
`POST`	`/api/connectors/:id/token`	create	A new token

Method	Path	Permission	Notes
`PUT`	`/api/connectors/:id`	edit	
`DELETE`	`/api/connectors/:id`	delete	

Git OAuth sign-in — `/api/git/oauth` (3)

Source: src/routes/gitOauth.js

Method	Path	Permission	Notes
`GET`	`/api/git/oauth/providers`	view	Which providers can be used for browser sign-in, and the callback to register
`GET`	`/api/git/oauth/start`	view	Step 1 — send the browser to the provider
`GET`	`/api/git/oauth/callback`	view	Step 2 — the provider sends the browser back here with a code