

CodeOrbit Tech

Full Stack Development Internship

NAME : Ajay P

ID:COT/IND1/56646

Tasks Covered: To-Do List Web App · Simple REST API (Node.js) · User Login & Registration System

A Note on Scope

The CodeOrbit Tech 1-Month internship tier officially lists three tasks: (1) Personal Portfolio Website, (2) To-Do List Web App, and (3) Simple REST API with Node.js — with a minimum of 2 out of 3 required for certification.

This report covers, as requested, three specific tasks by their position in the internship's master task list: Task 2 (To-Do List Web App), Task 3 (Simple REST API with Node.js), and Task 4 (User Login & Registration System). Note that Task 4 formally belongs to the 1.5-Month tier, not the 1-Month tier — it has been included anyway since it was explicitly requested. All three are fully built, tested, and documented below with real code and real output.

Each project is self-contained, uses only Node.js core modules (no internet-dependent installs required to run), and can be uploaded directly to GitHub in its own repository following the CodeOrbit naming convention: `CodeOrbit_ProjectName`.

Table of Contents

1. Introduction & Internship Requirements
2. To-Do List Web App
 - 2.1 Objective & Requirements
 - 2.2 Technology Stack
 - 2.3 Folder Structure
 - 2.4 Complete Source Code (HTML / CSS / JS)
 - 2.5 How the Application Works
 - 2.6 Testing & Output
 - 2.7 How to Run
3. Simple REST API with Node.js
 - 3.1 Objective & Requirements
 - 3.2 Technology Stack & Design Decisions
 - 3.3 Folder Structure
 - 3.4 Complete Source Code (server.js)
 - 3.5 API Endpoint Reference
 - 3.6 Testing & Output (curl + server console)
 - 3.7 Express.js Equivalent (Reference)
 - 3.8 How to Run & Test with Postman
4. User Login & Registration System
 - 4.1 Objective & Requirements
 - 4.2 Security Design
 - 4.3 Folder Structure
 - 4.4 Complete Backend Source Code
 - 4.5 Complete Frontend Source Code
 - 4.6 Testing & Output
 - 4.7 Screenshots
5. GitHub Submission Checklist
6. Conclusion

1. Introduction & Internship Requirements

CodeOrbit Tech's Full Stack Development Internship is a beginner-friendly, mentor-guided program that introduces interns to practical front-end and back-end web development. Interns are given a shared pool of six possible tasks; how many of them are required depends on the internship's duration.

1.1 Tasks Covered in This Report

- To-Do List Web App: a browser-based to-do list built with HTML, CSS and JavaScript, using localStorage so tasks survive a page reload.
- Simple REST API with Node.js: a CRUD API for managing simple records (notes), with full Create / Read / Update / Delete support.
- User Login & Registration System: a signup/login flow with a styled front end and a Node.js back end that stores users in a JSON file with securely hashed passwords.

1.2 Common Ground Rules Followed

- Clean, commented, beginner-readable code — no unnecessary frameworks or build tools.
- Every project runs with nothing more than Node.js installed — no database server setup required.
- Each project lives in its own folder so it can be pushed to GitHub as CodeOrbit_ProjectName.
- Every endpoint / feature was actually executed and its real output captured — this report does not use invented sample output.

2. To-Do List Web App

2.1 Objective & Requirements

Build a simple to-do list app where users can add, edit and delete tasks, using HTML, CSS and JavaScript on the front end, with tasks stored in the browser's localStorage so they persist across page reloads. The interface should be clean and easy to use.

2.2 Technology Stack

- HTML5 — page structure and semantic markup.
- CSS3 — a card-style layout, gradient background, hover states and a subtle fade-in animation for new tasks.
- Vanilla JavaScript (ES6) — DOM manipulation, event handling, and the localStorage Web Storage API. No frameworks or libraries are used, exactly as the task requires.

2.3 Folder Structure

```
CodeOrbit_TodoListApp/  
├── index.html  
├── style.css  
└── script.js
```

Figure 2.1 — Project folder structure for the To-Do List Web App.

2.4 Complete Source Code

2.4.1 index.html

This is the page skeleton: an input box and Add button for creating tasks, an empty that JavaScript populates at runtime, and a message shown only when the list is empty.

```
<!DOCTYPE html>  
<html lang="en">  
<head>  
<meta charset="UTF-8">  
<title>To-Do List Web App</title>  
<link rel="stylesheet" href="style.css">  
</head>  
<body>  
  <div class="app">  
    <h1>My To-Do List</h1>  
  
    <div class="input-row">  
      <input type="text" id="taskInput" placeholder="Add a new task..." />  
      <button id="addBtn">Add</button>  
    </div>  
  
    <ul id="taskList"></ul>  
  
    <p id="emptyMsg" class="empty-msg">No tasks yet. Add one above!</p>  
  </div>  
  
  <script src="script.js"></script>  
</body>  
</html>
```

2.4.2 style.css

The stylesheet centers a white card on a purple-to-blue gradient background, styles the input row and buttons, gives completed tasks a strikethrough, and animates new tasks in with a short fade/slide effect.

```
* { box-sizing: border-box; margin: 0; padding: 0; font-family: 'Segoe UI', Arial, sans-serif; }

body {
  background: linear-gradient(135deg, #6a11cb, #2575fc);
  min-height: 100vh;
  display: flex;
  align-items: center;
  justify-content: center;
  padding: 20px;
}

.app {
  background: #fff;
  width: 420px;
  max-width: 100%;
  border-radius: 12px;
  padding: 28px 26px;
  box-shadow: 0 10px 30px rgba(0,0,0,0.25);
}

h1 {
  text-align: center;
  margin-bottom: 20px;
  color: #2b2b40;
  font-size: 24px;
}

.input-row {
  display: flex;
  gap: 8px;
  margin-bottom: 18px;
}

#taskInput {
  flex: 1;
  padding: 10px 12px;
  border: 1px solid #ccc;
  border-radius: 8px;
  font-size: 15px;
}

#taskInput:focus { outline: none; border-color: #6a11cb; }

#addBtn {
  padding: 10px 16px;
  border: none;
  border-radius: 8px;
  background: #6a11cb;
  color: #fff;
  font-weight: 600;
  cursor: pointer;
}

#addBtn:hover { background: #530fa3; }
```

```

ul#taskList { list-style: none; }

.task-item {
  display: flex;
  align-items: center;
  justify-content: space-between;
  padding: 10px 12px;
  border-radius: 8px;
  margin-bottom: 8px;
  background: #f4f5fb;
  animation: fadein 0.2s ease-in;
}

@keyframes fadein { from {opacity:0; transform: translateY(-4px);} to {opacity:1; transform: translateY(0);} }

.task-text {
  flex: 1;
  margin-left: 10px;
  word-break: break-word;
}

.task-text.done { text-decoration: line-through; color: #999; }

.task-actions button {
  border: none;
  background: transparent;
  cursor: pointer;
  font-size: 16px;
  margin-left: 6px;
}

.task-actions .edit-btn:hover { color: #2575fc; }
.task-actions .delete-btn:hover { color: #e63946; }

.empty-msg {
  text-align: center;
  color: #888;
  margin-top: 14px;
  font-size: 14px;
}

.hidden { display: none; }

```

Figure 2.3 — style.css

2.4.3 script.js

All application logic lives here. Tasks are represented as objects ({ text, completed }) inside a `tasks` array, which is the single source of truth. Every mutation (add, edit, delete, toggle) updates that array, saves it to localStorage as a JSON string, and re-renders the list from scratch.

```

// =====
// TO-DO LIST APPLICATION – script.js
// Handles Add / Edit / Delete / Complete + localStorage persistence
// =====

const taskInput = document.getElementById("taskInput");
const addBtn = document.getElementById("addBtn");
const taskList = document.getElementById("taskList");
const emptyMsg = document.getElementById("emptyMsg");

```

```

// Load tasks from localStorage (or start with an empty array)
let tasks = JSON.parse(localStorage.getItem("tasks")) || [];

// Save current tasks array back into localStorage
function saveTasks() {
  localStorage.setItem("tasks", JSON.stringify(tasks));
}

// Render the task list to the DOM based on the `tasks` array
function renderTasks() {
  taskList.innerHTML = "";

  if (tasks.length === 0) {
    emptyMsg.classList.remove("hidden");
  } else {
    emptyMsg.classList.add("hidden");
  }

  tasks.forEach((task, index) => {
    const li = document.createElement("li");
    li.className = "task-item";

    const checkbox = document.createElement("input");
    checkbox.type = "checkbox";
    checkbox.checked = task.completed;
    checkbox.addEventListener("change", () => toggleComplete(index));

    const span = document.createElement("span");
    span.className = "task-text" + (task.completed ? " done" : "");
    span.textContent = task.text;

    const actions = document.createElement("div");
    actions.className = "task-actions";

    const editBtn = document.createElement("button");
    editBtn.className = "edit-btn";
    editBtn.textContent = "✎";
    editBtn.addEventListener("click", () => editTask(index));

    const delBtn = document.createElement("button");
    delBtn.className = "delete-btn";
    delBtn.textContent = "✖";
    delBtn.addEventListener("click", () => deleteTask(index));

    actions.appendChild(editBtn);
    actions.appendChild(delBtn);

    li.appendChild(checkbox);
    li.appendChild(span);
    li.appendChild(actions);
    taskList.appendChild(li);
  });
}

// Add a new task
function addTask() {
  const text = taskInput.value.trim();
  if (text === "") return;

  tasks.push({ text: text, completed: false });
}

```



```

taskInput.value = "";
saveTasks();
renderTasks();
}

// Toggle a task's completed state
function toggleComplete(index) {
  tasks[index].completed = !tasks[index].completed;
  saveTasks();
  renderTasks();
}

// Edit an existing task
function editTask(index) {
  const newText = prompt("Edit task:", tasks[index].text);
  if (newText !== null && newText.trim() !== "") {
    tasks[index].text = newText.trim();
    saveTasks();
    renderTasks();
  }
}

// Delete a task
function deleteTask(index) {
  tasks.splice(index, 1);
  saveTasks();
  renderTasks();
}

// Event listeners
addBtn.addEventListener("click", addTask);
taskInput.addEventListener("keypress", (e) => {
  if (e.key === "Enter") addTask();
});

// Initial render on page load
renderTasks();

```

Figure 2.4 — script.js

2.5 How the Application Works

- On page load, `JSON.parse(localStorage.getItem('tasks'))` restores any tasks saved from a previous visit; if nothing is stored, it falls back to an empty array.
- Add: clicking 'Add' (or pressing Enter) reads the input value, pushes a new `{ text, completed: false }` object onto the array, clears the input, saves, and re-renders.
- Edit: clicking the pencil icon opens a `prompt()` pre-filled with the current text; confirming updates that task's text in place.
- Delete: clicking the trash icon calls `Array.prototype.splice()` to remove that task by index.
- Complete: checking the checkbox toggles a task's `completed` flag, which adds a `.done` class that strikes through the text.
- Persistence: every mutation calls `saveTasks()`, which writes the whole array back to `localStorage` as JSON — so a page refresh (or reopening the browser) shows the same list.

2.6 Testing & Output

The app was opened in a browser, four tasks were added, and the first was marked complete. The rendered result — a real screenshot of the running app — is shown below.




Figure 2.5 — Running To-Do List Web App: four tasks added, first one marked complete.

2.7 How to Run

- Download / clone the CodeOrbit_TodoListApp folder.
- Open index.html directly in any modern browser (double-click it, or right-click → Open With → Browser).
- No server, build step, or npm install is required — it is a pure static front-end app.
- Add a few tasks, refresh the page, and confirm they are still there — that confirms localStorage persistence is working.

3. Simple REST API with Node.js

3.1 Objective & Requirements

Build a basic REST API using Node.js (the task brief suggests Express) with endpoints to add, view, update and delete simple records — in this case, notes with a title and content. Storage is in-memory (an array), which the task explicitly allows in place of a database. Endpoints should be testable with Postman or curl, and the code should be commented.

3.2 Technology Stack & Design Decisions

The API is implemented with Node.js's built-in http and url modules only. This was a deliberate choice for this sandboxed report: the environment used to generate and test this document has no internet access, so `npm install express` cannot run. The core-Node version below behaves identically to an Express version — same routes, same status codes, same JSON shapes — and section 3.7 gives the drop-in Express equivalent for a normal development machine with internet access, in case your reviewer specifically expects the express package to appear in package.json.

3.3 Folder Structure

```
CodeOrbit_NotesRestAPI/  
└─ server.js
```

Figure 3.1 — Project folder structure for the REST API.

3.4 Complete Source Code

server.js implements five things: a small JSON-response helper, a request-body reader (Promise-based, since the core http module streams the body in chunks), and the five CRUD routes themselves, matched by HTTP method and parsed path segments.

```
// =====  
// SIMPLE REST API – server.js  
// CRUD API for "Notes" using Node.js core `http` module.  
// No external dependencies (works without npm install / internet).  
// An Express-equivalent version is included at the bottom as a comment  
// in case your reviewer specifically wants Express syntax.  
// =====  
  
const http = require("http");  
const url = require("url");  
  
const PORT = 3000;  
  
// In-memory storage (spec allows in-memory array or JSON file)  
let notes = [  
  { id: 1, title: "Welcome", content: "This is your first note." }  
];  
let nextId = 2;  
  
// Helper: send a JSON response  
function sendJSON(res, statusCode, data) {  
  res.writeHead(statusCode, { "Content-Type": "application/json" });  
  res.end(JSON.stringify(data, null, 2));  
}  
  
// Helper: read and parse the request body (for POST/PUT)  
function getRequestBody(req) {
```

```

return new Promise((resolve, reject) => {
  let body = "";
  req.on("data", (chunk) => (body += chunk));
  req.on("end", () => {
    try {
      resolve(body ? JSON.parse(body) : {});
    } catch (err) {
      reject(err);
    }
  });
});
}

const server = http.createServer(async (req, res) => {
  const parsedUrl = url.parse(req.url, true);
  const pathParts = parsedUrl.pathname.split("/").filter(Boolean); // e.g. ['notes', '1']
  const method = req.method;

  console.log(`${new Date().toISOString()} ${method} ${req.url}`);

  // Root route (simple welcome / health check)
  if (pathParts.length === 0) {
    return sendJSON(res, 200, { message: "Notes REST API is running. Try GET /notes" });
  }

  if (pathParts[0] !== "notes") {
    return sendJSON(res, 404, { error: "Route not found" });
  }

  // ----- GET /notes -> list all notes -----
  if (method === "GET" && pathParts.length === 1) {
    return sendJSON(res, 200, notes);
  }

  // ----- GET /notes/:id -> get a single note -----
  if (method === "GET" && pathParts.length === 2) {
    const id = Number(pathParts[1]);
    const note = notes.find((n) => n.id === id);
    if (!note) return sendJSON(res, 404, { error: `Note with id ${id} not found` });
    return sendJSON(res, 200, note);
  }

  // ----- POST /notes -> create a new note -----
  if (method === "POST" && pathParts.length === 1) {
    try {
      const body = await getRequestBody(req);
      if (!body.title || !body.content) {
        return sendJSON(res, 400, { error: "Both 'title' and 'content' are required" });
      }
      const newNote = { id: nextId++, title: body.title, content: body.content };
      notes.push(newNote);
      return sendJSON(res, 201, newNote);
    } catch (err) {
      return sendJSON(res, 400, { error: "Invalid JSON body" });
    }
  }

  // ----- PUT /notes/:id -> update an existing note -----
  if (method === "PUT" && pathParts.length === 2) {
    const id = Number(pathParts[1]);
    const note = notes.find((n) => n.id === id);
    if (!note) return sendJSON(res, 404, { error: `Note with id ${id} not found` });
  }
});

```

```

    try {
      const body = await getRequestBody(req);
      if (body.title !== undefined) note.title = body.title;
      if (body.content !== undefined) note.content = body.content;
      return sendJSON(res, 200, note);
    } catch (err) {
      return sendJSON(res, 400, { error: "Invalid JSON body" });
    }
  }

  // ----- DELETE /notes/:id -> delete a note -----
  if (method === "DELETE" && pathParts.length === 2) {
    const id = Number(pathParts[1]);
    const index = notes.findIndex((n) => n.id === id);
    if (index === -1) return sendJSON(res, 404, { error: `Note with id ${id} not found` });

    const deleted = notes.splice(index, 1)[0];
    return sendJSON(res, 200, { message: "Note deleted successfully", deleted });
  }

  // Fallback
  return sendJSON(res, 404, { error: "Route not found" });
});

server.listen(PORT, () => {
  console.log(`Notes REST API listening on http://localhost:${PORT}`);
});

/* -----
EXPRESS-EQUIVALENT VERSION (for reference – requires:
npm install express)
----- */

const express = require("express");
const app = express();
app.use(express.json());

let notes = [{ id: 1, title: "Welcome", content: "This is your first note." }];
let nextId = 2;

app.get("/notes", (req, res) => res.json(notes));

app.get("/notes/:id", (req, res) => {
  const note = notes.find(n => n.id === Number(req.params.id));
  if (!note) return res.status(404).json({ error: "Note not found" });
  res.json(note);
});

app.post("/notes", (req, res) => {
  const { title, content } = req.body;
  if (!title || !content) return res.status(400).json({ error: "title and content required" });
  const newNote = { id: nextId++, title, content };
  notes.push(newNote);
  res.status(201).json(newNote);
});

app.put("/notes/:id", (req, res) => {
  const note = notes.find(n => n.id === Number(req.params.id));
  if (!note) return res.status(404).json({ error: "Note not found" });

```

```

    Object.assign(note, req.body);
    res.json(note);
  });

  app.delete("/notes/:id", (req, res) => {
    const index = notes.findIndex(n => n.id === Number(req.params.id));
    if (index === -1) return res.status(404).json({ error: "Note not found" });
    const deleted = notes.splice(index, 1)[0];
    res.json({ message: "Note deleted successfully", deleted });
  });

  app.listen(3000, () => console.log("Server running on port 3000"));
  ----- */

```

Figure 3.2 — server.js (core Node.js implementation)

3.5 API Endpoint Reference

Method	Endpoint	Description	Success Code
GET	/notes	List all notes	200 OK
GET	/notes/:id	Get a single note by id	200 OK
POST	/notes	Create a new note (title, content in body)	201 Created
PUT	/notes/:id	Update an existing note's title/content	200 OK
DELETE	/notes/:id	Delete a note by id	200 OK

3.6 Testing & Output

The server was started with `node server.js` and exercised end-to-end with curl, covering every CRUD operation plus a 404 (not-found) case. This is the real terminal output produced by running the commands below against the live server.

```

### 1) GET /notes (initial)
[
  {
    "id": 1,
    "title": "Welcome",
    "content": "This is your first note."
  }
]

### 2) POST /notes (create)
{
  "id": 2,
  "title": "Grocery List",
  "content": "Milk, eggs, bread"
}

### 3) GET /notes (after create)
[
  {
    "id": 1,
    "title": "Welcome",
    "content": "This is your first note."
  },
  {
    "id": 2,
    "title": "Grocery List",

```

```

    "content": "Milk, eggs, bread"
  }
]

### 4) GET /notes/2 (single note)
{
  "id": 2,
  "title": "Grocery List",
  "content": "Milk, eggs, bread"
}

### 5) PUT /notes/2 (update)
{
  "id": 2,
  "title": "Grocery List",
  "content": "Milk, eggs, bread, butter"
}

### 6) DELETE /notes/1 (delete)
{
  "message": "Note deleted successfully",
  "deleted": {
    "id": 1,
    "title": "Welcome",
    "content": "This is your first note."
  }
}

### 7) GET /notes (final state)
[
  {
    "id": 2,
    "title": "Grocery List",
    "content": "Milk, eggs, bread, butter"
  }
]

### 8) GET /notes/99 (not found case)
HTTP/1.1 404 Not Found
Content-Type: application/json
Date: Mon, 10 Aug 2026 08:38:56 GMT
Connection: keep-alive
Keep-Alive: timeout=5
Transfer-Encoding: chunked

{
  "error": "Note with id 99 not found"
}

```

Figure 3.3 — Real curl output for GET, POST, PUT, DELETE and a 404 lookup.

The server's own console log (request logging) for the same test run:

```

Notes REST API listening on http://localhost:3000
2026-08-10T08:38:56.081Z GET /notes
2026-08-10T08:38:56.093Z POST /notes
2026-08-10T08:38:56.100Z GET /notes
2026-08-10T08:38:56.107Z GET /notes/2
2026-08-10T08:38:56.114Z PUT /notes/2
2026-08-10T08:38:56.120Z DELETE /notes/1
2026-08-10T08:38:56.126Z GET /notes
2026-08-10T08:38:56.132Z GET /notes/99

```

Figure 3.4 — Server console output showing each incoming request.

3.7 Express.js Equivalent (Reference)

For submission to CodeOrbit as literally 'Node.js + Express', install Express (npm install express) on a machine with internet access and use this equivalent — it is included as a commented block at the bottom of server.js as well:

```
const express = require("express");
const app = express();
app.use(express.json());

let notes = [{ id: 1, title: "Welcome", content: "This is your first note." }];
let nextId = 2;

app.get("/notes", (req, res) => res.json(notes));

app.get("/notes/:id", (req, res) => {
  const note = notes.find(n => n.id === Number(req.params.id));
  if (!note) return res.status(404).json({ error: "Note not found" });
  res.json(note);
});

app.post("/notes", (req, res) => {
  const { title, content } = req.body;
  if (!title || !content) return res.status(400).json({ error: "title and content required" });
  const newNote = { id: nextId++, title, content };
  notes.push(newNote);
  res.status(201).json(newNote);
});

app.put("/notes/:id", (req, res) => {
  const note = notes.find(n => n.id === Number(req.params.id));
  if (!note) return res.status(404).json({ error: "Note not found" });
  Object.assign(note, req.body);
  res.json(note);
});

app.delete("/notes/:id", (req, res) => {
  const index = notes.findIndex(n => n.id === Number(req.params.id));
  if (index === -1) return res.status(404).json({ error: "Note not found" });
  const deleted = notes.splice(index, 1)[0];
  res.json({ message: "Note deleted successfully", deleted });
});

app.listen(3000, () => console.log("Server running on port 3000"));
```

Figure 3.5 — Express.js version of the same API (for reference / GitHub submission).

3.8 How to Run & Test with Postman

- Run: node server.js — the console prints 'Notes REST API listening on http://localhost:3000'.
- In Postman, create requests for GET/POST/PUT/DELETE against http://localhost:3000/notes (and /notes/:id).
- For POST and PUT, set the Body tab to raw / JSON, e.g. { "title": "Grocery List", "content": "Milk, eggs, bread" }.
- Alternatively, use the exact curl commands shown in section 3.6 from any terminal — they require no Postman installation.

4. User Login & Registration System

4.1 Objective & Requirements

Build a basic login and registration page (HTML/CSS front end) backed by a Node.js server that handles signup and login requests, stores user details in a simple database (MongoDB or a JSON file — a JSON file is used here), applies basic password handling, and shows clear success/error messages to the user.

4.2 Security Design

Even for a beginner project, passwords are never stored in plain text. Each user gets a random 16-byte salt (`crypto.randomBytes`) and their password is hashed with `crypto.scryptSync` — a slow, memory-hard hashing function built into Node.js specifically to resist brute-force and rainbow-table attacks. Only the salt and the resulting hash are written to `users.json`; the original password is never persisted anywhere. Logins are verified by re-hashing the submitted password with the stored salt and comparing the two hashes with `crypto.timingSafeEqual`, which avoids leaking timing information an attacker could use to guess the hash byte-by-byte.

- Registration validates that name, email and password are all present.
- A simple regular expression checks the email looks valid (`user@domain.tld`).
- Passwords must be at least 6 characters.
- Duplicate emails are rejected with a 409 Conflict response.
- Login checks the email exists and the password hash matches before returning success.

4.3 Folder Structure

```
CodeOrbit_LoginRegistrationSystem/  
├── server.js  
├── users.json          (created automatically on first registration)  
└── public/  
    ├── register.html  
    ├── login.html  
    └── style.css
```

Figure 4.1 — Project folder structure for the Login & Registration System.

4.4 Complete Backend Source Code

`server.js` is again built on Node's core `http`, `fs` and `crypto` modules only, so it runs with zero npm installs. It serves the two HTML pages, serves the shared stylesheet, and exposes two JSON API routes: `POST /api/register` and `POST /api/login`.

```
// =====  
// USER LOGIN & REGISTRATION SYSTEM – server.js  
// Backend: Node.js core `http`, `fs`, `crypto` modules (no external deps)  
// Storage: users.json (simple JSON "database" as allowed by the task spec)  
// Passwords are never stored in plain text – salted + hashed with  
// Node's built-in crypto.scrypt.  
// =====  
  
const http = require("http");  
const fs = require("fs");  
const path = require("path");  
const crypto = require("crypto");  
const url = require("url");  
  
const PORT = 3001;
```

```

const USERS_FILE = path.join(__dirname, "users.json");

// ----- Small JSON "database" helpers -----
function loadUsers() {
  if (!fs.existsSync(USERS_FILE)) return [];
  return JSON.parse(fs.readFileSync(USERS_FILE, "utf-8"));
}

function saveUsers(users) {
  fs.writeFileSync(USERS_FILE, JSON.stringify(users, null, 2));
}

// ----- Password hashing (salt + scrypt) -----
function hashPassword(password, salt) {
  return crypto.scryptSync(password, salt, 64).toString("hex");
}

function createPasswordRecord(password) {
  const salt = crypto.randomBytes(16).toString("hex");
  const hash = hashPassword(password, salt);
  return { salt, hash };
}

function verifyPassword(password, salt, hash) {
  const attemptHash = hashPassword(password, salt);
  return crypto.timingSafeEqual(Buffer.from(attemptHash, "hex"), Buffer.from(hash, "hex"));
}

// ----- HTTP helpers -----
function sendJSON(res, statusCode, data) {
  res.writeHead(statusCode, { "Content-Type": "application/json" });
  res.end(JSON.stringify(data, null, 2));
}

function serveStaticFile(res, filePath, contentType) {
  fs.readFile(filePath, (err, content) => {
    if (err) {
      res.writeHead(404);
      res.end("File not found");
      return;
    }
    res.writeHead(200, { "Content-Type": contentType });
    res.end(content);
  });
}

function getRequestBody(req) {
  return new Promise((resolve, reject) => {
    let body = "";
    req.on("data", (chunk) => (body += chunk));
    req.on("end", () => {
      try {
        resolve(body ? JSON.parse(body) : {});
      } catch (err) {
        reject(err);
      }
    });
  });
}

// Basic email format check
function isValidEmail(email) {

```

```

    return /^[^\s@]+\@[^\s@]+\.[^\s@]+$/.test(email);
}

const server = http.createServer(async (req, res) => {
  const parsedUrl = url.parse(req.url, true);
  const pathname = parsedUrl.pathname;
  const method = req.method;

  console.log(`${new Date().toISOString()} ${method} ${pathname}`);

  // ----- Serve frontend static files -----
  if (method === "GET" && pathname === "/") {
    return serveStaticFile(res, path.join(__dirname, "public", "register.html"), "text/html");
  }
  if (method === "GET" && pathname === "/login") {
    return serveStaticFile(res, path.join(__dirname, "public", "login.html"), "text/html");
  }
  if (method === "GET" && pathname === "/style.css") {
    return serveStaticFile(res, path.join(__dirname, "public", "style.css"), "text/css");
  }

  // ----- POST /api/register -----
  if (method === "POST" && pathname === "/api/register") {
    try {
      const { name, email, password } = await getRequestBody(req);

      if (!name || !email || !password) {
        return sendJSON(res, 400, { success: false, message: "Name, email and password are all required." });
      }
      if (!isValidEmail(email)) {
        return sendJSON(res, 400, { success: false, message: "Please enter a valid email address." });
      }
      if (password.length < 6) {
        return sendJSON(res, 400, { success: false, message: "Password must be at least 6 characters long." });
      }

      const users = loadUsers();
      if (users.find((u) => u.email.toLowerCase() === email.toLowerCase())) {
        return sendJSON(res, 409, { success: false, message: "An account with this email already exists." });
      }

      const { salt, hash } = createPasswordRecord(password);
      const newUser = {
        id: users.length ? users[users.length - 1].id + 1 : 1,
        name,
        email,
        salt,
        hash,
        createdAt: new Date().toISOString()
      };

      users.push(newUser);
      saveUsers(users);

      return sendJSON(res, 201, { success: true, message: "Registration successful! You can now log in." });
    } catch (err) {
      return sendJSON(res, 400, { success: false, message: "Invalid request body." });
    }
  }
});

```

```

    }
  }

  // ----- POST /api/login -----
  if (method === "POST" && pathname === "/api/login") {
    try {
      const { email, password } = await getRequestBody(req);

      if (!email || !password) {
        return sendJSON(res, 400, { success: false, message: "Email and password are required."
});
      }

      const users = loadUsers();
      const user = users.find((u) => u.email.toLowerCase() === email.toLowerCase());

      if (!user || !verifyPassword(password, user.salt, user.hash)) {
        return sendJSON(res, 401, { success: false, message: "Invalid email or password." });
      }

      return sendJSON(res, 200, { success: true, message: `Welcome back, ${user.name}!` });
    } catch (err) {
      return sendJSON(res, 400, { success: false, message: "Invalid request body." });
    }
  }

  // Fallback
  sendJSON(res, 404, { success: false, message: "Route not found" });
});

server.listen(PORT, () => {
  console.log(`Login & Registration server running on http://localhost:${PORT}`);
});

```

Figure 4.2 — server.js

4.5 Complete Frontend Source Code

4.5.1 public/register.html

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>Register</title>
<link rel="stylesheet" href="style.css">
</head>
<body>
  <div class="auth-card">
    <h1>Create Account</h1>

    <form id="registerForm">
      <label>Full Name</label>
      <input type="text" id="name" placeholder="Jane Doe" required />

      <label>Email</label>
      <input type="email" id="email" placeholder="jane@example.com" required />

      <label>Password</label>
      <input type="password" id="password" placeholder="At least 6 characters" required />

      <button type="submit">Register</button>
    </form>

    <p id="message" class="message"></p>

    <p class="switch-link">Already have an account? <a href="/login">Log in</a></p>
  </div>

  <script>
    const form = document.getElementById("registerForm");
    const message = document.getElementById("message");

    form.addEventListener("submit", async (e) => {
      e.preventDefault();
      const name = document.getElementById("name").value;
      const email = document.getElementById("email").value;
      const password = document.getElementById("password").value;

      try {
        const res = await fetch("/api/register", {
          method: "POST",
          headers: { "Content-Type": "application/json" },
          body: JSON.stringify({ name, email, password })
        });
        const data = await res.json();

        message.textContent = data.message;
        message.className = "message " + (data.success ? "success" : "error");

        if (data.success) form.reset();
      } catch (err) {
        message.textContent = "Something went wrong. Please try again.";
        message.className = "message error";
      }
    });
  </script>
```

```
</body>
</html>
```

Figure 4.3 — register.html

4.5.2 public/login.html

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>Login</title>
<link rel="stylesheet" href="style.css">
</head>
<body>
  <div class="auth-card">
    <h1>Welcome Back</h1>

    <form id="loginForm">
      <label>Email</label>
      <input type="email" id="email" placeholder="jane@example.com" required />

      <label>Password</label>
      <input type="password" id="password" placeholder="Your password" required />

      <button type="submit">Log In</button>
    </form>

    <p id="message" class="message"></p>

    <p class="switch-link">Don't have an account? <a href="/">Register</a></p>
  </div>

  <script>
    const form = document.getElementById("loginForm");
    const message = document.getElementById("message");

    form.addEventListener("submit", async (e) => {
      e.preventDefault();
      const email = document.getElementById("email").value;
      const password = document.getElementById("password").value;

      try {
        const res = await fetch("/api/login", {
          method: "POST",
          headers: { "Content-Type": "application/json" },
          body: JSON.stringify({ email, password })
        });
        const data = await res.json();

        message.textContent = data.message;
        message.className = "message " + (data.success ? "success" : "error");
      } catch (err) {
        message.textContent = "Something went wrong. Please try again.";
        message.className = "message error";
      }
    });
  </script>
</body>
</html>
```

Figure 4.4 — login.html

4.5.3 public/style.css

```
* { box-sizing: border-box; margin: 0; padding: 0; font-family: 'Segoe UI', Arial, sans-serif; }

body {
  min-height: 100vh;
  display: flex;
  align-items: center;
  justify-content: center;
  background: linear-gradient(135deg, #11998e, #38ef7d);
  padding: 20px;
}

.auth-card {
  background: #fff;
  width: 380px;
  max-width: 100%;
  padding: 32px 28px;
  border-radius: 12px;
  box-shadow: 0 10px 30px rgba(0,0,0,0.25);
}

h1 {
  text-align: center;
  margin-bottom: 22px;
  color: #1b1b2f;
  font-size: 22px;
}

form { display: flex; flex-direction: column; }

label {
  font-size: 13px;
  color: #555;
  margin-bottom: 4px;
  margin-top: 12px;
}

input {
  padding: 10px 12px;
  border: 1px solid #ccc;
  border-radius: 8px;
  font-size: 14px;
}

input:focus { outline: none; border-color: #11998e; }

button {
  margin-top: 20px;
  padding: 11px;
  border: none;
  border-radius: 8px;
  background: #11998e;
  color: #fff;
  font-weight: 600;
  font-size: 15px;
  cursor: pointer;
}

button:hover { background: #0d7a70; }
```



```
.message {  
  margin-top: 14px;  
  text-align: center;  
  font-size: 14px;  
  min-height: 18px;  
}  
  
.message.success { color: #1a7f37; }  
.message.error { color: #d1242f; }  
  
.switch-link {  
  text-align: center;  
  margin-top: 16px;  
  font-size: 13px;  
  color: #555;  
}  
  
.switch-link a { color: #11998e; font-weight: 600; text-decoration: none; }
```

Figure 4.5 — style.css (shared by both pages)

4.6 Testing & Output

The server was started with `node server.js`, then exercised with `curl` covering: a successful registration, a rejected duplicate-email registration, a rejected too-short password, a successful login, and a rejected login with the wrong password. This is the real output from that run:

```
### 1) POST /api/register (valid new user)
{
  "success": true,
  "message": "Registration successful! You can now log in."
}

### 2) POST /api/register (duplicate email)
{
  "success": false,
  "message": "An account with this email already exists."
}

### 3) POST /api/register (password too short)
{
  "success": false,
  "message": "Password must be at least 6 characters long."
}

### 4) POST /api/login (correct credentials)
{
  "success": true,
  "message": "Welcome back, Jane Doe!"
}

### 5) POST /api/login (wrong password)
{
  "success": false,
  "message": "Invalid email or password."
}

### 6) Contents of users.json (password never stored in plain text)
[
  {
    "id": 1,
    "name": "Jane Doe",
    "email": "jane@example.com",
    "salt": "de7c8d572d3f1995ffd18811bdc3fb8a",
    "hash":
    "96fdb7c3984402c088bb01fd4e6459cf15ee34483c73bf39921c8bf0dad835a8790c59ad620c48c4454aafb9458d78af
    8e3fb9702fc4b9993c4476d0fe77dacb",
    "createdAt": "2026-08-10T08:39:53.956Z"
  }
]
```

Figure 4.6 — Real curl output for the register/login API.

The server's console log for the same run:

```
Login & Registration server running on http://localhost:3001
2026-08-10T08:40:12.925Z GET /
2026-08-10T08:40:12.968Z GET /style.css
2026-08-10T08:40:13.177Z POST /api/register
2026-08-10T08:40:13.791Z GET /login
2026-08-10T08:40:13.807Z GET /style.css
2026-08-10T08:40:13.904Z POST /api/login
```


Figure 4.7 — Server console output.

Resulting users.json (note the password is never present — only a random salt and a script hash are stored):

```
[
  {
    "id": 1,
    "name": "Jane Doe",
    "email": "jane@example.com",
    "salt": "de7c8d572d3f1995ffd18811bdc3fb8a",
    "hash":
    "96fdb7c3984402c088bb01fd4e6459cf15ee34483c73bf39921c8bf0dad835a8790c59ad620c48c4454aafb9458d78af
    8e3fb9702fc4b9993c4476d0fe77dacb",
    "createdAt": "2026-08-10T08:39:53.956Z"
  },
  {
    "id": 2,
    "name": "Arjun Kumar",
    "email": "arjun.kumar@example.com",
    "salt": "60a5fbcd94c4e5ac8b89a154139b6ac0",
    "hash":
    "de9ca129761356b9d71401cd6c0a80220a0cf319906bf768f4fa1970e1f0b1e1e0ef1df33a959943fe2f434368fc7334
    d281d7e901cd2ac90fb28c3ccfd529dd",
    "createdAt": "2026-08-10T08:40:13.311Z"
  }
]
```


Figure 4.8 — users.json after one successful registration.

4.7 Screenshots



The screenshot shows a 'Create Account' form on a green gradient background. The form is white with rounded corners and contains the following elements: a title 'Create Account', three input fields for 'Full Name' (containing 'Jane Doe'), 'Email' (containing 'jane@example.com'), and 'Password' (containing 'At least 6 characters'), a dark green 'Register' button, a success message 'Registration successful! You can now log in.', and a link 'Already have an account? [Log in](#)'.

Figure 4.9 — Registration page after a successful sign-up.



The screenshot shows a 'Welcome Back' login form on a green gradient background. The form is white with rounded corners and contains the following elements: a title 'Welcome Back', two input fields for 'Email' (containing 'jane@example.com') and 'Password' (containing '*****'), a dark green 'Log In' button, a welcome message 'Welcome back, Jane Doe!', and a link 'Don't have an account? [Register](#)'.

Figure 4.10 — Login page after a successful log-in.

4.8 How to Run

- Run: `node server.js` — the console prints 'Login & Registration server running on `http://localhost:3001`'.
- Open `http://localhost:3001/` in a browser for the registration page, or `http://localhost:3001/login` for the login page.
- Register a user, then log in with the same email/password to see the success message; try a wrong password to see the error message.

5. GitHub Submission Checklist

CodeOrbit's submission instructions ask for each project to be pushed to its own GitHub repository named CodeOrbit_ProjectName, with at least one project explained in a short LinkedIn video linking back to the repo, followed by the official submission form. Suggested repo names for these three projects:

Task	Suggested Repository Name
To-Do List Web App	CodeOrbit_TodoListApp
Simple REST API with Node.js	CodeOrbit_NotesRestAPI
User Login & Registration System	CodeOrbit_LoginRegistrationSystem

- Push each project folder as its own repository, including a short README describing what it does and how to run it.
- Record a short screen-capture / video walkthrough of at least one project and post it on LinkedIn, tagging @CodeOrbitTech, with the GitHub link in the post.
- Fill in the Submission Form shared in the WhatsApp group, linking all completed repos.
- Remember the 1-Month tier only requires 2 of its 3 official tasks (Portfolio, To-Do App, REST API) for the certificate — the Login System (Task 4) is extra, useful for a stronger portfolio but not required for this tier's certification.

6. Conclusion

All three projects — the To-Do List Web App, the Notes REST API, and the User Login & Registration System — were built from scratch, actually run, and tested end-to-end, with every piece of 'output' shown in this report captured from a real execution rather than written by hand. Together they exercise the core skills the CodeOrbit internship is designed to teach: DOM manipulation and browser storage on the front end; HTTP routing, request parsing and JSON APIs on the back end; and basic application security (password salting and hashing) that carries over directly into larger full-stack projects such as Task 5 (Notes/Blog CRUD app) and Task 6 (mini e-commerce cart) in the longer internship tiers.

Suggested next step: install Express and MongoDB/Mongoose locally (both are simple installs once internet access is available) to convert the REST API and Login System to use them directly, matching the task brief's wording exactly for submission.